24 STANDARD





- Voltage: 208v, 230v, 480v, 575v
- Motor: 5 HP premium grade
- AMPs-FLA: 208-230v (13.7-12.6), 480v (6.3), 575v (5)
- Drive: Belt and pulley system with auto-tensioner
- CFM: 8500
- Weight: 400 lbs.
- Dimensions: 31" L x 82" W x 58" H
- Construction: Steel, aluminum, bolted, riveted, sealed
- Finish: White two-coat powder coat
- Applications: Clean and circulate, whole shop filtration
- Db: 68
- Standard Features: Easy no-tool filter changes
- Balanced/Machined Blower and drive assembly
- Greaseable bearings with grease fittings outside the unit
- Comes standard with spark arrestors
- Many different filter options to fit your needs
- Easy-hang Uni-strut mounting options available
- NOTE: This unit is mounted vertically

24 STANDARD FROM A HOIST RAIL



ONLY 45 MINUTES OF FILTER MAINTENANCE PER YEAR!!

ONE OF OUR MEDIUM SIZED UNITS, BUT AT 8500 CFM AND 4 LARGE INTAKES, IT'S STILL LARGER THAN ANY COMPETITOR IN THE WORLD.

THIS UNIT IS MOUNTED VERTICALLY AND CAN HAVE VENTED OR PIPED EXHAUST.

These units can be used where the the exhaust is piped away from the unit, creating a local low pressure area around the unit, or with deflected exhaust. This forces unwanted particles to the unit and away from people.

For all applications from SILICA and SMOKE to CARDBOARD DUST,
THIS UNIT TAKES CARE OF IT FOR YOUR SAFER SHOP

CALL ROD TANIS 616-990-8005



