

24 VT SPECIFICATIONS SHOWN MOUNTED VERTICAL



TANISAIR.com
by TanisTechnologies.com

- [24VT AMBIENT DUST COLLECTOR](#)
- [Voltage: 208v, 230v, 480v, 575v](#)
- [Motor: 5 HP premium grade](#)
- [AMPs-FLA: 208-230v \(13.7-12.6\), 460v \(6.3\), 575v \(5\)](#)
- [Drive: Belt and pulley system with auto-tensioner](#)
- [CFM: 8500](#)
- [Weight: 400 lbs.](#)
- [Dimensions: 31" L x 82" W x 58" H](#)
- [Construction: Steel, Aluminum, Bolted, Riveted, Sealed](#)
- [Finish: White, two-coat power coat](#)
- [Applications: Clean and circulate, whole shop filtration](#)
- [Db: 68](#)
- [Standard Features:](#)
- [Easy, no-tool filter changes](#)
- [Balanced/Machined Blower and drive assembly parts](#)
- [Greaseable bearings with easy-access grease fitting located outside unit.](#)
- [Comes standard with spark arrestors](#)
- [Many filter options to suit your needs](#)
- [Easy-hang Uni-strut mounting options available](#)
- **NOTE: THIS UNIT CAN BE MOUNTED VERTICLE OR HORIZONTAL**

24VT HORIZONTAL (36VT SHOWN AS AN EXAMPLE)



24VT AMBIENT DUST COLLECTOR

ONLY 45 MINUTES OF FILTER MAINTENANCE PER YEAR!!

ONE OF OUR MEDIUM SIZED UNITS, BUT AT 8500 CFM AND 4 LARGE INTAKES, IT'S STILL LARGER THAN ANY COMPETITOR IN THE WORLD.

THIS UNIT IS MOUNTED VERTICAL OR HORIZONTAL AND CAN HAVE VENTED OR PIPED EXHAUST.

These units can be used where the the exhaust is piped away from the unit, creating a local low pressure area around the unit. This forces unwanted particles to the unit and away from people.

**For all applications from SILICA and SMOKE to CARDBOARD DUST,
THIS UNIT TAKES CARE OF IT FOR A SAFER FACTORY**

CALL ROD TANIS 616-990-8005

