

DM0424&DM0408

Multi-Purpose low Speed Centrifuge

Features

- Quiet, compact, and convenient with LCD display
- Maximum up to 4000rpm Speed can be set in RPM/RCF, with 3 customizable routine programs (Blood, Urine & Faecal)
- 3 acceleration level & 4 level deceleration
- Maximum capacity 4×50mL, Accommodating different sizes of blood collection tubes and centrifuge tubes suitable for swing out rotor and angle rotor
- Automatic internal diagnosis and self-detection
- Maintenance-free brushless DC motor

Applications

Multi-purpose low speed centrifuge are versatile and can be used in applications from clinical to biochemical for qualitative analysis of serum, plasma, blood, and urine.



Specifications	DM0424	DM0408
Speed range	500-4000rpm increment: 100rpm	300-4000rpm increment: 100rpm
Max. RCF	2500×g	1900×g
Speed accuracy	±100rpm	±100rpm
Rotor	Swing6×15mL Swing4×50mL Angle 24×15mL, Angle 12×10mL or 8×15mL	Angle 8×15mL(Default) Angle 12×10mL or 8×15mL
Run time	1-99min, HOLD	1-99min, HOLD
Motor	Brushless DC motor	Brushless DC motor
Display	LCD	LED
Program	Blood: 3200rpm,10min. Urine: 1800rpm,5min. Faecal: 1300rpm,10min.	Blood: 3200rpm, 10min Urine: 1800rpm,5min Faecal: 1300rpm, 10min
Safety Device	Automatic internal diagnosis	Automatic internal diagnosis
Acceleration/deceleration	3 ↑ 4 ↓ steps	25s ↑ 35s ↓
Power Requirements	Single phase, 100-240V, 50Hz/60Hz, 110W	Single phase, 100-240V, 50Hz/60Hz, 85W
Dimension(W×D×H)	364×440×268mm	286×367×227mm
Weight	14.5kg	9.2kg
Noise Level	≤62dB(A)	≤60dB(A)

Available rotors

S6-15
Cat. No.19400082
for DM0424

Max. speed: 4000rpm
 Rotor capacity: 6×15mL
 Rotor material: Aluminum alloy
 Default adaptor: A15P22, A5P17


A12-10P
Cat.No.19400068
**for DM0424/DM0408
 DM0412**

Max. speed : 4000rpm
 Rotor capacity: 8×15mL or 12×10mL
 Rotor material: High strength plastic


S4-50
Cat. No.19400100
for DM0424

Max. Speed: 4000rpm
 Rotor capacity: 4×50mL
 Rotor material: Aluminum alloy
 Default adaptor: A15P30, A5P17



Available adapters

A15P30
Cat. No.19500024

50mL change 15mL adapter,
 Adapted to 17×120mm centrifuge
 tube, 13/16×100mm blood
 collection tube 4pcs/pk, for S4-50


A24-15P
Cat. No.19400101
for DM0424

Max. speed: 4000rpm
 Rotor capacity: 24×15mL
 Rotor material: High strength plastic
 Default adaptor: A15P22, A5P17


A15P22
Cat. No.19500021

15mL adapter for 17×120mm
 centrifuge tube, 13/16×100mm
 blood collection tube 24 pcs/pk,
 for S6-15, A24-15P, A8-15P


A5P17
Cat. No.19500022

5mL adapter, Adapted to 13×75mm
 blood collection tube 24 pcs/pk,
 for S4-50, S6-15, A24-15P


A8-15P
Cat. No.19400084
for DM0424/DM0408

Max. Speed: 4000rpm
 Rotor capacity: 8×15mL
 Rotor material: High strength plastic
 Default adaptor: A15P22


A2P17(Optional)
Cat. No.19500023

1.5/2mL Cryogenic Vials/ centrifuge
 tube adapter, 24 pcs/pk, for S4-50,
 S6-15, A24-15P, A12-10P, A6-50P

