

# GDLITE ENTRY SYSTEM



The GD Entry Lite Touch Screen Telephone Entry System comes pre-configured and tested, allowing for easy deployment. With a distributed configuration, no need for high voltage at the front door is needed, simply a single CAT5/6 cable is all that is required.

Our system supports traditional residents while simultaneously allowing residents with smart phones to use our one-way video calling applications for free. Residents can receive calls from the system over landlines, cell phones, and video applications or any mix of the bunch. The system will automatically call them on what is available first, with no need to be worried about defining a method for each tenant.

We allow for ease of configuration anywhere you are in the world with a secure connection when the system is connected to the internet. With 24/7 health monitoring included for the life of the system, you never have to worry about the status of your system. With the option to buy the system outright, you can eliminate recurring fees if you choose. Once you buy, you own this system and it will continue to run and operate for its lifetime!

## Features

- System can be hosted or on site
- Outdoor rated assembly
- High-fidelity speaker and noise-cancelling microphone
- Supports POTS, SIP, and VOIP services
- Easy remote management
- Multi-use and single-use pin code entry
- Cascading of calls to a single name on the screen, up to five numbers per name can be called on 1 telephone line
- Auto selection of app and POTS line calling of residents
- Easy app deployment to residents
- Customizable screen saver
- Intuitive, easy-to-use interface
- Iphone and Android video applications
- Find a resident and call them within two or three touches of the screen
- Integrates with almost any access control system

## SPECS

7" display

267mm x 131mm x 41mm  
(H x W x D)

2M camera with LED

Back end power is 120 volt Class 2

Either 12V DC or POE

IP65 waterproof

Waterproof speaker, 2W x 1

Echo-cancelling mic

Connected via Cat5E

USB cellular modem support

SIP/VOIP/POTS support

## Questions & Support

### PHONE

(425) 533-2045  
9am - 5pm PST

### EMAIL

service@GDEntry.com

**GDENTRY.COM**

# GDLITE ENTRY SYSTEM



## Specifications

### DISPLAY

Panel Size	7'
Brightness	400 nits
Resolution	800 x 1280

### HARDWARE

Processor	Quad Core A35
RAM	2GB
Storage	8GB

### OPERATING SYSTEM

OS	Android 8.1
----	-------------

### CONNECTIVITY

Ethernet	RJ45 10/100PoE
----------	----------------

### MULTIMEDIA

Microphone	Echo cancelling mic
Speaker	Waterproof speaker, 2W x 1
Camera	2M camera with LED

### SENSOR

Sensor	Proximity sensor; ambient sensor
Lighting	White
Monitor	Watchdog for device status

### MOUNTING

Mounts	Wall mount or flush mounting
--------	------------------------------

### POWER

Consumption	12W
Power Supply	Either 12V DC or POE