

2000 Series Multi Slide



www.AmericanWallZone.com | for more information







Features and Benefits

Sizing

- Standard sizing in 9' x 8' and 12' x 8' in 3 panel configuration.
- Standard sizing in 12' x 8' and 16' x 8' in 4 panel configuration.
- Maximum panel size is 4' x 8'.
- Maximum frame width of 3 panel door system at 12'.
- Maximum width of 4 panel door system at 16'.
- · Custom sizing available.

■ Frame

- KD or welded main frame.
- 7¾" total width 6¾" jamb depth all PVC multi-chambered profile frame system (on 3 panel).
- 10³/₁₆" total width 9 ³/₁₆" jamb depth all PVC multi-chambered profile frame system (on 4 panel).
- Integrated nail fin application with 1"or 1%" set back.
- Full length weather stripping on all 4 frame components.
- Integrated sill drainage with snap-in sill covers.

Sash

- Fully welded vinyl sash with internal aluminum reinforcement with ⁷/₈" standard IG, or a 1½" triple insulated glass system.
- Many high energy-efficient glass options for the most extreme temperature sensitive regions.
- Standard glazing, Cardinal™ LoE 366® dual glazed tempered glass.
- All stiles are metal reinforced for extreme wind load resistance
- Unique internal drainage system to minimize risk of seal failures interior glazed for better performance.

Hardware

- Truth Nexus 2 point lock with opposing lock points.
- Anti-lock feature preventing a "false" sense of lock up.
- Stainless steel roller housing and composite wheel with end adjustment, AAMA rated to carry a 500 pound panel for 10,000 cycles without change to adjustment.
- Hardware colors; white, beige, black powder coat, and brushed chrome.

Extruded Vinyl Colors



Optional Exterior Stocked Colors







Optional

 Black Exterior Specialty Laminate







Signature (Optional upgrade)