



Permanent Roof Anchor

Lag-It & Leave-It

INSPECTION FORM

If a smartphone is not available during the inspection, resort to a manual inspection following paper log guidelines. Take a photo of the QR Code for later reference and log the inspection data when smartphone service becomes available. Ensure that the manual inspection is detailed and comprehensive, covering all necessary aspects specified in the inspection guidelines. Later, transfer this recorded information into the appropriate digital log for documentation and reference.

☐ I am a competent person capable of certifying that the device is installed per manufacturer standards.

☐ I have read all instructions provided by the manufacturer

Anchor Install Address: _____

Inspector Name: _____

Name of Business: _____

Company Address: _____

Company Phone Number: _____

Company Email: _____

Homeowner Name: _____

Home Owner Phone Number: _____

Homeowner Email: _____

Product verification: Are all Rooftop Anchor components accounted for?
Please check all that apply.

☐ Lid

☐ Base

☐ D-Ring

☐ 2 - 5/16" - 3.5" Stainless Steel Lag Bolts

☐ 6 - 1/4" - 20 Stainless Steel Cap Head Screws

☐ Butyl adhesive is attached to the bottom of the roof anchor

Disclaimer: If this device is used without proper inspections, the manufacturer is not liable and all warranties are void.