



Permanent Roof Anchor

Lag-It & Leave-It

TECHNICAL DATA SHEET



FEATURES

- User Weight Range: 100-420 lbs.
- Minimum Breaking Strength (MSB): 5,000 Pounds
- Substrates: Wood & Metal (must be attached to a truss)
- D-Ring - Zinc Plated Forged Alloy Steel
- Butyl Adhesive Remains Flexible to temperatures as low as -70°F
- Body is made from 6061 Aluminum, Tumbled and Anodized
- Lag Screw - 5/16" x 3 1/2" Coarse thread 302 Stainless Steel
- Cap Screws - 1/4" - 20 x 1/2" 18-8 Stainless Steel
- Built-in Inspection Software
- Approx. Weight - 1 lbs.
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 & 1926.502



Designed, tested,
and assembled in
the United States

US Patent No: 11,879,256

WARNING

Compliance with fall protection equipment is vital and should strictly align with its intended design and the hierarchy of controls delineated in ANSI Z359.2. Users are mandated to all provided user instructions. Prior to employing a fall arrest system, individuals must receive comprehensive training in its safe utilization, as mandated by OSHA 29 CFR 1910.30 and 1926.503, or pertinent local safety regulations. Neglecting to comply with these guidelines and instructions could lead to severe injury or fatality.