



FLEXTRAY™ Wire Basket - Straight Sections

2" Deep FLEXTRAY



Height: 2.38" (60 mm)

Length: 118.312" (3 meter)

Wire Dia. Minimum: .196" (5.0 mm)

Finishes:

EG, GS, BLE, HD, 304S, 316S


	Part Number	Width		Wt. Per Pc.	
		in.	(mm)	lbs.	(kg)
	FT2X2X10	2	(50)	6.6	(2.99)
	FT2X4X10	4	(100)	8.2	(3.72)
	FT2X6X10	6	(150)	9.7	(4.40)
	FT2X8X10	8	(200)	11.2	(5.08)
	FT2X12X10	12	(300)	14.3	(6.48)
	FT2X16X10	16	(400)	17.4	(7.89)
	FT2X18X10	18	(450)	18.9	(8.57)
	FT2X20X10	20	(500)	20.4	(9.25)
	FT2X24X10	24	(600)	23.5	(10.66)
	FT2X30X10	30	(750)	28.1	(12.74)
	FT2X32X10	32	(800)	29.7	(13.47)

FT2X6 (6" wide) through FT2X32 (32" wide) are UL Classified

FLEXTRAY™ Wire Basket - Straight Sections

4" Deep FLEXTRAY

Part Number	Width		Wt. Per Pc.	
	in.	(mm)	lbs.	(kg)
FT4X4X10	4	(100)	11.25	(5.10)
FT4X6X10	6	(150)	12.79	(5.80)
FT4X8X10	8	(200)	14.32	(6.49)
FT4X12X10	12	(300)	17.39	(7.89)
FT4X16X10	16	(400)	20.45	(9.27)
FT4X18X10	18	(450)	21.99	(9.97)
FT4X20X10	20	(500)	23.52	(10.67)
FT4X24X10	24	(600)	26.59	(12.06)
FT4X30X10	30	(750)	31.19	(14.15)




Height: 4.38" (111 mm)
Length: 118.312" (3 meter)
Wire Diameter Minimum: .196" (5.0 mm)
Finishes: EG, GS, BLE, HD, 304S, 316S

All 4" deep Flextrays are UL Classified

6" Deep FLEXTRAY

Part Number	Width		Wt. Per Pc.	
	in.	(mm)	lbs.	(kg)
FT6X8X10	8	(200)	17.39	(7.89)
FT6X12X10	12	(300)	20.45	(9.27)
FT6X16X10	16	(400)	23.52	(10.67)
FT6X18X10	18	(450)	25.06	(11.37)
FT6X20X10	20	(500)	26.59	(12.06)
FT6X24X10	24	(600)	29.66	(13.45)



Height: 6.38" (162 mm)
Length: 118.312" (3 meter)
Wire Diameter Minimum: .196" (5.0 mm)
Finishes: EG, GS, BLE, HD, 304S, 316S

All 6" deep Flextrays are UL Classified

See page D-3 for finish information