

# GROUNDING PRODUCTS

## GROUND ACCESS WELLS

### Light Duty Ground Access Well

Catalog Number	Diameter (in)	Length (in)	Cover Type
PE6AHDH00L74	6	9	HDPE
PE9AHDH00L74	9	10	HDPE
PE10HDH00L74	10	18.875	HDPE
PE10UPH00009	10	18.25	Steel
38-8130-02	10	19	Steel with Steel/PC Ring



### Access Well with Cast Iron Cover

Catalog Number	Diameter	Length	Cover Type
38-6344-12*	12"	12"	Cast Iron
38-6343-36	10"	36"	Cast Iron
38-6343-42	10"	42"	Cast Iron

- Schedule 80 PVC well.
- Four 27" slots allow for ground electrode connections to be made before installation of test well. \* No Slots
- Cast iron cover fits into cast iron ring for extra support.



### Heavy Duty Well with Cast Iron Cover

Catalog Number	Diameter	Length	Cover Type
38-6344-18	12"	18"	Cast Iron
38-6344-24	12"	24"	Cast Iron
38-6344-30	12"	30"	Cast Iron
38-6344-36	12"	36"	Cast Iron

- 12" diameter Schedule 80 PVC well.
- Cast iron cover fits into cast iron ring for extra support.
- Tier 22: Driveway, Parking lot, and off-roadway applications subject to occasional non deliberate heavy vehicular traffic.



Contact thermOweld for other options

#### APPLICATION NOTES:

- Provides ready access to ground electrode for testing and inspection purposes.
- To prevent displacement by frost, the access well must be longer than the frost line is deep.