


Rigid IMC

Insulated Conduit Bushings 150°C with Aluminum Lugs for Threaded Rigid Conduit & IMC



Features

- The plastic liner won't chip, crack, swell or shrink. It resists corrosion, chemicals and temperature extremes
- One set screw provided with each fitting locks bushing in any desired position
- UL Listed for use with copper or aluminum grounding conductors
- RoHS compliant

Standard Materials

- Body - Malleable Iron / Ductile Iron
- Lug - Aluminum
- Insuliner - PEI rated at 150° C
- Clamping screw - Steel
- Set screw - Steel

Standard Finish

- Body - zinc plated
- Lug - aluminum
- Clamping screw - zinc plated
- Set screw - zinc plated

Applicable Third Party Standards

- UL Standard: 467
- UL Standard: 514B
- Fed. Spec. A-A-50553A
- NEMA: FB-1
- UL Listed File # E212551

U.S. Patent No. 6.808.181

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Inner Pack	Master Pack	Weight Per C (lb)	Weight Per C
BRC-50-1AKON	1/2	4-14	1.063	0.688	100	500	7.4
BRC-75-1AKON	3/4	4-14	1.250	0.688	50	250	10.7
BRC-100-1AKON	1	4-14	1.625	0.750	50	250	15.1
BRC-125-1AKON	1 1/4	4-14	2.000	0.813	25	125	18.4
BRC-125-2AKON	1 1/4	1/0-8	2.000	0.813	25	125	23.1
BRC-150-1AKON	1 1/2	4-14	2.313	0.813	25	125	22.8
BRC-150-2AKON	1 1/2	1/0-8	2.313	0.813	25	125	27.5
BRC-200-1AKON	2	4-14	2.750	0.875	10	50	27.3
BRC-200-2AKON	2	1/0-8	2.750	0.875	10	50	32.0
BRC-250-2AKON	2 1/2	1/0-8	3.313	1.000	-	10	57.3
BRC-250-3AKON	2 1/2	3/0-6	3.313	1.000	-	10	67.1
BRC-250-4AKON	2 1/2	250MCM-6	3.313	1.000	-	10	69.5
BRC-300-2AKON	3	1/0-8	4.000	1.000	-	10	72.7
BRC-300-3AKON	3	3/0-6	4.000	1.000	-	10	82.5
BRC-300-4AKON	3	250MCM-6	4.000	1.000	-	10	84.9
BRC-350-3AKON	3 1/2	3/0-6	4.375	1.063	-	10	88.1
BRC-350-4AKON	3 1/2	250MCM-6	4.375	1.063	-	10	89.9
BRC-400-3AKON	4	3/0-6	5.063	1.125	-	10	118.9
BRC-400-4AKON	4	250MCM-6	5.063	1.125	-	10	121.3
BRC-500-3AKON	5	3/0-6	6.125	1.188	-	5	163.0
BRC-500-4AKON	5	250MCM-6	6.125	1.188	-	5	165.4
BRC-600-3AKON	6	3/0-6	7.188	1.188	-	5	200.5
BRC-600-4AKON	6	250MCM-6	7.188	1.188	-	5	202.9