


Rigid IMC



Three Piece Coupling

Three piece Couplings for Rigid Conduit & IMC

Features

- Heavy-duty casting
- Concrete tight
- Direct burial without tape
- Couples conduits when conduit cannot be turned
- RoHS compliant

Standard Materials

- Malleable Iron / Ductile Iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Inner Pack	Master Pack	Weight Per C (lb)
EC50KON	1/2	1.313	1.375	1.375	10	100	26.1
EC75KON	3/4	1.563	1.563	1.563	5	50	36.6
EC100KON	1	1.625	1.875	1.875	5	50	55.3
EC125KON	1 1/4	2.125	2.375	2.375	5	25	110.5
EC150KON	1 1/2	2.375	2.813	2.813	5	25	171.9
EC200KON	2	2.625	3.313	3.313	2	10	202.6
EC250KON	2 1/2	3.125	4.063	4.063	2	10	327.4
EC300KON	3	3.188	4.688	4.688	-	5	442.0
EC350KON	3 1/2	3.563	5.063	5.063	-	1	607.8
EC400KON	4	4.000	5.750	5.750	-	1	718.3
EC500KON	5	4.000	7.250	7.250	-	1	1050.0
EC600KON	6	3.875	8.313	8.313	-	1	1250.0