



# POWER KABEL INC.

## MV-90 ALUMINUM 15KV XLP @ 100% COPPER TAPE SHIELD PVC JACKET

### APPLICATIONS & FEATURES

Primary power and distribution circuits in industrial and commercial installations, power circuits in generating plants where line to ground fault current are within shield capabilities. May be used in wet or dry locations, installed in raceways, duct, and open air, aerially or directly buried as permitted by NEC. UL Listed as MV-90. Rated as Sunlight Resistance. Oil Resistance I jacket.

### INDUSTRY COMPLIANCES

UL 1072 (Medium Voltage Power Cable.)

AEIC CS8 (Extruded Dielectric, Shielded Power Cables)

ICEA S-93-639/WC 74 (Shielded Power Cable for Use in the Transmission and Distribution of Electric Energy Rated 5 kV - 46 kV.)

ASTM B400 (Compact Round Concentric-Lay-Stranded Aluminum 1350 Conductors.)

ICEA S-97-682 (Utility Shielded Power Cables rated 5 kV - 46 kV.)

### CONSTRUCTION

<b>CONDUCTORS:</b>	Hard drawn Aluminum-1350 compacted Class B per ASTM B400.
<b>CONDUCTOR SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>INSULATION:</b>	Thermoset crosslinked polyethylene (XLPE). On request: TR-XLPE.
<b>INSULATION SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>METALLIC SHIELD:</b>	Soft annealed uncoated copper tape, 5 mil thick, 25% minimum overlap
<b>BINDER TAPE:</b>	A suitable polyester tape, as required
<b>JACKET:</b>	Black sunlight resistance and flame retardant polyvinyl chloride (PVC) compound.

AWG	STRANDS	INSULATION THICKNESS (MILS)	CONDUCTOR OD (INCHES)	INSULATION DIAMETER (INCHES)	JACKET THICKNESS (MILS)	OUTSIDE DIAMETER (INCHES)	POUNDS PER 1000 FT
2	7	175	0.27	0.65	80	0.91	406
1	19	175	0.30	0.68	80	0.94	438
1/0	19	175	0.34	0.72	80	0.97	480
2/0	19	175	0.38	0.76	80	1.01	528
3/0	19	175	0.42	0.81	80	1.06	587
4/0	19	175	0.48	0.86	80	1.11	658
250	37	175	0.52	0.92	80	1.17	725
300	37	175	0.57	0.97	80	1.22	800
350	37	175	0.62	1.01	80	1.29	897
400	37	175	0.66	1.05	80	1.33	970
500	37	175	0.74	1.13	80	1.41	1109
600	61	175	0.81	1.22	80	1.49	1253
750	61	175	0.91	1.31	80	1.59	1449
1000	61	175	1.06	1.47	110	1.80	1879

All values are nominal and subject to correction.