



# POWER KABEL INC.

## MV-90 ALUMINUM 15KV XLP @ 100% NEUTRAL PVC JACKET

### APPLICATIONS & FEATURES

Primary power and distribution circuits in industrial and commercial installations, power circuits in generating plants where line to ground fault current are within shield capabilities. May be used in wet or dry locations, installed in raceways, duct, and open air, aerially or directly buried as permitted by NEC. UL Listed as MV-90. Rated as Sunlight Resistance. Oil Resistance I jacket.

### INDUSTRY COMPLIANCES

UL 1072 (Medium Voltage Power Cable.)

AEIC CS8 (Extruded Dielectric, Shielded Power Cables)

ICEA S-93-639/WC 74 (Shielded Power Cable for Use in the Transmission and Distribution of Electric Energy Rated 5 kV - 46 kV.)

ASTM B400 (Compact Round Concentric-Lay-Stranded Aluminum 1350 Conductors.)

ICEA S-97-682 (Utility Shielded Power Cables rated 5 kV - 46 kV.)

### CONSTRUCTION

**CONDUCTORS:** Hard drawn Aluminum-1350 compacted Class B per ASTM B400.  
**CONDUCTOR SHIELD:** Semi conducting cross-linked polyethylene (XLPE).  
**INSULATION:** Thermoset crosslinked polyethylene (XLPE). On request: TR-XLPE.  
**INSULATION SHIELD:** Semi conducting cross-linked polyethylene (XLPE).  
**CONCENTRIC NEUTRAL:** Soft annealed solid copper wires per ASTM B3, helically applied and uniformly spaced. Full or 1/3 Neutral.  
**BINDER TAPE:** A suitable polyester tape, as required  
**JACKET:** Black sunlight resistance and flame retardant polyvinyl chloride (PVC) compound.

AWG	STRANDS	INSULATION THICKNESS (MILS)	CONDUCTOR OD (INCHES)	INSULATION DIAMETER (INCHES)	JACKET THICKNESS (MILS)	OUTSIDE DIAMETER (INCHES)	POUNDS PER 1000 FT
2	7	175	0.27	0.65	80	0.94	382
1	19	175	0.30	0.68	80	0.97	412
1/0	19	175	0.34	0.72	80	1.01	450
2/0	19	175	0.38	0.76	80	1.05	495
3/0	19	175	0.42	0.81	80	1.10	551
4/0	19	175	0.48	0.86	80	1.15	618
250	37	175	0.52	0.92	80	1.20	689
300	37	175	0.57	0.97	80	1.25	760
350	37	175	0.62	1.01	80	1.32	852
400	37	175	0.66	1.05	80	1.37	922
500	37	175	0.74	1.13	80	1.44	1055
600	61	175	0.81	1.22	80	1.53	1201
750	61	175	0.91	1.31	80	1.62	1390
1000	61	175	1.06	1.47	110	1.84	1810

All values are nominal and subject to correction.