



# POWER KABEL INC.

## MV-90 COPPER 8KV XLP @ 100% NEUTRAL PVC JACKET

### APPLICATIONS & FEATURES

Primary power and distribution circuits in industrial and commercial installations, power circuits in generating plants where line to ground fault current are within shield capabilities. May be used in wet or dry locations, installed in raceways, duct, and open air, aerially or directly buried as permitted by NEC. UL Listed as MV-90. Rated as Sunlight Resistance. Oil Resistance I jacket.

### INDUSTRY COMPLIANCES

UL 1072 (Medium Voltage Power Cable.)

ICEA S-93-639/WC 74 (Shielded Power Cable for Use in the Transmission and Distribution of Electric Energy Rated 5 kV - 46 kV.)

ICEA S-97-682 (Utility Shielded Power Cables rated 5 kV - 46 kV.)

AEIC CS8 (Extruded Dielectric, Shielded Power Cables)

ASTM B496 (Compact Round Concentric-Lay-Stranded Copper Conductors.)

### CONSTRUCTION

<b>CONDUCTORS:</b>	Soft annealed uncoated copper compacted Class B per ASTM B496
<b>CONDUCTOR SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>INSULATION:</b>	Thermoset crosslinked polyethylene (XLPE). On request: TR-XLPE.
<b>INSULATION SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>CONCENTRIC NEUTRAL:</b>	Soft annealed solid copper wires per ASTM B3, helically applied and uniformly spaced. Full or 1/3 Neutral.
<b>BINDER TAPE:</b>	A suitable polyester tape, as required
<b>JACKET:</b>	Black sunlight resistance and flame retardant polyvinyl chloride (PVC) compound.

AWG	STRANDS	INSULATION THICKNESS (MILS)	CONDUCTOR OD (INCHES)	INSULATION DIAMETER (INCHES)	JACKET THICKNESS (MILS)	OUTSIDE DIAMETER (INCHES)	POUNDS PER 1000 FT
6	7	115	0.17	0.43	60	0.68	257
4	7	115	0.21	0.48	60	0.73	321
2	7	115	0.27	0.53	60	0.78	422
1	19	115	0.30	0.56	60	0.81	485
1/0	19	115	0.34	0.60	80	0.89	601
2/0	19	115	0.38	0.64	80	0.93	703
3/0	19	115	0.42	0.69	80	0.98	829
4/0	19	115	0.48	0.74	80	1.03	986
250	37	115	0.52	0.80	80	1.08	1136
300	37	115	0.57	0.85	80	1.13	1310
350	37	115	0.62	0.89	80	1.18	1485
400	37	115	0.66	0.93	80	1.22	1657
500	37	115	0.74	1.01	80	1.32	2021
600	61	115	0.81	1.10	80	1.41	2376
750	61	115	0.91	1.19	80	1.50	2880
1000	61	115	1.06	1.35	80	1.66	3718

All values are nominal and subject to correction.