



# POWER KABEL INC.

## URD 35KV EPR/PVC @ 100% ALUMINUM 1/3 NEUTRAL

### APPLICATIONS & FEATURES

Underground primary residential and commercial distribution circuits. May be used in wet or dry locations, installed in underground ducts or direct burial. Low tension stripping compounds. Sealed conductor passes the production water penetration tests per ICEA--31-610 at 15 psi for 60 minutes. Strand Filled compound meets compatibility test requirements in accordance with ICEA-T-32-610

### INDUSTRY COMPLIANCES

ICEA S-94-649 (Concentric Neutral Cables Rated 5 Through 46 kV.)

ASTM B8 (Concentric-Lay-Stranded Copper Conductors, Hard, Medium-Hard, or Soft.)

AEIC CS8 (Extruded Dielectric, Shielded Power Cables rated 5 kV - 46 kV.)

ASTM B231 (Concentric-Lay-Stranded Aluminum 1350 Conductors.)

### CONSTRUCTION

<b>CONDUCTORS:</b>	Hard drawn aluminum Class B compressed or unilay compressed stranding per ASTM B231.
<b>CONDUCTOR SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>INSULATION:</b>	Thermoset tree-retardant cross-linked polyethylene (TR-XLPE)
<b>INSULATION SHIELD:</b>	Semi conducting cross-linked polyethylene (XLPE).
<b>CONCENTRIC NEUTRAL:</b>	Soft annealed solid copper wires per ASTM B3, helically applied and uniformly spaced. Full or 1/3 Neutral.
<b>BINDER TAPE:</b>	A suitable polyester tape, as required
<b>JACKET:</b>	Overlying (sleeve) black polyvinyl chloride (PVC)

AWG	STRANDS	INSULATION THICKNESS (MILS)	OD OVER INSULATION (INCHES)	CONCENTRIC NEUTRAL (No X AWG)	JACKET THICKNESS (MILS)	OUTSIDE DIAMETER (INCHES)	POUNDS PER 1000 FT
1/0	19	345	1.10	6 X 14	80	1.49	948
2/0	19	345	1.14	7 X 14	80	1.53	1026
3/0	19	345	1.19	9 x 14	80	1.58	1129
4/0	19	345	1.25	11 x 14	80	1.64	1247
250	37	345	1.30	13 X 14	110	1.76	1465
350	37	345	1.40	18 x 14	110	1.86	1722
500	37	345	1.53	16 X 12	110	2.06	2137
750	61	345	1.74	15 X 10	110	2.3	2756
1000	61	345	1.89	16 X 9	110	2.48	3317

All values are nominal and subject to correction.