

GROUNDING PRODUCTS

GROUND ACCESS WELLS

thermOweld® polymer concrete enclosures meet or exceed the test provisions of ANSI/SCTE 77 2013.

Testing requirements for ANSI/SCTE 77 2013 are:

- Three-Position Load testing to simulate actual application performance
- UV Degradation per ASTM G-154
- Fire Resistance per RUS 7CFR 1755.919 (PE-91)
- Chemical Resistance per ASTM D-543
- Water Absorption per ASTM D-570
- Impact Resistance per ASTM D2444
- Accelerated Service per ASTM D-756, procedure E

Stackable Access Wells

Stackable access wells are designed so they can be stacked to increase the well depth. Used for a variety of purposes, such as a splice box, pull box, equipment enclosure, or for any application requiring easy access to an underground service. The straight sides allow for easy adjustment of the box should the grade level change.



Rectangular Stackable Access Well

Catalog Number	Width	Length	Depth	Cover Type	Tier
38-8175-00	13"	24"	18"	Polymer Concrete	15
38-8171-00	13"	24"	12"	Polymer Concrete	15

Other sizes and tiers available upon request.

Tier 15: Driveway, parking lot, and off-roadway applications subject to occasional non-deliberate heavy vehicular traffic.

Square Stackable Access Well

Catalog Number	Width	Length	Depth	Cover Type	Tier
38-8131-00	8"	8"	12"	Polymer Concrete	15
38-8132-00	8"	8"	18"	Polymer Concrete	15
38-8145-00	12"	12"	12"	Polymer Concrete	15
38-8147-00	12"	12"	24"	Polymer Concrete	15

Other sizes and tiers available upon request.

Tier 15: Driveway, parking lot, and off-roadway applications subject to occasional non-deliberate heavy vehicular traffic.



GROUND ACCESS WELLS

Nestable Access Wells

Nestable access wells are designed for compact storage and are excellent for service box assemblies and offer flared design to prevent frost heave.

Nestable Access Well

Catalog Number	Width	Length	Depth	Cover Type	Tier
38-8166-00	12"	12"	24"	Polymer Concrete	15

Other sizes and tiers available upon request.

Tier 15: Driveway, parking lot, and off-roadway applications subject to occasional non-deliberate heavy vehicular traffic.



Cylindrical Access Wells

Cylindrical access wells prevent the enclosure cover from falling into the box.

Cylindrical Access Well

Catalog Number	Diameter	Depth	Cover Type	Tier
38-8185-00	27"	36"	Polymer Concrete	8

Other sizes and tiers available upon request.

Tier 8: Sidewalk applications with a safety factor for non-deliberate vehicular traffic.

