

Rigid PVC Conduit & Fittings

Listed to UL 651

Schedule 40

Rated for use with 90° C Wiring

Schedule 40 is sunlight resistant. Meets or exceeds the requirements of NEMA TC 2 and UL 651 for Schedule 40 Conduit.



Trade Size	Part Number	Average O.D.	Minimum Average I.D.	Minimum Wall	Weight Per Foot	10 Ft Crate Quantity
		(in)	(in)	(in)	(lb)	(ft)
½	8102	0.840	0.578	0.109	0.165	6000
¾	8103	1.050	0.780	0.113	0.220	4400
1	8104	1.315	1.004	0.133	0.326	3600
1¼	8105	1.660	1.335	0.140	0.441	3300
1½	8106	1.900	1.564	0.145	0.528	2250
2	8108	2.375	2.021	0.154	0.730	1400
2½	8110	2.875	2.414	0.203	1.158	930
3	8112	3.500	3.008	0.216	1.609	880
3½	8114	4.000	3.486	0.226	1.935	630
4	8116	4.500	3.961	0.237	2.292	570
5	8120	5.563	4.975	0.258	3.105	380
6	8124	6.625	5.986	0.280	4.030	260
8*	880747	8.625	7.853	0.322	6.065	140

* UL 651 does not include 8"



Schedule 40

Rated for use with 90° C Wiring

Schedule 40 is sunlight resistant. Meets or exceeds the requirements of NEMA TC 2 and UL 651 for Schedule 40 Conduit.



Trade Size	Part Number	Average O.D.	Minimum Average I.D.	Minimum Wall	Weight Per Foot	20 Ft Crate Quantity
		(in)	(in)	(in)	(lb)	(ft)
½	8502	0.840	0.578	0.109	0.165	12000
¾	8503	1.050	0.780	0.113	0.220	8800
1	8504	1.315	1.004	0.133	0.326	7200
1¼	8505	1.660	1.335	0.140	0.441	6600
1½	8506	1.900	1.564	0.145	0.528	4500
2	8508	2.375	2.021	0.154	0.730	2800
2½	8510	2.875	2.414	0.203	1.158	1860
3	8512	3.500	3.008	0.216	1.609	1760
3½	8514	4.000	3.486	0.226	1.935	1260
4	8516	4.500	3.961	0.237	2.292	1140
5	8520	5.563	4.975	0.258	3.105	760
6	8524	6.625	5.986	0.280	4.030	520
8*	924297	8.625	7.853	0.322	6.065	280

* UL 651 does not include 8"



Item availability may vary by region.

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.
alliedeg.com