

Rigid PVC Conduit & Fittings

Listed to UL 651

Schedule 80

Rated for use with 90° C Wiring

Schedule 80 is sunlight resistant. Meets or exceeds the requirements of NEMA TC 2 and UL 651 for Schedule 80 Conduit



Trade Size	Part Number	Average O.D.	Minimum Average I.D.	Minimum Wall	Weight Per Foot	10 Ft Crate Quantity
		(in)	(in)	(in)	(lb)	(ft)
½	9302	0.840	0.502	0.147	0.205	6000
¾	9303	1.050	0.698	0.154	0.278	4400
1	9304	1.315	0.910	0.179	0.410	3600
1¼	9305	1.660	1.227	0.191	0.565	3300
1½	9306	1.900	1.446	0.200	0.726	2250
2	9308	2.375	1.881	0.218	1.004	1400
2½	9310	2.875	2.250	0.276	1.531	930
3	9312	3.500	2.820	0.300	2.049	880
3½	924024	4.000	3.280	0.318	2.499	630
4	9316	4.500	3.737	0.377	3.122	570
5	9320	5.563	4.713	0.375	4.330	380
6	9324	6.625	5.646	0.432	5.954	260



PVC Conduit & Fittings

Schedule 80

Rated for use with 90° C Wiring

Schedule 80 is sunlight resistant. Meets or exceeds the requirements of NEMA TC 2 and UL 651 for Schedule 80 Conduit.



Trade Size	Part Number	Average O.D.	Minimum Average I.D.	Minimum Wall	Weight Per Foot	20 Ft Crate Quantity
		(in)	(in)	(in)	(lb)	(ft)
½	925785	0.840	0.502	0.147	0.205	12000
¾	9503	1.050	0.698	0.154	0.278	8800
1	9504	1.315	0.910	0.179	0.410	7200
1¼	924298	1.660	1.227	0.191	0.565	6600
1½	9506	1.900	1.446	0.200	0.726	4500
2	9508	2.375	1.881	0.218	1.004	2800
2½	924299	2.875	2.250	0.276	1.531	1860
3	9512	3.500	2.820	0.300	2.049	1760
3½	-	4.000	3.280	0.318	2.499	1260
4	9516	4.500	3.737	0.377	3.122	1140
5	9520	5.563	4.713	0.375	4.330	760
6	9524	6.625	5.646	0.432	5.954	520



Allied Tube & Conduit® Catalog

Item availability may vary by region.

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.
800.882.5543

31