

Rigid PVC Conduit & Fittings

Utility Duct - Type DB-60 for Direct Burial

Rated for use with 90° C Wiring



Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	20 Ft Crate Quantity
		(in)	(in)	(lb)	(ft)
2	7508	2.375	0.060	0.361	2800
3	7512	3.500	0.092	0.711	1760
4	7516	4.500	0.121	1.202	1140
5	7520	5.563	0.152	1.866	760
6	7524	6.625	0.182	2.660	520

Meets NEMA TC 6 and 8 and ASTM F 512

Utility Duct - Type DB-100 for Direct Burial

Rated for use with 90° C Wiring



Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	Crate Quantity
		(in)	(in)	(lb)	(ft)
3	924289	3.500	0.112	0.879	1760
4	924290	4.500	0.145	1.499	1140
5	924291	5.563	0.179	2.292	760
6	924292	6.625	0.213	3.253	520

Meets NEMA TC 6 and 8 and ASTM F 512

Utility Duct - Type DB-120 for Direct Burial

Rated for use with 90° C Wiring



Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	Crate Quantity
		(in)	(in)	(lb)	(ft)
1	924293	1.315	0.060	0.164	7200
1½	924294	1.900	0.060	0.258	4500
2	6108	2.375	0.077	0.415	2800
3	6112	3.500	0.118	0.964	1760
4	6116	4.500	0.154	1.594	1140
5	6120	5.563	0.191	2.433	760
6	6124	6.625	0.227	3.448	520

Meets NEMA TC 6 and 8 and ASTM F 512

Item availability may vary by region.

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.
alliedeg.com