

Rigid PVC Conduit & Fittings

Listed to UL 651

Utility Duct - Type EB-20 for Encased Burial

Rated for use with 90° C Wiring



Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	Crate Quantity
		(in)	(in)	(lb)	(ft)
2	2008	2.375	0.060	0.361	2800
3	2012	3.500	0.061	0.514	1760
4	2016	4.500	0.082	0.900	1140
5	2020	5.563	0.103	1.268	760
6	2024	6.625	0.125	1.729	520

Meets NEMA TC 6 and 8 and ASTM F 512

Utility Duct - Type EB-35 for Encased Burial

Rated for use with 90° C Wiring



Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	Crate Quantity
		(in)	(in)	(lb)	(ft)
2	3508	2.375	0.060	0.361	2800
3	3512	3.500	0.076	0.596	1760
4	3516	4.500	0.100	0.923	1760
5	3520	5.563	0.126	1.650	760
6	-	6.625	0.152	2.375	520

Meets NEMA TC 6 and 8 and ASTM F 512

Telephone Duct - Type C

	Trade Size	Part Number	Average O.D.	Minimum Wall	Weight Per Foot	Crate Quantity
			(in)	(in)	(lb)	(ft)
White	4	924572	4.350	0.149	1.493	1260
Gray	4	924301	4.350	0.149	1.493	1260

Meets CAO 8546

Type C duct has minimum pipe stiffness of 120 lbs/in/in

Item availability may vary by region.

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.
800.882.5543

