



## 1. Product and Company Identification

**SDS Seal N Shine** 

Eazy Gleam Products Pty Ltd 36 Richland Avenue Coopers Plains Queensland 4108 Phone Emergency Contact: (07) 04 sales@eazygleam.com.au

Phone (07) 3274 2593 (07) 0419 714 909

Fax (07) 3277 2450 Poisons Information Centre **13 11 26** 

Product Name: Product Code: Intended Use:

# **Seal N Shine**

SNS1, SNS4, SNS20, SNS205 A clear high gloss silicone cleaner and protectant for bumpers, tyres, side mouldings, mud flaps and silicone lubricant and release agent for food packaging.

## 2. Hazards Identification

Hazardous Chemical according to classification by Safe Work Australia Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail

GHS Classification:	Flammable Liquid Category 2 Aspiration Hazard Category 1 Toxic to reproduction Category 2 Skin Corrosion/Irritation Cat 2 Chronic Aquatic Toxicity Category 2 Specific Target Organ Toxicity (single exposure) Category 3 Specific Target Organ Toxicity (repeated exposure) Category 3
GHS Signal Word:	DANGER
Hazard Statement:	H225 Highly flammable liquid and vapour, H304 May be fatal if swallowed and enters airways H315 Causes skin irritation H336 May cause drowsiness or dizziness H373 May cause damage to organs through prolonged or repeated exposure H361 Suspected of damaging the unborn child H411 Toxic to aquatic life with long lasting effects
Precautionary Statement	ts:
General:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use.
Preventative:	<ul> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground/bond container and receiving equipment.</li> <li>P241 Use explosion proof electrical/ventilation/lighting equipment</li> <li>P242 Use only non-sparking tools</li> <li>P243 Take precautionary measures against static discharge</li> <li>P260 Do not breathe mist/vapours/spray</li> <li>P261 Avoid breathing mist/vapours/spray</li> <li>P264 Wash thoroughly after handling.</li> <li>P271 Use only outdoors or in a well ventilated area.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/eye protection/face protection</li> <li>P281 Use personal protective equipment as required.</li> </ul>
Response:	P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician P302+ P352 IF ON SKIN: Wash with plenty of soap and water P303 + P361 + P353 IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water /shower P308 + P313 If exposed or concerned: Get medical advice/attention

	P304 + P340 If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P331 Do NOT induce vomiting.
	P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
	P314 Get medical advice/attention if you feel unwell.
	P332 + P313 If skin irritation occurs: Get medical advice/attention
	P362 Take off contaminated clothing and wash before reuse.
	P370 + P378 In case of fire: Use foam/water pray/fog for extinction.
	P391 Collect spillage.
Storage:	PP403 + P233 Store in a well ventilated place. Keep container tightly closed.
-	P405 + P235 Store locked up. Keep cool.
Disposal:	P501 Dispose of contents/container in accordance with local regulations.

# 3. Composition / Information on Ingredients

## **Ingredients Names and Proportions**

<b>Chemical Entity</b> Solvent naphtha (petroleum) Light aliphatic With components:	Cas Number 64742-82-1	Proportion(%) 100
n-Hexane	110-54-3	10 - 30
Ethylbenzene	100-41-4	<5
Remianing ingredients are not considered hazardous		

	4. First aid Measures		
In case of eye contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. If irritation persists transport to nearest medical facility for additional treatment.		
In case of skin contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available		
If Ingested:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.		
If Inhaled:	Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.		
Symptoms caused by e	exposure		
Inhalation:	Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.		
Skin:	May include burning sensation and or a dried/cracked appearance.		
Eyes: Ingestion:	May include burning sensation, redness, swelling and or blurred vision. May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.		

#### Medical attention and special treatment

Treat symptomatically

5. Fire Fighting Measures		
Suitable Extinguishing Media:	Foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet	
Specific Hazards arising from the Chemical:	Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface of water. Vapour is heavier than air, can spread along ground and distant ignition is possible.	
Special protective equipment for fire fighters:Wear full protective clothing and self contained breathing apparatus. Hazchem code 3Y		
6. Accidental Release Measures		

Seal N Shine

Personal Precautions:         Avoid contact with spilled or released material. Shut off leaks, if possible without personal insis. Isolate hazard area and dery ently to unnecessary or unprotected personel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.           Environmental Precautions:         Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using of gs prays. Ventilate contaminated area thoroughly.           Methods of cleanup:         For small spills (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or self disposed. Nilow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (<1drum), transfer by means such as a vacuum truck to a saivage tank for recovery or self disposed or such as a vacuum truck to a saivage tank for recovery or disposed to such as a vacuum truck to a saivage tank for recovery or disposed to flow any residues to evaporate or use an appropriate absorbent material and dispose of safely.           Precautions for safe handling:         Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated areas.           Conditions for safe storage:         Store in a well ventilated area, areas the vapor of such as a count material and dispose of safely.           Disposure Controls and Personal Protection         Enserelectrical continuity by earthing all equipment. Flameproof equip		- 3 -	
and enfering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct is flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.         Methods of cleanup:       For small splis (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or addie disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (>1 drum), transfer by means such as a vacuum truck to a safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.         Procautions for safe handling:       Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat. drink or smoke in contaminated areas. Electrostatic closcharge may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.         Conditions for safe storage:       Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near aerosols, strong oxidants and corrosives.         Exposure Control Measures:       From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Heakarie. ??Zmg/m12(20pm) TWA (8tr)         Biological Monitoring:       No biological limit allocated	Personal Precautions:	risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static	
product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (>1/drum), transfer by means such water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. <b>F. Handling and Storage</b> Precautions for safe handling:       Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing, Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.         Conditions for safe storage:       Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near aerosols, strong oxidants and corrosives.         Exposure Control Measures:       From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Hexane: 72mg/m <sup>2</sup> (20pm) TWA (8hr)         Biological Monitoring:       No biological limit allocated.         Engineering Controls:       Ensure that dequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.         Individual Protection       Wear safety goggles.         Skin protection: <th>Environmental Precautions:</th> <th>and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate</th>	Environmental Precautions:	and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate	
Precautions for safe handling:       Highly flammable product. Avoid breating vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.         Conditions for safe storage:       Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near aerosols, strong oxidants and corrosives. <b>Exposure Controls and Personal Protection</b> Exposure Control Measures:       From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Hexane: 72mg/m³ (20ppm) TWA (8hr)         Biological Monitoring:       No biological limit allocated.         Engineering Controls:       Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.         Individual Protection       Wear safety goggles.         Skin protection:       Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.         Respiratory protection:       If work practices do ont maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When usin	Methods of cleanup:	product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (>1drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate	
in a well-ventilated area. Ensure that the workplace is ventilated such that the         Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing.         Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas.         Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.         Conditions for safe storage:       Store in a well ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near aerosols, strong oxidants and corrosives.         Exposure Control Measures:       From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Hexane: 72mg/m <sup>2</sup> (20pm) TWA (8hr)         Biological Monitoring:       No biological limit allocated.         Engineering Controls:       Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.         Individual Protection       Wear safety goggles.         Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.         Respiratory protection:       If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point ~65°C), re		7. Handling and Storage	
Individual Protection       Wear safety goggles.         Skin protection:       Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.         Respiratory protection:       If work practices do not maintain airborne levels below the exposure standard, use appropriate respirators should comply with AS1716 or an equivalent approved by a state/territory authority.	Precautions for safe handling:	in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or	
Exposure Control Measures:       From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Hexane: 72mg/m³ (20ppm) TWA (8hr) Shell X55: 450mg/m³ TWA (8hr)         Biological Monitoring:       No biological limit allocated.         Engineering Controls:       Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.         Individual Protection Measures:       Eye and face protection:         Skin protection:       Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.         Respiratory protection:       If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.         Thermal Hazards:       Not applicable.			
n-Hexane: 72mg/m³ (20ppm) TWA (8hr) Shell X55: 450mg/m³ TWA (8hr)Biological Monitoring:No biological limit allocated.Engineering Controls:Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.Individual Protection Measures:Wear safety goggles.Eye and face protection:Wear safety goggles.Skin protection:Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.Respiratory protection:If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.Thermal Hazards:Not applicable.		8. Exposure Controls and Personal Protection	
Engineering Controls:Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.Individual Protection Measures: Eye and face protection:Wear safety goggles. Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.Respiratory protection:If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.Thermal Hazards:Not applicable.	Exposure Control Measures:	n-Hexane: 72mg/m <sup>3</sup> (20ppm) TWA (8hr)	
Individual Protection Measures: Eye and face protection:Wear safety goggles. Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.Respiratory protection:If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.Thermal Hazards:Not applicable.	Biological Monitoring:	No biological limit allocated.	
Eye and face protection:Wear safety goggles.Skin protection:Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.Respiratory protection:If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.Thermal Hazards:Not applicable.	Engineering Controls:	recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep	
Skin protection:       Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for incidental splashes.         Respiratory protection:       If work practices do not maintain airborne levels below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.         Thermal Hazards:       Not applicable.	Individual Protection Measures:		
appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.         Thermal Hazards:       Not applicable.	, i	Use solvent resistant gloves, nitrile for longer term protection of PVC and neoprene for	
		appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point >65°C). respirators should comply with AS1716 or an equivalent approved by a state/territory authority.	
9. Physical and Chemical Properties			
		9. Physical and Chemical Properties	

Colourless Liquid Appearance: Density (g/ml@15°C): Odour: Solubility (kg/m<sup>3</sup>): Parafinic sweet Auto ignition temp (°C) Initial Boil point range: 50 - 135°C Vapour Density: Flash point: -30°C (Abel) >1 Flammability: Highly flammable (air=1@15°C) Vapour pressure: Typical 34.5 Upper/lower flammability: 1.0 – 7.5 (kPa@20°C) or explosive limits (%)

0.67 – 0.755 Not miscible with water 280 (ASTM E-659) >1

Seal N Shine

## 10. Stability and Reactivity

Reactivity: Chemical Stability: Possible Hazardous reactions: Conditions to avoid: Incompatible materials: Stable under normal conditions of use Stable under normal conditions of use Stable under normal conditions of use Avoid heat, sparks, open flames and other ignition sources Strong oxidizing agents.

**Hazardous Decomposition products:** Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

#### **11. Toxicological Information**

Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 2000 mg/kg
Skin corrosion/irritation:	Irritating to skin. Prolonged contact may cause defatting of skin which can lead to dermatitis.
Serious eye damage/irritation:	Expected to be non-irritating to eyes.
Respiratory or skin sensitisation:	Not expected to be a sensitiser.
Germ cell mutagenicity:	Not mutagenic.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Causes foetus toxicity in animals at doses which are maternally toxic. Affects reproductive system in animals at doses which produces other toxic affects (n-Hexane).
Specific Target Organ Toxicity (STOT) – single exposure:	Not expected to be a respiratory irritant.
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system.
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **12. Ecological Information**

#### Ecotoxicity

#### Acute toxicity:

Fish –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/I
Aquatic invertebrate –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/l
Algae –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/I
Microorganisms –	Expected to be harmful: 1 < LC/EC/IC50 <= 10mg/l

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available

Algae –	Data not available
Microorganisms –	Data not available

#### Persistence and degradability

Readily biodegradable. Oxidises by photo-chemical reactions in air.

### Bioaccumulative potential

Has the potential to bioaccumulate.

#### Mobility in soil

Floats on water. Absorbs on soil.

### **13 Disposal Considerations**

Ensure waste disposal conforms to local waste disposal regulations.

14. Transport Information		
UN number:	1268	
Proper shipping name:	Petroleum Distillates, N.O.S. (solvent naphtha)	
Australian Dangerous Goods class:	3	
Australian Dangerous Goods packing group:	11	
Hazchem code:	3YE	

15. Regulatory Information	
Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14

### 16. Other Information

The information herein is, to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions of application are beyond our control, Eazy Gleam Products does not accept liability for any damages resulting from the use of, or reliance on, this information, in inappropriate contexts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State and Local Government regulations.

Date: 2 November 2016