

MAKING BONDS AS STRONG AS STEEL





At ORIENTAL we are proud of our heritage of supplying high quality conveyor belts to discerning customers across the globe.

In 1954 when we manufactured our first conveyor belt, to the introduction of the country's first Nylon-Nylon synthetic fabric reinforced belt in 1978, Oriental Rubber has been a pioneer in the design and development of critical applications.

Our proven success in establishing new generation products such as the MAXX ARMOUR[™] and POWERSAVE[™] belts has now led to enhancing our range of the MAXX STEELFLEX[™] belts using steel cord as the high tensile bearing member.

In order to complete our portfolio of belts and meet the demands of our valued customers, Oriental is now offering MAXX STEELFLEX[™] belts with steel reinforcement upto 2400 mm wide.

With this addition, we are strengthening our partnership with you....**MAKING BONDS AS STRONG AS STEEL!**



ALL

THE

MILESTONES



Addition of belt press line in South Africa



C O N V E Y

ALL

ТНЕ

WAY

PRODUCT RANGE

Belts are available with a high tensile heavy duty steel cord in the following variants:





BELT SELECTION CHART

Туре	Rated Break Strength	Minimum Cord Diameter	Cord pitch	Approx Carcass Weight	Reference elongation at 1/7th minimum breaking strength	Min Cover Thickness	Min Drive Pulley Diameter (60-100% load factor)	Elastic Modulus
UoM	N/mm	mm	mm	kg/m ²	%	mm	mm	N/mm
ST 500	500	2.8	14	5.3	0.1-0.3	4	500	35000
ST 630	630	2.8	11	5.8	0.1-0.3	4	500	44100
ST 800	800	3.2	12	6.7	0.1-0.3	4	500	56000
ST 1000	1000	3.6	12	8	0.1-0.3	4	630	70000
ST 1250	1250	4.3	14	9.7	0.1-0.3	4	630	87500
ST 1400	1400	4.5	14	10.3	0.1-0.3	4	800	98000
ST 1600	1600	5.2	15	12.1	0.1-0.3	4	800	112000
ST 1800	1800	5.1	13.5	12.4	0.1-0.3	4	800	126000
ST 2000	2000	5.1	12	13.2	0.1-0.3	4	800	140000
ST 2250	2250	5.2	11	14.2	0.1-0.3	4	800	157500
ST 2500	2500	6.8	15	17.8	0.1-0.3	5	1000	175000
ST 3150	3150	7.4	15	20.3	0.1-0.3	6	1250	220500
ST 3500	3500	8	15	22.5	0.15-0.3	6	1250	245000
ST 4000	4000	8.6	15	26	0.15-0.3	7	1250	280000
ST 4500	4500	9.4	16	28	0.15-0.3	7	1400	315000
ST 5000	5000	10.4	17	31.4	0.15-0.3	8	1600	350000
ST 5400	5400	10.8	17	32.9	0.15-0.3	8	1600	378000
ST 6300	6300	11.8	17	39.5	0.15-0.3	9	1800	441000
ST 7100	7100	12.8	18	48.5	0.15-0.3	9	1900	497000

Notes

The above values are based on ISO 15236. Other combinations are also offered on request.

The above values are given for the design purpose only.

Oriental reserves the right to change these values without notice, in tune with technical development.

2 2 For calculation of belt weight, consider weight of 1 mm thick cover =1.11kg/m² for M grade ; = 1.26 kg/m² for FR grade.

ALL

ТНЕ

WAY

COVER GRADE SELECTION

Cover Type	Standard & Grade	Min. Tensile Strength (MPa)	Min. Elongation at break (%)	Max. Abrasion loss (mm3)	Appliction characteristics	Reference Material	
	DIN- X	25	450	120			
	SANS-M	25	450	120			
	AS-M	24	450	150			
	IS-M24	24	450	150	Suitable for	Iron ore, coal,	
	BS-M24	24	450	150	lumps, sharp	lignite,	
	ISO-H	24	450	120	edged rugged material	limestone rock etc.	
	DIN-Y	20	400	150			
	SANS-C	20	400	150			
	JIS-S	18	450	200			
General Purpose	SANS-N	17	400	150			
	Purpose AS-N		400	200			
	IS-N17	17	400	150			
	BS-N17	17	400	150	a italia fan		
	RMA1	17	400	150	conveying	sand,	
	ARPM RMA I	17	400	125	moderately	wood chips etc	
	DIN-Z	15	350	250	abrasive material		
	ISO-L	15	350	200			
	RMA2	14	400	200			
	ARPM RMA II	14	400	175	_		
	DIN-W	18	400	90			
	ISO-D	18	400	100	Cut & gouge	sharp big lumps with abrasive	
Abrasion	HAR	18	400	90	abrasion		
Resistant	SAR	17	400	70	resistance properties	fine & granular	
	AS-A	17	400	70	properties	materials	
	ISO-Ka	20	400	200			
	FR-IS	17	350	175		$\sim \sim $	
	FR-ISO 340	15	350	175			
Fire Resistant	FR-SANS F	15	350	110	Excellent		
for	FR-DIN K	15	350	175	flame	Coal, Minerals	
application	FR-DIN S	15	350	175	propagation &	a ores	
	FRAS-F	15	350	175	_ low burning rate.		
	FR-CAN CSA-C	15	350	175	_		
	FR-MSHA-2G	15	350	175			
FR for under	MSHA-BELT	15	350	110	suitable for		
ground application	FRUG-AS	15	350	100	- underground coal conveying	Coal	
	IS HRT1	12.5	350	250	suitable for	coko	
Heat Resistant	IS HRT2	12.5	12.5 350		medium	casting sand,	
	DIN T	12.5	350	250	upto 150°c	clay etc.	
	IS-OR	12	250	175	suitable for oily	oil treated	
Oil Resistant	AS-Z	12	250	175	materials, high	tertilizers, oil coated products,	
	DIN-G	12	250	175	resistance.	other abrasive materials	

Note: Special Grades available on request.

COVER THICKNESS:

Minimum cover thickness of a steel cord belt should not be less than 0.7 times the cord diameter. Grade of the top cover is a function of the characteristic of the material to be conveyed and the operating condition of the conveyor. Additional thickness is therefore generally required which is guided by the following table as given in DIN 22101.

COVER LAYERS

Determina	tion of the stan o	dard values fo f carrying side	or additions to the mine cover layers	nimum thickness		
Characteri	stics and their a	ssessment	Sum of assessment values	Addition to minimum thickness, mm (standard values)		
Loading	Favourable	1				
conditions	Average	2	5 to 6	0 to 1		
conditions	Unfavourable	3				
Looding	Low	1				
frequency	Average	2	7 to 8	1 to 3		
nequency	High	3				
	Small	1				
	Average	2	9 to 11	3 to 6		
particle size	High	3				
	Low	1				
Bulk density	Average	2	12 to 13	6 to 10		
	High	3				
	Low	1				
Abrasiveness	Average	2	14 to 15	> 10		
	High	3				

Example: Let us consider a conveyor system where the parameters are as follows:

Parameters	Characteristics	Assessment Values
Loading Condition	Average	2
Loading Frequency	High	3
Maximum Particle Size	Small	1
Bulk Density	Average	2
Abrasiveness	Average	2

The sum of assessment value is therefore 10, which falls in the group of 9-11.

A minimum of 3-6 mm of cover thickness should therefore be added to the minimum carry cover thickness(which is 0.7 times of cord diameter or 4 mm whichever is higher).

$\mathsf{C} \ \mathsf{O} \ \mathsf{N} \ \mathsf{V} \ \mathsf{E} \ \mathsf{Y}$

TRANSITION DISTANCE

The distance between the terminal pulley and the first fully troughed idler at lead end or tail end of the conveyor should be adequate so that the edges of the belt are not overstressed. Design values for transition distance are given in the following table.

ALL



ТНЕ

TAKE UP

Main function of the take up is to maintain adequate tension throughout the entire stretch of the conveyor belt during its operation and also in the idle condition. The length of the take up is dependent upon the elongation of the conveyor belts. The total elongation of the steel cord belt including permanent and elastic elongation is limited to 0.3%.

The take up length is calculated as

 $T_1 = 0.3\%$ of C-C distance of conveyor

It is however advisable to keep some extra length in the take up for any additional splice required.

	Transition Distance (mm)											
Polt width in	Pu	lley Not Lif	ted	Pulley	lifted to 1/	3 depth	Pulley lifted to 1/2 depth Transition Distance (mm)					
mm	Transit	ion Distanc	e (mm)	Transit	ion Distanc	e (mm)						
	20 °	35 °	45 °	20 °	35 °	45 °	20 °	35 °	45 °			
800	1200	2080	-	1000	1720	-	800	1280	-			
1000	1500	2600	3300	1250	2150	2700	1000	1600	2000			
1200	1800	3120	3960	1500	2580	3240	1200	1920	2400			
1400	2100	3640	4620	1750	3010	3780	1400	2240	2800			
1600	2400	4160	5280	2000	3440	4320	1600	2560	3200			
1800	2700	4680	5940	2250	3870	4860	1800	2880	3600			
2000	3000	5200	6600	2500	4300	5400	2000	3200	4000			
2200	3300	5720	7260	2750	4730	5940	2200	3520	4400			
2400	3600	6240	7920	3000	5160	6480	2400	3840	4800			

CONVEY

ТНЕ

VERTICAL CURVES:

Vertical curves in belt conveyors are most commonly used to negotiate the bends or to get access to the next conveyor for discharge. However it is to be ensured that there is no lifting of the belt from the idlers or there is no undue stress at the edge of the belt.

ALL

CONCAVE CURVE: The design values for the minimum radius of curvature are derived from the following equation:



Conveyor installation with concave and convex transition curves

CONVEX CURVE: The design values for the minimum radius of curvature for conveyor with three-part-equal-length idler arrangement are as per the following table:

	Minimum radius of curvature in meter									
Belt width in mm	Troughing angle									
	20 °	35 °	45 °							
800	30	49	61							
1000	37	62	76							
1200	44	74	91							
1400	52	86	107							
1600	59	99	122							
1800	66	111	137							
2000	74	123	152							
2200	81	136	167							
2400	88	148	183							

RIP PROTECTION

RIP CHECK BREAKER

On request by the customer, Oriental MAXX STEELFLEX[™] is embedded with high strength textile weft fabric, to protect the belt from through cut. It hinders the penetration of foreign material into the conveyor belt and acts as a barrier against ripping.

The high elongation of the transverse reinforcement is advantageously used to maintain the flexibility of the belt and does not have any adverse effect on the pulley diameter.

up to 3.5 M tall

STEEL BREAKER

Insertion of steel breaker as transverse reinforcement greatly enhances the rip resistance of the conveyor belt. High flexibility of the steel breaker does not impair the trough ability of the belt.

RIP DETECTION SYSTEM

This system is used in combination with sensor loop and a series of transmitter and receiver sets with PLC. The sensor loops are embedded under the carry cover of the conveyor belt at regular intervals. As soon as a rip is detected the PLC commands the motor to stop, further damage to the belt is thus avoided.

Reel Diameter (mm)															
Belt Length (m)							Belt Th	icknes	s (mm)					
	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40
100	1240	1340	1430	1520	1600	1680	1750	1830	1890	1960	2020	2090	2150	2210	2260
125	1390	1500	1600	1700	1790	1880	1960	2040	2120	2190	2260	2330	2440	2470	2530
150	1520	1640	1750	1860	1960	2060	2150	2230	2320	2400	2480	2550	2630	2700	2770
175	1640	1770	1890	2010	2120	2220	2320	2410	2500	2590	2680	2760	2840	2920	2990
200	1750	1890	2020	2150	2260	2370	2480	2580	2680	2770	2860	2950			
225	1860	2010	2150	2280	2400	2520	2630	2740	2840	2940					
250	1960	2120	2260	2400	2530	2650	2770	2880	2990						
275	2060	2200	2370	2520	2650	2780	2910								
300	2150	2320	2480	2630	2770	2910									
325	2230	2410	2580	2740	2880										
250	2320	2500	2680	2840	2990										
275	2400	2590	2770	2940											
400	2480	2680	2860												
425	2550	2760	2950												
450	2630	2840	-												
475	2700	2920													
500	2770	2990													
525	2840														
550	2910														
575	2970														

REEL DIAMETER

Note: It is possible to supply belts in higher length in elliptical reels.

$\mathsf{C} ~\mathsf{O} ~\mathsf{N} ~\mathsf{V} ~\mathsf{E} ~\mathsf{Y}$

ORIENTAL follows a documented quality management system for ensuring reliable and consistent quality. It is certified ISO 9001:2008 quality management system and has NABL accredited laboratory.

ALL

THF

Raw materials are procured from selected vendors as per the agreed specification and undergo qualifying tests as per the quality assurance plan before being used.

The recipe of the rubber mix is formulated to achieve the best of physical properties to ensure a long life of the MAXX STEELFLEX[™] conveyor belt. All the batches from the mixer undergo rheological analysis in the Monsanto rheometer.

Cord pull out test is carried out for steel cords in the universal testing machine before being released for production.

Finished steel cord conveyor belts are visually inspected and tested to verify their conformance with the customer's specifications and their sustainability for the desired application.

Oriental Rubber has the most modern rubber testing laboratory to ensure conformance of the product with the international standards. Important technical parameters are tested in the fully equipped laboratory, some of which are given below.

A. Compounds	D. Pipe Conveyor
Oscillating die rheometer	3-point bend test
Moving die rheometer	Pipe – outward force testing machine
Mooney viscometer	Pipe – Bending test rig
Air circulating ageing oven	Troughability
Swelling	Pipe fatigue test
B. Destructive Tests	Aspect ratio of pipe under load and no load
Load cyclic fatigue test	conditions
10T UTM machine – Rip/Tear resistance	E. Fire Retardant Tests
25T cord breaking strength	Flame test chamber (ISO/CAN/SANS/AS/IS)
Abrasion tester	Drum friction test(ISO/CAN/SANS/AS/IS)
Troughability	Propane midscale gallery test (MSHA)
Scott fatigue test	Methane midscale gallery test (SANS)
C. New Generation Belt Test	LOI testing
Rip Resistance	Antistatic test
Impact Resistance	
Tear Resistance	

Manufacture of the MAXX STEELFLEX[™] belts are carried out in the latest steel cord line, which ensures equal tension on all the cords during vulcanization. Online records of vulcanization are maintained.

WAY

up to

50 Tons

heavy

INDUSTRIES



Mining

Steel

Cement

Ports

Power



Locations shown are for graphical representation only. Map is not to scale.

Oriental Rubber Industries Pvt. Ltd.

Corporate Office: Shravani Gardens, 20, Viman Nagar, Nagar Road, Pune - 411 014. INDIA. € +91-20-6627 0800 Email: info@orientalrubber.com

68



Oriental Rubber Industries Pvt. Ltd. Gat No. 525 Koregaon Bhima, Tal-Shirur Pune - 412 216. INDIA.



Oriental Rubber Industries Pvt. Ltd. Gat No. 735 Karandi, Tal-Shirur Pune - 412 210. INDIA.



Oriental Rubber Industries SA (Pty) Ltd: 523 Commissioner Street, Boksburg PO Box 6159 Dunswart 1508, Gauteng South Africa info@orientalrubber.co.za | +27 (11) 914 1738





tion only without any warranties of any kind. Use of this information is at the sole risk of user/ ormation/Data provided in this Brochure is for ge eral info Oriental Rubber Industries P. Ltd. and its associate companies/Directors/Employees assume no responsibility for the accuracy, completeness or reliability of saic Information/data and shall not be liable for any damages arising from its use. Specifications/Parameters may change without prior notice.

