



RAPID SET

RAPID SET is a specially blended copolymer emulsion containing fast drying modifiers which enhances asphalt sealers to achieve a faster drying time. **RAPID SET** has a resistance to oils, fuels and grease. Use **RAPID SET** where increased durability is needed, excellent for airport runways and taxi areas, along with all commercial and industrial properties

Coverage

Mix well before using, add after sealer has been diluted. Use 3 to 5 gal to every 100 gal of concentrated asphalt emulsion, depending on porosity.

Smooth to medium surfaces: 2 gal to every 100 gal of concentrated asphalt emulsion.

Rough to excessively rough surfaces: 3 to 5 gal to every 100 gal of concentrated. Asphalt emulsion with 2 lbs. additional Sand 60 mesh.

Method of Application

Add sealer into agitated machine, add water, then slowly mix in **RAPID SET** while agitating. Add any additional sand (4 lbs per gal max.) Mix well before application.

Weather Limitations

For best results, do not apply on rainy days or when temperature is expected to drop below 45° F during the next 24 hrs. On hot days, pavement shall be pre-dampened with a fog system.

Drying Time

4 hrs or less at 70°F, 50% humidity, depending on percentage add and application thickness.

Color
Light Brown

Clean Up
Water when wet,
Bio D ® when dry.

Packaging
5 gal pails
55 gal drums