

BREWER COTE®

The Pavement Maintenance Specialists of Arizona
Est 1979



For
Rent

Trailer Mounted Heated Emulsion Sprayer

FEATURES

5' Aluminum spray wand with 35 1/2 " hose
Round "U" bottom for easy cleaning & 3' drain
Gear pump rated minimum 10 gal per minute
Circulation and bypass control for wand pressure
Large 16" lockdown removable manway
20 lb propane tank, regulator and pressure gauge
150,000 btu propane burner, removable hand torch
Honda Engine with 6:1 gear reduction drive
Lower engine speed means longer pump life
8 gal flush tank for clean out of pump and wand
3" heat tube, vented to haet pump (pump enclosed)
3" welded steel channel frame, fenders & tail light guards
Expanded metal sides for safer "standing while filling"
2000 # jack stand, swivel and electric brakes
Front storage area with tie downs
Pintle Hitch

SKID MOUNTED UNIT SPECIFICATIONS

Model QS/E	250 gal
Height	4"
Length	7'6"
Width	3'6"
Weight	850 lbs

ENGINE SPECIFICATIONS

GX Honda Engine with
6:1 Gear Reduction

PUMP SPECIFICATIONS

1" Positive Displacement
Gear Pump

5226 W. Missouri Avenue Glendale Arizona 85301
www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com