

BREWER COTE [®] *Of Arizona*

BREWER COTE PORTABLE PUMP KIT 2

BC-PPK 2 #480442

The 5.5 HP Power Built OHV Engine runs our 1 ½” Nomad Gear Pump with ease. It is Designed for a multitude of uses, capable of pumping tack, crack filler and other Asphalt or coal tar emulsions straight from the drum, or mounted to your buck tank. Viscous sealers may also be sprayed if connected with gravity flow.

FEATURES

- 5.5 HP Power Built OHV with 6 to 1 Gear Reduction
(Lower engine speed means longer pump life!)
- 1½” Nomad Pump rated a minimum of 10 GPM
- Tee Inlet for Priming and Washout
- 30’ x ½” High pressure Spray Hose – 5’ Aluminum Wand
- 10’ x 1” Suction Hose with connections for Gravity Feed
- Adjustable Pressure Relief Valve
- All Steel Plumbing (No Heat problems)
- 1 yr. Manufacturer’s Warranty

OPTIONS

- 5.5 HP Honda Engine (with low oil shut down)
- 50’ Spray Hose and 6’ Wand
- 1½” Basket Type Strainer
- Hose Reels (manual and spring loaded)

SPECIFICATIONS

Weight	75 lbs.
Length	30”
Width	16”
Height	14”

PUMP SPECIFICATIONS

- 1½” Nomad Positive Displacement Gear Pump
- 1 yr. Manufacturer’s Warranty

ENGINE SPECIFICATIONS

- 5.5 HP Power Built OHV
- 6 to 1 Gear Reduction
- 1 yr. Manufacturer’s Warranty

“The Pavement Maintenance Specialists”

5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com

BREWER COTE *Of Arizona*®

BREWER COTE PORTABLE PUMP KIT 3

BC-PPK-3

#480443

The Brewer Cote Portable Pump Kit is designed for a multitude of uses will draw from drums and tanks to spray SS1H and other less viscous materials. High viscosity materials such as coal tar emulsions should be set up with gravity feed or drums may be laid on their side to allow material to flow.

FEATURES

Complete Briggs & Stratton 8 HP engine with 6 to 1 gearbox
1½" Bowie Pump equipped with bypass control valve, to regulate Pressure.

#9100 Rubber geared rotary pump, capacity 30 GPM.

1½" Basket type strainer for priming, washout

Important: Pump must be primed through strainer Before starting.

Complete aluminum spray wand 30' x 3/4", High-pressure spray hose,
10' x 1", Suction hose with connections for gravity feed.

Unit built on channel with handles, two men can move easily
weight 150 lbs., length 36", width 26", height 21".

WARRANTY

All parts have full warranties for 1 year (for defective workmanship), though We stress again the importance of priming the pump due to the problem of friction that will cause severe damage to the gears if not lubricated. Service and accessories are available at Brewer Cote Office, along with specifications and/or Technical Service.

"The Pavement Maintenance Specialists"

5226 W Missouri Avenue, Glendale, Arizona 85301

www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com