

BREWER COTE® *Of Arizona*



The QwikFire Cracksealant Melter was designed for the serious applicator, by experienced Pavement Maintenance Specialists. This gravity flow, (pump system optional) oil jacketed workhorse is powered by an 8 hp electric start engine, including quick heat up (less than 1 hr.) and quiet operation. Electronic ignition, material, and oil thermostats, you don't have to worry about over-heating and additional training. Our hydraulic controlled auger mixing system actually grinds the cold sealant for excellent recovery and performance. The QuickFire Melter features the lowest (46") sealant loading deck in the industry and has a comfortable curbside operation. The U design allows material to flow to the rear for the most efficient application and with the removable top, the easiest to clean.

Features

- Oil jacketed design that completely wraps around to allow heat up time in less than an hr.
- 1" Thick high temperature ceramic insulation.
- Electronic ignition to avoid overheating material, and temperature control on both material and oil.
- 8 hp Briggs and Stratton engine with electric start and charging.
- Bolt on lid for easy cleaning and agitator maintenance.
- Sealed agitator shaft with grease zerk.
- Drag King and V Squeegee Hangars
- 500,000 BTU Hand Torch with hose for warming application tools
- The Tank and Oil Jacket is designed with 3/16" gauge steel, the inner heat shield is 10-gauge steel.
- Hydraulic Speed control mixer, with forward and reverse

Options

- | | |
|---------------------------------|--------------------------------------|
| 8 hp Honda Engine | 11 hp Propane Engine |
| Additional Propane Tank | 2 5/16" Ball Hitch (Pintle included) |
| Special Paint | Deck Insulation |
| Custom Configurations | Pump Systems |
| (Built to mount across trailer) | (13 hp Upgrade) |
- * All specifications are subject to change without notice

Specifications

	<u>50 gal Skid</u>	<u>50 gal</u>	<u>75 gal</u>	<u>100 gal</u>	<u>100 gal pumper</u>
Weight	450 lbs	1000 lbs	1250 lbs	1500 lbs	2000 lbs
Length	6'-0"	10'-6"	12'-0"	12'-8"	15'-4"
Width	3'-10"	5'-3"	5'-3"	5'-3"	6'
Height	2'-6"	4'	4'	4'-6"	4'-10"
GVW	—	2,000 LB	2,500 LB	3,000 LB	3,500 LB

Specifications

Optional Pump Specification's
 1 1/2" Flowserve Pump with bypass for Circulation
 24 volt Electrical Heated 20' Hose w/Trigger pump Control
 1 yr. Manufacturer's Warranty

Standard Engine Specification's
 8 hp Electric Start Briggs & Stratton Intek I/C
 1 yr. Manufacturer's Warranty

If you don't see what you're looking for ask your Brewer Rep ~ Trailer Spec's referenced

BREWER COTE OF ARIZONA INC ® 'THE PAVEMENT MAINTENANCE SPECIALISTS'
 5226 W. MISSOURI AVENUE, GLENDALE, ARIZONA 85301

WWW.BREWERCOTEAZ.COM TEL. 623-931-3728 TOLL 888-931-3728 FAX 623-842-0714 SALES@BREWERCOTEAZ.COM