

BREWER COTE [®] *of Arizona*

Specifications

Universal Aro-1 Air Operated Double Diaphragm Pump

This air operated double diaphragm pump should be the manufacturers current production model. This unit shall be capable of pumping and applying, without any further equipment modifications, all approved grades of cold applied asphalt rubber sealants, specification joint sealants and fiber modified sealants. All qualified bidders must have and maintain a complete inventory of repair parts as well as having experienced service personnel for this equipment. A factory trained person shall be made available for initial start-up and training in the operation of the pump.

Body Construction
Aluminum – Lube Free

Diaphragm
Buna

Drum Pump Kit
Polypropylene Suction Pipe
Steel Drum Lid w/hinge loading Hatch

Sealant Hose

Hose should be $\frac{3}{4}$ " inside diameter(I.D.) and not less than 25 ft in length, nylon braid reinforced with quick clamp disconnect to the pump. The hose is specifically manufactured for the handling of cold applied petroleum based product

Applicator Wand

The wand applicator shall be constructed of Steel with sufficient strength to stand up to normal day-to-day operation. It shall have two handles, one of which is connected to a quarter turn ball valve used to control flow material. Support handle to be attached to wand. A variety of nozzles are available and attachable to the applicator wand.

"The Pavement Maintenance Specialists"

5226 W Missouri Avenue Glendale Arizona 85301

www.brewercoteaz.com Tel.623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sales@brewercoteaz.com