

Brewer Cote *of Arizona* ®



RHINO HIDE

is a blend of emulsified asphalt, clean aggregate modifiers, fiber, rubber & drying agents. Designed especially for heavy duty repairs of alligatoring and Skin patching, along with serious crack repair. Rhino Hide can be used to build up depressions, fill expansion joints and wide cracks or any other job requiring a Towel Grade, heavy duty, fast drying modified asphalt.

The Pavement Maintenance Specialists

RHINO HIDE

SURFACE PREPERATION

Surface must be dry, clean, and free from all loose material, dirt, and dust.

APPLICATION

Pour/trowel into alligator areas and work with squeegee.

FILLING ALLIGATORRED AREA

Pour in alligatorred areas and work with squeegee, feather in edges

FILLING CRACKS

Fill cracks, scrape excess from surface before setting.
(Use V-shape squeegee).

FILLING "BIRD BATHS"

Fill with lifts of 1" depth maximum, allow to harden before applying seal coating. A second coat can be applied after the 1st coat dries to blend better with the sub strait. If traffic cannot be avoided after 4 hrs., cover area. Clean area of all dirt, dust and loose with band before opening for traffic material. Surface must be dry and clean

WEATHER LIMITATIONS

For best results, do not use when rain is in the forecast and temperature is not expected to drop below 55° F. Rhino Hide is no substitute for properly replaced asphalt, Rhino Hide will prolong the life of the deteriorated asphalt

DRYING TIME

½" Lifts; 4 hrs., 1" Lift; 6-8 hrs., based on 77° F, 50% Hum. Test for traffic ability before opening. If traffic Must be opened, broadcast with sand.

COVERAGE

5 Gal covers: 8 sq./ft
1" thick 96 ln/ft @ 1"x 1"

CLEAN UP

Paint Thinner or
Biodegradable solvents.

COLOR

Black, when dry

PACKING:

5 gal pails
55 gal drums.

NOTE:

Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100° F.



www.brewercoteaz.com Tel 623-931-3728 Toll 888-931-3728 Fax 623-842-0714 sale@brewercoteaz.com