

AR-92

Asphalt Release Agent

AR-92 is a water soluble release agent which prevents asphalt from sticking to the sides and bottom of truck beds. Proper application produces a rich foam which allows asphalt loads to easily slide from truck beds when tilted. Will not affect the composition of the asphalt mix.

Directions for Use

AR-92 is dispensed through standard proportioning valves. Standard dilution is 40 parts of water to 1 part AR-92.

Surface treated must be clean of any asphalt accumulation. Apply solution to sides, bed and spreader bar of the truck. For best results, fill truck with asphalt while the coating is still wet.

Safety Reminder

Consult Product Label and Safety Data Sheet (SDS) before use. Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Safety Data Sheet (SDS). The label and SDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Yellow Liquid
Odor	Mild
pH (1% solution, 22°C)	7-8
Foaming	High
Flash Point	None
Rinsability	Complete
Stability/Storage	2 Years
Emulsification	Complete
Solubility	100%
Phosphate Content	None

Product Number

G5-55

Packaging

55 Gallon Drum

Distributor

Brewer Cote of Arizona The Pavement Maintenance Specialists
5226 W Missouri Avenue, Glendale, Arizona 85301
www.brewercoteaz.com 888-931-3728 sales@brewercoteaz.com