



Distributor  
 Brewer Cote of Arizona  
 The Pavement Maintenance Specialists  
 5226 W Missouri Avenue, Glendale, AZ 85301  
 Tel. 623-931-3728 Toll 888-933728  
 www.brewercoteaz.com sales@brewercoteaz.com

# GLENZOIL 20 PLUS

## PRODUCT DESCRIPTION

This crack sealant barrier material is a unique, biodegradable, non-toxic liquid that prevents tracking and picking of freshly applied hot-melt sealants. It forms a temporary protective barrier that allows traffic immediate access to the repaired pavement, yet it does not affect the sealant or asphalt. Glenzoil 20 Plus requires only one person to apply, saving labor costs, and eliminates the mess and costs associated with conventional blotting materials.

## PRODUCT FEATURES

- All Natural
- Biodegradable
- Contains No Petroleum/Silicone
- Non Flammable
- Non Toxic
- No Harmful Environmental Effects



## PRODUCT BENEFITS

- Cost Effective
  - Requires one person to apply
  - Eliminates using sand and associated costs
  - Completes the job in less time
  - Decreases job cost & increases production
  - Eliminates need to set up long stretches of cones
- Easy to Use
  - Apply with hand held sprayer directly to sealant
  - Does not require specialized application equipment
- Safe to Use
  - Non Toxic

Item No.	Description
G7-5G	Glenzoil 20 Plus - 5 Gallon Pail
G7-4CS	Glenzoil 20 Plus - 4 Gallon Case
G7-55	Glenzoil 20 Plus - 55 Gallon Drum



# GLENZOIL 20 PLUS

---

**GENERAL:** EMULSO Glenzoil 20 Plus is a liquid specifically designed to prevent tracking of freshly applied hotmelt crack and joint sealants. When properly applied to the surface of the sealant, **Glenzoil 20 Plus** will provide a barrier between the sealant and the vehicle tires thereby eliminating picking and tracking of the sealant until it has set up.

**PERFORMANCE SPECIFICATIONS:** **Glenzoil 20 Plus** will prevent the picking of freshly applied hot-melt rubberized sealants with no effect on the composition or performance of the sealant or surrounding asphalt. It will provide an effective barrier over the surface of the sealant without excessive evaporation even when applied to the sealant at their recommended pour temperatures. **Glenzoil 20 Plus** will effectively prevent picking of the sealant until such a time as the sealant cures. After approximately thirty to sixty minutes, **Glenzoil 20 Plus** will dissipate leaving only a slight residue which will wash away with the first rainfall. **Glenzoil 20 Plus** contains no surfactants which have shown to significantly reduce the slip resistance of the sealants surface. Friction testing has shown **Glenzoil 20 Plus** to have no more effect on the slip resistance of the sealant than water. **Glenzoil 20 Plus** contains no hazardous ingredients and is not harmful to the user or the environment.

**APPLICATION:** Successful application is generally achieved with the use of a hand held pump up sprayer. Application rate will vary depending on the sealant temperature, ambient temperature, surface temperature, width and depth of the crack, distance and time of application after the application of sealant, traffic volume, etc. On average, rate of application will be one gallon of **Glenzoil 20 Plus** to every 50 - 100 gallons of hot-melt rubberized sealant.

Spray **Glenzoil 20 Plus** directly onto the surface of the sealant. An adjustable tip on the spray wand is necessary to adjust the spray stream to a width that will cover the sealant in one pass. The entire surface of the sealant must be wetted with **Glenzoil 20 Plus** to prevent picking of the sealant. Although **Glenzoil 20 Plus** is effective when applied immediately following the application of the sealant, yield is better if the sealant is allowed to seek its level and begin to cool, especially with wide or deep sealant reservoirs and wide or thick band-aid overlaps.

**PACKAGING:** Packaging of EMULSO **Glenzoil 20 Plus** consists of individual 5 U.S. gallon plastic pails each weighing 47 pounds. Standard palletization consists of 36 pails weighing 1752 pounds. Pails contain a lid pour spout for easy transfer to spray equipment on the job site.

**STORAGE:** Pallets should not be stacked higher than two high. Pails may be stored outside. If frozen, thaw, shake well and use. Shelf life is one year.

**SAFETY PRECAUTIONS:** Before using **Glenzoil 20 Plus**, all personnel involved with the use of **Glenzoil 20 Plus** should read and understand the MATERIAL SAFETY DATA SHEET for EMULSO **Glenzoil 20 Plus**. Personnel should also read and understand the MATERIAL SAFETY DATA for the hot-melt sealant being used in conjunction with **Glenzoil 20 Plus** before sealing is started. DO NOT test the effectiveness of **Glenzoil 20 Plus** by touching the sealant with unprotected skin. It is important to note that the application of **Glenzoil 20 Plus** to the surface of the hot-melt crack sealant will not significantly cool the sealant and skin contact with the hot sealant material will cause burns.

**WARRANTY:** EMULSO CORPORATION warrants that **Glenzoil 20 Plus** will perform as outlined in this product data sheet. EMULSO shall not be responsible for improperly placed or misused material. Remedies against EMULSO CORPORATION, as agreed to by EMULSO, are limited to replacing nonconforming product or refund (full or partial) of purchase price from EMULSO CORPORATION. All claims for breach of this warranty must be made within thirty days of the date of use or six months from the date of delivery by EMULSO CORPORATION, whichever is earlier. There shall be no other warranties expressed or implied.