QuikSeam

The most effective way of protecting pavement joints against water infiltration

Peel & Stick


Water Proof
Full Depth Seal
Increases Density
All In One Joint Sealer
Utility Cuts
Highways
Airports
New Construction
Overlays




Seam and Water Infiltration Sealants

Peel and Stick on Vertical and Horizontal Pavement Surfaces











Completely seals edges and finish surface on longitudinal joints

Installs by removing release liner, self-adhering to vertical pavement edge or surface cracks and joints prior to placement of hot mix

Product #	Description Application	
QJP95000	9 inch wide x 50 feet long QuikSeam, 37.5 sq.ft.	Vertical Joint
PPSA33263	12 inch wide x 50 feet long PavePrep, 50 sq.fc.	Underlayment
PPSA33265	18 inch wide x 50 feet long PavePrep, 75 sq.fc.	Underlayment
PPSA33270	24 inch wide x 50 feet long PavePrep, 100 sq.ft.	Underlaymens
GT33215	18 inch wide x 50 feet long GeoTac, 75 sq.ft.	Waterproof Membrane





Bituminous Pads for Traffic Control Devices, Reflectors, Speed Bumps and Temporary Signage

Peel & Stick Pads

Adhesive Rubberized Asphalt Apply Heat No Mess Easy to Install

Concrete or Blacktop





Anchor bituminous pads when concrete deck cannot be drilled

Install by peeling and sticking pads on pavement where traffic control sign, speed bump, or reflector is to be located; heat and bond.

Product #	Description	Qty
QH4000	QuikHold Pads 4 in. x 4 in. squares	100
QH9000	QuikHold Pads 8 in. x 8 in. squares	25
QHI 200	QuikHold Pads 12 in. x 12 in. squares	25



Quik Fill

Repair Cracks, Fatigued Surfaces , Low Spots and Pot Holes in pavement

Coated Granules

Alligator Areas
Fatigued Surfaces
Cracks & Joints
Depressions
Pot Holes





Fill and brush material into cracks, fatigued, alligator and low spots; heat then over seal with QuikJoint or QuikSeam.

Product #	Description	Qty
Q59010	QuikSeam Roll 9 inch wide x 10 feet long (7.50 sq.ft.)	2
QF6500	Quikfill 6 gallon plastic pail 50 lb filler	1

