



Brewer Cote
OF ARIZONA



The Soft Heat SH- MA10 is the ultimate evolution of the popular Melter/Applicator combination crack sealant machine. It is ideal for all types of crack sealant work. Completely self-contained, it can efficiently melt and apply hot sealants to parking areas, road ways, mill and fill perimeters and traffic control loops. Thanks to the heat sourcing of infrared technology, initial startup and recovery times are less than half that of traditional torch fired units. The virtually even distribution of heat across the burner surface combined with the actual flame never touching the melting pan yields undamaged material at an astonishing rate. Fuel usage is a fraction of traditional units. No more annoying blow-outs means even lower operating cost without the frustration of time lost.

SH-MA10

Melter / Applicator

The SH-MA10 draws from over 25 years of experience in the manufacture and design of melter applicators. Both inner and outer tanks are built of 14 ga. steel. Standard features include temperature gauge with guards, four 1/4" thick steel wheels for stability, propane bottle platform (bottle not included), stay cool handle on no-splash lid, spring loaded control valve and 3" steel screed with seal-off plate for clean starts and stops. The built in hand agitator incorporates a revolutionary block-off plate to seal the material vat from the valve. This allows quick in field servicing of a valve clog. Regulator is self-maximizing to prevent over pressurizing of the burner and hose is 4' of protective braided stainless steel. Battery powered electronic ignition and back up lighter stick port means you are never stranded with an unsolvable ignition problem. Quality welded construction by skilled tradesmen in the USA means each unit comes fully assembled to stay fully assembled. This is simply the most productive MA10 built.

SPECIFICATIONS:

Length – 47"

Width – 27"

Height – 36"

Capacity – 10 gal.