

WARRIOR DIAMOND, INC.



14 HP



22 HP

RAPID RABBIT™ CRACK CHASERS & SAW BLADES

The Industry's Fastest, Easiest to Use Equipment for Routing Random Cracks in Concrete & Asphalt
Available in 14 HP & 22 HP Subaru Gas Engines for Every Size Job

◇ FEATURES ◇

- ◇ Extremely Operator Friendly
- ◇ Center Mounted Blade makes following random cracks easy & accurate
- ◇ Rapid Rabbit™ Crack Chasers are safer to operate than carbide cutter units
- ◇ Eliminates percussive fractures often caused by carbide cutters
- ◇ Uses Warrior Diamond, Inc. Blades for extra smooth routing of even the most erratic random cracks
- ◇ Depth of cut indicator directly in operator's line of sight, minimizes cutting too deep & saves on Sealant costs
- ◇ Patented Z-Triangle Arbor prevents blade from turning on Arbor, eliminating the need to replace expensive spindle shafts
- ◇ Produces a perfect Sealant Reservoir for maximum pavement life
- ◇ Standard Options include dry cutting with Spray Mist & Vacuum Attachment
- ◇ Push button Electric Depth Control on the handle
- ◇ Subaru Engine with cyclone air filter for extended engine life

Distributed By

BREWER COTE OF ARIZONA INC® THE PAVEMENT MAINTENANCE SPECIALISTS
5226 W. MISSOURI AVENUE, GLENDALE ARIZONA 85301

www.brewercoteaz.com • tel. 623-931-3728 • toll 888-931-3728 • fax 623-842-0714 • sales@brewercoteaz.com

WARRIOR DIAMOND, INC.

Model	RR 14	RR 22
Materials Cut	Cured Concrete & Asphalt	Cured Concrete & Asphalt
Blade Width	.250" – 375" – 500"	.250" – 375" – 500" – 750"
Blade Rotation	Down-cut as viewed by Operator	Down-cut as viewed by Operator
Blade Shaft Speed	4600 rpm	4800 rpm
Cutting Depth	1 ½" (38mm) & 1 ¼" end of life	1 ½" (38mm) & 1 ¼" end of life
Dimensions		
Handle Up Most Position	43" x 24" x 50"	46" x 31" x 53"
Handle Down Most Position	62" x 24" x 29"	64" x 31" x 38"
Engine	14 HP (9.9KW) Subaru Robin Model EX-40 Air cooled, 4 Cycle, Single-Slat cylinder overhead valve Gasoline Engine	22 HP (16.4KW) Subaru Robin Model EH-65 Air cooled, 4 Cycle, V-Twin cylinder overhead valve Gasoline Engine
Starting System	Manuel recoil Starter/Electric Start with automatic Mechanical Compression Release and zero kick back	Electric Start with automatic Mechanical Compression Release and zero kick back
Air Filter	Duel element cleaner / Cyclone filter	Heavy Duty
Oil System	Oil Alert with automatic shut down Sensor	Oil Alert with automatic shut down Sensor
Blade Raise / Lower System	Electric actuated with switch on handle bar	Electric actuated with switch on handle bar
Handle	Three position adjustable	Three position adjustable
Wheels	Hard Polyurethane	Hard Polyurethane
Weight / Shipping Weight	270 Lbs	470 Lbs



Blade Diameter	Blade Thickness	Concrete Part #	Asphalt Part #
6"	0.250"	R62501	R62504
6"	0.375"	R63751	R63754
6"	0.500"	R65001	R65004
6"	0.750"	R67951	R67504

Approximate Existing Crack Width	Finished Routed Width
¼"	⅜"
⅜"	½"
½"	⅝"
¾"	⅞"