




Canyon Surgical Associates
Clinic Remodel

South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

Construction Documents

DESIGN TEAM	
<p>ARCHITECT NJRA Architects, Inc. 5223 South Ascension Way, Suite 350 Murray, Utah 84123 Phone: 801.364.9259</p> <p>Contacts: Project Architect: Selvam Rajavelu Project Manager: Katarne Jones Email: katjon@njraarchitects.com</p>	
<p>MECHANICAL ENGINEER Spectrum Engineers 324 South State Street, Suite 400 Salt Lake City, Utah 84111 Phone: 801.328.5151</p> <p>Contacts: Project Manager: Monica Downing Email: monica.downing@speceng.com</p>	
<p>ELECTRICAL ENGINEER Spectrum Engineers 324 South State Street, Suite 400 Salt Lake City, Utah 84111 Phone: 801.328.5151</p> <p>Contacts: Project Engineer: Jason Worthen Project Manager: Brendan Arita Email: brendan.arita@speceng.com</p>	



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Cover Sheet

G001

INTERIM LIFE SAFETY MEASURES

IMPLEMENTATION OF INTERIM LIFE SAFETY MEASURES (ILSM) IS REQUIRED IN OR ADJACENT TO ALL CONSTRUCTION AREAS AND THROUGHOUT BUILDINGS WITH EXISTING LSC DEFICIENCIES. ILSM APPLY TO ALL PERSONNEL INCLUDING CONSTRUCTION WORKERS. MUST BE IMPLEMENTED UPON PROJECT DEVELOPMENT, AND CONTINUOUSLY ENFORCED THROUGHOUT PROJECT COMPLETION. ILSM ARE INTENDED TO PROVIDE A LEVEL OF LIFE SAFETY COMPARABLE TO THAT DESCRIBED IN CHAPTERS 1 THROUGH 7.31 AND THE APPLICABLE OCCUPANCY CHAPTERS OF THE LSC. EACH ILSM ACTION MUST BE DOCUMENTED THROUGH WRITTEN POLICIES AND PROCEDURES, EXCEPT AS STATED BELOW. FREQUENCIES FOR INSPECTION, TESTING, TRAINING, AND ILSM CONSIST OF THE FOLLOWING ACTIONS:


- ENSURING EXITS PROVIDE FREE AND UNOBSTRUCTED EGRESS. PERSONNEL SHALL RECEIVE TRAINING IF ALTERNATIVE EXITS MUST BE DESIGNATED. BUILDINGS OR AREAS UNDER CONSTRUCTION MUST MAINTAIN ESCAPE FACILITIES FOR CONSTRUCTION WORKERS AT ALL TIMES. MEANS OF EGRESS IN CONSTRUCTION AREAS MUST BE INSPECTED DAILY.
- ENSURING FREE AND UNOBSTRUCTED ACCESS TO EMERGENCY DEPARTMENTS/ SERVICES AND FOR EMERGENCY FORCES.
- ENSURE FIRE ALARM, DETECTION, AND SUPPRESSION SYSTEMS ARE NOT IMPAIRED. A TEMPORARY, BUT EQUIVALENT, SYSTEM SHALL BE PROVIDED WHEN ANY FIRE SYSTEM IS IMPAIRED. TEMPORARY SYSTEMS MUST BE INSPECTED AND TESTED MONTHLY.
- ENSURING TEMPORARY CONSTRUCTION PARTITIONS ARE SMOKE TIGHT AND BUILT OF NONCOM OR LIMITED COMBUSTIBLE MATERIALS THAT WILL NOT CONTRIBUTE TO THE DEVELOPMENT OR SPREAD OF FIRE.
- PROVIDING ADDITIONAL FIRE-FIGHTING EQUIPMENT AND USE TRAINING OF PERSONNEL.
- PROHIBITING SMOKING IN ACCORDANCE WITH MA.1.3.1.5 AND IN OR ADJACENT TO ALL CONSTRUCTION AREAS.
- DEVELOPING AND ENFORCING STORAGE, HOUSEKEEPING, AND DEBRIS REMOVAL PRACTICES THAT REDUCE THE FLAMMABLE AND COMBUSTIBLE FIRE LOAD OF THE BUILDING TO THE LOWEST LEVEL NECESSARY FOR DAILY OPERATIONS.
- CONDUCTING A MINIMUM OF TWO FIRE DRILLS PER SHIFT PER QUARTER.
- INCREASING HAZARD SURVEILLANCE OF BUILDINGS, GROUNDS, AND EQUIPMENT WITH SPECIAL ATTENTION TO EXCAVATIONS, CONSTRUCTION AREAS CONSTRUCTION STORAGE, AND FIELD OFFICES.
- TRAINING PERSONNEL WHEN STRUCTURAL OR COMPARTMENT FEATURES OF FIRE SAFETY ARE COMPROMISED.
- CONDUCTING ORGANIZATION WIDE SAFETY EDUCATION PROGRAMS TO ENSURE AWARENESS OF ANY LSC DEFICIENCIES, CONSTRUCTION HAZARDS, AND THESE ILSM.

PROJECT DESCRIPTION

THIS PROJECT INCLUDES THE FOLLOWING SCOPE OF WORK:

- EXPANSION OF THE EXISTING SURGICAL CLINIC INTO AN ADJACENT CLINIC SPACE WITH:
 - FIVE (5) NEW/REMODELED EXAM ROOMS.
 - EXPANDED WAITING ROOM AND BREAK ROOM.
 - TWO (2) NEW OFFICES
 - REMOVAL AND REINSTALLATION OF EXISTING CASEWORK AND NEW CASEWORK FOR STORAGE.
 - NEW STORAGE ROOM AND MODIFICATION OF HALL STORAGE CASEWORK FOR RELOCATION OF EXISTING STORAGE ROOM WITH TELECOM CABINET.
- ALL ASSOCIATED M/E/P WORK THROUGHOUT THE SPACE AS SHOWN IN DRAWINGS AND REMOVAL AND REINSTALLATION OF EXISTING CEILING TO REMAIN AS REQUIRED FOR M/E/P WORK ABOVE.
- NEW DOORS, WINDOWS AND ACCESSORIES AS SHOWN IN DRAWINGS.
- AS ADD ALTERNATE 1: PROVIDE TRANSOM WINDOWS IN OFFICES AS NOTED IN DRAWINGS.

VICINITY MAP



INFECTION CONTROL RISK ASSESSMENT

CONSTRUCTION ACTIVITY TYPE

Type D:
Major demolition or construction that creates major disruption, i.e. noise, dust, vibration, odor, or mechanical systems

INFECTION CONTROL RISK GROUP

Medium

CONSTRUCTION CLASS

Construction Activity Type:

IC Risk Group	Type A	Type B	Type C	Type D
Lowest	Class I	Class II	Class III	Class IV
Medium	Class I	Class II	Class III	Class IV
High	Class I	Class II	Class IV	Class IV
Highest	Class II	Class IV	Class IV	Class IV

INFECTION CONTROL PROTOCOLS

During Construction (Class IV):

- Perform work using methods to minimize raising dust or tracking dust into other areas.
- Immediately replace ceiling tile upon completion of inspection.
- Use active dust control measures.
- Use water mist to control dust while cutting.
- Seal doors, ducts, vents and HVAC units.
- Place dust control mats at entries to work area; keep them clean and effective.
- Remove debris only in tightly covered containers.
- Construct barriers to prevent dust and other contaminant migration prior to beginning work.
- Maintain negative air pressure in work space using HEPA filtration units.
- Seal all pipes, conduits and penetrations.
- Construct and use anteroom for all entry to work area; HEPA vacuum all personnel, or have them change clothing before they leave the work area.
- All personnel wear shoe covers while in the work area and remove them before entering the hospital.

Upon Completion (Class IV):

- Clean work area.
- Wipe all horizontal surfaces with disinfectant.
- Remove final debris only in tightly covered containers.
- Vacuum using HEPA filtered vacuum; mop with disinfectant as appropriate.
- Remove all seals from doors, ducts, vents and HVAC units.
- Remove construction barriers in a manner that minimizes the spread of dust and debris.

ABBREVIATIONS

&	AND	DWL	DOWEL	INT.	INTERIOR	P.S.F.	POUNDS PER SQUARE FOOT	V.C.P.	VITREOUS CLAY PIPE
@	AT	DN.	DOWN	INV.	INVERT	R	RADIUS	W	WATER CLOSET
Ø	DIAMETER	D.S.	DOWN SPOUT	J	JANITOR	REC.	RECOMMENDATION	W.C.	WATER HEATER
(E) EXIST.	EXISTING	D.W.V.	DRAINAGE WASTE VENT	JT.	JOINT	REG.	REGISTER	W.R.	WATER RESISTANT
(N)	NEW	DWG.	DRAWING	JST.	JOIST	REQ'D	REQUIRED	W.P.	WATERPROOF
¢	PENNY	E	EACH	L	LAMINATED	R.A.	RETURN AIR	W.W.F.	WELDED WIRE FABRIC
#	POUND OR NUMBER	E.W.C.	ELEC. WATER COOLER	L.DG.	LANDING	REV.	REVISION	W.D.W.	WINDOW
A	ACOUSTIC	EL/ELEC.	ELECTRIC	LAV.	LAVATORY	R.D.	ROOF DRAIN	W/	WITH
AC	ADDENDUM	ELEV.	ELEVATION	L.V.	LIGHT	RFG.	ROOFING	W/O	WITHOUT
ADD	ADDENDUM	EQUIP.	EQUIPMENT	LI.	LIGHT	RGH.	ROUGH	WD.	WOOD
A/C	AIR CONDITIONING	EXH.	EXHAUST	L.W.C.	LIGHT WEIGHT CONCRETE	RND.	ROUND		
ALT.	ALTERNATE	EXST.	EXISTING	LVR.	LOUVER	S	SCREW		
AL	ALUMINUM	E.J.	EXPANSION JOINT	M	MACHINE BOLT	SCR.	SECTION		
A.B.	ANCHOR BOLT	EXT.	EXTERIOR	M.B.	MACHINE BOLT	SECT.	SECTION		
ARCH	ARCHITECTURAL	F	FEET	MFR.	MANUFACTURER	SEL.	SELECT		
ASP.	ASPHALT	F.V./V.	FIELD VERIFY	M.O.	MASONRY OPENING	SHT.	SHEET		
B	BASEMENT	FIN.	FINISH(ED)	MATL.	MATERIAL	SIM.	SIMILAR		
B.M.	BENCHMARK	F.E.	FIRE EXTINGUISHER	MAX.	MAXIMUM	SLDG.	SLIDING		
BLKG.	BLOCKING	F.E.C.	FIRE EXTINGUISHER CABINET	MECH.	MECHANICAL	SM.	SMOOTH		
BD.	BOARD	FXR.	FIXTURE	MIL.	METAL	SPEC.	SPECIFICATION		
B.O.	BOTTOM OF	FL.	FLASHING	MIN.	MINIMUM	SPL.	SPLASH		
BLDG.	BUILDING	G	GALVANIZED	M.LDG.	MOLDING	SQ.	SQUARE		
C	CABINET	GALV.	GALVANIZED	MULL.	MULLION	S.S.	STAINLESS STEEL		
CABT	CABINET	GA.	GAUGE	N	NATURAL GRADE	STD.	STANDARD		
C.I.P.	CAST IN PLACE	CA.	GENERAL CONTRACTOR	N.G.	NATURAL GRADE	STRUC.	STRUCTURE		
C.B.	CATCH BASIN	G.S.N.	GENERAL STRUCTURAL NOTES	NOM.	NOMINAL	S.A.	SUPPLY AIR		
CLG.	CEILING	GL.	GLASS	N/A	NOT APPLICABLE	S.G.P.	SUSPENDED		
CL	CENTER LINE	GD.	GRADE	N.I.C.	NOT IN CONTRACT	SW.BD.	SWITCHBOARD		
C.T.	CERAMIC TILE	GRL.	GRILLE	N.T.S.	NOT TO SCALE	T	TYPICAL		
CH	CHANNEL	GRD.	GROUND	O	ON CENTER	TELCO	TELEPHONE COMPANY		
C.O.	CLEAN OUT	GYP.	GYP. GYPSUM	O.C.	ON CENTER	T.G.	TEMPERED GLASS		
CLR.	CLEAR	H	HARDWARE	O.D.	OUTSIDE DIAMETER	T&G	TONGUE & GROOVE		
CL.	CLOSET	HDW.	HARDWARE	O.F.S.	OVERFLOW SCUPPER	T&B	TOP & BOTTOM		
COL.	COLUMN	HDWD.	HARDWOOD	O.F.C.I.	OWNER FURNISHED, CONTRACTOR INSTALLED	T.O.	TOP OF		
CONC.	CONCRETE	HR.	HEATER	O.F.O.I.	OWNER FURNISHED, OWNER INSTALLED	T.O.C.	TOP OF CURB		
CMU	CONCRETE MASONRY UNIT	HT.	HEIGHT	P	PAINT	T.O.D.	TOP OF DECK		
COND.	CONDITION	H.P.	HIGH POINT	PT.	PAINTED	T.O.P.	TOP OF PARAPET		
CONN.	CONNECTION	H.M.	HOLLOW METAL	PR.	PAIR	TY.	TYPICAL		
CONST.	CONSTRUCTION	HORIZ.	HORIZONTAL	PNL.	PANEL	U	UNLESS NOTED OTHERWISE		
CONT.	CONTINUOUS	H.B.	HOSE BIB	PR.	PAIR	U.N.O.	UNLESS NOTED OTHERWISE		
CJ	CONTROL JOINT	H.W.	HOT WATER	PNL.	PANEL	V.	VENT		
CJ	CONTROL JOINT	HR.	HOUR	d	PENNY	V.T.R.	VENT THROUGH ROOF		
D	DAMP PROOFING	I	INCH	PL.	PLASTIC LAMINATE	VERT.	VERTICAL		
D.P.	DECK BEARING	IN.	INCH	PL.	PLATE	V.G.	VERTICAL GRAIN		
D.B.	DECK BEARING	LD.	INSIDE DIAMETER	FLBG.	PLUMBING	VEST.	VESTIBULE		
DIAG.	DIAGONAL	INSUL.	INSULATION	P.S.I.	POUND PER SQUARE INCH	V.C.T.	VINYL COMPOSITION TILE		
DIA.	DIAMETER								
DIM.	DIMENSION								
DISP.	DISPENSER								


DEFERRED SUBMITTALS



THE CONTRACTOR SHALL SUBMIT THE FOLLOWING TO THE BUILDING OFFICIAL FOR REVIEW WITH AN ACCOMPANYING LETTER FROM THE ARCHITECT STATING THAT THE CONTENTS OF THE SUBMITTAL ARE IN CONFORMANCE WITH THE DESIGN. WORK RELATED TO THE DEFERRED SUBMITTAL IS NOT TO COMMENCE UNTIL THE BUILDING OFFICIAL HAS APPROVED THE SUBMITTAL.

- DETAILS AND ENGINEERING CALCULATIONS FOR ALL NONSTRUCTURAL COMPONENTS THAT ARE PERMANENTLY ATTACHED TO STRUCTURES AND THEIR SUPPORTS AND ATTACHMENTS. THESE SHALL BE DESIGNED AND CONSTRUCTED TO RESIST THE EFFECTS OF EARTHQUAKE MOTIONS IN ACCORDANCE WITH ASCE 7-05, REFERENCE TO SECTION 1413.1. THIS INCLUDES:
 - ELECTRICAL SYSTEMS
 - MECHANICAL SYSTEMS
 - PLUMBING SYSTEMS
 - DECORATIVE ARCHITECTURAL COMPONENTS.
- DETAILS AND ENGINEERING CALCULATIONS FOR THE FIRE SPRINKLER AND FIRE DETECTION SYSTEMS, WHICH ARE TO BE DESIGN-BUILD BY THE CONTRACTOR TO COMPLY WITH NFPA 13 AND SHALL INCLUDE:
 - FIRE ALARM PLANS (INCLUDING CO DETECTOR LOCATIONS)
 - AUTOMATIC FIRE SPRINKLER PLANS
 - HOOD FIRE SUPPRESSION
 - CLASS "K" FIRE EXTINGUISHER LOCATIONS(S)

DEFINITIONS

- GENERAL: BASIC CONTRACT DEFINITIONS ARE INCLUDED IN THE CONDITIONS OF THE CONTRACT.
- "APPROVED": WHEN USED TO CONVEY ARCHITECT'S ACTION ON CONTRACTOR'S SUBMITTALS, APPLICATIONS, AND REQUESTS, "APPROVED" IS LIMITED TO ARCHITECT'S DUTIES AND RESPONSIBILITIES AS STATED IN THE CONDITIONS OF THE CONTRACT.
- "DIRECTED": A COMMAND OR INSTRUCTION BY ARCHITECT, OTHER TERMS INCLUDING "REQUESTED," "AUTHORIZED," "SELECTED," "REQUIRED," AND "PERMITTED" HAVE THE SAME MEANING AS "DIRECTED."
- "INDICATED": REQUIREMENTS EXPRESSED BY GRAPHIC REPRESENTATIONS OR IN WRITTEN FORM ON DRAWINGS, IN SPECIFICATIONS, AND IN OTHER CONTRACT DOCUMENTS, OTHER TERMS INCLUDING "SHOWN," "NOTED," "SCHEDULED," AND "SPECIFIED" HAVE THE SAME MEANING AS "INDICATED."
- "REGULATIONS": LAWS, ORDINANCES, STATUTES, AND LAWFUL ORDERS ISSUED BY AUTHORITIES HAVING JURISDICTION, AND RULES, CONVENTIONS, AND AGREEMENTS WITHIN THE CONSTRUCTION INDUSTRY THAT CONTROL PERFORMANCE OF THE WORK.
- "TURNISH": SUPPLY AND DELIVER TO PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS.
- "INSTALL": UNLOAD, TEMPORARILY STORE, UNPACK, ASSEMBLE, ERECT, PLACE, ANCHOR, APPLY, WORK TO DIMENSION, FINISH, CURE, PROTECT, CLEAN, AND SIMILAR OPERATIONS AT PROJECT SITE.
- "PROVIDE": FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE.
- "PROJECT SITE": SPACE AVAILABLE FOR PERFORMING CONSTRUCTION ACTIVITIES. THE EXTENT OF PROJECT SITE IS SHOWN ON DRAWINGS AND MAY OR MAY NOT BE IDENTICAL WITH THE DESCRIPTION OF THE LAND ON WHICH PROJECT IS TO BE BUILT.





1 Typical Mounting Heights
SCALE: 3/8" = 1'-0"

LEGEND - MATERIALS	
HATCH PATTERN BELOW INDICATES REPRESENTATION OF BUILDING MATERIALS IN BUILDING SECTIONS, WALL SECTIONS AND DETAILS.	
	Concrete
	Finish Wood
	Gypsum Board
	Blocking
	Steel
	Stone
	Earth
	Gravel
	Masonry Concrete Block
	Ball Insulation
	Masonry Brick
	Insulation Rigid

GENERAL INFORMATION SYMBOLS & TAGS	
SHEET NUMBERING SYSTEM PROJECT AREA SHEET NUMBER SEQUENCE SHEET TYPE DISCIPLINE	ROOM TAG ROOM NAME DENOTES OCCUPANT LOAD IN CODE COMPLIANCE PLANS. OFFICE-4 155 SF (O.L. 999) ROOM COUNT DESIGNATION DENOTES ROOM AREA OF 155 SQUARE FEET ROOM NUMBER, LETTER "A" IN THE ROOM NUMBER DENOTES "AREA A" IN THE PROJECT, NUMBER "3" DENOTES "FLOOR LEVEL 3", NUMBER "24" DENOTES ROOM NUMBERING SEQUENCE IN THE PROJECT AREA.
GRID TAG GRID REFERENCE LETTER - A, B, C, ETC. (USED FOR HORIZONTAL GRID SEQUENCE, TYPICALLY FROM LEFT TO RIGHT) GRID REFERENCE NUMBER - 1, 2, 3, ETC. (USED FOR VERTICAL GRID SEQUENCE, TYPICALLY FROM TOP TO BOTTOM)	DATUM POINT TAG B.O.C. BOTTOM OF CEILING B.O.H. BOTTOM OF HEADER HEIGHT ABOVE FINISH FLOOR
NORTH ARROW 	SPOT ELEVATION DENOTES BUILDING REFERENCE ELEVATION T.O.W. TOP OF WALL T.O.C. TOP OF CURB D.B.E. DECK BEARING ELEVATION F.F.E. FINISH FLOOR ELEVATION B.O.V. BOTTOM OF VENER T.O.S. TOP OF SIDEWALK T.O.C. TOP OF CURB
BUILDING SECTIONS SECTION TAGS ARE INDICATED ON OVERALL DIMENSION FLOOR PLANS BUILDING SECTION SHEET WHERE DRAWN	VERTICAL ELEVATION DENOTES FLOOR LEVEL DENOTES BUILDING REFERENCE ELEVATION
WALL SECTIONS SECTION TAGS ARE INDICATED ON DIMENSION FLOOR PLANS WALL SECTION SHEET WHERE DRAWN	CENTER LINE
DETAIL TAGS DETAIL NUMBER SHEET WHERE DRAWN	FLOW ARROW WATER DRAINAGE DIRECTION SHOWN ON SITE AND ROOF PLANS FROM HIGH TO LOW POINT.
DETAIL TAGS DETAIL NUMBER SHEET WHERE DRAWN	FLOOR PLAN MATCHLINE DETAIL LOCATION NUMBER SHEET WHERE DRAWN
EXTERIOR ELEVATION TAGS TAGS ARE INDICATED ON OVERALL DIMENSION FLOOR PLANS AND KEY PLAN EXTERIOR ELEVATION NUMBER SHEET WHERE DRAWN	REVISION TAG CLOUD INDICATES DRAWING REVISION AREA REVISION NUMBER
INTERIOR ELEVATION TAGS TAGS ARE INDICATED ON FINISH FLOOR PLANS INTERIOR ELEVATION NUMBER SHEET WHERE DRAWN	KEYED NOTES - PROJECT SPECIFIC KEYED NOTES THAT ARE PROJECT SPECIFIC AS INDICATED ON PLANS, SECTIONS AND ELEVATIONS DIVISION # DIVISION NOTE
KEYED NOTES - GENERIC KEYED NOTES THAT ARE NOT PROJECT SPECIFIC AS INDICATED ON GENERIC, TYPICAL DETAILS. 	KEYED NOTES - GENERIC KEYED NOTES THAT ARE NOT PROJECT SPECIFIC AS INDICATED ON GENERIC, TYPICAL DETAILS.
WALL TAG WALL TAGS ARE INDICATED ON DIMENSION FLOOR PLANS. WALL TYPES ARE INDICATED IN SHEET A501A.	WALL TAG WALL TAGS ARE INDICATED ON DIMENSION FLOOR PLANS. WALL TYPES ARE INDICATED IN SHEET A501A.
DOOR TAG DOOR TAGS ARE INDICATED ON DIMENSION FLOOR PLANS THE FIRST LETTER "A" AND THE FOLLOWING THREE DIGITS "124" DENOTES ROOM NUMBER SUFFIX "C" DENOTES SEQUENCE OF DOOR ACCESSING THE ROOM.	WINDOW TAG WINDOWS TAGS ARE INDICATED ON DIMENSION FLOOR PLANS
FLOOR FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR FLOOR COVERING AND FINISHES REQUIRED. 	FLOOR FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR FLOOR COVERING AND FINISHES REQUIRED.
WALL BASE TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR WALL BASE TYPE. 	WALL BASE TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR WALL BASE TYPE.
WALL FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR WALL FINISHES REQUIRED. 	WALL FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR WALL FINISHES REQUIRED.
CEILING FINISH TAG TAGS ARE INDICATED ON REFLECTED CEILING PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR CEILING FINISHES REQUIRED. 	CEILING FINISH TAG TAGS ARE INDICATED ON REFLECTED CEILING PLAN. SEE FINISH SCHEDULE, SHEET A603A. FOR CEILING FINISHES REQUIRED.
OTHER FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN & INTERIOR ELEVATIONS. SEE FINISH SCHEDULE, SHEET A603A. FOR FINISHES REQUIRED. 	OTHER FINISH TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN & INTERIOR ELEVATIONS. SEE FINISH SCHEDULE, SHEET A603A. FOR FINISHES REQUIRED.
CABINET TAG CABINET TYPES ARE INDICATED ON INTERIOR ELEVATIONS & CABINET LEGEND, SHEET A505A. 	CABINET TAG CABINET TYPES ARE INDICATED ON INTERIOR ELEVATIONS & CABINET LEGEND, SHEET A505A.
SIGN TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE SIGN TYPE DETAIL 5/AS04A 	SIGN TAG TAGS ARE INDICATED ON FINISH FLOOR PLAN. SEE SIGN TYPE DETAIL 5/AS04A

Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6

5171 Cottonwood Street #650
 Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

General Information

G003

DOORS AND DOORWAYS






FIG. 404.2.4 TWO DOORS IN A SERIES


FIG. 404.2.2 MANEUVERING CLEARANCE AT SLIDING AND FOLDING DOORS




CLEAR FLOOR SPACE




REACH RANGES




GENERAL SITE AND BUILDING ELEMENTS




COMMUNICATION ELEMENTS AND FEATURES




BUILDING BLOCKS




PROTRUDING OBJECTS




PLUMBING ELEMENTS AND FACILITIES




ACCESSIBLE ROUTES






LEGEND - DEMOLITION FLOOR PLAN

BUILDING COMPONENTS (DOORS, WALLS, ETC) INDICATED BELOW IN THIS LEGEND ARE DRAWN AT 1/4" = 1'-0" SCALE. COMPONENTS SHALL APPEAR HALF THE SIZE (SMALLER) ON PLANS DRAWN AT 1/8" = 1'-0" SCALE.




LEGEND - FLOOR & DIMENSION PLANS

BUILDING COMPONENTS (DOORS, WALLS, ETC) INDICATED BELOW IN THIS LEGEND ARE DRAWN AT 1/4" = 1'-0" SCALE. COMPONENTS SHALL APPEAR HALF THE SIZE (SMALLER) ON PLANS DRAWN AT 1/8" = 1'-0" SCALE.



LEGEND - REFLECTED CEILING PLAN

BUILDING COMPONENTS (CEILING, LIGHT FIXTURES, ETC) INDICATED BELOW IN THIS LEGEND ARE DRAWN AT 1/4" = 1'-0" SCALE. COMPONENTS SHALL APPEAR HALF THE SIZE (SMALLER) ON PLANS DRAWN AT 1/8" = 1'-0" SCALE.



GENERAL NOTES

- A. STRUCTURAL, MECHANICAL, AND ELECTRICAL DRAWINGS (IF PRESENT) ARE SUPPLEMENTAL TO THE ARCHITECTURAL DRAWINGS. IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO CHECK WITH THE ARCHITECTURAL DRAWINGS BEFORE THE INSTALLATION OF MECHANICAL OR ELECTRICAL CONSTRUCTION. ANY DISCREPANCIES BETWEEN THE ARCHITECTURAL AND CONSULTING ENGINEERS' DRAWINGS SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION FOR CLARIFICATION. ANY CONSTRUCTION INSTALLED IN CONFLICT WITH THE ARCHITECTURAL DRAWINGS SHALL BE CORRECTED BY THE GENERAL CONTRACTOR AT HIS/HER OWN EXPENSE AND AT NO EXPENSE TO THE OWNER OR ARCHITECT.
- B. ALL WORK SHALL COMPLY WITH THE CURRENT ADA ACCESSIBILITY GUIDELINES (AMERICANS WITH DISABILITIES ACT).
- C. REFER TO THE CODE COMPLIANCE PLAN FOR APPLICABLE CODES GOVERNING THIS WORK. CODE REQUIREMENTS AND REGULATIONS SHALL BE CONSIDERED AS MINIMUM. WHERE THE CONTRACT DOCUMENTS EXCEED (WITHOUT VIOLATING) CODE AND REGULATION REQUIREMENTS, CONTRACT DOCUMENTS SHALL TAKE PRECEDENCE. IF CONFLICT EXIST, THE MORE STRINGENT SHALL APPLY. COMPLY WITH REQUIREMENTS OF THE ADOPTED EDITIONS OF THE INTERNATIONAL CODE COUNCIL CODES, THE CODES AND STANDARDS REFERENCED WITHIN THE ICC CODES AND THE AMERICANS WITH DISABILITIES ACT.
- D. THE CONTRACTOR SHALL PROVIDE ADEQUATE BARRICADES AND PROTECTIVE DEVICES SEPARATING CONSTRUCTION AREAS. TEMPORARY PASSAGES SHALL BE PROVIDED AS REQUIRED. PRIOR TO DELIVERY OF MATERIALS TO CONSTRUCTION ZONE AND REMOVAL OF WASTE FROM SITE, THE CONTRACTOR SHALL CHECK WITH THE OWNER FOR AN ACCEPTABLE ROUTE AND TIME.
- E. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROPER LOCATION AND SIZE OF OPENINGS FOR ALL TRADES AND SHALL COORDINATE ALL CONSTRUCTION AS INDICATED BY THE CONTRACT DOCUMENTS, INCLUDING SHOP DRAWINGS REVIEWED BY THE ARCHITECT.
- F. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO COMMENCEMENT OF WORK.
- G. FOR ALL REMODEL WORK AS OCCURS, THE CONTRACTOR SHALL COORDINATE WITH THE OWNER ALL MEASURES TO ACCOMPLISH THE WORK WITH THE MINIMUM OF INTERRUPTION TO NORMAL BUILDING PROCEDURES, SYSTEM SHUTDOWNS OF HVAC, PLUMBING, ELECTRICAL, AND NOISY CONSTRUCTION INCLUDING ROTO HAMMER, SAW CUTTING, CONCRETE ANCHORS, ETC. SHALL BE COORDINATED WITH THE OWNER AT LEAST 72 HOURS PRIOR TO COMMENCEMENT.
- H. ALL DIMENSIONS ARE SHOWN TO FACE OF GYPSUM BOARD OF NEW CONSTRUCTION OR STRUCTURAL WALL, UNLESS NOTED OTHERWISE.
- I. ALL DRAWINGS, THOUGH NOTED TO SCALE ARE FOR ILLUSTRATION ONLY. THE CONTRACTOR SHALL NOT SCALE DRAWINGS.
- J. WHEN A DETAIL IS IDENTIFIED AS TYPICAL, THE CONTRACTOR IS TO APPLY THIS DETAIL IN ESTIMATING AND CONSTRUCTION TO EVERY LIKE CONDITION WHETHER OR NOT THE REFERENCE IS REPEATED IN EVERY INSTANCE.
- K. DRAWINGS HAVE BEEN DETAILED IN COMPLIANCE WITH U.L. LISTING REQUIREMENTS AND ICBO REPORTS FOR THE MATERIALS SPECIFIED. IF AN ALTERNATE OR SUBSTITUTED MATERIAL IS ACCEPTED AS AN EQUAL BY THE GENERAL CONTRACTOR, HE/SHE WILL ASSUME THE RESPONSIBILITY FOR WHATEVER CONSTRUCTION MODIFICATION AND/OR ADDITIONAL COSTS ARE REQUIRED.
- L. ALL TRASH SHALL BE REMOVED DAILY. BUILDING MATERIALS MAY NOT BE STORED IN THE CORRIDORS AT ANY TIME. BLOCKAGE OF ANY REQUIRED EXIT IS PROHIBITED.
- M. ALL PENETRATIONS INTO SOUND OR FIRE RATED PARTITIONS, FLOORS OR CEILING ASSEMBLIES SHALL BE SEALED WITH APPROVED PERMANENT RESILIENT SEALANT. REFER TO IBC CURRENT VERSION FOR REQUIREMENTS FOR OPENINGS IN FIRE RATED WALLS. FOR OPENINGS LESS THAN 16 SQUARE INCHES, THE SPACE BETWEEN THE WALL AND ALLOWED PENETRATIONS MUST BE SEALED TO PREVENT THE MOVEMENT OF HOT FLAME OR GASES. ELECTRICAL DEVICES, RECESSED CABINETS, ETC. SHALL BE SEALED, LINED, INSULATED OR OTHERWISE TREATED TO MAINTAIN THE INTEGRITY OF THE ASSEMBLY. SEE PENETRATION DETAILS.
- N. ABBREVIATIONS THROUGHOUT THE PLAN ARE THOSE IN COMMON USE. THE ARCHITECT SHALL DEFINE THE INTENT OF ANY IN QUESTION.
- O. THE CONTRACTOR SHALL VERIFY SIZES AND LOCATIONS OF WATER AND DRAIN INSTALLATIONS AND OTHER REQUIRED SERVICES WITH EQUIPMENT MANUFACTURERS. MAINTAIN ALL EXISTING SPRAY-APPLIED FIRE PROOFING ON STEEL STRUCTURAL MEMBERS, WHERE EXISTING FIRE PROOFING IS REMOVED FOR INSTALLATION OF NEW BEAMS, UNISTRUTS, ETC. THE CONTRACTOR SHALL PATCH AGAIN WITH EQUIVALENT FIRE PROOFING MATERIAL TO MATCH ADJACENT EXISTING MATERIAL.
- Q. ALL WOOD CANTS, NAILERS, CURBS, ETC. THROUGHOUT JOB SHALL BE FIRE RETARDANT PRESSURE-TREATED, AS PER I.B.C. CURRENT VERSION. SEE RELEVANT DETAILS.
- R. CONTRACTOR SHALL REFER TO THE PROJECT MANUAL FOR A COMPLETE LIST OF GENERAL CONDITIONS, SPECIAL CONDITIONS AND OTHER NOTES.

GENERAL NOTES - DEMOLITION FLOOR PLAN

- A. CONTRACTOR SHALL VERIFY ALL EXISTING SITE AND BUILDING CONDITIONS INCLUDING UNDERGROUND UTILITIES AND SERVICE LINES, IRRIGATION LINES AND SUB SURFACE STRUCTURES AND ALL OTHER EXISTING CONSTRUCTION BOTH ABOVE AND BELOW GRADE.
- B. PRIOR TO REMOVAL OF EXISTING BUILDING MATERIALS (INCLUDING WALLS, DOORS, WINDOWS, CEILING, ETC.) INDICATED IN THE DEMOLITION PLANS, CONTRACTOR SHALL THOROUGHLY COORDINATE ARCHITECTURAL FLOOR PLANS, CEILING PLANS, FINISH SCHEDULES AND ALL CONSULTANT DRAWINGS TO DETERMINE EXACT EXTENT OF REMOVAL.
- C. COORDINATE WITH OWNER'S REPRESENTATIVE REGARDING ITEMS SHOWN TO BE REMOVED THAT WILL BECOME PROPERTY OF THE OWNER. CAREFULLY REMOVE SUCH ITEMS SO AS NOT TO DAMAGE THEM.
- D. IN EXISTING WALLS THAT ARE NOTED TO REMAIN, ANY NAILS, SCREWS, OR OPENINGS THAT REMAIN AS A RESULT OF EXISTING EQUIPMENT REMOVAL OR WALL REMOVAL SHALL BE PATCHED WITH SMOOTH, EVEN, INVISIBLE TRANSITION. IN PLACES WHERE THE EXISTING WALL IS CUT FOR INSTALLATION OF POWER OUTLETS, SWITCH, THERMOSTAT, ETC. PATCH OPENINGS IN WALL WITH GYPSUM BOARD. PROVIDE SMOOTH, EVEN, INVISIBLE TRANSITION BETWEEN NEW AND EXISTING WALL FINISH.
- E. THE OWNER'S STAFF WILL CONTINUE TO OCCUPY AREAS DIRECTLY ADJACENT TO THE CONSTRUCTION AREA. THE CONTRACTOR AND SUB-CONTRACTORS SHALL TAKE ALL NECESSARY MEASURES TO MINIMIZE DISRUPTION ACTIVITIES CONDUCTED BY THE OWNER'S STAFF. THE CONTRACTOR SHALL NOTIFY THE OWNER'S REPRESENTATIVE OF NOISY ACTIVITIES, SHUT-DOWNS, AND ANY OTHER ACTIVITIES WHICH MAY DISRUPT NORMAL OPERATIONS PRIOR TO PERFORMING THE WORK.
- F. ONCE FLOORING DEMOLITION HAS OCCURRED, CLEAN AND PREPARE FLOOR TO RECEIVE NEW FLOOR COVERINGS. THIS SHALL BE COORDINATED WITH THE FINISH SCHEDULE AND MANUFACTURER OF NEW PRODUCTS FOR FLOOR PREPARATION REQUIREMENTS.
- G. ITEMS SHOWN ON THESE FLOOR PLANS FOR REMOVAL ARE BUILT-IN ITEMS, EQUIPMENT, FURNITURE, & OTHER ITEMS EXISTING IN THE SPACE THAT ARE NOT BUILT-IN SHALL BE REMOVED OR CLEARED TEMPORARILY BY THE OWNER.

GENERAL NOTES - FLOOR & DIM. PLANS

- A. REFER TO THE CODE COMPLIANCE PLANS FOR INDICATION OF FIRE RATED WALLS.
- B. AT LOCATIONS WITHOUT CEILINGS (ROOMS OPEN TO STRUCTURE ABOVE), EXTEND ALL WALLS, SOFFITS, AND HEADERS (INCLUDING ALL STUD FRAMING, GYPSUM BOARD, INSULATION & CMU, WHERE APPLICABLE) TO THE METAL ROOF DECK ABOVE.
- C. WHEN FLOOR HEIGHT VARIES IN A ROOM, THE CEILING HEIGHT SHOWN IS THE HEIGHT ABOVE THE FLOOR AT THE ENTRY, UNO.
- D. SEE INTERIOR ELEVATIONS FOR TOILET AND BATHROOM ACCESSORIES (GRAB BARS, MIRRORS, DISPENSERS, ETC.).
- E. AT ALL VERTICAL EDGES OF INTERIOR CMU WALLS THAT ARE VISIBLE, USE BULLNOSE CMU BLOCKS FROM FINISHED FLOOR ELEVATION TO A HEIGHT OF 7'-4".
- F. FOR CLARITY SAKE, DIMENSIONS ARE NOT SHOWN AT THE FOLLOWING LOCATIONS:
 - G. WHERE THE FACE OF WALL COINCIDES WITH THE MAIN GRID LINE OR 4'-0" X 4'-0" SUBGRID.
 - H. WHERE THE CENTER OF WALL COINCIDES WITH THE MAIN GRID LINE OR 4'-0" X 4'-0" SUBGRID.
- G. VERIFY WITH ARCHITECT FOR DIMENSIONS NOT SHOWN.
- H. SEE STRUCTURAL DRAWINGS FOR CMU WALLS, MASONRY COLUMNS, AND MASONRY BEAMS. SEE BUILDING EXTERIOR ELEVATIONS FOR VENEER TYPES. SEE FINISH SCHEDULE FOR CMU THAT IS HONED, SCORED, SEALED, PAINTED, ETC.
- I. SEE CIVIL, FOOD SERVICE, PLUMBING, AND MECHANICAL DRAWINGS FOR FLOOR SINKS, FLOOR DRAINS, AND OPENINGS IN FLOOR SLABS AND ROOFS FOR DUCTWORK, ETC.
- J. SEE DOOR AND WINDOW SCHEDULE FOR THE REQUIRED DOOR AND WINDOW OPENING SIZES.
- K. SEE FINISH SCHEDULE AND STRUCTURAL DRAWINGS AND PROVIDE RECESS IN CONCRETE FLOOR SLAB AS REQUIRED TO ACCOMMODATE FLOOR FINISHES. CONCRETE FLOOR SLAB THAT IS ON GRADE, SHALL BE RECESSED AS REQUIRED. FOR A THICK SET MORTAR FOR CERAMIC TILE FINISH, SLOPE SHALL BE AT 1/8" PER FOOT TOWARDS THE FLOOR DRAIN. CONCRETE FLOOR SLAB THAT IS NOT ON GRADE, NEED NOT BE RECESSED. IN SUCH LOCATION, USE THIN SET MORTAR FOR CERAMIC TILE FINISH WITH A GENTLE SLOPE TOWARDS DRAIN.
- L. ALL PENETRATIONS (PIPES, CONDUITS, JOISTS, ETC.) THROUGH FIRE RATED BARRIER WALLS SHALL BE SEALED COMPLETELY WITH FIRE RATED SEALANTS. FILL GAP BETWEEN FLUTES OF THE METAL DECK AND METAL TRACK TOP RUNNER WITH FIRE RATED SEALANTS. SEAL TIGHTLY AROUND PIPES, CONDUITS, DUCTS, ETC. THAT PENETRATES THE FIRE BARRIER WALL WITH FIRE RATED SEALANTS. APPLY SEALANTS AS PER MANUFACTURER'S RECOMMENDATIONS WITH ANY ADDITIONAL MATERIAL AS REQUIRED. INSTALL AROUND PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE FIRE WALL. SEE MECHANICAL DRAWINGS FOR FIRE AND SMOKE DAMPERS.
- M. WALL CABINETS HAVE A DEPTH OF 1'-3" UNLESS NOTED OTHERWISE.
- N. ALL MASONRY MORTAR JOINTS LOCATED INSIDE THE BUILDING SHALL BE TOOLED JOINTS, UNLESS NOTED OTHERWISE. MASONRY JOINTS ON THE BUILDING EXTERIOR SIDE SHALL BE RAKED JOINTS AS INDICATED IN BUILDING EXTERIOR ELEVATIONS.
- O. SEE OVERALL FLOOR PLAN SHEETS FOR ANGLES, PIVOT POINT AND DIMENSIONS BETWEEN GRID LINES.
- P. SEE CODE COMPLIANCE FLOOR PLANS FOR LOCATION OF FIRE BARRIER, NON RATED WALLS, ETC.
- Q. SEE ENLARGED FLOOR PLANS FOR ADDITIONAL DIMENSIONS.
- R. IN SOME PROJECTS, DUE TO THE LARGE BUILDING FOOTPRINT SIZE, FLOOR PLANS ARE SPLIT AS AREAS A, B, C, ETC. AND EACH AREA IS INDICATED ON SEPARATE SHEETS. MATCH LINES INDICATE THE BOUNDARIES OF EACH AREA. WHEN CONTRACTORS ARE PREPARING BID FOR THE PROJECT, COST SHALL INCLUDE ONLY THE BUILDING ELEMENTS AND ASSOCIATED CONSTRUCTION WORK CALLED OUT WITH KEYED NOTES IN THE AREA INDICATED ON THE SHEET. KEYED NOTES INDICATED OUTSIDE THE MATCH LINE IN ADJACENT FLOOR AREAS SHALL NOT BE COUNTED FOR THAT AREA. THIS AVOIDS DUPLICATION OF BUILDING ELEMENTS AND CONSTRUCTION WORK.

GENERAL NOTES - DOOR SCHEDULE

- A. SEE PROJECT MANUAL FOR DOOR HARDWARE SCHEDULE.
- B. SUB-CONTRACTOR UNDER SECTION 'ALUMINUM ENTRANCES AND STOREFRONT', SHALL PROVIDE ALL THE DOOR HARDWARE FOR ALL ALUMINUM DOORS. SEE DOOR SCHEDULE FOR ALUMINUM DOORS AND THE REQUIRED HARDWARE.
- C. SUB-CONTRACTOR UNDER SECTION 'DOOR HARDWARE', SHALL PROVIDE ALL THE DOOR HARDWARE FOR ALL THE WOOD AND HOLLOW METAL DOORS. SEE DOOR SCHEDULE FOR WOOD AND HOLLOW METAL DOORS AND THE REQUIRED HARDWARE.
- D. ALL EXTERIOR DOORS SHALL BE INSULATED.
- E. FIELD VERIFY WINDOW AND DOOR FRAME OPENING SIZES BEFORE FRAME INSTALLATION. OVERALL DIMENSIONS INDICATED FOR EACH FRAME TYPE ARE ROUGH OPENING SIZES IN WALLS. CONTRACTOR SHALL ADJUST INNER DIMENSIONS AS REQUIRED TO MAKE DOORS AND WINDOWS WORK.
- F. ELECTRICAL DEVICES SUCH AS MAG. LOCKS, CARD READERS AND ALARM SYSTEMS BEING PART OF THE DOOR FUNCTION ARE INCLUDED AS PART OF THE ELECTRICAL PLANS AND THE HARDWARE GROUPS. GENERAL CONTRACTOR IS RESPONSIBLE TO COORDINATE LOCATIONS OF CARD READERS ETC. SHOWN ON ARCHITECTURAL AND ELECTRICAL DRAWINGS WITH ALL TRADES INVOLVED.
- G. COORDINATE DOORS & GATES OUTSIDE BUILDING WITH SITE PLAN.


GENERAL NOTES - REFLECTED CEILING PLAN

- A. SEE MECHANICAL DRAWINGS FOR DIFFUSER LOCATIONS IN CEILING. CONTRACTOR SHALL COORDINATE WITH LIGHT FIXTURES (AS INDICATED IN ELECTRICAL DRAWINGS) AND MOVE DIFFUSERS AROUND THE LIGHT FIXTURE IF THERE IS ANY CONFLICT BETWEEN THE TWO.
- B. SOME OF THE ITEMS ON CEILING INDICATED IN MECHANICAL AND ELECTRICAL DRAWINGS, MAY OR MAY NOT BE INDICATED ON ARCHITECTURAL CEILING PLANS. SEE MECHANICAL AND ELECTRICAL DRAWINGS AND COORDINATE WITH ARCHITECT FOR ANY REQUIRED CLARIFICATIONS.
- C. CONTRACTOR SHALL NOT HANG CEILING TILES AND LIGHTS FROM DUCTS. FOR AREAS ABOVE THE CEILING WHERE OVERSIZE DUCTS OCCUR SEE DETAIL 11 / A503A.
- D. PAINT ALL VISIBLE EXPOSED ITEMS LIKE METAL DECK, STEEL ANGLES, STEEL BEAMS, STEEL TRUSSES, MISCELLANEOUS EXPOSED STEEL STRUCTURAL COMPONENTS, HOLLOW METAL DOORS, DOOR FRAMES & WINDOW FRAMES, PAINT EXPOSED SURFACES (WITH COLORS AND ACCENT COLORS AS SELECTED BY ARCHITECT) EXCEPT WHERE NATURAL FINISH OR MATERIAL IS SPECIFICALLY NOTED AS A SURFACE NOT TO BE PAINTED. DO NOT PAINT CONCEALED SURFACES, FINISHED METAL SURFACES, OPERATING PARTS AND PRE FINISHED ITEMS.

GENERAL NOTES - INTERIOR ELEVATIONS

- A. PROVIDE LOCKS FOR CABINETS AS INDICATED ON THE CABINET LEGEND ON SHEET A505A AND IF INDICATED ON INTERIOR ELEVATIONS.
- B. IN ROOMS WHERE CABINETS ARE REQUIRED TO BE LOCKED, PROVIDE LOCKS OPERABLE WITH SINGLE KEY.
- C. FOR TYPICAL MOUNTING HEIGHTS, SEE SHEET G003. FOLLOW THE HEIGHT UNLESS NOTED OTHERWISE IN INTERIOR ELEVATIONS. VERIFY WITH ARCHITECT FOR ITEMS NOT INDICATED.
- D. CONTRACTOR SHALL VERIFY WITH OWNER FOR OWNER FURNISHED CONTRACTOR INSTALLED ITEMS AND PROVIDE BACKING IN WALL AS REQUIRED FOR INSTALLATION.
- E. INTERIOR ELEVATIONS OF CERTAIN ROOMS ARE NOT DRAWN AND ARE NOTED AS SIMILAR ELEVATIONS OF ROOMS THAT ARE INDICATED IN THE DRAWINGS.
- F. CONTRACTOR SHALL PROVIDE FILLER PANELS (PLASTIC LAMINATE WRAPPED OVER 5/8" PARTICLE BOARD) WHEREVER GAP OCCURS BETWEEN CABINETS AND WALL.
- G. SEE FINISH FLOOR PLANS AND FINISH SCHEDULE A603A FOR WALL, CABINET AND COUNTERTOP FINISHES.
- H. SEE SHEET A505A FOR CABINET LEGEND (TYPES B1, W1, T1, ETC.), UNLESS NOTED OTHERWISE. ALL THE CABINETS AND COUNTERTOPS IN EACH ROOM SHALL BE OF THE SAME FINISH (PL1, PL2, SS1, ETC.) AS INDICATED ON THE INTERIOR ELEVATION OF EACH ROOM, WHERE MULTIPLE FINISHES ARE REQUIRED FOR CABINETS, WALLS, ETC. IN THE ROOM, EACH FINISH IS INDICATED SEPARATELY. CONTACT ARCHITECT FOR REQUIRED CLARIFICATIONS.
- I. COUNTERTOPS ARE TYPICALLY SUPPORTED BY WALLS AND BASE CABINETS. IN PLACES WHERE COUNTERTOP SPAN EXCEEDS 4'-0", STEEL SUPPORTS SHALL BE PROVIDED AS INDICATED IN DETAILS 4 / A505B AND 5 / A505B.
- J. AS INDICATED ON INTERIOR ELEVATIONS, WALL CABINETS AT CERTAIN LOCATIONS MAY REQUIRE A VERTICAL OR A SLOPED FASCIA PANEL.
- K. AN ENLARGED FLOOR PLAN HAS BEEN INCLUDED ALONG WITH INTERIOR ELEVATIONS FOR ROOMS THAT ARE COMPLEX IN DESIGN. SUCH COMPLEX ROOMS ARE INDICATED ON THE A400 SERIES SHEETS (STARTING WITH SHEET A401). ENLARGED FLOOR PLANS ARE NOT SHOWN FOR ROOMS THAT ARE SIMPLE IN DESIGN. INTERIOR ELEVATIONS OF SUCH SIMPLE ROOMS ARE INDICATED ON THE A250 SERIES SHEETS (STARTING WITH SHEET A251).
- L. FOR ALL CABINETS PROVIDE BACKING IN WALL AS PER DETAIL 3/A505B.

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6
5171 Cottonwood Street #650
Murray, Utah 84107



CODE COMPLIANCE LEGEND				
SYMBOL	DESCRIPTION	FIRE RESISTANCE RATING	DOOR FIRE RATING	WINDOW FIRE RATING
	COMMON PATH OF TRAVEL	N/A	N/A	N/A
	TRAVEL DISTANCE	N/A	N/A	N/A
	OCCUPANT LOAD	N/A	N/A	N/A
	SMOKE PARTITION WALL	0 HOUR	SMOKE	SMOKE
	SMOKE BARRIER WALL	1 HOUR	1/3 HOUR	1/3 HOUR
	1 HOUR FIRE RATED WALL	1 HOUR	3/4 HOUR	3/4 HOUR
	2 HOUR FIRE RATED WALL	2 HOUR	1-1/2 HOUR	1-1/2 HOUR

- KEYED NOTES**
- 01.31 LINE AND ARROW INDICATES "COMMON PATH OF TRAVEL" DIRECTION AND DISTANCE OF 31' BETWEEN POINTS C1 AND C2. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.
 - 01.32 LINE AND ARROW INDICATES "COMMON PATH OF TRAVEL" DIRECTION AND DISTANCE OF 20' BETWEEN POINTS C3 AND C4. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.
 - 01.33 LINE AND ARROW INDICATES "COMMON PATH OF TRAVEL" DIRECTION AND DISTANCE OF 20' BETWEEN POINTS C5 AND C6. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.
 - 01.51 LINE AND ARROW INDICATES "TRAVEL DISTANCE" OF 84' BETWEEN POINTS T1 AND T2. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.
 - 01.52 LINE AND ARROW INDICATES "TRAVEL DISTANCE" OF 93' BETWEEN POINTS T3 AND T2. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.
 - 01.53 LINE AND ARROW INDICATES "TRAVEL DISTANCE" OF 153' BETWEEN POINTS T4 AND T2. THIS IS LESS THAN THE MAXIMUM ALLOWED DISTANCE OF XX'.

CODE REVIEW

APPLICABLE CODES
International Building Code (IBC) 2021
International Existing Building Code (IEBC) 2021
International Fire Code (IFC) 2021
International Mechanical Code (IMC) 2021
International Plumbing Code (IPC) 2021
ANSI/ASHRAE/IES Standard 90.1 2016
National Electrical Code (NEC) with Utah amendments 2020
NFPA 101 Life Safety Code 2018
ANSI 117.1 2017 Accessible and usable buildings and facilities 2017
ADA Standards for accessible design 2010
Guidelines for design & construction of hospital and healthcare facilities 2010

OCCUPANCY CLASSIFICATION
Business Group: B (Unchanged)

FIRE SPRINKLER SYSTEM
Building is equipped throughout with an automatic sprinkler system.

CONSTRUCTION TYPE
Level 6 Remodel: Type II-A (Unchanged)

BUILDING HEIGHT
Allowable Height: 247'-9"
Actual Height: Remains unchanged

NUMBER OF STORIES
Existing: 9 Stories + Penthouse
Remains unchanged. Remodel to occur on Level 6

FLOOR AREA
Allowable Floor Area per Floor: Unlimited
Actual Floor Area: Remains Unchanged
Area of Remodel: 2,450 Sq. Ft.

FIRE-RESISTANCE RATING REQUIREMENTS FOR BUILDING ELEMENTS
Primary structural frame: 2 hour
Bearing walls - Exterior: 2 hour
Bearing walls - Interior: 2 hour
Nonbearing walls and partitions - Exterior: 0 hour
Nonbearing walls and partitions - Interior: 0 hour
Floor construction and associated secondary members: 2 hour
Roof construction and associated secondary members: 1 hour

SPACES WITH ONE EXIT OR EXIT ACCESS DOORWAY
Maximum Occupant Load of Space (Occupancy - B): 49
Common Path of Travel (Occupancy - B): 100 feet

EXIT ACCESS TRAVEL DISTANCE
Maximum Travel Distance (Occupancy - B): 300 feet

CORRIDOR FIRE-RESISTANCE RATING
Corridor Walls (Occupancies B): 0 hour


MINIMUM CORRIDOR WIDTH
Minimum corridor width required: 44 inches
Actual corridor width provided: 60 inches

DEAD END CORRIDORS
Occupancy - B: Not to exceed 50 feet

MEANS OF EGRESS SIZING
Level 6 occupant loads & egress have been calculated in entirety when the hospital was originally permitted & constructed. This calculated occupant load & egress width will remain unchanged due to the remodel.

Occupant Load for Total Clinic (Table 1004.5): 4990/150 = 34 occupants

1 Code Compliance Floor Plan - Level 6
SCALE: 3/16" = 1'-0"



Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Code Compliance
Plan Level 6

G111



1 Demolition Floor Plan - Level 6
SCALE: 1/4" = 1'-0"

KEYED NOTES


- 01.03 DASHED LINE INDICATES FLOOR TO CEILING DUST PROOF CONSTRUCTION BARRIER TO PREVENT DUST AND DIRT MIGRATION AND TO SEPARATE AREAS OCCUPIED BY THE OWNER FROM FUMES AND NOISE. CONSTRUCTION BARRIER TO BE ERRECTED WITH 3/8" X 20 GA. MIL STUDS @ 14" O.C. FRAMING WITH 5/8" TYPE X GYPSUM BOARD ON BOTH SIDES. TAPE & SEAL ALL JOINTS AND OPENINGS. SEAL JOINTS AT PERIMETER. PAINT WALL ON EXISTING CORRIDOR SIDE. PARTITION TO BE EQUIPPED WITH 4'-0" LOCKABLE HALL DOOR WITH STICKY MATS ON BOTH SIDES OF DOOR. COORDINATE WITH OWNER FOR EXACT LOCATION OF CONSTRUCTION BARRIER.
- 02.01 WALL, EXISTING TO REMAIN. PROTECT WALL FROM DAMAGE DURING CONSTRUCTION.
- 02.02 WALL, EXISTING INDICATED WITH DASHED LINE TO BE REMOVED. REMOVE EXISTING WALL INCLUDING STUDS, GYPSUM BOARD, STUD BRACING ABOVE CEILING, ELECTRICAL, MECHANICAL, AND PLUMBING ITEMS LOCATED IN THE WALL.
- 02.03 REMOVE GYPSUM BOARD FROM ROOM SIDE OF WALL AS REQUIRED FOR IN-WALL M/E/P WORK. PATCH AND REPAIR AND PAINT WALL TO MATCH ADJACENT EXISTING U.N.O. ON FINISH SCHEDULE.
- 02.04 CAREFULLY REMOVE FURNITURE AS REQUIRED FOR CONSTRUCTION. COORDINATE WITH OWNER, STORE AND REINSTALL FURNITURE AFTER CONSTRUCTION IS COMPLETED.
- 02.05 DOOR, EXISTING TO REMAIN. PROTECT DOOR FROM DAMAGE DURING CONSTRUCTION.
- 02.06 DOOR AND DOOR FRAME, EXISTING INDICATED WITH DASHED LINE TO BE CAREFULLY REMOVED. SALVAGE DOOR AND HARDWARE FOR RELOCATION.
- 02.07 DOOR, EXISTING INDICATED WITH DASHED LINE TO BE CAREFULLY REMOVED. DOOR FRAME, EXISTING TO REMAIN. PROTECT DOOR FRAME FROM DAMAGE DURING CONSTRUCTION AND PATCH, REPAIR AND PAINT FRAME PER DOOR AND DOOR FRAME, EXISTING INDICATED WITH DASHED LINE TO BE REMOVED.
- 02.08 WINDOW, EXISTING TO REMAIN. PROTECT WINDOW FROM DAMAGE DURING CONSTRUCTION.
- 02.09 WINDOW, EXISTING TO REMAIN. PROTECT WINDOW FROM DAMAGE DURING CONSTRUCTION.
- 02.10 WALL, EXISTING INDICATED WITH DASHED LINE TO BE REMOVED TO EXTENT REQUIRED FOR NEW DOOR OPENING. COORDINATE EXACT LOCATION WITH NEW FLOOR PLAN.
- 02.11 PLUMBING FIXTURE, EXISTING INDICATED WITH DASHED LINE TO BE REMOVED. SEE PLUMBING DRAWINGS.
- 02.12 CASEWORK, EXISTING TO REMAIN. PROTECT DURING CONSTRUCTION. CABINET (AND COUNTERTOP WHERE OCCURS), EXISTING TO REMAIN. PROTECT CABINET AND COUNTERTOP FROM DAMAGE DURING CONSTRUCTION.
- 02.13 CABINETS, BASE AND WALL, AND COUNTERTOP, EXISTING INDICATED WITH DASHED LINE TO BE CAREFULLY REMOVED. CONSULT NEW CASEWORK DRAWING AND SALVAGE WHERE POSSIBLE AND APPLICABLE TO REINSTALL. PATCH AND REPAIR EXISTING WALLS TO REMAIN AFTER CASEWORK REMOVAL.
- 02.14 FLOOR COVERING, EXISTING TO REMAIN. PROTECT FLOOR COVERING FROM DAMAGE DURING CONSTRUCTION.
- 02.15 FLOOR COVERING, EXISTING INDICATED IN THIS AREA TO BE REMOVED. AS OCCURS, CAREFULLY REMOVE CARPET IN GOOD CONDITION AND SALVAGE TO BE REINSTALLED. REMOVE EXISTING FLOORING AND BASE INCLUDING ADHESIVE ALL THE WAY DOWN TO THE BARE CONCRETE FLOOR. CLEAN FLOOR AND PREP FOR NEW FLOOR FINISHES. COORDINATE EXTENT OF REMOVAL WITH FINISH FLOOR PLANS FOR NEW FLOOR COVERING LOCATIONS AND TRANSITION LINE BETWEEN EXISTING AND NEW FLOOR COVERINGS.
- 02.16 DOOR, EXISTING TO REMAIN. PROTECT DURING CONSTRUCTION. FIELD VERIFY EXISTING HARDWARE AND MODIFY FOR NEW LOCKING HARDWARE. COORDINATE WITH OWNER AND ADJACENT CLINIC TO REMOVE ANY EXIT SIGNS INDICATED AT THIS DOOR.
- 02.17 COORDINATE WITH OWNER FOR WALL MOUNTED EQUIPMENT TO REMAIN. SALVAGE AND REINSTALL SELECTED EQUIPMENT IN THIS ROOM OR COORDINATE TO PROTECT IN PLACE DURING CONSTRUCTION.
- 02.18 CASEWORK, INCLUDING BUT NOT LIMITED TO WALL AND BASE CABINETS AND COUNTERTOP WITH INTEGRAL SINK, ALONG THIS WALL INDICATED WITH DASHED LINE TO BE CAREFULLY REMOVED AND SALVAGED TO BE REINSTALLED ON RELOCATED WALL. IF CASEWORK IS DAMAGED PROVIDE NEW CABINET AND/OR COUNTERTOP AND INTEGRAL SINK TO MATCH EXISTING.
- 02.19 COORDINATE WITH OWNER FOR ANY REMOVAL OF WALL OR FLOOR MOUNTED ITEMS. SALVAGE AND RETURN TO OWNER. PATCH AND REPAIR SURFACES AND PAINT WALLS TO MATCH EXISTING.
- 02.20 EXISTING FIRE EXTINGUISHER TO REMAIN. FIELD VERIFY CONDITIONS AND IF REQUIRED FOR NEW CONSTRUCTION, CAREFULLY REMOVE AND RELOCATE. SEE DETAIL 3/ASDC FOR MOUNTING IF REQUIRED.
- 02.21 REMOVE EXISTING WALL BELOW HEIGHT OF AND MODIFY FRAMING FOR NEW HEADER. COORDINATE WITH NEW CEILING PLANS FOR EXTENT OF HEADER.
- 02.22 CARPET, EXISTING TO BE REMOVED ONLY AS REQUIRED FOR NEW CONSTRUCTION OR REMOVE AND REINSTALL AT CONTRACTOR'S OPTION. CAREFULLY REMOVE CARPET AND BASE AND SALVAGE. REINSTALL/PATCH AND REPAIR CARPET IN THIS AREA PER FINISH PLAN.
- 02.23 CASEWORK, EXISTING TO BE CAREFULLY REMOVED. IF CASEWORK IS IN GOOD CONDITION AFTER REMOVAL SALVAGE AND REINSTALL IN NEW EXAM ROOM.
- 02.31 EXISTING SERVER CABINET TO BE RELOCATED. SEE ELECTRICAL DRAWINGS.

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107


NJRA Project # 2402.00
Construction Documents June 27, 2024

Demolition
Floor Plan
Level 6

A111



1 Reflected Ceiling Demolition Plan - Level 6
SCALE: 1/4" = 1'-0"



KEYED NOTES


- 02.15 CEILING, EXISTING TO REMAIN. PROTECT CEILING FROM DAMAGE DURING CONSTRUCTION. COORDINATE WITH M/E/P DRAWINGS FOR LOCATIONS OF FIXTURES TO REMAIN OR BE REMOVED. REMOVE EXISTING CEILING TILES AND GRIDS, LIGHT FIXTURES, HVAC DIFFUSERS, ETC. ONLY AS REQUIRED FOR ANY ABOVE CEILING M/E/P WORK. RE-INSTALL AFTER ALL ABOVE CEILING WORK IS COMPLETE. REPLACE TO MATCH EXISTING IF DAMAGED DURING CONSTRUCTION.
- 02.16 CEILING, EXISTING INDICATED WITH DASHED LINES IN THIS AREA TO BE CAREFULLY REMOVED. COORDINATE WITH M/E/P DRAWINGS FOR LOCATIONS OF FIXTURES TO REMAIN OR BE REMOVED. SALVAGE TILES AND FIXTURES FOR REINSTALLATION AS APPLICABLE PER NEW RCP AND M/E/P DRAWINGS.
- 02.24 REMOVE EXISTING WALL BELOW HEIGHT OF AND MODIFY FRAMING FOR NEW HEADER. COORDINATE WITH NEW CEILING PLANS FOR EXTENT OF HEADER. GYPSUM BOARD HEADER, EXISTING TO REMAIN.
- 02.27

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Demolition
Ceiling Plan
Level 6 - Area
A

A112



1 Floor Plan - Level 6
SCALE: 1/4" = 1'-0"

KEYED NOTES


- 06.01 CABINET. SEE CABINET LEGEND ON SHEET 1/A505A, AND INTERIOR ELEVATIONS, FOR CABINET TYPES SUCH AS BASE CABINETS, WALL CABINETS, TALL CABINETS, ETC. FIELD VERIFY THAT FINISH, CONSTRUCTION AND SIZE MATCH EXISTING CASEWORK IN EXAM 1.
- 06.03 CABINETS, UPPER AND BASE, SALVAGED TO BE REINSTALLED, IF DAMAGED DURING CONSTRUCTION PROVIDE NEW CABINETS TO MATCH THE EXISTING CABINETS IN EXAM 3.
- 06.05 PROVIDE PLASTIC LAMINATE PANEL ON EXPOSED VISIBLE SIDE AS REQUIRED TO CREATE A FINISHED END.
- 06.06 CABINET. SEE CABINET LEGEND ON SHEET 1/A505A, AND INTERIOR ELEVATIONS, FOR CABINET TYPES SUCH AS BASE CABINETS, WALL CABINETS, TALL CABINETS, ETC.
- 06.07 INSTALL SALVAGED CABINET HARDWARE AS NEEDED.
- 08.01 DOOR AND DOOR FRAME. SEE DOOR SCHEDULE.
- 08.02 SLIDING BARN DOOR. BASIS OF DESIGN: AD SYSTEMS. SEE DOOR SCHEDULE AND DETAILS ON SHEET A504A.
- 08.03 REINSTALL SALVAGED DOOR AND HARDWARE IN NEW FRAME PER DOOR SCHEDULE. PROVIDE ADDITIONAL HARDWARE AND ACCESSORIES AS REQUIRED.
- 08.04 HOLLOW METAL FRAME TRANSOM WINDOW (ABOVE). SEE WINDOW TYPES. BID WINDOW AS PART OF ADD ALTERNATE 1.
- 09.01 INSTALL NEW GYPSUM BOARD, 5/8" THICK, TYPE 'X', ATTACHED TO EXISTING METAL STUD FRAMING AFTER ALL IN WALL M/E/P WORK IS COMPLETE IN AREAS WHERE EXISTING GYPSUM BOARD HAS BEEN REMOVED. PATCH AND REPAIR TO MATCH EXISTING WALL CONSTRUCTION AND PAINTER FINISH SCHEDULE.
- 10.03 PAPER TOWEL DISPENSER, OWNER FURNISHED, CONTRACTOR INSTALLED. CONTRACTOR SHALL PROVIDE BACKING IN WALL AS REQUIRED. SEE RELEVANT DETAILS 1/G003 AND 1/G004 FOR MOUNTING HEIGHT, LOCATION, ETC.
- 10.04 SOAP DISPENSER, OWNER FURNISHED, CONTRACTOR INSTALLED. CONTRACTOR SHALL PROVIDE BACKING FOR ALL OWNER FURNISHED ITEMS. SEE RELEVANT DETAILS 1/G003 AND 1/G004 FOR MOUNTING HEIGHT, LOCATION, ETC.
- 10.05 SHARPS DISPOSAL, OFCI, SEE SHEET G003 FOR MOUNTING HEIGHT. COORDINATE EXACT LOCATION WITH OWNER.
- 10.06 GLOVES DISPENSER, OFCI, SEE SHEET G003 FOR MOUNTING HEIGHT. COORDINATE EXACT LOCATION WITH OWNER.
- 11.01 FRIDGE, UNLESS NOTED OTHER WISE, THIS APPLIANCE SHALL BE OWNER FURNISHED CONTRACTOR INSTALLED.
- 11.02 WALL MOUNTED DRY ERASE BOARD, OFCI, PROVIDE BACKING PER DETAIL 5/A502A. COORDINATE EXACT LOCATION AND WALL MOUNTED ITEMS WITH OWNER.
- 11.03 WORKSTATION EQUIPMENT TO BE OFCI. COORDINATE WITH ELECTRICAL DRAWINGS TO PROVIDE REQUIRED POWER AND DATA.
- 12.01 FURNITURE, OFOI.
- 12.02 WATER FEATURE, OFOI, SEE ELECTRICAL DRAWINGS.
- 12.07 COUNTERTOP, MONOLITHIC MATERIAL (SOLID SURFACE), MATCH EXISTING FINISHES. PROVIDE GROMMET AS REQUIRED.
- 12.08 COUNTERTOP WITH INTEGRAL SINK, MONOLITHIC MATERIAL (SOLID SURFACE) SALVAGED AND REINSTALLED, IF DAMAGED IN CONSTRUCTION PROVIDE NEW SOLID SURFACE COUNTERTOP WITH INTEGRAL SINK TO MATCH EXISTING.
- 22.02 WALL MOUNTED HAND WASH SINK. SEE RELEVANT DETAILS 1/G003 AND 1/G004 FOR MOUNTING HEIGHT, LOCATION, ETC. SEE PLUMBING DRAWINGS.
- 26.01 RELOCATED SERVER RACK CABINET. SEE ELECTRICAL DRAWINGS.

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Floor Plan
Level 6

A113






1 Dimension Floor Plan - Level 6
SCALE: 1/4" = 1'-0"

KEYED NOTES


06.04 NEW CASEWORK DIMENSIONS TO MATCH EXISTING CASEWORK TO REMAIN IN EXAM ROOMS 1 AND 2. FIELD VERIFY.

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024


Dimension
Floor Plan
Level 6

A114





1 Reflected Ceiling Plan - Level 6
SCALE: 1/4" = 1'-0"



KEYED NOTES


- 09.02 PAINT EXISTING SOFFIT, OR HEADER AS OCCURS, TO MATCH ADJACENT WALL COLOR.
- 09.03 ACOUSTIC CEILING TILES AND GRIDS. CEILING TILES TO BE ARMSTRONG CORTEGA, 704, 24" X 24" X 3/4", EDGE DETAIL: REGULAR, FIELD VERIFY AND MATCH EXISTING. GRIDS SHALL BE 15/16" PRELUDE XL EXPOSED TEE HEAVY DUTY. ANGLE MOLDING SHALL BE 7/8" WITH BERC 2 CLIPS. SEE CEILING DETAILS ON SHEET A503A. SEE M/E/P DRAWINGS FOR LIGHTS AND DIFFUSERS.
- 09.04 ACOUSTIC CEILING TILES AND GRIDS. CEILING TILES TO BE ARMSTRONG ULTIMA HEALTH ZONE (ITEM # 1933) 24" X 24" X 3/4" EDGE DETAIL: SQUARE LAY-IN. GRIDS SHALL BE 15/16" PRELUDE XL EXPOSED TEE HEAVY DUTY. ANGLE MOLDING SHALL BE 7/8" WITH BERC 2 CLIPS. SEE CEILING DETAILS ON SHEET A503A. SEE M/E/P DRAWINGS FOR LIGHTS AND DIFFUSERS.
- 09.05 CLEAN AND RE-INSTALL CEILING TILES. GRIDS, FIXTURES AS NOTED AFTER ALL ABOVE CEILING WORK IS COMPLETE. REPLACE TO MATCH EXISTING IF DAMAGED DURING CONSTRUCTION.
- 09.11 GYPSUM BOARD HEADER. SEE DETAIL 6/A503A UNLESS NOTED OTHERWISE WITH A SEPARATE SPECIFIC DETAIL.

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107


NJRA Project # 24002.00
Construction Documents June 27, 2024

Reflected
Ceiling Plan
Level 6

A116



1 Finish Floor Plan Level 1
SCALE: 1/4" = 1'-0"




KEYED NOTES

01.01 LINE OF TRANSITION BETWEEN DIFFERENT FLOOR FINISHES. SEE DETAILS ON SHEET A603A.


SAMPLE LAYOUTS

SAMPLE LAYOUT 1



NOTE: AS INDICATED IN ROOM NUMBER 101, MAJORITY OF THE ROOMS IN THE PROJECT SHALL HAVE A SINGLE TYPE OF FLOOR FINISH, WALL BASE AND WALL FINISH. WALL FINISH INDICATED AS "W2" SHALL APPLY TO ALL FOUR WALLS FROM FLOOR TO CEILING.

SAMPLE LAYOUT 2




NOTE: AS INDICATED IN ROOM NUMBER 102, SOME ROOMS SHALL HAVE MULTIPLE FLOOR AND WALL FINISHES. SEE GENERAL NOTE "C" ON SHEET A603A FOR FLOOR COVERING TRANSITIONS. THE WALL FINISH INDICATED AS "W2" IN THE ROOM (WITHOUT AN ARROW POINTING TO ANY SPECIFIC WALL) SHALL APPLY TO THE WEST, NORTH AND EAST WALL, WHERE WALL FINISHES ARE INDICATED WITH AN ARROW POINTING TO THE SOUTH SIDE, WALL SHALL HAVE MULTIPLE FINISHES SUCH AS "W2" AND "W4". SEE INTERIOR ELEVATIONS FOR TRANSITION DETAILS BETWEEN "W3" AND "W4".

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024


Finish Plan
Level 6

A117




NOTE: CASEWORK IN EXAM ROOMS TO MATCH EXISTING EXAM 1 CASEWORK.

1 Typical Exam Casework
SCALE: 3/8" = 1'-0"



NOTE: EXISTING CABINETS REMOVED IN GOOD CONDITION THAT PROVIDE EQUIVALENT STORAGE SPACE AND MAINTAIN 3'-0" CLR OPEN SPACE CAN BE USED IN PLACE OF NEW CABINETS.

2 Break Area
SCALE: 3/8" = 1'-0"



NOTE: EXISTING CABINETS REMOVED IN GOOD CONDITION THAT PROVIDE EQUIVALENT STORAGE SPACE CAN BE USED IN PLACE OF NEW CABINETS.

3 Hall
SCALE: 3/8" = 1'-0"

KEYED NOTES


- 05.01 IN-WALL STEEL ANGLE SUPPORTS FOR COUNTERTOP WHERE KNEE SPACE OCCURS BELOW. LOCATE COUNTER SUPPORTS AT 3'-0" O.C. MAX. SEE DETAIL 5/A505B. PAINT TO MATCH WALL COLOR. PROVIDE 16 GA STUDS AT COUNTERTOP SUPPORT. TYPICAL.
- 06.02 FILLER PANEL PLASTIC LAMINATE WRAPPED OVER 3/4" PARTICLE BOARD. PROVIDE FILLER PANEL BETWEEN CABINETS AND BETWEEN CABINET AND WALL. TYPICAL.
- 06.04 NEW CASEWORK DIMENSIONS TO MATCH EXISTING CASEWORK TO REMAIN IN EXAM ROOMS 1 AND 2. FIELD VERIFY.
- 06.08 CABINET FASCIA. SEE DETAIL 2/A505B.
- 09.08 WALL BASE. SEE FINISH FLOOR PLANS FOR WALL BASE TYPE INDICATED WITH A WALL BASE TAG (AS B1, B2, B3, ETC.). SEE FINISH SCHEDULE ON SHEET A603A FOR MATERIAL, SIZE, COLOR, ETC. FOR EACH WALL BASE TAG.
- 12.07 COUNTERTOP, MONOLITHIC MATERIAL (SOLID SURFACE), MATCH EXISTING FINISHES. PROVIDE GROMMET AS REQUIRED.

GENERAL NOTES

- A. SEE SHEET G003 AND G005 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com





Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Interior Elevations

A251



KEYED NOTE

- LINE OF FLOOR OR ROOF DECK AS OCCURS.
- TO ACCOMMODATE FOR STRUCTURE DEFLECTION, PROVIDE SLIP CONNECTION BETWEEN TOP RUNNER TRACK AND METAL STUD FRAMING. SEE DETAIL 9 / A502B
- STUD FRAMING AROUND DUCT OPENINGS. SEE DETAIL 11 / A502A
- METAL STUDS, 20 GA STRUCTURAL (35 MILS) AT 16" O.C. U.N.O. BASED ON WALL TYPES INDICATED IN FLOOR PLANS. PROVIDE STUD SIZE AS INDICATED IN WALL TYPES WITH TRACK RUNNERS AT TOP AND BOTTOM. FOR STUD FRAMING AROUND DOOR AND WINDOW OPENINGS. SEE DETAIL 11 / A502A
- LINE OF CEILING AS OCCURS. SEE REFLECTED CEILING PLAN.
- STEEL STUDS: C-H SHAPED, 20 GA STRUCTURAL AT 24" O.C.
- PROVIDE ACOUSTIC INSULATION BLANKET FOR FULL DEPTH OF THE STUD CAVITY THROUGHOUT. UNO, FOR 4" & 3 5/8" STUDS PROVIDE R-13 UNFACED BATT INSULATION AND FOR 6" STUDS PROVIDE R-19 UNFACED BATT INSULATION. PROVIDE KRAFT FACED INSULATION FOR ALL APPLICATIONS AT EXTERIOR WALLS.
- GYPSUM BOARD, 5/8" THICK, TYPE 'X', U.N.O. ATTACHED TO METAL STUD FRAMING. SEE GENERAL NOTE 'B' BELOW.
- ANCHOR BASE TRACK TO CONCRETE FLOOR BELOW. SEE DETAIL 8 / A502A
- FILL GAP BETWEEN DECK AND METAL TRACK TOP RUNNER WITH FIRESTOP SEALANT, SEAL TIGHTLY AROUND ALL PIPES, CONDUITS, DUCTS, ETC., ON EACH SIDE OF THE FIRE BARRIER WALL (CONTINUOUS) WITH APPROVED FIRESTOP SEALANT INSTALLED AROUND ALL PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE FIRE BARRIER.
- FILL GAP BETWEEN DECK AND METAL TRACK TOP RUNNER WITH ACOUSTIC SEALANT, SEAL TIGHTLY AROUND ALL PIPES, CONDUITS, DUCTS, ETC., ON EACH SIDE OF THE WALL (CONTINUOUS) AND AROUND ALL PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE WALL.
- STOP GYPSUM BOARD 1/4" ABOVE THE FLOOR TYP. ON EACH SIDE OF WALL. PROVIDE ACOUSTIC SEALANT AT SOUND WALLS AND FIRESTOP SEALANT AT RATED WALLS ON EACH SIDE OF THE WALL (CONTINUOUS).
- OUTLET BOX AS OCCURS. PROVIDE FIRE BARRIER MOLDABLE PUTTY PADS AND FIRESTOP SEALANT AROUND ELECTRICAL BOXES AT ALL RATED WALLS AND SOUND BARRIER WALLS AND AT BACK TO BACK ELECTRICAL BOXES AT SMOKE PARTITION WALLS TYP.
- PROVIDE STRAPPING AND BLOCKING AT FURRING WALL. SEE DETAIL 12 / A502A
- LINE INDICATES EXISTING WALL OR STRUCTURE. PROVIDE 1/4" AIR GAP.
- GYPSUM BOARD SHAFT LINER PANEL, 1" THICK, TYPE 'X', ATTACHED TO C-H STUDS.
- STEEL RUNNER, Z SHAPED WITH UNEQUAL LEGS OF 1" AND 2", 20 GA, ATTACHED TO FLOOR AND STRUCTURE ABOVE WITH FASTENERS LOCATED NO GREATER THAN 2" FROM ENDS AND NO MORE THAN 24" O.C. RUNNERS SHOULD BE POSITIONED WITH SHORT LEG TO FINISHED SIDE OF WALL.
- STOP STUD RUNNER AT BASE PLATES.
- STEEL PLATE, 3/8" THICK WITH 4-1/2" DIA. HILTI-HY200 EPOXY ANCHORS WITH 2-3/8" HILTI-HIT-2 ANCHORS. EMBED INTO CONCRETE 2-3/8".
- TUBE STEEL 3" x 3" x 3/16" AT 4'-0" O.C.
- WALL CAP, SOLID SURFACE MATERIAL ATTACHED TO WALL BELOW.
- PLYWOOD, 3/4" THICK, CONTINUOUS FIRE TREATED. ATTACH PLYWOOD TO VERTICAL STEEL TUBE POST WITH L SHAPED METAL CLIPS AND FASTENERS.
- PROVIDE 1/4" RADIUS ROUNDED EDGE, CONTINUOUS.
- METAL STUDS 16 GA STRUCTURAL (35 MIL) AT 16" O.C. PROVIDE RUNNERS AT TOP AND BOTTOM. ATTACH TOP RUNNER TO PLYWOOD AND VERTICAL STEEL POST.
- LINE OF FLOOR.
- RESILIENT CHANNEL, 2" x 1/2", INSTALLED HORIZONTALLY AND SPACED AT 24" O.C.
- WHERE CONDITIONS PROHIBIT EXTENDING STUDS TO DECK, PROVIDE CROSS BRACING FROM TOP RUNNER OF WALL TO STRUCTURE ABOVE WITH 5/8" 20 GA STUDS AT 4'-0" O.C. ALTERNATE DIRECTION OF BRACING TO STRUCTURE EVERY 48" AS CONDITIONS ALLOW.
- TOP TRACK, 18 GA. REQUIRED AT CROSS-BRACED WALLS.















GENERAL NOTES
















- CONTRACTOR SHALL VERIFY ITEMS LIKE SEMI OR FULLY RECESSED MISCELLANEOUS BOXES, PANELS, PLUMBING LINES, CONDUITS, PIPES, ETC., THAT ARE CONCEALED IN THE WALL IF 5/8" METAL STUDS ARE INADEQUATE. CONTRACTOR SHALL NOTIFY THE ARCHITECT AND USE 6" STUDS. COORDINATE WITH ALL THE CONSULTANT DRAWINGS PRIOR TO WALL CONSTRUCTION AND USE 6" OR 8", 20 GAUGE METAL STUDS FOR FRAMING IN LIEU OF 5/8" METAL STUDS.
- USE 5/8" CEMENTITIOUS BOARD IF CERAMIC OR PORCELAIN WALL TILES ARE INDICATED IN THE FINISH SCHEDULE AS WALL FINISH. CEMENTITIOUS BOARD SHALL EXTEND FROM FINISHED FLOOR TO HEIGHT OF TILE. 5/8" WATER RESISTANT GYPSUM BOARD TO BE USED ABOVE TILE HEIGHT IN RESTROOMS. SEE FLOOR PLANS FOR CERTAIN UNIQUE LOCATIONS THAT REQUIRE LEAD LINED GYPSUM BOARD, IMPACT RESISTANT GYPSUM BOARD, SOUND ATTENUATION GYPSUM BOARD, ETC.
- PROVIDE CONTROL JOINT AS PER DETAIL 14 / A502A WHEN LENGTH OF GYPSUM BOARD EXCEEDS 50' IN ONE DIRECTION OR AS DIRECTED BY ARCHITECT. COORDINATE WITH ARCHITECT FOR CONTROL JOINT LOCATIONS. WHEN GYPSUM BOARD OR CEMENTITIOUS BOARD IS ATTACHED VERTICALLY, USE 1" LONG #6 DRYWALL SCREWS TO EACH STUD. SCREWS ARE 8" O.C. AT PERIMETER AND 12" AT INTERMEDIATE STUD. WHEN GYPSUM BOARD IS ATTACHED HORIZONTALLY TO STUDS, HORIZONTAL JOINTS SHALL BE STAGGERED WITH THOSE ON THE OPPOSITE SIDE. SCREWS FOR HORIZONTAL APPLICATION SHALL BE 8" O.C. AT VERTICAL EDGES AND 12" O.C. AT INTERMEDIATE STUDS.
- FOR LOCATION OF FIRE RATED WALLS AND SMOKE PARTITION WALLS SEE CODE COMPLIANCE PLAN.
- SEE DIMENSION FLOOR PLANS FOR WALL TYPES USED IN THIS PROJECT. SOME WALL TYPES MAY NOT BE USED IN THIS PROJECT.
- WHERE LEAD LINED WALLS ARE INDICATED ON THE DRAWINGS, USE 1/2" GA STUDS IN LIEU OF THE GAUGE OF STUDS CALLED OUT IN THE WALL TYPES.
- IN PLACES WHERE MECHANICAL DUCTS ARE DESIGNED TO PENETRATE THE FLOOR, TO MEET THE REQUIREMENTS OF FIRE RATING, PROVIDE A TWO-HOUR FIRE RATED ENCLOSURE AT TOP AND BOTTOM OF SHAFT AS INDICATED IN DETAILS 5 / A502B AND 8 / A502B
- IN PLACES WHERE A TWO-HOUR HORIZONTAL ENCLOSURE IS REQUIRED TO SEPARATE THE DUCTS FROM THE SPACE BELOW, PROVIDE A TWO-HOUR FIRE RATED HORIZONTAL ASSEMBLY AS PER DETAILS 5 / A502B AND 8 / A502B
- IN PLACES WHERE BACKING IS REQUIRED IN WALLS TO SUPPORT WALL HUNG EQUIPMENT, CABINETS, ETC., PROVIDE BACKING IN WALL PER DETAILS 5 / A502A AND 13 / A502A














Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6
 5171 Cottonwood Street #450
 Murray, Utah 84107


NJRA Project # 2402.00
Construction Documents June 27, 2024

1 Wall Types (Note: See dimension floor plans for location of wall types used in this project. Some wall types shown above may not be used in this project.)
SCALE: 1 1/2" = 1'-0"









KEYED NOTES

- CONTINUOUS SEALANT ON BOTH SIDES OF THE FRAME.
- DOOR FRAME SEEN BEYOND.
- CLOSER & CARRIAGE TRACK PER MFR.
- GYPSUM BOARD, 5/8" THICK, TYPE 'X', ATTACH TO METAL STUD FRAMING. SEE WALL TYPES.
- STEEL RUNNER (18 GAUGE) FASTENED WITH SCREWS TO STRUT STUDS AT EACH END. SEE DETAIL 7/A502A.
- HOLLOW METAL DOOR FRAME, FRAME THICKNESS VARIES WITH WALL THICKNESS. SEE FLOOR PLAN AND WALL SECTIONS, PAINT FRAME.
- SEE WALL TYPES FOR WALL WIDTH AND STUD SIZE.
- FRAME DEPTH SHALL BE WALL WIDTH PLUS 1".
- LINE OF WALL, AS OCCURS.
- PROVIDE DOUBLE METAL STUDS AT FRAME JAMBS, WALL ENDS, ETC. PROVIDE STEEL STRAPS (6" HIGH 16 GAUGE STRAPS AT 2'-0" O.C.) SEE DETAIL 7/A502A.
- DOOR HINGE AS OCCURS. SEE DOOR AND HARDWARE SCHEDULE. SEE FLOOR PLAN FOR DOOR SWING.

1 Door Frame in Stud Wall
SCALE: 3" = 1'-0"

KEYED NOTES

- VALANCE WITH END CAPS PER MFR.
- LINE OF VALANCE ABOVE.
- CLOSER & CARRIAGE TRACK PER MFR.
- ALUMINUM DOOR FRAME PER MFR.
- BOTTOM TRACK PER MFR.
- SILL GUIDE PER MFR.
- DOOR, SEE DOOR SCHEDULE. FINISH TO MATCH ALL NEW DOORS IN THE PROJECT.
- EPDM GASKET BOTH SIDES PER MFR.
- BACK TO BACK 1" LADDER PULLS.
- LINE OF FRAME ABOVE.
- STILE POCKET PER MFR.
- FOR JAMB FRAMING CONDITION SEE DETAIL 7/A502A. PROVIDE 16 GA STUDS AT JAMBS AS OPPOSITE TO 18GA AS CALLED OUT ON DETAIL 7/A502A.

2 Barn Door Plan View Detail
SCALE: 3" = 1'-0"

KEYED NOTES

- 2 X 6 X CONT. FIRE TREATED WOOD BLOCKING FOR THE FULL LENGTH OF VALANCE PLUS 6" ON EITHER SIDE.
- VALANCE WITH END CAPS PER MFR.
- DOOR, SEE DOOR SCHEDULE. FINISH TO MATCH ALL NEW DOORS IN THE PROJECT.
- FOR HEADER FRAMING CONDITION SEE DETAIL 7/A502A.

3 Barn Door Frame at Wall
SCALE: 3" = 1'-0"

KEYED NOTES

- 2 X 6 X CONT. FIRE TREATED WOOD BLOCKING FOR THE FULL LENGTH OF VALANCE PLUS 6" ON EITHER SIDE.
- VALANCE WITH END CAPS PER MFR.
- CLOSER & CARRIAGE TRACK PER MFR.
- ALUMINUM DOOR FRAME PER MFR.
- BOTTOM TRACK PER MFR. SEEN BEYOND, NOT TO CONTINUE IN DOOR OPENING.
- SILL GUIDE PER MFR.
- DOOR, SEE DOOR SCHEDULE. FINISH TO MATCH ALL NEW DOORS IN THE PROJECT.
- FOR HEADER FRAMING CONDITION SEE DETAIL 7/A502A.

4 Barn Door Detail Section Head and Sill
SCALE: 3" = 1'-0"

KEYED NOTES

- ROOM NUMBER (1/32" RAISED TEXT CHARACTERS, HELVETICA FONT, MATTE FINISHED OPAQUE ACRYLIC SHEET) ATTACHED TO FRONT PANEL.
- MATTE FINISHED OPAQUE ACRYLIC FRONT PANEL (WITH TRANSPARENT WINDOW) ATTACHED TO BASE PANEL.
- TRANSPARENT WINDOW FOR TEXT INSERT (HELVETICA FONT). TEXT INSERT SHALL BE FURNISHED AND INSTALLED BY SIGN CONTRACTOR.
- BRAILLE CHARACTERS AS PER ADA (AMERICANS WITH DISABILITIES ACT) REQUIREMENTS DENOTING ROOM NUMBER AND NAME.
- RADIUS CORNER, 1" TYPICAL.
- MATTE FINISHED OPAQUE ACRYLIC FRONT PANEL ATTACHED TO BASE PANEL.
- PROVIDE APPROPRIATE SYMBOL FOR MEN, WOMEN, UNSEX, BOYS AND GIRLS TOILET ROOM AS OCCURS.
- PROVIDE APPROPRIATE SYMBOL FOR STAIR, DISABLED SIGN, ETC. AS INDICATED.
- ROOM NAME (1/32" RAISED TEXT CHARACTERS, HELVETICA FONT, MATTE FINISHED OPAQUE ACRYLIC SHEET) ATTACHED TO FRONT PANEL.
- PROVIDE DISABLED SYMBOL AS INDICATED IN THE SIGN FOR ALL ROOMS THAT ARE WHEEL CHAIR ACCESSIBLE.
- LINE OF WALL.
- MATTE FINISHED, OPAQUE ACRYLIC SHEET BASE PANEL ATTACHED TO SHIM PLATE.
- SHIM PLATE, ALUMINUM, 1/4" THICK, CONCEALED, WITH PRE-DRILLED HOLES FOR COUNTERSUNK FASTENERS. USE APPROPRIATE FASTENERS DEPENDING ON THE SUBSTRATE.
- RECESS 1/16" FOR TEXT INSERT, FOR SIGN 'TYPE - S1' ONLY.
- SIGNAGE.
- SIGN AT ALL ACCESSIBLE LOCATION.
- DOOR FRAME, SEE DOOR SCHEDULE.
- DOOR, SEE DOOR SCHEDULE.
- OPENING IN WALL.
- LINE OF FLOOR.

5 Room Signage Detail
SCALE: N.T.S.

KEYED NOTES

NOTE:
A. PROVIDE ROOM SIGN AT EACH DOORWAY OR A WALL OPENING LEADING TO A ROOM. SEE FINISH FLOOR PLAN FOR REQUIRED NUMBER OF SIGNS. SIGN TYPE, ROOM NAMES, ETC.
B. SIGN CONTRACTOR SHALL COORDINATE WITH OWNER AND PROVIDE TEXT INSERTS FOR OCCUPANTS PROPER NAME FOR ALL 'TYPE S1' WALL SIGNS.
C. ALL COLORS SHALL BE SELECTED BY ARCHITECT AND MOUNTED ON WALL OR DOOR PER DETAIL 'B'.

6 Sign Mounting Elevations
SCALE: 1/2" = 1'-0"

KEYED NOTES

- DOOR, SEE DOOR SCHEDULE FOR DOOR TYPE.
- FRAME SEEN BELOW.
- HOLLOW METAL WINDOW FRAME AS OCCURS, ANCHOR AS RECOMMENDED BY FRAME MANUFACTURER. PAINT FRAME.
- GLAZING, SEE WINDOW SCHEDULE.
- CONTINUOUS SEALANT ON BOTH SIDES OF FRAME, AT BUILDING EXTERIOR SIDE USE CAULKING WITH BACKER ROD. VERIFY CAULKING COLOR WITH ARCHITECT.
- WINDOW GLAZING STOP, STOPS SHALL BE LOCATED ON THE (MORE SECURE) ROOM SIDE (AS OPPOSED TO THE LESS SECURE CORRIDOR SIDE), COORDINATE WITH ARCHITECT FOR LESS AND MORE SECURE AREAS THAT ARE NOT APPARENT IN FLOOR PLAN.
- PROVIDE DOUBLE METAL STUDS AT FRAME JAMBS, WALL ENDS, ETC. PROVIDE STEEL STRAPS (6" HIGH 16 GAUGE STRAPS AT 2'-0" O.C.) SEE DETAILS ON SHEET A502A.

7 Door Frame Head Detail @ Transom
SCALE: 3" = 1'-0"

KEYED NOTES



- SCHEDULED WALL, SEE DIMENSION PLAN.
- HOLLOW METAL WINDOW FRAME AS OCCURS, ANCHOR AS RECOMMENDED BY FRAME MANUFACTURER. PAINT FRAME.
- GLAZING, SEE WINDOW SCHEDULE.
- CONTINUOUS SEALANT ON BOTH SIDES OF FRAME, AT BUILDING EXTERIOR SIDE USE CAULKING WITH BACKER ROD. VERIFY CAULKING COLOR WITH ARCHITECT.
- WINDOW GLAZING STOP, STOPS SHALL BE LOCATED ON THE (MORE SECURE) ROOM SIDE (AS OPPOSED TO THE LESS SECURE CORRIDOR SIDE), COORDINATE WITH ARCHITECT FOR LESS AND MORE SECURE AREAS THAT ARE NOT APPARENT IN FLOOR PLAN.
- PROVIDE DOUBLE METAL STUDS AT FRAME JAMBS, WALL ENDS, ETC. PROVIDE STEEL STRAPS (6" HIGH 16 GAUGE STRAPS AT 2'-0" O.C.) SEE DETAILS ON SHEET A502A.

8 HM Window Jamb Detail (Head & Sill Sim)
SCALE: 3" = 1'-0"

KEYED NOTES

- WINDOW FRAME, EXISTING.
- LINE OF WINDOW FRAME SEEN BELOW.
- LINE OF WINDOW WALL (WHERE OCCURS) SEEN BELOW.
- DASHED LINE INDICATES VERTICAL WALL SURFACE BELOW THE SILL AND WINDOW OPENING.
- GLAZING, EXISTING.
- WALL, CONSTRUCT WALL PER WALL TYPES.
- NOT USED.
- MULLION MATE BRAKE FORMED METAL END CAP ATTACHED TO WALL WITH FASTENERS. CAP WIDTH SIZE SHALL MATCH WALL THICKNESS. PAINT EXPOSED END CAP TO MATCH WALL COLOR.
- TAPE AND FLOAT END CAP TO GYPSUM BOARD WALL AS REQUIRED FOR A SMOOTH EVEN TRANSITION.
- FACTORY APPLIED GASKET WITH ADHESIVE ON BOTH SIDES.
- PARTITION CLOSURE, CLOSURE SHALL BE EXTRUDED ALUMINUM, ANODIZED FINISH, PRE-ASSEMBLED AND SPRING LOADED TO PROVIDE A TIGHT FIT FOR VERTICAL JUNCTURES OF PARTITIONS AND WINDOW WALLS. CLOSURE SHALL BE SOUND TESTED TO A COMPOSITE STC OF 56 WITH ACOUSTICAL BATTS FOR SOUND ATTENUATION. BASIS-OF-DESIGN IS MULLION MATE AND/OR WINDOW MATE - SERIES 40 PLUS MANUFACTURED BY GORDON INTERIOR SPECIALTIES DIVISION, GORDON, INC., 5023 HAZEL JONES ROAD, BOSSIER CITY, LA 71111, (800) 747-8954, FAX (800) 877-8746, WWW.GORDONINTERIORS.COM. VERIFY WITH ARCHITECT AND GET APPROVAL PRIOR TO INSTALLING EQUIVALENT PRODUCT BY OTHER MANUFACTURERS.
- PROVIDE PAINTABLE ACOUSTICAL CAULK, CONTINUOUS.


9 Wall Cap Detail
SCALE: 3" = 1'-0"




- KEYED NOTES**
- FILE DRAWER. MINIMUM WIDTH SHALL BE 1'-4" TO HANG FOLDERS (FOR 8-1/2" x 11" SIZE PAPER).
 - DETAIL FOR STEEL SUPPORTS FOR COUNTERTOP AT STUD WALLS.
 - DETAIL FOR STEEL SUPPORTS FOR COUNTERTOP AT MASONRY AND CONCRETE WALLS.
 - STEEL SUPPORT FOR COUNTERTOP. SEE RELEVANT DETAIL FOR STUD WALL, CMU, AND CONCRETE WALL. SUPPORT IS NOT REQUIRED IF THERE IS AN ADJACENT BASE CABINET.
 - FILLER PANEL FOR EXTENDED WALL CABINET. TYPICALLY LOCATED AT ROOM CORNER.
 - SINK. SEE ARCHITECTURAL AND PLUMBING DRAWINGS FOR SINK TYPE.
 - PROVIDE END PANEL MATCHING THE FRONT SUB PANEL. IF THERE IS A ADJACENT BASE CABINET, END PANEL IS NOT REQUIRED.

1 Cabinet Legend
SCALE: 3/8" = 1'-0"


Note: See Interior Elevations (S.I.E.) for occurrence of cabinet types used in this project. Some cabinet type shown above may not be used in this project.




2 Wall Cabinet with Door
SCALE: 1" = 1'-0"




3 Wall Cabinet without Door
SCALE: 1" = 1'-0"




4 Wall Cabinet Door & Shelf
SCALE: 1" = 1'-0"




5 Base Cabinet with Door
SCALE: 1" = 1'-0"




6 Base Cabinet with Drawer and Door
SCALE: 1" = 1'-0"




7 Base Cabinet with Drawers
SCALE: 1" = 1'-0"




8 Base Cabinet with Drawers
SCALE: 1" = 1'-0"



9 Base Cabinet with Two File Drawers
SCALE: 1" = 1'-0"



10 Base Cabinet without Door
SCALE: 1" = 1'-0"



KEYED NOTES

1. END PANEL AT BOTH ENDS TO BE CONTINUOUS WITHOUT BREAK/REVEAL BETWEEN SLANTED FASCIA (DUST TOP) AND WALL OR FULL HEIGHT CABINET.
2. SLANTED FASCIA (DUST TOP), TYPICAL MITERED AT CORNER.

1 Slanted Fascia (Dust Top) Miter Detail at Corner Cabinets
SCALE: 3/4" = 1'-0"

KEYED NOTES

1. LINE OF WALL
2. LINE OF CEILING. SEE REFLECTED CEILING PLAN.
3. BRACE PANEL. PROVIDE BRACE AS REQUIRED TO SUPPORT THE VERTICAL FASCIA PANEL. LOCATE BRACE AT 3'-0" O.C.
4. SLANTED FASCIA PANEL. PLASTIC LAMINATE WRAPPED OVER PLYWOOD.
5. WALL CABINET BODY AS OCCURS.
6. VERTICAL FASCIA. PLASTIC LAMINATE WRAPPED OVER PLYWOOD.
7. CABINET DOOR. SEE CABINET TYPES AND DETAILS.

NOTE: FOR SLANTED FASCIA CORNER CONDITION, SEE DETAIL 1 / A505B. SEE INTERIOR ELEVATIONS FOR VERTICAL AND SLANTED FASCIA LOCATIONS.

2 Wall Cabinet Fascia
SCALE: 1 1/2" = 1'-0"

KEYED NOTES

1. LINE OF WALL.
2. FASTENERS AS REQUIRED. ALIGN WITH STUDS WHERE POSSIBLE.
3. STEEL BACKING PLATE. PLATE SHALL BE 1/2 GAUGE, 6" WIDE WITH REQUIRED LENGTH TO COVER CABINETS.
4. SOLID WOOD BLOCKING, TYPICALLY ATTACHED TO CABINET BODY.
5. COUNTERTOP AND BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
6. CABINET BASE BOX. BOX SHALL BE BUILT WITH PLYWOOD, 3/4" THICK, PRESSURE TREATED. BASE BOX SHALL BE ANCHORED TO FLOOR WITH STEEL "L" CLIPS AND FASTENERS AS REQUIRED. BASE CABINET SHALL BE ATTACHED TO THE BASE BOX.
7. LINE OF FLOOR.
8. NEW WALL (OR EXISTING WALL WHERE OCCURS). SEE WALL TYPE FOR WALL CONSTRUCTION.

NOTE: WHEN CABINETS ARE MOUNTED TO CONCRETE WALL OR MASONRY (CMU BLOCKS) WALL, BACKING PLATES ARE NOT REQUIRED. PROVIDE COMPATIBLE MASONRY WALL ANCHORS AND FASTENERS TO ATTACH THE CABINETS.

3 Typical Cabinet Body Attachment to Walls
SCALE: 1" = 1'-0"

KEYED NOTES

1. LINE OF FLOOR.
2. WALL BASE. SEE FINISH SCHEDULE.
3. LINE OF MASONRY OR CONCRETE WALL AS OCCURS.
4. COUNTERTOP SUPPORT. PAINTED. SUPPORT SHALL BE STEEL ANGLE, 2"x2"x1/4". PIECES MITERED AND WELDED @ 90° ANGLE AS INDICATED. CHAMFER EXPOSED EDGE (BELOW COUNTERTOP EDGE) AND GRIND ALL EXPOSED EDGES SMOOTH. ATTACH SUPPORT TO MASONRY OR CONCRETE WALL WITH 3/8" EPOXY BOLTS, AS SHOWN. SUPPORTS SHALL BE LOCATED VERTICALLY ON WALL AT 4'-0" O.C. MAXIMUM.
5. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
6. PROVIDE GROMMETS AT COMPUTER MONITOR LOCATIONS, KNEE SPACES, COUNTERTOP EQUIPMENT, ETC.
7. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B

4 Steel Support For Countertop at Masonry & Concrete Walls
SCALE: 1" = 1'-0"

KEYED NOTES

1. LINE OF FLOOR.
2. WALL BASE. SEE FINISH SCHEDULE.
3. WALL. SEE FLOOR PLAN & WALL TYPES.
4. COUNTERTOP SUPPORT. PAINTED. SUPPORT SHALL BE STEEL ANGLE, 2"x2"x1/4". PIECES MITERED AND WELDED @ 90° ANGLE AS INDICATED. CHAMFER EXPOSED EDGES SMOOTH. ATTACH SUPPORT TO METAL STUDS INSIDE WALL WITH 1/2" BOLTS, AS SHOWN. AT FLOOR, PROVIDE 3" WIDE X 6" LONG X 1/4" THICK, BASE STEEL PLATE WELDED TO VERTICAL STEEL ANGLE. ATTACH BASE PLATE TO FLOOR WITH TWO 1/2" DIAMETER ANCHOR BOLTS (ON EITHER SIDE OF THE VERTICAL ANGLE) WITH 3" MINIMUM EMBED IN CONCRETE FLOOR. CONTRACTOR SHALL REVIEW INTERIOR ELEVATIONS AND LOCATE SUPPORTS DURING WALL CONSTRUCTION. SUPPORT SPACING SHALL NOT EXCEED 4'-0" O.C. MAXIMUM.
5. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
6. PROVIDE GROMMETS AT COMPUTER MONITOR LOCATIONS, KNEE SPACES, COUNTERTOP EQUIPMENT, ETC.
7. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B

5 Steel Support for Countertop at Stud Wall
SCALE: 1" = 1'-0"

KEYED NOTES

1. COUNTERTOP. PLASTIC LAMINATE WRAPPED OVER WOOD SUBSTRATE, 3/4" THICK. SUBSTRATE SHALL BE AS PER ARCHITECTURAL WOODWORK INSTITUTE (AWI) STANDARDS FOR "PREMIUM" GRADE. PROVIDE FULL ROUND EDGE AS INDICATED. WHERE PLASTIC LAMINATE COUNTERTOP IS CALLED OUT AT SINK LOCATIONS, USE EXTERIOR GRADE MARINE PLYWOOD WITH AN IMPERVIOUS SEAL. SEE DETAIL 9 / A505B
2. BACKSPLASH. INTEGRAL. PLASTIC LAMINATE SHALL RUN CONTINUOUSLY FROM COUNTERTOP TO BACKSPLASH. BACKSPLASH SHALL HAVE A 3/4" RADIUS EDGE AT TOP AS INDICATED.
3. PROVIDE FULL ROUND (BULL NOSE) EDGE AT ALL PLASTIC LAMINATE COUNTERTOPS, TYPICAL.
4. BASE CABINET DOOR AS OCCURS.
5. EXPOSED END OF THE COUNTERTOP SHALL BE WRAPPED WITH PLASTIC LAMINATE, UNLESS NOTED OTHERWISE. WHERE INDICATED IN FINISH FLOOR PLANS AND/OR INTERIOR ELEVATIONS, PROVIDE SOLID SURFACE END CAP AS PER DETAIL "E".
6. SIDESPLASH. PLASTIC LAMINATE OVER WOOD SUBSTRATE, 3/4" THICK. SUBSTRATE SHALL BE AS PER ARCHITECTURAL WOODWORK INSTITUTE (AWI) STANDARDS FOR "PREMIUM" GRADE. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPLASH ABUTS WALL AND COUNTERTOP. UNLESS NOTED OTHERWISE, SIDESPLASH IS REQUIRED AT ALL LOCATIONS WHERE COUNTERTOP ABUTS VERTICAL SURFACES SUCH AS WALLS, BUILDING COLUMNS, TALL CABINETS, ETC.
7. COUNTERTOP. MONOLITHIC MATERIAL. ATTACH COUNTERTOP TO BASE CABINET AND/OR STEEL SUPPORTS WHERE OCCURS.
8. PROVIDE 1/8" RADIUS AT ALL EXPOSED EDGE MATERIAL.
9. BACKSPLASH. MONOLITHIC MATERIAL. ATTACH BACKSPLASH TO COUNTERTOP TO PERFORM AS INTEGRAL BACKSPLASH. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPLASH ABUTS WALL.
10. SIDESPLASH. MONOLITHIC MATERIAL. ATTACH SIDESPLASH TO WALL. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPLASH ABUTS WALL AND COUNTERTOP. UNLESS NOTED OTHERWISE, SIDESPLASH IS REQUIRED AT ALL LOCATIONS WHERE COUNTERTOP ABUTS VERTICAL SURFACES SUCH AS WALLS, BUILDING COLUMNS, TALL CABINETS, ETC.
11. BASE CABINET AS OCCURS. SEE INTERIOR ELEVATIONS. AT KNEE SPACE LOCATIONS AND WHERE THERE ARE NO BASE CABINETS TO SUPPORT THE COUNTERTOP, PROVIDE STEEL SUPPORTS PER DETAILS 4 / A505B AND 5 / A505B
12. END CAP. SOLID SURFACE MATERIAL ATTACHED TO COUNTERTOP. PROVIDE MATCHING BULL NOSE EDGE AT FRONT AND 1/8" RADIUS EDGE AS INDICATED.
13. LINE OF WALL.

6 Typical Countertop Detail
SCALE: 1" = 1'-0"

NOTE: SEE INTERIOR ELEVATIONS AND FINISH FLOOR PLANS FOR LOCATIONS OF DIFFERENT COUNTERTOPS (P.L. AND/OR "M.M.") REQUIRED IN THIS PROJECT. SEE FINISH SCHEDULE, SHEET A603A, FOR COLOR, STYLE, ETC. FOR VARIOUS COUNTERTOP MATERIALS ("P.L." DENOTES PLASTIC LAMINATE AND "M.M." DENOTES MONOLITHIC MATERIAL).

KEYED NOTES

1. LINE OF WALL, AS OCCURS. IF CABINET IS LOCATED AT AN ISLAND, PROVIDE PLASTIC LAMINATE COVERED BACK PANEL, WHERE EXPOSED. NO BACKSPLASH IS NECESSARY.
2. DOOR PULL. SEE SPECIFICATIONS IN PROJECT MANUAL.
3. PLASTIC LAMINATE CABINET DOOR.
4. WALL BASE. SEE FINISH SCHEDULE.
5. CABINET BASE. COORDINATE WITH ELECTRICAL DRAWINGS FOR POWER, DATA OUTLETS THAT ARE LOCATED HERE.
6. LINE OF FLOOR.
7. SEAL TIGHTLY AROUND PIPE PENETRATIONS WITH CAULKING. PROVIDE STAINLESS STEEL ESCUTCHEON PLATE AROUND DRAIN AND WATER LINES.
8. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL 9 / A505B
9. SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION. SEE DETAIL 6 / A505B
10. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
11. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL 3 / A505B

7 Sink with Base Cabinet
SCALE: 1" = 1'-0"

KEYED NOTES

1. STAINLESS STEEL SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION.
2. INTEGRAL MONOLITHIC MATERIAL SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION.
3. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
4. BASE CABINET OR FASCIA PANEL AS OCCURS. SEE INTERIOR ELEVATIONS.
5. LINE OF WALL.
6. SEAL EXPOSED CUT EDGE OF COUNTERTOP WITH SEALER TO PREVENT WATER DAMAGE.
7. PROVIDE SMOOTH AND SEAMLESS TRANSITION WHERE SINK IS ATTACHED TO COUNTERTOP. UNLESS NOTED OTHERWISE, SINK COLOR SHALL MATCH COUNTERTOP COLOR. VERIFY WITH ARCHITECT FOR SINK COLOR IF A MATCHING PREFORMED SINK IS NOT AVAILABLE.

8 Typical Sink Detail
SCALE: 1" = 1'-0"

KEYED NOTES

1. LINE OF WALL.
2. KNEE AND TOE CLEARANCE REQUIRED FOR ADA.
3. SKIRT PANEL. PLASTIC LAMINATE REMOVABLE ACCESS PANEL WITH 2" ALUMINUM Z-CLIPS MOUNTED ON BACK SIDE OF PANEL (TOTAL 4 CLIPS - TWO ON EACH SIDE OF PANEL).
4. PLASTIC LAMINATE SUPPORT PANEL. 2" X 2" X 1" THICK X CONT. ANCHORED TO CABINET. THIS PANEL TO BE ON EACH END OF CABINET TO SUPPORT ACCESS PANEL. INSTALL TWO ALUMINUM Z-CLIPS ON EACH SIDE OF CABINET TO SUPPORT ACCESS PANEL. OPENING ABOVE PANEL TO BE KEPT AT MINIMUM JUST ENOUGH TO REMOVE ACCESS PANEL.
5. WALL BASE. SEE FINISH SCHEDULE.
6. LINE OF FLOOR.
7. SEAL TIGHTLY AROUND PIPE PENETRATIONS WITH CAULKING. PROVIDE STAINLESS STEEL ESCUTCHEON AROUND DRAIN AND WATER LINES.
8. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
9. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL 6 / A505B
10. SINK. SEE PLUMBING DRAWINGS. SINK SHALL PROVIDE ADA COMPLIANT BOWL DEPTH. SEE DETAIL 9 / A505B
11. PLASTIC LAMINATE FASCIA PANEL.
12. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL 3 / A505B

NOTE: PROVIDE STEEL SUPPORT WITHIN ASSEMBLY WHERE COUNTER IS UNSUPPORTED, TYP.

9 Sink without Base Cabinet
SCALE: 1" = 1'-0"

KEYED NOTES


1. DRAWER BOTTOM PANEL. SEE SPECIFICATIONS IN PROJECT MANUAL FOR TYPICAL DRAWER CONSTRUCTION.
2. FILE DRAWER BODY.
3. ALUMINUM STRAP (2" WIDE X 1/8" THICK) ATTACHED TO DRAWER BODY WITH FASTENERS AT 4" O.C. AS REQUIRED.
4. FILE FOLDER. OWNER FURNISHED OWNER INSTALLED ITEM.
5. DRAWER SLIDE.

10 File Drawer Section
SCALE: 3/8" = 1'-0"

KEYED NOTES

1. LINE OF WALL.
2. EXTEND THIS WALL CABINET TO WALL AS INDICATED.
3. FIXED SHELF.
4. OUTLINE OF CABINET THAT OCCURS ON SIDE WALL.
5. OUTLINE OF CABINET THAT OCCURS ON FRONT WALL.
6. FILLER PANEL. PLASTIC LAMINATE OVER 3/4" PARTICLE BOARD, AS REQUIRED.


11 Wall Cabinet - Extended at Corners
SCALE: 1" = 1'-0"



KEYED NOTES

1. LINE OF WALL.
2. DOOR PULL. SEE SPECIFICATIONS IN PROJECT MANUAL.
3. PLASTIC LAMINATE CABINET DOOR.
4. WALL BASE. SEE FINISH SCHEDULE.
5. CABINET BASE. COORDINATE WITH ELECTRICAL DRAWINGS FOR POWER AND DATA OUTLETS THAT ARE LOCATED HERE.
6. LINE OF FLOOR.
7. ADJUSTABLE SHELF. UNLESS NOTED OTHERWISE ON INTERIOR ELEVATIONS, PROVIDE A MINIMUM OF FIVE SHELVES. NOTCH SHELF 1/8" AT SUPPORT TO PREVENT SLIDE OUT.
8. FASCIA PANEL AS OCCURS. SEE INTERIOR ELEVATION. SEE DETAIL 2 / A505B
9. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL 3 / A505B
10. LINE OF CEILING. SEE REFLECTED CEILING PLAN.


1 Tall Cabinet with One Door
SCALE: 1" = 1'-0"



KEYED NOTES

1. LINE OF WALL.
2. DOOR PULL. SEE SPECIFICATIONS IN PROJECT MANUAL.
3. PLASTIC LAMINATE CABINET DOOR.
4. WALL BASE. SEE FINISH SCHEDULE.
5. CABINET BASE. COORDINATE WITH ELECTRICAL DRAWINGS FOR POWER AND DATA OUTLETS THAT ARE LOCATED HERE.
6. LINE OF FLOOR.
7. ADJUSTABLE SHELF. UNLESS NOTED OTHERWISE ON INTERIOR ELEVATIONS, PROVIDE A MINIMUM OF FOUR SHELVES. NOTCH SHELF 1/8" AT SUPPORTS TO PREVENT SLIDE OUT.
8. FIXED SHELF. MULTI-CORE, 1" THICK, PREMIUM GRADE-PANEL CORE PRODUCT USED FOR LAMINATED CASEWORK.
9. FASCIA PANEL AS OCCURS. SEE INTERIOR ELEVATION. SEE DETAIL 2 / A505B
10. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL 3 / A505B
11. LINE OF CEILING. SEE REFLECTED CEILING PLAN.

2 Tall Cabinet with Two Doors
SCALE: 1" = 1'-0"




KEYED NOTES

1. GYPSUM BOARD, 5/8" THICK. (USE TYPE 'X' IF WALLS ARE FIRE RATED) ATTACHED TO METAL STUD.
2. FIRE EXTINGUISHER CABINET. SEMI RECESSED. VERIFY WITH MANUFACTURER FOR ROUGH OPENING SIZE REQUIREMENTS.
3. HAND HELD FIRE EXTINGUISHER.
4. CABINET DOOR.
5. COVER ALL SIDES OF CABINET WITH 5/8" THICK, TYPE 'X' GYPSUM BOARD.

3 Fire Extinguisher Cabinet Detail
SCALE: 1" = 1'-0"



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

Cabinet
Details

A505C



DOOR SCHEDULE


DOOR #	# OF PANELS	DOOR				FRAME			DETAILS				DOOR #	FIRE RATING (MINUTES)	HARDWARE GROUP	COMMENTS
		W1	W2	HEIGHT	THICKNESS	MATERIAL	TYPE (1/A601A)	DEPTH	MATERIAL	JAMB	HEAD	THRESHOLD				
A107A	1	3' - 7 1/4"		7' - 0"	PER MFR	WD	A	8	PER MFR	PER MFR	2/A504A	4/A504A	A107A			1, 2
A109A	1	3' - 7 1/4"		7' - 0"	PER MFR	WD	A	8	PER MFR	PER MFR	2/A504A	4/A504A	A109A			2
A110A	1	3' - 7 1/4"		7' - 0"	PER MFR	WD	A	8	PER MFR	PER MFR	2/A504A	4/A504A	A110A			2
A111A	1	3' - 7 1/4"		7' - 0"	PER MFR	WD	A	8	PER MFR	PER MFR	2/A504A	4/A504A	A111A			2
A113A	1	3' - 0"		7' - 0"	1 3/4"	WD	A	1	5 7/8"	HM	1/A504A	1/A504A	A113A			1
A114A	1	3' - 0"		7' - 0"	1 3/4"	WD	A	1	5 7/8"	HM	1/A504A	1/A504A	A114A			1
A118A	1	3' - 0"		7' - 0"	1 3/4"	WD	A	5	5 7/8"	HM	1/A504A	6/A504A	A118A		1	
A119A	1	3' - 0"		7' - 0"	1 3/4"	WD	EXIST	EXIST	EXIST	HM	EXIST	EXIST	A119A		2	3
A120A	1	3' - 0"		7' - 0"	1 3/4"	WD	A	5	5 7/8"	HM	1/A504A	6/A504A	A120A		1	

COMMENTS

- REMOVE AND REINSTALL EXISTING DOOR PANEL, HARDWARE AND ACCESSORIES REMOVED IN GOOD CONDITION WITH NEW FRAME AND ACCESSORIES AS REQUIRED.
- SLIDING BARN STYLE DOOR, CLEAR OPENING TO BE 36 INCHES.
- PROVIDE NEW HARDWARE FOR DEADBOLT LOCK ON EXISTING DOOR AND FRAME.

KEYED NOTES

- VISION PANEL, GLAZING IN VISION PANEL SHALL BE 1/4" THICK, CLEAR, TEMPERED, GLAZING, FOR WOOD DOOR. PROVIDE WOOD TRIM CLEAR, FLUSH WITH THE FACE OF THE DOOR, AROUND THE VISION PANEL OPENING. STAIN AND SPECIES OF WOOD TRIM SHALL MATCH WOOD DOOR. FOR HOLLOW METAL DOOR, PROVIDE METAL TRIM AROUND VISION PANEL. GLAZING SHALL BE FIRE RATED IF DOORS ARE REQUIRED TO BE FIRE RATED.
- FOR EXTERIOR DOORS OF THIS TYPE, GLAZING SHALL BE TINTED, INSULATED, TEMPERED, LOW E, AND 1" THICK. FOR INTERIOR DOORS OF THIS TYPE, GLAZING SHALL BE CLEAR, TEMPERED AND 1/4" THICK. STAINLESS STEEL WELDED WIRE MESH (15 GAUGE) ATTACHED TO DOOR. PROVIDE FRAME AROUND THE OPENING IN DOOR TO SECURE THE MESH IN PLACE.
- METAL LOUVER IN DOOR FOR VENTILATION.




NOTE: REFER TO "DOOR SCHEDULE" TABLE FOR DOOR TYPES REQUIRED FOR THIS PROJECT. SOME DOOR TYPE ELEVATIONS INDICATED ABOVE, MAY NOT BE APPLICABLE TO THIS PROJECT.

1 Door Types

SCALE: 1/4" = 1'-0"

KEYED NOTES

- GLAZING SHALL BE CLEAR, TEMPERED, AND 1/4" THICK.
- DOOR FRAME, SEE DOOR SCHEDULE.
- WHERE DOOR OCCURS AT MASONRY WALL (8" HIGH, C.M.U. BLOCKS), AND WITH A TYPICAL DOOR HEIGHT OF 7'-0", USE 4" FRAME AS FRAME HEAD INSTEAD OF THE STANDARD 2" FRAME.




NOTE: REFER TO "DOOR SCHEDULE" FOR FRAME TYPES REQUIRED FOR THIS PROJECT. SOME FRAME TYPE ELEVATIONS INDICATED ABOVE MAY NOT BE APPLICABLE TO THIS PROJECT.

2 Frame Types

SCALE: 1/4" = 1'-0"

KEYED NOTES

- HOLLOW METAL WINDOW FRAME, SEE DETAIL 7/ A504A.
- GLAZING SHALL BE 1/4" THICK AND CLEAR.



3 Window Schedule

SCALE: 1/4" = 1'-0"

WINDOW GENERAL NOTES

A. FIELD VERIFY WINDOW AND DOOR FRAME OPENING SIZES BEFORE FRAME INSTALLATION. OVERALL DIMENSIONS INDICATED FOR EACH FRAME TYPE ARE ROUGH OPENING SIZES IN WALLS. CONTRACTOR SHALL ADJUST INNER DIMENSIONS AS REQUIRED TO MAKE DOORS AND WINDOWS WORK.
B. NATIONAL FENESTRATION RATING COUNCIL (NFRC) CERTIFICATION:

- EACH WINDOW AND DOOR LOCATED IN WALLS WHICH SEPARATE UNCONDITIONED SPACE (BUILDING INTERIOR) FROM UNCONDITIONED SPACE (BUILDING EXTERIOR) SHALL BE LABELED BY THE MANUFACTURER TO CERTIFY COMPLIANCE WITH THE REQUIREMENTS OF NFRC.
- THE U-FACTOR AND SHGC FOR EACH GLAZED FENESTRATION PRODUCT (DOOR AND WINDOW) SHALL BE DETERMINED IN ACCORDANCE WITH NFRC 100-97 (PROCEDURE FOR DETERMINING FENESTRATION PRODUCT U-FACTORS) AND NFRC 200-95 (PROCEDURE FOR PRODUCT SOLAR HEAT GAIN COEFFICIENTS AT NORMAL INCIDENCE). ONCE THE PROJECT BEGINS, THE SUCCESSFUL CONTRACTOR SHALL USE THE CMA METHOD (COMPONENT MODELING APPROACH) TO GENERATE A "BID REPORT" FOR SITE-BUILT PRODUCTS THAT ARE TO BE INSTALLED. ONCE ALL PRODUCTS HAVE BEEN INSTALLED, BUT PRIOR TO FINAL INSPECTION, THE CONTRACTOR SHALL RETAIN AN ACE (APPROVED CALCULATION ENTITY) TO GENERATE THE NFRC LABEL CERTIFICATE FOR THE PROJECT BASED ON THE ACTUAL PRODUCTS INSTALLED.
- THE U-FACTOR AND SHGC FOR EACH PRODUCT (EXCEPT FOR NON-GLAZED DOORS) USED IN THIS PROJECT, AS DETERMINED THROUGH THE METHODS LISTED ABOVE, SHALL MEET OR EXCEED THE FOLLOWING BASIS-OF-DESIGN VALUES.

WINDOWS:
TRIFAB VIG 451T ALUMINUM FRAME BY KAWNEER WITH "SOLARBAN 40" SOLAR CONTROL LOW-E CLEAR INSULATED GLASS BY PPG INDUSTRIES
0.36 (OVERALL U-FACTOR)
0.36 (OVERALL SHGC)

DOORS:
ALUMINUM DOORS: KAWNEER "500 STANDARD ENTRANCE, WIDE STILE"
0.72 (OVERALL U-FACTOR)
0.24 (OVERALL SHGC)

4. THE U-VALUE FOR NON-GLAZED DOORS (EXTERIOR HOLLOW METAL DOORS) SHALL MEET MINIMUM REQUIREMENTS OF THE IECC (U-VALUE 1.20 FOR UNINSULATED HOLLOW METAL DOORS).

CLARIFICATION REGARDING FENESTRATION: DOOR AND WINDOW SYSTEMS THAT DO NOT MEET THERMAL RESISTANCE VALUES LISTED ABOVE SHALL NOT BE USED ON THIS PROJECT, EVEN IF THE SYSTEM MEETS ALL OTHER SPECIFICATION REQUIREMENTS. THE CONTRACTOR WILL BE REQUIRED TO SUBMIT A BID REPORT (AS STATED ABOVE) AT THE BEGINNING OF THE CONTRACT PERIOD, VERIFYING THAT THE PROPOSED PRODUCTS MEET THESE VALUES.

FINISH SCHEDULE




TAG	FINISH TYPE	SIZE	MATERIAL DESCRIPTION	MANUFACTURER	STYLE	MODEL #	COLOR	COMMENTS
F1	FLOOR FINISH	12" X 24"	LVT (LUXURY VINYL TILE)	MANNINGTON COMMERCIAL	COLOR ANCHOR - STRIDE	TBD	TBD	1
F2	FLOOR FINISH	12" X 24"	LVT (LUXURY VINYL TILE)	MANNINGTON COMMERCIAL	COLOR ANCHOR - STRIDE	TBD	TBD	1
F3	FLOOR FINISH		CARPET TILES	MATCH EXISTING	MATCH EXISTING	-	MATCH EXISTING	2
B1	WALL BASE	4" HIGH	RUBBER BASE	ROPPE	PINNACLE STANDARD TOE	-	TBD	1
B2	WALL BASE	4" HIGH	BROADLOOM BASE	MATCH EXISTING	MATCH EXISTING	-	MATCH EXISTING	2
W1	WALL FINISH		PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	-	MATCH EXISTING	3
W2	WALL FINISH		ACCENT PAINT	SHERWIN WILLIAMS	EGGSHELL FINISH	-	MATCH EXISTING	3
MS1	MISC. SURFACE FINISH		LIQUID APPLIED - DOOR FRAME PAINT	SHERWIN WILLIAMS	SEMI GLOSS FINISH	-	MATCH ADJACENT EXISTING	-
PL1	PLASTIC LAMINATE FINISH		PLASTIC LAMINATE SHEET OVER SUBSTRATE	LAMINART	MATCH EXISTING	-	MATCH EXISTING	4
MM1	MONOLITHIC MATERIAL		SOLID SURFACE COUNTERTOP	CORIAN SOLID SURFACE	-	-	MATCH EXISTING	4

COMMENTS

- LVT TO BE ORDERED WITH A SQUARE EDGE AND INSTALLED IN A STAGGERED INSTALLATION PATTERN. COLOR TO BE SELECTED BY OWNER FROM THE MANUFACTURERS STYLE RANGE. BASE COLOR TO BE SELECTED BASED ON FLOORING COLOR.
- CARPET TILES TO BE EXISTING SALVAGED TILES REINSTALLED, WHERE DAMAGE OR CONDITION PREVENTS THIS, PROVIDE NEW CARPET TILES TO MATCH EXISTING. INSTALL NEW TILES IN SUCH A WAY THAT MINIMIZES CONTRAST OF NEW AND OLD TILES. IN A SINGLE ROOM INSTALL ALL SALVAGED BROADLOOM BASE OR PROVIDE NEW BASE TO MATCH CARPET.
- COORDINATE FIELD COLOR AND ACCENT COLOR SELECTION FROM EXISTING CLINIC AND CONFIRM SELECTION WITH OWNER.
- PROVIDE COLOR SELECTION FOR APPROVAL BASED ON MANUFACTURER. MANUFACTURER PROVIDED IN SCHEDULE AS BASIS OF DESIGN.


GENERAL NOTES

- BASES OF DESIGN FOR FINISHES, FINISHES INDICATED ON THE FINISH SCHEDULE ARE BASED ON THE NAMED MANUFACTURER AND THEIR PRODUCTS. SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE THE NAMED PRODUCT OR A COMPARABLE PRODUCT BY ONE OF THE APPROVED MANUFACTURERS LISTED IN THE PROJECT MANUAL. SEE RELEVANT SPECIFICATION SECTION.
- SEE "SAMPLE LAYOUTS" INDICATED ON FINISH PLANS FOR CLARIFICATION ON HOW DIFFERENT TYPES OF REQUIRED FINISHES ARE INDICATED WITH FINISH TAGS FOR FLOORS, WALLS, MISCELLANEOUS SURFACE, ETC. SEE FINISH FLOOR PLANS FOR REQUIRED FINISHES (INDICATED WITH FINISH TAGS SUCH AS F1, B1, W1, ETC.).
- LINE OF TRANSITION BETWEEN DIFFERENT TYPES OF FLOOR COVERING IS INDICATED ON THE FINISH FLOOR PLANS. IN PLACES WHERE TWO DIFFERENT FLOOR COVERINGS ABUT EACH OTHER, CONTRACTOR SHALL FOLLOW THE RELEVANT APPLICABLE "FLOOR COVERING TRANSITION DETAILS" INDICATED IN THIS CONSTRUCTION DOCUMENTS, WHERE TWO ROOMS ARE REQUIRED TO HAVE DIFFERENT FLOOR COVERINGS, LINE OF TRANSITION SHALL TYPICALLY OCCUR BELOW THE CENTER OF THE DOOR (LOCATED BETWEEN THE TWO ROOMS). AS THESE TRANSITION LINES ARE NOT INDICATED BELOW THE DOOR ON THE FINISH FLOOR PLANS, CONTRACTOR SHALL PROVIDE METAL TRANSITION STRIP (MANUFACTURED BY SCHLUTER OR EQUIVALENT) AS REQUIRED. AT EXTERIOR DOORS, PROVIDE ALUMINUM THRESHOLD MATCHING THE DOORWAY. FOR REMODEL PROJECTS, COORDINATE WITH DEMOLITION FLOOR PLAN AND NEW FLOOR PLAN TO DETERMINE WHERE NEW ABUTS EXISTING FLOOR COVERING THAT IS SCHEDULED TO REMAIN.
- LINE OF TRANSITION BETWEEN DIFFERENT TYPES OF WALL FINISH IS INDICATED ON THE INTERIOR ELEVATIONS AND FINISH FLOOR PLANS. FOR REQUIRED WALL PROTECTION TYPE (INDICATED WITH TAG WP1, WP2, ETC.) ON WALLS, COORDINATE WITH FINISH FLOOR PLANS AND INTERIOR ELEVATIONS.
- THERE ARE MISCELLANEOUS SURFACES THAT ARE EXPOSED AND WILL REQUIRE A FINISH. SUCH MISCELLANEOUS SURFACES ARE INDICATED IN THE DRAWINGS WITH FINISH TAGS SUCH AS MS1, MS2, ETC.
- PAINT ALL EXPOSED VISIBLE ITEMS SUCH AS METAL DECK, STEEL ANGLES, STEEL BEAMS, STEEL TRUSSES, MISC. STEEL ITEMS, PIPES, CONDUITS, ETC. UNLESS SPECIFICALLY NOTED AS A SURFACE NOT TO BE PAINTED. IF NATURAL FINISH IS REQUIRED, PAINT SURFACES USING FIELD COLORS AND ACCENT COLORS SPECIFIED BY THE ARCHITECT. DO NOT PAINT CONCEALED SURFACES, FINISHED METAL SURFACES, OPERATING PARTS, AND PRE-FINISHED ITEMS. VERIFY PAINTING SURFACE (SUCH AS STEEL, CONCRETE, MASONRY, GYPSUM BOARD, WOOD, ETC.) AND USE THE APPROPRIATE PAINT AND METHOD INDICATED IN THE PROJECT MANUAL UNDER RELEVANT SPECIFICATION SECTION. ALL HOLLOW METAL DOOR AND WINDOW FRAMES SHALL BE PAINTED. USE SEMI-GLOSS FINISH ON DOOR FRAMES.
- IN ROOMS AND AREAS WHERE GYPSUM BOARD CEILING IS INDICATED, PAINT CEILING WITH THE SAME COLOR AND TYPE AS ADJACENT WALLS. IN WET ROOMS (LIKE RESTROOM, KITCHEN, ETC.) WHERE EPOXY PAINT IS INDICATED AS A REQUIREMENT ON WALLS, PAINT CEILINGS AND SOFFITS WITH EPOXY TYPE PAINT. ALL GYPSUM BOARD SOFFITS SHALL BE PAINTED. COORDINATE ACCENT COLOR LOCATIONS WITH ARCHITECT WHERE INDICATED.
- SEE INTERIOR ELEVATIONS FOR PLASTIC LAMINATE FINISHES OVER CABINETS, COUNTERTOPS, WALLS, ETC. PLASTIC LAMINATE FINISHES ARE INDICATED AS PL1, PL2, ETC. COUNTERTOPS THAT ARE MONOLITHIC MATERIAL (SUCH AS SOLID SURFACE, QUARTZ, ETC. AND NOT PLASTIC LAMINATE WRAPPED), ARE INDICATED AS MM1, MM2, ETC.
- WHERE PORCELAIN AND/OR CERAMIC TILE FINISHES ARE INDICATED, PROVIDE METAL EDGE STRIPS (MANUFACTURED BY SCHLUTER OR EQUIVALENT) AT ALL OUTSIDE VERTICAL CORNERS AND TOP OF WAINSCOT.
- IN ROOMS AND AREAS (SUCH AS TOILET ROOMS, SHOWERS, ETC.) WHERE CERAMIC OR PORCELAIN TILES ARE INDICATED FOR WALL AND FLOOR FINISH, INSTALL BOTTOM ROW OF WALL TILE FIRST PER DETAIL 1/A603B. PROVIDE QUARTZ THRESHOLD AT DOORS TO TOILET ROOMS THAT ARE USED BY MULTIPLE USERS. SEE DETAILS 3 & 4 SHEET A603B.
- WHERE GYPSUM BOARD WALL ABUTS MASONRY WALL, PROVIDE REVEAL AS PER DETAIL 2/A603B.





NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.384.9259
www.njraarchitects.com



SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
801-478-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

SYMBOL LEGEND - PIPING	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
SYMBOL	DESCRIPTION
	SHUT OFF VALVE
	GATE VALVE
	CHECK VALVE
	AUTOMATIC 2-WAY VALVE
	AUTOMATIC 3-WAY VALVE
	GLOBE VALVE
	BALL VALVE
	RELIEF VALVE
	PRESSURE REDUCING VALVE
	BUTTERFLY VALVE
	SOLENOID VALVE
	ANGLE VALVE
	VENTURI VALVE
	BALANCING OR PLUG COCK
	FLOW SETTER
	EXPANSION VALVE
	GAS COCK
	MANUAL AIR VENT
	STRAINER
	GAUGE COCK
	FLEXIBLE CONNECTION
	PRESSURE GAUGE
	THERMOMETER
	PIPE REDUCER
	REFRIGERANT SITE GLASS
	REFRIGERANT STRAINER
	REFRIGERANT FILTER DRIER
	90 DEGREE ELBOW UP
	90 DEGREE ELBOW DOWN
	90 DEGREE TEE UP
	90 DEGREE TEE DOWN
	PIPE UNION
	PIPE CAP
	PIPE ANCHOR
	FLOAT AND THERMOSTATIC TRAP

SYMBOL LEGEND - MECH	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
SYMBOL	DESCRIPTION
	SQUARE OR RECTANGULAR SUPPLY DIFFUSER
	SQUARE OR RECTANGULAR RETURN DIFFUSER
	SQUARE OR RECTANGULAR EXHAUST DIFFUSER
	ROUND DIFFUSER
	LINEAR SLOT GRILLE OR DIFFUSER
	FLEXIBLE DUCT
	SIDEWALL GRILLE OR REGISTER
	DUCT HIGH EFFICIENCY TAKE OFF WITH BALANCING DAMPER
	BALANCING DAMPER
	FIRE DAMPER
	FIRE / SMOKE COMBINATION DAMPER
	THERMOSTAT - SENSOR - HUMIDISTAT

SYMBOL LEGEND - DUCTWORK	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
SYMBOL	DESCRIPTION
	RECTANGULAR SUPPLY DUCT UP
	RECTANGULAR SUPPLY DUCT DOWN
	RECTANGULAR RETURN DUCT UP
	RECTANGULAR RETURN DUCT DOWN
	RECTANGULAR EXHAUST DUCT UP
	RECTANGULAR EXHAUST DUCT DOWN
	ROUND SUPPLY DUCT UP
	ROUND SUPPLY DUCT DOWN
	ROUND RETURN DUCT UP
	ROUND RETURN DUCT DOWN
	ROUND EXHAUST DUCT UP
	ROUND EXHAUST DUCT DOWN
	OVAL SUPPLY DUCT UP
	OVAL SUPPLY DUCT DOWN
	OVAL RETURN DUCT UP
	OVAL RETURN DUCT DOWN
	OVAL EXHAUST DUCT UP
	OVAL EXHAUST DUCT DOWN
	SPIRAL OVAL DUCT
	SPIRAL ROUND DUCT
	DUCT INSULATION
	DUCT LINING
	90° RECTANGULAR ELBOW WITH TURNING VANES
	90° ROUND RADIUS ELBOW
	GORED OVAL RADIUS ELBOW
	DUCT SIZE OR SHAPE TRANSITION
	DUCT TO BE DEMOLISHED

PIPING LEGEND	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
ABBREVIATION	DESCRIPTION
—CHWR—	CHILLED WATER RETURN
—CHWS—	CHILLED WATER SUPPLY
—CA—	COMPRESSED AIR
—CD—	CONDENSATE DRAIN
—CO2—	CARBON DIOXIDE
—CWR—	CONDENSER WATER RETURN
—CWS—	CONDENSER WATER SUPPLY
—FP—	FIRE PROTECTION
—FOR—	FUEL OIL RETURN
—FOS—	FUEL OIL SUPPLY
—FOV—	FUEL OIL VENT
—GR—	GLYCOL RETURN
—GS—	GLYCOL SUPPLY
—HPC—	HIGH PRESSURE CONDENSATE
—MPC—	MEDIUM PRESSURE CONDENSATE
—LPC—	LOW PRESSURE CONDENSATE
—HPS—	HIGH PRESSURE STEAM
—MPS—	MEDIUM PRESSURE STEAM
—LPS—	LOW PRESSURE STEAM
—HHWR—	HEATING HOT WATER RETURN
—HHWS—	HEATING HOT WATER SUPPLY
—LPG—	LIQUID PROPANE GAS
—LPS—	LOW PRESSURE STEAM
—MA—	MEDICAL AIR
—NG—	NATURAL GAS
—NO—	NITROUS OXIDE
—O—	OXYGEN
—PC—	PUMPED CONDENSATE
—RG—	REFRIGERANT GAS
—RL—	REFRIGERANT LIQUID
—SMR—	SNOW MELT RETURN
—SMS—	SNOW MELT SUPPLY
—VAC—	VACUUM

SYMBOL LEGEND - MISC	
REFERENCE LINES AND SYMBOLS	
SYMBOL	DESCRIPTION
	VIEW OR DETAIL INDICATOR: # INDICATES DETAIL NUMBER, SHEET INDICATES DRAWING SHEET WHERE VIEW OR DETAIL IS SHOWN.
	ELEVATION OR SECTION INDICATOR: # INDICATES VIEW NUMBER, SHEET INDICATES DRAWING SHEET WHERE VIEW IS SHOWN.
	ROOM / SPACE INDICATOR
	KEYNOTE INDICATOR
	REVISION INDICATOR
	PLUMBING FIXTURE INDICATOR
	EQUIPMENT INDICATOR
	REGISTER, GRILLE, OR DIFFUSER INDICATOR
	BREAKLINE
	MATCHLINE INDICATOR
	CONTRACT LIMIT LINE: DASHDOT, WIDE LINE
	NEW CONNECTION TO EXISTING
	POINT OF DEMOLITION

ABBREVIATIONS	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
ABBREVIATION	DESCRIPTION
(E)	EXISTING
(F)	FUTURE
AC	AIR CONDITION(-ING,-ED)
APD	AIR PRESSURE DROP
BD	BALANCING DAMPER
BHP	BRAKE HORSE POWER
BTU	BRITISH THERMAL UNIT
BTUH	BTU/HOUR
CFH	CUBIC FEET PER HOUR
CFM	CUBIC FEET PER MINUTE
CV	CONTROL VALVE
DB	DRY BULB TEMPERATURE
DCW	DOMESTIC COLD WATER
DHW	DOMESTIC HOT WATER
DHWR	DOMESTIC HOT WATER RECIRC
DP	DEPTH, DEEP, OR DROP IN PRESSURE
EA	EXHAUST AIR
EER	ENERGY EFFICIENCY RATIO
EFF	EFFICIENCY
ELEC	ELECTRIC
ELEV	ELEVATION
ENT	ENTERING
EVAP	EVAPORAT(-E, -ING, -ED, -OR)
EXT	ENTERING WATER TEMPERATURE
EXT	EXTERNAL
FD	FIRE DAMPER
FLA	FULL LOAD AMPS
FFI	FINS PER INCH
FFM	FEET PER MINUTE
FFS	FEET PER SECOND
FSD	FIRE SMOKE DAMPER
GE	GREASE EXHAUST
GPH	GALLONS PER HOUR
GPM	GALLONS PER MINUTE
HD	HEAD
HG	MERCURY
HP	HORSEPOWER
HR	HOUR
HTG	HEATING
HZ	HERTZ (FREQUENCY)
IN	INCH
KW	KILOWATT
LAT	LEAVING AIR TEMPERATURE
LBS	POUNDS
LH	LATENT HEAT
LRA	LOCKED ROTOR AMPS
LVG	LEAVING WATER TEMPERATURE
LWT	LEAVING WATER TEMPERATURE
MBH	THOUSAND BTU PER HOUR
MCA	MINIMUM CIRCUIT AMPS
MFR	MANUFACTURER(-ER, -ED)
NC	NORMALLY CLOSED OR NOISE CRITERIA
NIC	NOT IN CONTRACT
NO	NORMALLY OPEN
NPSH	NET POSITIVE SUCTION HEAD
NTS	NOT TO SCALE
OA	OUTSIDE AIR
OD	OUTSIDE DIAMETER
OZ	OUNCE
PD	PRESSURE DROP OR DIFFERENCE
PG	PROPYLENE GLYCOL
PH	PHASE
PPM	PARTS PER MILLION
PSF	POUNDS PER SQUARE FOOT
PSI	POUNDS PER SQUARE INCH
PSIA	PSI ABSOLUTE
PSIG	PSI GAUGE
RA	RETURN AIR
RECIRC	RECIRCULATE (-ER, -ED, -ING)
REFR	REFRIGERATION
REQD	REQUIRED
RLA	RATED LOAD AMPS
RPM	REVOLUTIONS PER MINUTE
SA	SUPPLY AIR
SCFM	STANDARD CUBIC FEET PER MINUTE
SCW	SOFT COLD WATER
SH	SENSIBLE HEAT
SP	STATIC PRESSURE
SPEC(S)	SPECIFICATION(S)
SO	SQUARE
SS	SANITARY SEWER, SOIL, WASTE
STD	STANDARD
TA	TRANSFER AIR
TD	TEMP. DROP OR DIFF.
TEMP	TEMPERATURE
TOT	TOTAL
TSTAT	THERMOSTAT
TYP	TYPICAL
V	VOLT, VOLTAGE OR VENT
VAC	VACUUM
VAV	VARIABLE AIR VOLUME
VEL	VELOCITY
VENT	VENT, VENTILATION
VERT	VERTICAL
VFD	VARIABLE FREQUENCY DRIVE
VOL	VOLUME
VTR	VENT THROUGH ROOF
WB	WET BULB TEMP
WC	WATER COLUMN
WG	WATER GAUGE
WPD	WATER PRESSURE DROP
WTR	WATER

- ### MECHANICAL GENERAL NOTES
- THE MECHANICAL DRAWINGS SHOW THE GENERAL DESIGN, ARRANGEMENT, & EXTENT OF THE MECHANICAL SYSTEM. BECAUSE OF THE SMALL SCALE OF THE DRAWINGS, THESE DRAWINGS DO NOT SHOW ALL OFFSETS, BENDS, OR ELBOWS NECESSARY FOR THE COMPLETE INSTALLATION IN THE SPACE PROVIDED. CONTRACTOR SHALL MAKE ALTERATIONS AS MAY BE NECESSARY TO MAKE THE SYSTEM COMPLETE & OPERATIONAL IN ACCORDANCE WITH THE DESIGN INTENT.
 - MAJOR DEVIATIONS SUCH AS CHANGES IN SIZES, WEIGHTS, QUANTITIES, OR MATERIAL REQUIRE PRIOR TO INSTALLATION. MATERIALS FURNISHED & INSTALLED AS THOUGH SHOWN AND CALLED OUT IN BOTH DOCUMENTS.
 - THE DRAWINGS & SPECIFICATIONS HAVE BEEN PREPARED TO SUPPLEMENT EACH OTHER & SHALL BE INTERPRETED AS AN INTEGRAL UNIT WITH THE ITEMS SHOWN ON ONE & NOT THE OTHER BEING FURNISHED & INSTALLED AS THOUGH SHOWN AND CALLED OUT IN BOTH DOCUMENTS.
 - THE ENTIRE MECHANICAL INSTALLATION SHALL CONFORM TO ALL CODES, RULES, REGULATIONS, & REQUIREMENTS OF THE BUILDING OWNER. THE REQUIREMENTS OF THE MOST RECENTLY ADOPTED BUILDING CODES, MECHANICAL CODE, PLUMBING CODE, ELECTRICAL CODE, & ALL OTHER APPLICABLE CITY, COUNTY, STATE, & FEDERAL CODES & REGULATIONS IN EFFECT.
 - THE ENTIRE MECHANICAL INSTALLATION SHALL CONFORM TO ALL CODES, RULES, REGULATIONS, & REQUIREMENTS OF THE BUILDING OWNER.
 - ALL MECHANICAL COMPONENTS AND EQUIPMENT SHALL BE INSTALLED TO CONFORM WITH ANY APPLICABLE LOCAL SEISMIC REQUIREMENTS.
 - PRIOR TO FABRICATION & INSTALLATION OF ANY MECHANICAL COMPONENT THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF ALL MECHANICAL WORK WITH ALL OTHER BUILDING TRADES, INCLUDING BUILDING TRADES HIRED DIRECTLY BY THE OWNER. WHERE CONFLICTS MAY OCCUR, THEY SHALL BE RESOLVED PRIOR TO INSTALLATION.
 - VERIFY ALL REQUIRED SERVICE CONNECTIONS, INCLUDING ELECTRICAL CHARACTERISTICS, FOR ALL EQUIPMENT PRIOR TO ORDERING OR FABRICATING MECHANICAL EQUIPMENT AND COMPONENTS.
 - THE SPACE ABOVE CEILINGS IS LIMITED. CAREFUL COORDINATION IS REQUIRED WITH ALL TRADES BEFORE ANY PIPE, DUCT, OR EQUIPMENT IS ORDERED &/OR INSTALLED. ANY CONFLICTS &/OR CHANGES FOUND DURING INSTALLATION THAT RESULTS FROM THE LACK OF COORDINATION BY THE CONTRACTORS DURING THE SHOP DRAWING PROCESS ARE THE RESPONSIBILITY OF THE CONTRACTOR.
 - ALL MECHANICAL INFORMATION IS NOT SHOWN ON THE MECHANICAL DRAWINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF ALL INFORMATION ON ALL OTHER CONSTRUCTION DOCUMENTS.
 - THE CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW & USE, WHERE APPROPRIATE, ALL THE MECHANICAL DETAILS SHOWN ON THE DRAWINGS. DETAILS MAY OR MAY NOT BE CALLED OUT ON THE DRAWINGS WITH SYMBOLS OR KEYED NOTES. ANY CHANGES RESULTING FROM FAILURE TO INSTALL THE MECHANICAL SYSTEM WITHOUT USING THE INCLUDED DETAILS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
 - ALL EQUIPMENT SHALL BE INDEPENDENTLY SUPPORTED FROM STRUCTURAL MEMBERS. STRUCTURAL ELEMENTS SHOWN IN DETAILS MAY OR MAY NOT PERTAIN TO ANY PORTION OF THE BUILDING. COORDINATE ALL MOUNTING REQUIREMENTS WITH ARCHITECTURAL & STRUCTURAL DRAWINGS AND SPECIFICATIONS.
 - ALL MECHANICAL COMPONENTS AND EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH ALL MANUFACTURER RECOMMENDATIONS.
 - ALL SIMILAR EQUIPMENT SHALL BE OF THE SAME MANUFACTURER. AIR INLETS & OUTLETS OF SIMILAR TYPES SHALL BE OF THE SAME MANUFACTURER.
 - ANY PART OF THE MECHANICAL INSTALLATION THAT FAILS, IS DEEMED UNFIT, OR BECOMES DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED OR REPLACED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR EQUIPMENT CHECK-IN, SAFEGUARDING, & DAMAGE.
 - COORDINATE WITH ARCHITECTURAL REFLECTED CEILING PLAN FOR EXACT LOCATION OF ALL CEILING DIFFUSERS & GRILLES.
 - CONTRACTOR SHALL OPERATE INSTALLED &/OR MODIFIED SYSTEMS & DEMONSTRATE ALL ASPECTS OF THE SYSTEM TO THE ENGINEER &/OR OWNER TO PROVE ALL ASSOCIATED SYSTEMS ARE OPERATIONAL.
 - DURING CONSTRUCTION THE CONTRACTOR SHALL MAINTAIN A SET OF AS-BUILT REDLINED RECORD DRAWINGS AT THE PROJECT SITE. ALL CHANGES OR DEVIATIONS IN LAYOUT, ROUTING, EQUIPMENT, COMPONENTS, & ACCESSORIES SHALL BE RECORDED. THESE REDLINED DRAWINGS SHALL BE GIVEN TO THE ARCHITECT / ENGINEER AFTER THE FINAL INSPECTION IN ACCORDANCE WITH PROJECT SPECIFICATIONS.
 - ALL DUCT ELBOWS SHALL BE LONG RADIUS, UNLESS NOTED OTHERWISE.

- ### DEFINITIONS
- NOTE: ALL DEFINITIONS MAY NOT BE USED.
- INDICATED: THE TERM "INDICATED" REFERS TO GRAPHIC REPRESENTATIONS, NOTES, OR SCHEDULES ON THE DRAWINGS, OTHER PARAGRAPHS OR SCHEDULES IN THE SPECIFICATIONS, AND SIMILAR REQUIREMENTS IN THE CONTRACT DOCUMENTS. WHERE TERMS SUCH AS "SHOWN", "NOTED", "SCHEDULED", AND "SPECIFIED" ARE USED, IT IS TO HELP THE READER LOCATE THE REFERENCE. NO LIMITATION ON LOCATION IS INTENDED.
- DIRECTED: TERMS SUCH AS "DIRECTED", "REQUESTED", "AUTHORIZED", "SELECTED", "APPROVED", "REQUIRED", AND "PERMITTED" MEAN "DIRECTED BY THE ENGINEER", "REQUESTED BY THE ENGINEER", AND SIMILAR PHRASES.
- APPROVED: THE TERM "APPROVED", WHERE USED IN CONJUNCTION WITH THE ENGINEER'S ACTION ON THE CONTRACTOR'S SUBMITTALS, APPLICATIONS, AND REQUESTS, IS LIMITED TO THE ENGINEER'S DUTIES AND RESPONSIBILITIES AS STATED IN GENERAL AND SUPPLEMENTARY CONDITIONS.
- FURNISH: THE TERM "FURNISH" IS USED TO MEAN "SUPPLY AND DELIVER TO THE PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS."
- INSTALL: THE TERM "INSTALL" IS USED TO DESCRIBE OPERATIONS AT PROJECT SITE INCLUDING THE ACTUAL UNLOADING, UNPACKING, ASSEMBLY, ERECTION, PLACING, ANCHORING, APPLYING, WORKING TO DIMENSION, FINISHING, CURING, PROTECTING, CLEANING, AND SIMILAR OPERATIONS."
- PROVIDE: THE TERM "PROVIDE" MEANS "TO FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE."
- INSTALLER: AN "INSTALLER" IS THE CONTRACTOR OR AN ENTITY ENGAGED BY THE CONTRACTOR, EITHER AS AN EMPLOYEE, SUBCONTRACTOR, OR SUB-SUBCONTRACTOR, FOR PERFORMANCE OF A PARTICULAR CONSTRUCTION ACTIVITY, INCLUDING INSTALLATION, ERECTION, APPLICATION, AND SIMILAR OPERATIONS. INSTALLERS ARE REQUIRED TO BE EXPERIENCED IN THE OPERATIONS THEY ARE ENGAGED TO PERFORM.


MECHANICAL SHEET INDEX	
M001	MECHANICAL COVER SHEET
M111	MECHANICAL DEMOLITION PLAN LEVEL 6
M112	MECHANICAL PLAN LEVEL 6
M001	MECHANICAL DETAILS AND SCHEDULES

Canyon Surgical Associates
Clinic Remodel
 South Office Tower - Level 6
 5171 Cottonwood Street #650
 Murray, Utah 84107

NJRA Project # 2402.00
Construction Documents June 27, 2024

MECHANICAL
COVER SHEET

M001



KEYED NOTES

- 1 REMOVE, SALVAGE AND RELOCATE THERMOSTAT. SEE SHEET M112 FOR NEW LOCATION.
- 2 CONTRACTOR TO BALANCE EXISTING SUPPLY TO CFM INDICATED ON SHEET M112.
- 3 REMOVE, CLEAN AND SALVAGE RETURN GRILLE. SEE SHEET M112 FOR NEW LOCATION. IF DIFFUSER IS DAMAGED DURING CONSTRUCTION CONTRACTOR IS TO REPLACE IT WITH LIKE-IN-KIND.
- 4 REMOVE EXISTING RETURN GRILLE.
- 5 REMOVE, CLEAN AND SALVAGE SUPPLY DIFFUSER. SEE SHEET M112 FOR NEW LOCATION. IF DIFFUSER IS DAMAGED DURING CONSTRUCTION CONTRACTOR IS TO REPLACE IT WITH LIKE-IN-KIND.
- 6 REMOVE EXISTING SUPPLY DIFFUSER AND ASSOCIATED DUCT WORK BACK TO MAIN. PATCH AND SEAL PENETRATIONS IN MAIN DUCT AIR TIGHT.
- 7 REMOVE EXHAUST FAN AND ASSOCIATED DUCT SERVING AS AN AIR TRANSFER IN THE EXISTING STORAGE SPACE.
- 8 REMOVE TRANSFER AIR GRILLE AND ASSOCIATED DUCTWORK.
- 9 REMOVE EXISTING SUPPLY DIFFUSER AND ASSOCIATED DUCT TO POINT INDICATED.

GENERAL NOTES


- A. THIS CONTRACTOR SHALL CLOSELY COORDINATE MECHANICAL AND PLUMBING WITH ELECTRICAL, ARCHITECTURAL, AND BUILDING STRUCTURE.
- B. ALL LOW-PRESSURE RECTANGULAR DUCTWORK TO BE LINED WITH INSULATION WITH AN R-VALUE OF R-6. ALL LOW-PRESSURE ROUND DUCTWORK TO BE WRAPPED WITH INSULATION WITH AN R-VALUE OF R-6. NO DUCT LINER IN OUTSIDE AIR DUCTWORK OR DUCTWORK WITH IN DUCT HUMIDIFIERS.
- C. ALL DUCT DIMENSIONS ARE INSIDE CLEAR DIMENSIONS.
- D. FLEXIBLE DUCT MAY BE USED AT FINAL TERMINATION OF DUCT TO DIFFUSER OR GRILLE. MAXIMUM FLEXIBLE DUCT LENGTH IS 5'-0". PROVIDE DUCT SUPPORTS EVERY 3 FEET. FLEXIBLE DUCT SHALL NOT BE COMPRESSED OR KINKED BY ANY OBJECTS SUCH AS STRUCTURE, PIPING, ETC.
- E. GRILLES AND DUCTWORK ARE SIZED INDEPENDENTLY. THE NECK SIZE OF GRILLES MAY NOT MATCH THE ASSOCIATED DUCT SIZE. PROVIDE TRANSITION TO GRILLES AS NECESSARY.
- F. PROVIDE BALANCING DAMPER WITH LOCKING QUADRANT IN EACH DUCT BRANCH OF SUPPLY.
- G. GC TO HIRE NEBB OR AABC CERTIFIED THIRD PARTY TEST AND BALANCE (TAB) CONTRACTOR. TAB CONTRACTOR SHALL ADJUST SHEAVES, BELTS, DAMPERS, ETC AS NECESSARY TO BALANCE SYSTEM TO AIRFLOWS REQUIRED AT LOWEST POSSIBLE SPEEDS. FOLLOW PROCEDURES AS LAID FORTH IN THE CURRENT VERSION OF "PROCEDURAL STANDARDS FOR TESTING, ADJUSTING AND BALANCING OF ENVIRONMENTAL SYSTEMS" BY NEBB. PROVIDE REPORT ON NEBB FORMS TO ENGINEER FOR REVIEW.
- H. ALL MATERIALS WITHIN PLENUMS SHALL BE NONCOMBUSTIBLE OR SHALL BE LISTED AND LABELED AS HAVING A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE-DEVELOPED INDEX OF NOT MORE THAN 50 WHEN TESTED IN ACCORDANCE WITH ASTM E 84 OR UL 723.
- I. WHERE PIPE, OR DUCT PENETRATES A RATED ASSEMBLY OR FLOOR AND IS NOT REQUIRED TO BE PROTECTED BY A DAMPER, ALL SPACE BETWEEN THE DUCT AND ASSEMBLY IS TO BE FIRE CAULKED. INSULATION OR COVERINGS ARE NOT TO CONTINUE THROUGH ASSEMBLY UNLESS TESTED AS PART OF AN APPROVED PENETRATION FIRESTOP SYSTEM.
- J. THIS PROJECT WILL REQUIRE AFTER HOURS AND WEEKEND WORK TO RUN PIPING/DUCTWORK OR MODIFY SYSTEMS IN OR AFFECTING OCCUPIED SPACES. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER.
- K. PROVIDE TEMPORARY NEGATIVE PRESSURE UNIT DURING CONSTRUCTION. COORDINATE LOCATION WITH OWNER.
- L. COORDINATE EXACT THERMOSTAT LOCATIONS WITH FURNITURE AND OWNER. FAILURE TO DO SO MAY REQUIRE MOVING THERMOSTATS AT CONTRACTOR'S COST.
- M. ALL CONTROLS WIRING SHALL BE INSTALLED IN RACEWAYS AND BE THE RESPONSIBILITY OF THE CONTROLS CONTRACTOR. RACEWAYS SHALL CONFORM TO THE FOLLOWING ELECTRICAL SPECIFICATIONS: HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS, RACEWAYS AND BOXES FOR ELECTRICAL SYSTEMS AND SEISMIC CONTROLS FOR ELECTRICAL SYSTEMS.
- N. CONTRACTOR SHALL FIELD VERIFY EXISTING FIELD CONDITIONS PRIOR TO ORDERING OR FABRICATING. ADDITIONAL COST WILL NOT BE ALLOWED FOR CONTRACTOR'S FAILURE TO BECOME FAMILIAR WITH EXISTING SITE CONDITIONS.
- O. PROVIDE SOUND BOOT ON ALL RETURN GRILLES. SOUND BOOT TO BE SHEET METAL WITH ACOUSTICAL DUCT LINER. DUCT BOARD IS NOT AN APPROVED MATERIAL FOR SOUND BOOTS. SEE SOUND BOOT DETAIL.
- P. PIPING AND DUCTWORK SHALL NOT BE SUPPORTED FROM THE ROOF DECK, JOIST BRIDGING OR OTHER PIPES. HANG PIPES FROM BEAMS, JOIST OR SUPPLEMENTARY STRUCTURAL MEMBERS. WHERE POSSIBLE INSTALL ALL PIPING AND DUCTWORK WITHIN 12" FROM SUPPORTING STRUCTURE.



1 MECHANICAL DEMOLITION PLAN - LEVEL 6
SCALE: 1/4" = 1'-0"

C:\Users\mtd\Documents\240149-Mech-Central_monica_downing.rvt

6/28/2024 1:51:14 PM




KEYED NOTES

- 1 RELOCATED CEILING DIFFUSER.
- 2 RELOCATED CEILING RETURN GRILLE.
- 3 RELOCATED THERMOSTAT.
- 4 CONTRACTOR TO BALANCE EXISTING SUPPLY DIFFUSER TO CFM INDICATED.
- 5 DUCT TRANSITIONS DOWN TO RUN BELOW EXISTING SUPPLY DUCT.

GENERAL NOTES


- A. THIS CONTRACTOR SHALL CLOSELY COORDINATE MECHANICAL AND PLUMBING WITH ELECTRICAL, ARCHITECTURAL, AND BUILDING STRUCTURE.
- B. ALL SUPPLY AND RETURN DUCTWORK TO BE EXTERNALLY WRAPPED WITH INSULATION WITH AN R-VALUE OF R-6.
- C. ALL LOW-PRESSURE RECTANGULAR DUCTWORK TO BE LINED WITH INSULATION WITH AN R-VALUE OF R-6. ALL LOW-PRESSURE ROUND DUCTWORK TO BE WRAPPED WITH INSULATION WITH AN R-VALUE OF R-6. NO DUCT LINER IN OUTSIDE AIR DUCTWORK OR DUCTWORK WITH IN DUCT HUMIDIFIERS.
- D. ALL DUCT DIMENSIONS ARE INSIDE CLEAR DIMENSIONS.
- E. FLEXIBLE DUCT MAY BE USED AT FINAL TERMINATION OF DUCT TO DIFFUSER OR GRILLE. MAXIMUM FLEXIBLE DUCT LENGTH IS 5'-0". PROVIDE DUCT SUPPORTS EVERY 3 FEET. FLEX DUCT SHALL NOT BE COMPRESSED OR KINKED BY ANY OBJECTS SUCH AS STRUCTURE, PIPING, ETC.
- F. GRILLES AND DUCTWORK ARE SIZED INDEPENDENTLY. THE NECK SIZE OF GRILLES MAY NOT MATCH THE ASSOCIATED DUCT SIZE. PROVIDE TRANSITION TO GRILLES AS NECESSARY.
- G. PROVIDE BALANCING DAMPER WITH LOCKING QUADRANT IN EACH DUCT BRANCH OF SUPPLY.
- H. GC TO HIRE NEBB OR AABC CERTIFIED THIRD PARTY TEST AND BALANCE (TAB) CONTRACTOR. TAB CONTRACTOR SHALL ADJUST SHEAVES, BELTS, DAMPERS, ETC AS NECESSARY TO BALANCE SYSTEM TO AIRFLOWS REQUIRED AT LOWEST POSSIBLE SPEEDS. TAB CONTRACTOR SHALL VERIFY THE OUTSIDE AIR AT EACH RTU IS AS SCHEDULED. FOLLOW PROCEDURES AS LAID FORTH IN THE CURRENT VERSION OF "PROCEDURAL STANDARDS FOR TESTING ADJUSTING AND BALANCING OF ENVIRONMENTAL SYSTEMS" BY NEBB. PROVIDE REPORT ON NEBB FORMS TO ENGINEER FOR REVIEW.
- I. ALL MATERIALS WITHIN PLENUMS SHALL BE NONCOMBUSTIBLE OR SHALL BE LISTED AND LABELED AS HAVING A FLAME SPREAD INDEX OF NOT MORE THAN 25 AND A SMOKE-DEVELOPED INDEX OF NOT MORE THAN 50 WHEN TESTED IN ACCORDANCE WITH ASTM E 84 OR UL 723.
- J. WHERE PIPE OR DUCT PENETRATES A RATED ASSEMBLY OR FLOOR AND IS NOT REQUIRED TO BE PROTECTED BY A DAMPER, ALL SPACE BETWEEN THE DUCT AND ASSEMBLY IS TO BE FIRE CALKED. INSULATION OR COVERINGS ARE NOT TO CONTINUE THROUGH ASSEMBLY UNLESS TESTED AS PART OF AN APPROVED PENETRATION FIRESTOP SYSTEM.
- K. THIS PROJECT WILL REQUIRE AFTER HOURS AND WEEKEND WORK TO RUN PIPING/DUCTWORK OR MODIFY SYSTEMS IN OR AFFECTING OCCUPIED SPACES. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER.
- L. PROVIDE TEMPORARY NEGATIVE PRESSURE UNIT DURING CONSTRUCTION. COORDINATE LOCATION WITH OWNER.
- M. COORDINATE EXACT THERMOSTAT LOCATIONS WITH FURNITURE AND OWNER. FAILURE TO DO SO MAY REQUIRE MOVING THERMOSTATS AT CONTRACTOR'S COST.
- N. ALL CONTROLS WIRING SHALL BE INSTALLED IN RACEWAYS AND BE THE RESPONSIBILITY OF THE CONTROLS CONTRACTOR. RACEWAYS SHALL CONFORM TO THE FOLLOWING ELECTRICAL SPECIFICATIONS: HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS, RACEWAYS AND BOXES FOR ELECTRICAL SYSTEMS AND SEISMIC CONTROLS FOR ELECTRICAL SYSTEMS.
- O. CONTRACTOR SHALL FIELD VERIFY EXISTING FIELD CONDITIONS PRIOR TO ORDERING OR FABRICATING. ADDITIONAL COST WILL NOT BE ALLOWED FOR CONTRACTOR'S FAILURE TO BECOME FAMILIAR WITH EXISTING SITE CONDITIONS.
- P. PROVIDE SOUND BOOT ON ALL RETURN GRILLES. SOUND BOOT TO BE SHEET METAL WITH ACOUSTICAL DUCT LINER. DUCT BOARD IS NOT AN APPROVED MATERIAL FOR SOUND BOOTS. SEE SOUND BOOT DETAIL.
- Q. PIPING AND DUCTWORK SHALL NOT BE SUPPORTED FROM THE ROOF DECK, JOIST BRIDGING OR OTHER PIPES. HANG PIPES FROM BEAMS, JOIST OR SUPPLEMENTARY STRUCTURAL MEMBERS WHERE POSSIBLE. INSTALL ALL PIPING AND DUCTWORK WITHIN 12" FROM SUPPORTING STRUCTURE.



NOT IN SCOPE OF WORK


NOT IN SCOPE OF WORK

MECHANICAL PLAN - LEVEL 6
SCALE: 1/4" = 1'-0"




C:\Users\mid\Documents\240149-Mech-Central_monica_drawing.rvt


6/28/2024 1:51:17 PM




REGISTER - GRILLE- DIFFUSER SCHEDULE											
ACCEPTABLE MANUFACTURERS:			REMARKS:								
KRUEGER TUTTLE & BAILEY TITUS PRICE			(1) PROVIDE TRANSITION AS NECESSARY. (2) COORDINATE EXACT COLOR SELECTION WITH OWNER AND ARCHITECT.								
LABEL	TYPE	MAX AIRFLOW (CFM)	FACE SIZE	NECK SIZE	BLOW PATTERN	PD (IN-WC)	THROW(S) (FT)	MAX NC	MANUFACTURER	MODEL	REMARKS
R-1	PERFORATED RETURN GRILLE	545	24" X 12"	SEE PLANS	N/A	0.231	N/A	30	PRICE INDUSTRIES	PDDR	ALL
R-2	PERFORATED RETURN GRILLE	2690	24" X 24"	SEE PLANS	N/A	0.172	N/A	30	PRICE INDUSTRIES	PDDR	ALL
S-1	SQUARE PLAQUE DIFFUSER	350	24" X 24"	8" Ø	4-WAY	0.115	4-6-10	30	PRICE INDUSTRIES	SPD	ALL
S-2	SQUARE PLAQUE DIFFUSER	545	24" X 24"	10" Ø	4-WAY	0.180	5-8-12	30	PRICE INDUSTRIES	SPD	ALL




4 FLEX DUCT SUPPORT
SCALE: N.T.S.




3 DUCT HANGERS
SCALE: N.T.S.




2 DUCT OFFSETS DETAIL
SCALE: N.T.S.




7 CEILING DIFFUSER DETAIL
SCALE: N.T.S.



6 DUCT LINER
SCALE: N.T.S.



5 RETURN AIR GRILLE WITH SOUND BOOT
SCALE: N.T.S.



1 DUCT HIGH EFFICIENCY TAKE-OFFS
SCALE: N.T.S.

DUCT SIZE	RECTANGLE OPENING
6" Ø	6" X 9"
8" Ø	8" X 12"
10" Ø	10" X 14"
12" Ø	12" X 16"
14" Ø	14" X 18"

NOTE:
1. CONSTRUCT FITTING PER SMACNA HVAC DUCT CONSTRUCTION STANDARDS

C:\Users\mid\Documents\240149-Mech-Central_monica_downing.rvt

6/28/2024 1:51:18 PM

SYMBOL LEGEND - MISC	
REFERENCE LINES AND SYMBOLS	
SYMBOL	DESCRIPTION
	VIEW OR DETAIL INDICATOR: # INDICATES DETAIL NUMBER, SHEET INDICATES DRAWING SHEET WHERE VIEW OR DETAIL IS SHOWN.
	ELEVATION OR SECTION INDICATOR: # INDICATES VIEW NUMBER, SHEET INDICATES DRAWING SHEET WHERE VIEW IS SHOWN.
	ROOM / SPACE INDICATOR
	KEYNOTE INDICATOR
	REVISION INDICATOR
	PLUMBING FIXTURE INDICATOR
	EQUIPMENT INDICATOR
	REGISTER, GRILLE, OR DIFFUSER INDICATOR
	BREAKLINE
	MATCHLINE INDICATOR
	CONTRACT LIMIT LINE: DASHDOT, WIDE LINE
	NEW CONNECTION TO EXISTING
	POINT OF DEMOLITION

SYMBOL LEGEND - PIPING	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
SYMBOL	DESCRIPTION
	HOSE BIBB / WALL HYDRANT
	CLEANOUT TO GRADE
	FLOOR CLEANOUT
	WALL CLEANOUT
	FLOOR DRAIN
	FLOOR SINK

DEFINITIONS	
NOTE: ALL DEFINITIONS MAY NOT BE USED.	
INDICATED: THE TERM "INDICATED" REFERS TO GRAPHIC REPRESENTATIONS, NOTES, OR SCHEDULES ON THE DRAWINGS, OTHER PARAGRAPHS OR SCHEDULES IN THE SPECIFICATIONS, AND SIMILAR REQUIREMENTS IN THE CONTRACT DOCUMENTS. WHERE TERMS SUCH AS "SHOWN", "NOTED", "SCHEDULED", AND "SPECIFIED" ARE USED, IT IS TO HELP THE READER LOCATE THE REFERENCE, NO LIMITATION ON LOCATION IS INTENDED.	
DIRECTED: TERMS SUCH AS "DIRECTED", "REQUESTED", "AUTHORIZED", "SELECTED", "APPROVED", "REQUIRED", AND "PERMITTED" MEAN "DIRECTED BY THE ENGINEER", "REQUESTED BY THE ENGINEER", AND SIMILAR PHRASES.	
APPROVED: THE TERM "APPROVED", WHEN USED IN CONJUNCTION WITH THE ENGINEER'S ACTION ON THE CONTRACTOR'S SUBMITTALS, APPLICATIONS, AND REQUESTS, IS LIMITED TO THE ENGINEER'S DUTIES AND RESPONSIBILITIES AS STATED IN GENERAL AND SUPPLEMENTARY CONDITIONS.	
FURNISH: THE TERM "FURNISH" IS USED TO MEAN "SUPPLY AND DELIVER TO THE PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS."	
INSTALL: THE TERM "INSTALL" IS USED TO DESCRIBE OPERATIONS AT PROJECT SITE INCLUDING THE ACTUAL "UNLOADING, UNPACKING, ASSEMBLY, ERECTION, PLACING, ANCHORING, APPLYING, WORKING TO DIMENSION, FINISHING, CURING, PROTECTING, CLEANING, AND SIMILAR OPERATIONS."	
PROVIDE: THE TERM "PROVIDE" MEANS "TO FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE."	
INSTALLER: AN "INSTALLER" IS THE CONTRACTOR OR AN ENTITY ENGAGED BY THE CONTRACTOR, EITHER AS AN EMPLOYEE, SUBCONTRACTOR, OR SUB-SUBCONTRACTOR, FOR PERFORMANCE OF A PARTICULAR CONSTRUCTION ACTIVITY, INCLUDING INSTALLATION, ERECTION, APPLICATION, AND SIMILAR OPERATIONS. INSTALLERS ARE REQUIRED TO BE EXPERIENCED IN THE OPERATIONS THEY ARE ENGAGED TO PERFORM.	


PIPING LEGEND	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
ABBREVIATION	DESCRIPTION
---160---	160°F HOT WATER
----160R----	160°F HOT WATER RETURN / CIRCULATION
---180---	180°F HOT WATER
----180R----	180°F HOT WATER RETURN / CIRCULATION
---AW---	ACID WASTE
---AV---	ACID VENT
---CO2---	CARBON DIOXIDE
---CWV---	COMBINATION WASTE AND VENT
---CA---	COMPRESSED AIR
---CD---	CONDENSATE DRAIN
---DCW---	DOMESTIC COLD WATER
---DHW---	DOMESTIC HOT WATER
---DHWV---	DOMESTIC HOT WATER RECIRCULATION
---DI---	DEIONIZED WATER
---DSW---	DOMESTIC SOFT WATER
---D---	DEMOLISHED PIPING
---FP---	FIRE PROTECTION
---FOR---	FUEL OIL RETURN
---FOS---	FUEL OIL SUPPLY
---FOV---	FUEL OIL VENT
---GW---	GREASE WASTE
---HPC---	HIGH PRESSURE CONDENSATE
---MPC---	MEDIUM PRESSURE CONDENSATE
---LPC---	LOW PRESSURE CONDENSATE
---ICW---	INDUSTRIAL COLD WATER
---IHW---	INDUSTRIAL HOT WATER
---IW---	IRRIGATION WATER
---LPG---	LIQUID PROPANE GAS
---MA---	MEDICAL AIR
---NG---	NATURAL GAS
---NO---	NITROGEN OXIDE
---O---	OXYGEN
---OD---	OVERFLOW ROOF DRAIN / STORM DRAIN
---PC---	PUMPED CONDENSATE
---RD---	ROOF DRAIN / STORM DRAIN
---SS---	SANITARY SEWER
---VAC---	VACUUM
---V---	VENT

SYMBOL LEGEND - PIPING	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
SYMBOL	DESCRIPTION
	SHUT OFF VALVE
	GATE VALVE
	CHECK VALVE
	AUTOMATIC 2-WAY VALVE
	AUTOMATIC 3-WAY VALVE
	GLOBE VALVE
	BALL VALVE
	RELIEF VALVE
	PRESSURE REDUCING VALVE
	BUTTERFLY VALVE
	SOLENOID VALVE
	ANGLE VALVE
	VENTURI VALVE
	BALANCING OR PLUG COCK
	FLOW SETTER
	EXPANSION VALVE
	GAS COCK
	MANUAL AIR VENT
	STRAINER
	GAUGE COCK
	FLEXIBLE CONNECTION
	PRESSURE GAUGE
	THERMOMETER
	PIPE REDUCER
	REFRIGERANT SITE GLASS
	REFRIGERANT STRAINER
	REFRIGERANT FILTER DRIER
	90 DEGREE ELBOW UP
	90 DEGREE ELBOW DOWN
	90 DEGREE TEE UP
	90 DEGREE TEE DOWN
	PIPE UNION
	PIPE CAP
	PIPE ANCHOR
	FLOAT AND THERMOSTATIC TRAP

ABBREVIATIONS	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED.	
(E)	EXISTING
(F)	FUTURE
AC	AIR CONDITIONING (-ING, -ED)
APD	AIR PRESSURE DROP
BD	BALANCING DAMPER
BHP	BRAKE HORSE POWER
BTU	BRITISH THERMAL UNIT
BTU/H	BTU/HOUR
CFH	CUBIC FEET PER HOUR
CFM	CUBIC FEET PER MINUTE
CV	CONTROL VALVE
DB	DRY BULB TEMPERATURE
DCW	DOMESTIC COLD WATER
DHW	DOMESTIC HOT WATER
DHWV	DOMESTIC HOT WATER RECIRC
DP	DEPTH, DEEP, OR DROP IN PRESSURE
EA	EXHAUST AIR
EER	ENERGY EFFICIENCY RATIO
EFF	EFFICIENCY
ELEC	ELECTRIC
ELEV	ELEVATION
ENT	ENTERING
EVAP	EVAPORATE (-E, -ING, -ED, -OR)
EXT	ENTERING WATER TEMPERATURE
EXT	EXTERNAL
FD	FIRE DAMPER
FLA	FULL LOAD AMPS
FPI	FINS PER INCH
FFM	FEET PER MINUTE
FFS	FEET PER SECOND
FSD	FIRE SMOKE DAMPER
GE	GREASE EXHAUST
GPH	GALLONS PER HOUR
GPM	GALLONS PER MINUTE
HD	HEAD
HG	MERCURY
HP	HORSEPOWER
HR	HOUR
HTG	HEATING
HZ	HERTZ (FREQUENCY)
IN	INCH
KW	KILOWATT
LAT	LEAVING AIR TEMPERATURE
LBS	POUNDS
LH	LATENT HEAT
LRA	LOCKED ROTOR AMPS
LVG	LEAVING
LWT	LEAVING WATER TEMPERATURE
MBH	THOUSAND BTU PER HOUR
MCA	MINIMUM CIRCUIT AMPS
MFR	MANUFACTURER (-ER, -ED)
NC	NORMALLY CLOSED OR NOISE CRITERIA
NIC	NOT IN CONTRACT
NO	NORMALLY OPEN
NPSH	NET POSITIVE SUCTION HEAD
NTS	NOT TO SCALE
OA	OUTSIDE AIR
OD	OUTSIDE DIAMETER
OZ	OUNCE
PD	PRESSURE DROP OR DIFFERENCE
PG	PROPYLENE GLYCOL
PH	PHASE
PPM	PARTS PER MILLION
PSF	POUNDS PER SQUARE FOOT
PSI	POUNDS PER SQUARE INCH
PSIA	PSI ABSOLUTE
PSIG	PSI GAUGE
RA	RETURN AIR
RECIRC	RECIRCULATE (-ER, -ED, -ING)
REFR	REFRIGERATION
REQD	REQUIRED
RLA	RATED LOAD AMPS
RPM	REVOLUTIONS PER MINUTE
SA	SUPPLY AIR
SCFM	STANDARD CUBIC FEET PER MINUTE
SCW	SOFT COLD WATER
SH	SENSIBLE HEAT
SP	STATIC PRESSURE
SPEC(S)	SPECIFICATION(S)
SQ	SQUARE
SS	SANITARY SEWER, SOIL, WASTE
STD	STANDARD
TA	TRANSFER AIR
TD	TEMP. DROP OR DIFF.
TEMP	TEMPERATURE
TOT	TOTAL
TSTAT	THERMOSTAT
TYP	TYPICAL
V	VOLT, VOLTAGE OR VENT
VAC	VACUUM
VAV	VARIABLE AIR VOLUME
VEL	VELOCITY
VENT	VENT, VENTILATION
VERT	VERTICAL
VFD	VARIABLE FREQUENCY DRIVE
VOL	VOLUME
VTR	VENT THROUGH ROOF
WB	WET BULB TEMP
WC	WATER COLUMN
WG	WATER GAUGE
WPD	WATER PRESSURE DROP
WTR	WATER

PLUMBING GENERAL NOTES	
1.	THE PLUMBING DRAWINGS SHOW THE GENERAL DESIGN, ARRANGEMENT AND EXTENT OF THE PLUMBING SYSTEM. BECAUSE OF THE SMALL SCALE OF THE DRAWINGS, THESE DRAWINGS DO NOT SHOW ALL OFFSETS, BENDS OR ELBOWS NECESSARY FOR THE COMPLETE INSTALLATION IN THE SPACE PROVIDED. CONTRACTOR SHALL MAKE SUCH SLIGHT ALTERATIONS AS MAY BE NECESSARY TO MAKE THE SYSTEM COMPLETE AND OPERATIONAL IN ACCORDANCE WITH THE DESIGN INTENT. MAJOR DEVIATIONS SUCH AS CHANGES IN COMPONENT SIZES, WEIGHTS, QUANTITIES OR MATERIAL REQUIRE PRIOR APPROVAL BY THE DESIGN ENGINEER.
2.	THE DRAWINGS AND SPECIFICATIONS HAVE BEEN PREPARED TO SUPPLEMENT EACH OTHER AND SHALL BE INTERPRETED AS AN INTEGRAL UNIT WITH THE ITEMS SHOWN ON ONE AND NOT THE OTHER BEING FURNISHED AND INSTALLED AS THOUGH SHOWN AND CALLED OUT IN BOTH.
3.	THE ENTIRE PLUMBING INSTALLATION SHALL CONFORM TO THE REQUIREMENTS OF THE MOST RECENTLY ADOPTED BUILDING CODES, MECHANICAL CODE, PLUMBING CODE, ELECTRICAL CODE, AND ALL OTHER APPLICABLE CITY, COUNTY, STATE, AND FEDERAL CODES AND REGULATIONS IN EFFECT.
4.	THE ENTIRE PLUMBING INSTALLATION SHALL CONFORM TO ANY CODES, RULES, REGULATIONS AND REQUIREMENTS OF THE BUILDING OWNER PRIOR TO FABRICATION AND INSTALLATION OF ANY PLUMBING COMPONENT THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF ALL PLUMBING WORK WITH ALL OTHER BUILDING TRADES, INCLUDING BUILDING TRADES HIRED DIRECTLY BY THE OWNER, WHERE CONFLICTS MAY OCCUR, THEY SHALL BE RESOLVED PRIOR TO INSTALLATION.
6.	ALL PLUMBING INFORMATION IS NOT SHOWN ON THE PLUMBING DRAWINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL INFORMATION ON ALL OTHER CONSTRUCTION DOCUMENTS.
7.	THE CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW AND USE, WHERE APPROPRIATE, ALL THE PLUMBING DETAILS SHOWN ON THE DRAWINGS. DETAILS MAY OR MAY NOT BE CALLED OUT ON THE DRAWINGS WITH SYMBOLS OR KEYPAD NOTES. ANY CHANGES RESULTING FROM FAILURE TO INSTALL THE PLUMBING SYSTEM WITHOUT USING THE INCLUDED DETAILS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
8.	ANY PART OF THE PLUMBING INSTALLATION THAT FAILS, IS UNFIT, OR BECOMES DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED OR REPLACED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
9.	PROVIDE PROPER PROVISIONS FOR EXPANSION, CONTRACTION, OR MOVEMENT OF ALL PIPING.
10.	PROVIDE LARGE ENOUGH PIPE SLEEVES THROUGH WALL OR FLOOR TO ALLOW FOR ANTICIPATED DIFFERENTIAL MOVEMENT.
11.	ALL PIPING SHALL BE SUPPORT WITH CLEVIS HANGERS (MSS TYPE 1), PERFORATED METAL STRAPS OR PLASTIC STRAPPING (PLUMBER TAPE) SHALL NOT BE USED TO SUPPORT OR BRACE ANY PIPE.
12.	PROVIDE PIPE HANGERS WITH 18 INCHES OF ALLOWED CHANGES OF DIRECTION.
13.	PROVIDE SWAY BRACING FOR ALL PIPING 4" AND LARGER AT ALL CHANGES IN DIRECTION GREATER THAN 45 DEGREES.
14.	ALL STEEL CLEVIS HANGERS USED TO SUPPORT COPPER PIPING SHALL BE COPPER OR PLASTIC COATED.
15.	COPPER PIPING SHALL NOT COME IN CONTACT WITH FIRE TREATED LUMBER. PROVIDE 1/2" THICK SLIP-ON CLOSED CELL INSULATION WHERE COPPER PIPING IS ADJACENT TO FIRE TREATED LUMBER. CLOSED CELL INSULATION SHALL EXTEND A MINIMUM OF 1-1/2" PAST LUMBER.
16.	ALL EXPOSED PIPING SHALL BE INSTALLED IN A NEATLY ARRANGED MANNER PARALLEL TO THE BUILDING STRUCTURE.
17.	ALL EXPOSED DOMESTIC WATER PIPE IN OCCUPIED SPACES SHALL BE POLISHED CHROME PLATED.
18.	ALL EXPOSED DRAINAGE PIPING IN OCCUPIED SPACES INCLUDING TRAPS UNDER SINKS SHALL BE POLISHED CHROME PLATED.
19.	DRAWINGS SHOW GENERAL ARRANGEMENT OF THE DRAIN WASTE AND VENT SYSTEM WITH THE REQUIRED CLEANOUTS. CONTRACTOR SHALL PROVIDE ALL ADDITIONAL CLEANOUTS AS REQUIRED BY THE PLUMBING CODE.
20.	ALL SANITARY DRAINAGE SYSTEM PIPING 3" AND LARGER SHALL BE SLOPED IN DIRECTION OF FLOW AT A MINIMUM OF 1/8" PER FOOT.
21.	ALL SANITARY DRAINAGE SYSTEM PIPING SMALLER THAN 3" SHALL BE SLOPED IN DIRECTION OF FLOW AT A MINIMUM OF 1/4" PER FOOT.
22.	SLOPE VENT SYSTEM TOWARDS DRAINAGE SYSTEM.
23.	SIMILAR EQUIPMENT SHALL BE OF THE SAME MANUFACTURER.
24.	ALL EQUIPMENT SHALL PROVIDE THE SCHEDULED PERFORMANCE AT THE JOB SITE ELEVATION.
25.	FIXTURE AND EQUIPMENT MODEL NUMBERS SHOWN IN PLUMBING FIXTURE SCHEDULE AND PLUMBING EQUIPMENT SCHEDULE ARE SHOWN TO ESTABLISH THE TYPE OF PRODUCT THAT SHALL BE USED. THE SELECTED PRODUCT SHALL MEET THE SCHEDULED PERFORMANCE DATA SHOWN ON THE SCHEDULE EVEN IF A DIFFERENT MODEL IS SUPPLIED THAT IS DIFFERENT THAN THAT SCHEDULED.
26.	ALL EQUIPMENT SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE EQUIPMENT MANUFACTURER'S INSTALLATION INSTRUCTIONS. PROVIDE ALL NECESSARY FITTINGS, TRANSITIONS, VALVES AND OTHER DEVICES AND ACCESSORIES REQUIRED FOR A COMPLETE, WORKABLE INSTALLATION.
27.	SEE "PLUMBING FIXTURE SCHEDULE" FOR INDIVIDUAL TRAPS, WASTE, VENT, AND DOMESTIC WATER PIPING FOR INDIVIDUAL FIXTURES.
28.	ALL PLUMBING EQUIPMENT SHALL BE LISTED AND LABELED BY AN APPROVED TESTING AGENCY.
29.	FIXTURES, EQUIPMENT AND PIPING INSTALLATION SHALL MEET NSF STANDARDS.

PLUMBING SHEET INDEX	
P001	PLUMBING COVER SHEET
P111	PLUMBING DEMOLITION PLAN LEVEL 6
P112	PLUMBING PLAN LEVEL 6
P001	PLUMBING DETAILS AND SCHEDULES



Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6
5171 Cottonwood Street #450
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 27, 2024

PLUMBING COVER SHEET


P001

C:\Users\mid\Documents\240149-Mech-Central_monica_downing.rvt

6/28/2024 1:52:12 PM



1 PLUMBING DEMOLITION PLAN - LEVEL 6
SCALE: 1/4" = 1'-0"




KEYED NOTES


- 1 REMOVE EXISTING SINK, INSTANTANEOUS WATER HEATER AND ASSOCIATED PIPING BACK TO MAINS.
- 2 EXISTING ICE WATER CONNECTION TO REMAIN.
- 3 SOLID SURFACE SINK IS INTEGRATED WITH COUNTERTOP, REMOVE AND SALVAGE SINK, REMOVE PIPING BACK TO POINTS INDICATED. SEE RENOVATION PLANS FOR NEW LOCATION. IF SINK IS DAMAGED DURING CONSTRUCTION PROVIDE LIKE-IN-KIND.
- 4 TO REMOVE SANITARY PIPING WILL REQUIRE AFTER HOURS AND WEEKEND WORK. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER IN AFFECTING OCCUPIED SPACES.
- 5 REMOVE SANITARY WASTE AND VENT PIPING FROM SOLID SURFACE SINK TO POINT INDICATED.
- 6 REMOVE DOMESTIC COLD WATER AND HOT WATER LINE FROM SOLID SURFACE SINK TO POINT INDICATED.
- 7 REMOVE VENT ELBOW AND PREPARE FOR NEW CONNECTION. SEE SHEET P112.

GENERAL NOTES

- A. ALL DOMESTIC WATER PIPING TO BE COPPER. ALL HOT WATER AND HOT WATER RECIRCULATING PIPING TO BE INSULATED WITH 1" UP TO 1-1/4" PIPE AND 1-1/2" INSULATION FOR PIPING 1-1/2" AND LARGER. DOMESTIC COLD-WATER PIPING TO BE INSULATED WITH 1/2" UP TO 1-1/4" PIPING AND 1" INSULATION FOR PIPING 1-1/2" OR LARGER.
- B. THE CONTRACTOR SHALL CLOSELY COORDINATE MECHANICAL AND PLUMBING WITH ELECTRICAL, ARCHITECTURAL, AND BUILDING STRUCTURE.
- C. DISSIMILAR METAL PIPING CONNECTIONS SHALL HAVE DIELECTRIC ISOLATORS.
- D. ALL DOMESTIC WATER PIPING TO BE PRESSURE TESTED, CLEANED, AND DISINFECTED. SEE SPECIFICATIONS.
- E. BALL VALVES SHALL BE FULL PORT AND LEAD FREE. PROVIDE WITH HANDLE/STEM EXTENSIONS FOR PROPER FUNCTION WHEN FULLY INSULATED. EXTENSIONS TO BE SEALED AND VAPOR PROOF.
- F. ALL PLUMBING PIPING TO BE LOCATED ON WARM SIDE OF BUILDING ENVELOPE.
- G. ALL DOMESTIC WASTE AND VENT PIPING TO BE CAST IRON.
- H. THIS PROJECT WILL REQUIRE AFTER HOURS AND WEEKEND WORK TO RUN PIPING/DUCTWORK OR MODIFY SYSTEMS IN OR AFFECTING OCCUPIED SPACES. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER.
- I. PROVIDE BALANCE REPORT OF DOMESTIC WATER RECIRCULATING SYSTEM TO ENGINEER. PROVIDE PAT PORTS AND PRESSURE GAUGES ON EACH SIDE OF RECIRCULATING PUMP. PROVIDE THERMOMETER ON DISCHARGE SIDE OF PUMP.
- J. THE CONTRACTOR SHALL FIELD VERIFY EXISTING FIELD CONDITIONS PRIOR TO ORDERING OR FABRICATING. ADDITIONAL COST WILL NOT BE ALLOWED FOR CONTRACTOR'S FAILURE TO BECOME FAMILIAR WITH EXISTING SITE CONDITIONS.
- K. TEST WASTE AND VENT PIPING FOR LEAKAGE. SEE SPECIFICATIONS.
- L. PIPING SHALL NOT BE SUPPORTED FROM THE ROOF DECK, JOIST BRIDGING OR OTHER PIPES. HANG PIPES FROM BEAMS, JOIST OR SUPPLEMENTARY STRUCTURAL MEMBERS, WHERE POSSIBLE INSTALL ALL PIPING WITHIN 12" FROM SUPPORTING STRUCTURE.
- M. WHERE JURISDICTION REQUIRES, THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING SEISMIC RESTRAINT. PROVIDE DESIGN DRAWINGS TO AUTHORITY HAVING JURISDICTION AND MECHANICAL ENGINEER FOR REVIEW.
- N. PLUMBING PIPING SCHEDULE:
 - a. DOMESTIC WATER ABOVE GRADE= TYPE L COPPER - SOLDERED
 - b. WASTE & VENT ABOVE GRADE = CAST IRON - HUBLESS COUPLINGS WITH HEAVY DUTY COUPLINGS



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.384.9259
www.njraarchitects.com



SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #450
Murray, Utah 84107


NJRA Project # 24002.00
Construction Documents June 27, 2024

PLUMBING DEMOLITION PLAN LEVEL 6

P111

C:\Users\mid\Documents\240149-Mech-Central_monica_downing.rvt

6/28/2024 1:51:22 PM




1 PLUMBING PLAN - LEVEL 6
 SCALE: 1/4" = 1'-0"

KEYED NOTES


- 1 PROVIDE ELBOW IN EXISTING DOMESTIC HOT WATER RECIRCULATION LINE TO PROVIDE CONTINUOUS LOOP TO AND FROM THE PATIENT TOILET A133.
- 2 LOCATE INSTANTANEOUS WATER HEATER BELOW WALL MOUNTED PLUMBING FIXTURE.
- 3 CONNECT TO SEWER LINE IN THIS APPROXIMATE LOCATION.
- 4 TO RUN SANITARY PIPING AND MODIFY EXISTING SANITARY PIPING WILL REQUIRE AFTER HOURS AND WEEKEND WORK. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER IN AFFECTING OCCUPIED SPACES.
- 5 RELOCATED INTEGRATED SINK AND ASSOCIATED FAUCET.

GENERAL NOTES

- A. ALL DOMESTIC WATER PIPING TO BE COPPER. ALL HOT WATER AND HOT WATER RECIRCULATING PIPING TO BE INSULATED WITH 1" UP TO 1-1/4" PIPE AND 1-1/2" INSULATION FOR PIPING 1-1/2" AND LARGER. DOMESTIC COLD-WATER PIPING TO BE INSULATED WITH 1/2" UP TO 1-1/4" PIPING AND 1" INSULATION FOR PIPING 1-1/2" OR LARGER.
- B. THE CONTRACTOR SHALL CLOSELY COORDINATE MECHANICAL AND PLUMBING WITH ELECTRICAL, ARCHITECTURAL, AND BUILDING STRUCTURE.
- C. DISSIMILAR METAL PIPING CONNECTIONS SHALL HAVE DIELECTRIC ISOLATORS.
- D. ALL DOMESTIC WATER PIPING TO BE PRESSURE TESTED, CLEANED, AND DISINFECTED. SEE SPECIFICATIONS.
- E. BALL VALVES SHALL BE FULL PORT AND LEAD FREE. PROVIDE WITH HANDLE/STEM EXTENSIONS FOR PROPER FUNCTION WHEN FULLY INSULATED. EXTENSIONS TO BE SEALED AND VAPOR PROOF.
- F. ALL PLUMBING PIPING TO BE LOCATED ON WARM SIDE OF BUILDING ENVELOPE.
- G. ALL DOMESTIC WASTE AND VENT PIPING TO BE CAST IRON.
- H. THIS PROJECT WILL REQUIRE AFTER HOURS AND WEEKEND WORK TO RUN PIPING/DUCTWORK OR MODIFY SYSTEMS IN OR AFFECTING OCCUPIED SPACES. COORDINATE ALL SHUTDOWNS 72 HOURS IN ADVANCE WITH OWNER.
- I. PROVIDE BALANCE REPORT OF DOMESTIC WATER RECIRCULATING SYSTEM TO ENGINEER. PROVIDE PAT PORTS AND PRESSURE GAUGES ON EACH SIDE OF RECIRCULATING PUMP. PROVIDE THERMOMETER ON DISCHARGE SIDE OF PUMP.
- J. THE CONTRACTOR SHALL FIELD VERIFY EXISTING FIELD CONDITIONS PRIOR TO ORDERING OR FABRICATING. ADDITIONAL COST WILL NOT BE ALLOWED FOR CONTRACTOR'S FAILURE TO BECOME FAMILIAR WITH EXISTING SITE CONDITIONS.
- K. TEST WASTE AND VENT PIPING FOR LEAKAGE. SEE SPECIFICATIONS.
- L. PIPING SHALL NOT BE SUPPORTED FROM THE ROOF DECK, JOIST BRIDGING OR OTHER PIPES. HANG PIPES FROM BEAMS, JOIST OR SUPPLEMENTARY STRUCTURAL MEMBERS. WHERE POSSIBLE INSTALL ALL PIPING WITHIN 12" FROM SUPPORTING STRUCTURE.
- M. WHERE JURISDICTION REQUIRES, THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING SEISMIC RESTRAINT. PROVIDE DESIGN DRAWINGS TO AUTHORITY HAVING JURISDICTION AND MECHANICAL ENGINEER FOR REVIEW.
- N. PLUMBING PIPING SCHEDULE:
 - a. DOMESTIC WATER ABOVE GRADE= TYPE L COPPER - SOLDERED
 - b. WASTE & VENT ABOVE GRADE = CAST IRON - HUBLESS COUPLINGS WITH HEAVY DUTY COUPLINGS



NJRA Architects, Inc.
 5223 S. Ascension Way, Suite 350
 Murray, Utah 84123 801.384.9259
 www.njraarchitects.com



SPECTRUM ENGINEERS
 324 S. State St., Suite 400
 Salt Lake City, UT 84111
 800-678-7077
 801-328-5151
 fax: 801-328-5155
 www.spectrum-engineers.com


Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6

5171 Cottonwood Street #450
 Murray, Utah 84107

NJRA Project # 24002.00
 Construction Documents June 27, 2024


PLUMBING PLAN LEVEL 6

P112




WATER HEATER (ELECTRIC)													
ACCEPTABLE MANUFACTURERS:				REMARKS:									
LOCHINVAR AO SMITH BRADFORD WHITE RHEEM STATE BOCK				(1) FLOW RATE CAPACITY SIZED WITH AN INLET TEMPERATURE OF 52°F AND OUTLET TEMPERATURE OF 105°F.									
LABEL	LOCATION	TYPE	FLOW RATE (GPM)	EFFICIENCY (UEF)	ELECTRICAL				OPERATING WEIGHT (LBS)	MANUFACTURER	MODEL	REMARKS	
					VOLTS	PHASE	Hz	kW					
EW-1	EXAM 6	TANKLESS POINT OF USE	1.0	0.96	240	1	60	8	33	5	EEMAX	HA008240	ALL
EW-1	EXAM 4	TANKLESS POINT OF USE	1.0	0.96	240	1	60	8	33	5	EEMAX	HA008240	ALL
EW-1	EXAM 1	TANKLESS POINT OF USE	1.0	0.96	240	1	60	8	33	5	EEMAX	HA008240	ALL
EW-1	EXAM 5	TANKLESS POINT OF USE	1.0	0.96	240	1	60	8	33	5	EEMAX	HA008240	ALL
EW-2	EXAM 3	TANKLESS POINT OF USE	1.7	0.92	240	1	60	13	54	7	EEMAX	HA013240	ALL


PLUMBING FIXTURE SCHEDULE									
REFER TO PLUMBING SPECIFICATIONS FOR COMPLETE FIXTURE COMPONENTS									
LABEL	DESCRIPTION	WASTE	VENT	CW	HW	MANUFACTURER	MODEL	REMARKS	
LAV	COUNTERTOP LAVATORY	1 1/4"	1 1/2"	1/2"	1/2"	FIXTURE: KOHLER DURING WALL CONSTRUCTION FAUCET: CHICAGO INSULATION: TRUEBRO TMV: WEBSTONE CARRIER: ZURN	FIXTURE: K-2030-0 FAUCET: 786-GN2FC246ABCP INSULATION: LAVGUARD 2 TMV: H-77211W-TG CARRIER: Z1231EZ	SET TMV AT 110 DEG. F.	
WCO	WALL CLEANOUT	0"	0"	0"	0"	ZURN	Z1446	SIZE TO MATCH PIPE BEING SERVED	




3 PIPE SLEEVE THROUGH INTERIOR WALL
SCALE: N.T.S.



2 PIPE HANGERS DETAIL
SCALE: N.T.S.



4 INSTANTANEOUS WATER HEATER (WITH THX)
SCALE: N.T.S.



1 CLEANOUT - WALL DETAIL
SCALE: N.T.S.

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

CATEGORY INSERT COLOR SCHEDULE	
INSERT COLOR	TYPE/APPLICATION
BLUE	DATA
YELLOW	WIRELESS

COPPER PATCH CORD SCHEDULE (CATEGORY 6A F/UTP CABLES W/RJ-45 CONNECTORS)			
LENGTH (FEET)	COLOR	QUANTITY	UNIT COST (EACH)
5'	BLUE	20% OF TOTAL PORTS IN TDRS	-
7'	BLUE	60% OF TOTAL PORTS IN TDRS	-
10'	BLUE	20% OF TOTAL PORTS IN TDRS	-

WIRELESS PATCH CORD PATCH CORD SCHEDULE (CATEGORY 6A F/UTP W RJ/45 CONNECTORS)			
LENGTH (METER)	COLOR	QUANTITY	UNIT COST (EACH)
7'	YELLOW	100% OF TOTAL PORTS IN TDRS	-

EQUIPMENT/CABLE LIST		
THE ITEMS INDICATED BELOW SHALL NOT BE CONSTRUED AS A "BILL OF MATERIALS". THIS LIST IDENTIFIES ITEMS OF SIGNIFICANCE USED DURING THE DESIGN OF THE CABLING INSTALLATION. WHERE THE ITEMS INDICATED ARE ONE PORTION OF AN ASSEMBLY, THE ENTIRE ASSEMBLY SHALL BE PROVIDED UNLESS OTHERWISE SPECIFIED. PROVIDE ALL MISCELLANEOUS HARDWARE AND SUPPORTS, WHICH MAY NOT BE LISTED HERE, FOR A COMPLETE INSTALLATION. COMPARE CATALOG NUMBERS WITH DESCRIPTIONS AND NOTIFY ENGINEER OF DISCREPANCIES PRIOR TO BID. IF CATALOG NUMBERS DO NOT MATCH DESCRIPTIONS, THE DESCRIPTIONS TAKE PRECEDENCE. PROVIDE COMPLETE SUBMITTAL FOR APPROVAL PRIOR TO PURCHASING ANY EQUIPMENT OR CABLE. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.		
SYMBOL	ITEM DESCRIPTION	ACCEPTABLE TYPES
	STATION CABLE, DATA - CATEGORY 6A F/UTP PLENUM RATED, BLUE, DATA	SIEMON 9A8P4-AS-06-R1A
	STATION CABLE, DATA - CATEGORY 6A F/UTP, PLENUM RATED, YELLOW, WIRELESS DATA	SIEMON 9A8P4-AS-05-R1A
	DATA OUTLET, SINGLE GANG FACEPLATE, WHITE, 4 POSITION	SIEMON 10GMX-FPS04-02
	CATEGORY 6A JACK - DATA, BLUE	SIEMON Z6A-S06
	BLANK INSERT, WHITE	SIEMON MX-BL-02
	DATA OUTLET, SURFACE MOUNT BOX, WHITE, 2 POSITION (C=CEILING MOUNTED BOX)	SIEMON MX-SM22-02
	CATEGORY 6A JACK - DATA, YELLOW	SIEMON Z6A-S05
	BLANK FILLER PANEL, 1RU ANGLED	SIEMON PNL-BLNKA-1
	48 PORT, 1RU ANGLED PATCH PANEL WITH OUTLETS - DETACHABLE REAR MING	SIEMON Z6AS-PA-48
	FIRE-RATED SLEEVES (2"x2" FOR ROOM PENETRATIONS, 4"x4" FOR J-HOOK PATHWAYS)	STIEZ PATH, HILTI
	SMOKE/ACOUSTICAL-RATED SLEEVES (2"x2" FOR ROOM PENETRATIONS, 4"x4" FOR J-HOOK PATHWAYS)	STI EZ PATH, HILTI
	TELECOMMUNICATIONS MAIN GROUNDING BUS BAR	
	TELECOMMUNICATIONS GROUNDING BUS BAR	


NOTE: ALL RACKS, LADDER, PATCH PANELS AND ACCESSORIES SHALL BE BLACK IN COLOR.

GENERAL SHEET NOTES

- UNLESS OTHERWISE NOTED, INSTALL ALL CABLE INSIDE RACEWAY SYSTEMS. WHERE RACEWAY SYSTEMS HAVE NOT BEEN PROVIDED OR SPECIFIED, INSTALL CABLE THROUGH THE SPECIFIED "CADDY" CLIPS AT THE MINIMUM INTERVALS IDENTIFIED IN THE SPECIFICATIONS. SUPPORT "CADDY" CLIPS DIRECTLY FROM THE BUILDING STRUCTURE, NOT FROM OTHER BUILDING SYSTEM SUPPORT WIRES OR CABLE.
- PROVIDE PLENUM RATED CABLE IN ALL AIR PLENUMS. IF A PLENUM RATED CABLE IS NOT SPECIFIED, PROVIDE THE PLENUM RATED EQUIVALENT TO THE SPECIFIED CABLE.
- LABEL ALL CABLE INSTALLED UNDER THIS CONTRACT REGARDLESS OF LENGTH.
- THE EQUIPMENT LABELING IDENTIFIED ON DETAILS IN THESE DRAWINGS ARE EXAMPLES ONLY OF THE ACTUAL LABELING, WHICH IS REQUIRED AS PART OF THIS CONTRACT. PRIOR TO FABRICATION, SUBMIT THE NOMENCLATURE FOR ALL LABELS TO THE OWNER FOR REVIEW. THIS REQUIREMENT INCLUDES, BUT IS NOT LIMITED TO, ALL CABLE LABELING AND ALL EQUIPMENT LABELING.
- IF OUTLET IS TERMINATED IN CEILING SPACE, LABEL THE T-BAR GRID WITH THE OUTLET NUMBER FOR EASY LOCATION AND IDENTIFICATION.
- GROUND ALL EQUIPMENT RACKS INSTALLED UNDER THIS CONTRACT IN COMPLIANCE WITH THE CONTRACT DOCUMENTS.
- FOR EVERY PULL SPECIFIED, COIL 15 FEET OF EXCESS CABLE AT THE STATION END FOR FUTURE USE. NEATLY COIL 15 FEET ABOVE THE CEILING OR BELOW THE FLOOR, WHERE APPLICABLE.
- PROVIDE THE QUANTITY OF PATCH PANELS REQUIRED +20% FOR THE TOTAL DATA OUTLETS SHOWN ON FLOOR PLANS FOR THE PARTICULAR LEVEL.
- RACK SPACE ALLOCATION SHOULD BE FOLLOWED PER DRAWINGS. IF THERE IS A SYSTEM THAT HAS NO RACK SPACE AVAILABLE, PLEASE CALL BOE SAUSEDO AT 801-707-3905.
- COORDINATE WITH ALL SUB-CONTRACTORS TO ENSURE THAT ALL CABLES ARE PROTECTED FROM ANY DIRECT PAINT OR INCIDENTAL OVERSPRAY.
- CONTRACTOR TO PROVIDE FIRE-RATED SLEEVES THROUGH 1-HOUR RATED WALLS AND HIGHER. NUMBER OF SLEEVES TO BE DETERMINED AND CALCULATED BY MAXIMUM CABLE TRAY CAPACITY AT WALL PENETRATION. FINAL QUANTITY OF SLEEVES TO BE DETERMINED BY CONTRACTOR.
- CONTRACTOR TO PROVIDE SMOKE AND ACOUSTICAL-RATED SLEEVES THROUGH SMOKE WALLS AND ALL OTHER NON-RATED PENETRATIONS. (2) 4" SLEEVES PER ROOM FOR CABLE CAPACITY AND SERVICE SEPARATION. FINAL QUANTITY OF SLEEVES TO BE DETERMINED BY CONTRACTOR.
- CONTRACTOR TO PROVIDE FIRE-RATED SLEEVES THROUGH 1-HOUR RATED WALLS AND HIGHER. (1) SLEEVE PER J-HOOK PATHWAY FOR CABLE CAPACITY AND SERVICE SEPARATION.
- CONTRACTOR TO PROVIDE SMOKE AND ACOUSTICAL-RATED SLEEVES THROUGH SMOKE WALLS AND ALL OTHER NON-RATED PENETRATIONS. (1) SLEEVE PER J-HOOK PATHWAY FOR CABLE CAPACITY AND SERVICE SEPARATION.
- THE USE OF ZIP-TIES IS NOT ALLOWED TO BUNDLE CABLES (LACE OR TRAIN) IN LADDER RACK, CABLE TRAY, OR TO FINAL TERMINATION POINT. CONTRACTOR SHOULD UTILIZE "HOOK AND LOOP" FOR BUNDLING OF ALL CABLES.
- THE USE OF ZIP-TIES IS NOT ALLOWED FOR THE SUPPORT OF CABLE OR THE ATTACHMENT OF CABLES IN ANY CEILING SPACE. THE USE OF J-HOOKS IS REQUIRED FOR NON-CONTINUOUS PATHWAYS IN CEILINGS. CONTRACTORS SHOULD UTILIZE "HOOK AND LOOP" FOR BUNDLING OF ALL CABLES.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107


NJRA Project # 24002.00
Construction Documents June 28, 2024

TELECOM
SCHEDULES
AND NOTES


EE002




C:\Users\lbaa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanAfta.rvt




5 FIRE STOP FOR METAL CONDUIT THROUGH GYPSUM WALL BOARD
SCALE: NTS



6 TYPICAL FIRE STOP FOR CABLES/CONDUIT THROUGH CONCRETE FLOORING
SCALE: NTS




7 TYPICAL FIRE STOP FOR CABLES/CONDUIT THROUGH CONCRETE WALLS
SCALE: NTS




- NOTES:
1. TYPICAL FOR WOOD AND METAL STUD ROUGH-IN.
 2. PLASTER RINGS NOT SHOWN.
 3. LOCATE ALL OUTLET BOXES IN ACCORDANCE WITH ARCHITECTURAL AND MECHANICAL DRAWINGS AND WITH ALL APPLICABLE SHOP DRAWINGS.
 4. IN ACCORDANCE WITH IBC 714.3.2 EXCEPTION 1, OUTLETS ON OPPOSITE SIDES OF WALLS OR PARTITIONS IN THE SAME STUD SPACE IN A RATED FIRE SEPARATION WALL MUST BE SEPARATED BY A MINIMUM OF 24" HORIZONTAL DISTANCE OR LISTED, SOUND AND FIRE RATED PUTTY PADS SHALL BE USED ON THE OUTLET BOXES.
 5. IN NON-RATED WALLS, OUTLETS ON OPPOSITE SIDES OF WALLS OR PARTITIONS MUST BE SEPARATED BY 16" FOR SOUND ATTENUATION.


1 TYPICAL ROUGH-IN REQUIREMENTS DETAIL
SCALE: NTS



2 TYPICAL RACEWAY SUPPORT METHODS DETAIL
SCALE: NTS



4 RECESSED FIXTURE MOUNTING DETAIL
SCALE: NTS




3 TYPICAL CONDUIT RACK DETAIL
SCALE: NTS


Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107


6/28/2024 10:30:26 AM



E2 RECEPTACLE MOUNTING DETAILS
SCALE: NTS




D2 FIRE ALARM MOUNTING DETAILS
SCALE: NTS



C2 SWITCH MOUNTING DETAILS
SCALE: NTS


C4 COMMUNICATIONS MOUNTING DETAILS
SCALE: NTS



B2 LIGHTING MOUNTING DETAILS
SCALE: NTS

B3 BOX MOUNTING DETAILS
SCALE: NTS

B4 TYPICAL WALL MOUNTED DEVICES ALIGNMENT DETAIL
SCALE: NTS




GENERAL SHEET NOTES

- MOUNTING HEIGHTS OF ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE FOLLOWING ORDER OF PRIORITY:
A - ELEVATIONS (ARCHITECTURAL, ELECTRICAL, MECHANICAL, ETC.)
B - EQUIPMENT SHOP DRAWINGS.
C - FIELD INSTRUCTIONS.
- LOCATE RECEPTACLES SERVING THE SAME TYPE OF USE AT A UNIFORM HEIGHT UNLESS DIRECTED OTHERWISE.
- MECHANICAL, ELECTRICAL, AND COMMUNICATION ROOMS: COORDINATE LOCATION OF LIGHTING AND POWER RECEPTACLES WITH EQUIPMENT, PIPING, AND DUCTWORK. DO NOT INSTALL RECEPTACLES BEHIND EQUIPMENT OR WHERE OTHERWISE INACCESSIBLE. POSITION LIGHTING REGARDLESS OF WHERE SHOWN ON DRAWING TO PROVIDE PROPER ILLUMINATION.
- MOUNT RECEPTACLE BOXES FOR SWITCHES AND RECEPTACLES WITH LONG AXIS OF THE DEVICE VERTICAL UNLESS OTHERWISE INDICATED.
- SET BOXES WITH PLASTER RINGS FLUSH WITH FINISHED SURFACE.
- LOCATE BOX COVERS OR DEVICE PLATES SO THEY WILL NOT SPAN DIFFERENT TYPES OF BUILDING FINISHES EITHER VERTICALLY OR HORIZONTALLY.
- VERIFY ALL DOOR CONDITIONS ON ARCHITECTURAL DRAWINGS PRIOR TO INSTALLING SWITCHES.
- LOCATE WIRING DEVICES WHICH ARE ADJACENT AND ARE COMPATIBLE VOLTAGES IN ONE PLATE.
- WHERE DEVICES ARE LOCATED IN CLOSE PROXIMITY OF THE SAME VERTICAL PLANE, ALIGN DEVICES VERTICALLY PER THE TYPICAL WALL MOUNTED DEVICES ALIGNMENT DETAIL, UNLESS OTHERWISE INDICATED.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
801-475-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #450
Murray, Utah 84107


NJRA Project # 2402.00
Construction Documents June 28, 2024

TYPICAL
MOUNTING
DETAILS

EE701

C:\Users\baa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanArla.rvt

6/28/2024 10:30:18 AM



1 LEVEL 6 ELECTRICAL DEMOLITION PLAN
SCALE: 1/4" = 1'-0"

GENERAL SHEET NOTES


- 1 UNLESS NOTED OTHERWISE REMOVE ALL LIGHTING FIXTURES DEVICES AND EQUIPMENT SHOWN DASHED. REMOVE CONDUIT AND WIRING BACK TO PANELBOARD OF ORIGIN OR TO FIRST ACTIVE DEVICE THAT REMAINS.
- 2 SALVAGE ALL LIGHT FIXTURES, TWIST-LOCK RECEPTACLES AND WALLPLATES, CEILING SPEAKERS AND SECURITY AND FIRE ALARM DEVICES TO OWNER. PROTECT SALVAGED EQUIPMENT FROM DAMAGE.
- 3 PRIOR TO SUBMITTING BID, VISIT THE SITE AND FIELD VERIFY THE EXTENT OF ELECTRICAL DEMOLITION WORK TO MEET THE INTENT OF THE BID DOCUMENTS AND INCLUDE ALL COSTS IN BID.
- 4 PRIOR TO REMOVAL OF ANY ELECTRICAL EQUIPMENT OR WIRING, FIELD VERIFY THAT THE EQUIPMENT OR WIRING IS INACTIVE OR NO LONGER IN USE.
- 5 REMOVE ALL DEVICES, RACEWAYS AND WIRING FROM WALLS TO BE REMOVED. WHERE ACTIVE RACEWAYS OCCUR IN WALLS TO BE REMOVED, RE-ROUTE THE RACEWAY WITH ASSOCIATED WIRING TO KEEP THE CIRCUIT OPERATIONAL.
- 6 REMOVE ALL FIRE ALARM DEVICES WHERE EXISTING WALLS AND CEILINGS ARE BEING REMOVED WITH ASSOCIATED CONDUIT AND WIRING. EXISTING FIRE ALARM DEVICES AND SYSTEM NOT INDICATED FOR REMOVAL SHALL REMAIN ACTIVE THROUGHOUT DEMOLITION AND CONSTRUCTION UNTIL THE NEW SYSTEM IS TESTED AND OPERATIONAL. MAINTAIN ALL CLASS A FIRE ALARM INITIATING AND INDICATING LOOPS WHERE EXISTING DEVICES ARE REMOVED.
- 7 REMOVE ALL ABANDONED RACEWAY, CONDUIT, WIRING AND CABLING WHETHER ABANDONED PREVIOUS TO THIS PROJECT OR AS A RESULT OF THIS PROJECT. NOT ALL ABANDONED ITEMS ARE SHOWN ON THESE PLANS AND FIELD VERIFICATION OF DEMOLITION SCOPE EXTENT IS REQUIRED.
- 8 DEVICES MARKED "RR" ARE TO BE REMOVED AND RELOCATED PER NEW PLANS. EXTEND CIRCUITING AS REQUIRED FOR RELOCATION.
- 9 REFER TO ARCHITECTURAL DRAWINGS FOR REMOVAL OF MOTORS, CONDUIT, CONDUCTOR AND CONTROL WIRING ASSOCIATED WITH EXISTING MOTORIZED DOORS, PARTITIONS AND LIGHTING.
- 10 DEMOLISH ALL DATA AND WI-FI ACCESS POINTS WHETHER SHOWN ON DRAWINGS OR NOT WITHIN SCOPE OF WORK AREA.
- 11 REMOVE FEEDERS FOR ALL DEMOLISHED PANELS, DISCONNECTS, ETC. BACK TO SOURCE
- 12 ALL ITEMS INDICATED TO REMAIN SHALL BE PROTECTED DURING ALL PHASES OF CONSTRUCTION.
- 13 CONTRACTOR TO TRACE AND LABEL ALL EXISTING LOADS TO REMAIN, THAT ARE CURRENTLY FED FROM PANELS THAT ARE BEING DEMOLISHED IN THIS PHASE. THESE LOADS TO BE RE-FED FROM NEW PANELS IN NEXT PHASE.
- 14 ALL HVAC UNITS TO BE REMOVED BY MECHANICAL CONTRACTOR UNLESS NOTED OTHERWISE. REMOVE ALL ASSOCIATED RACEWAYS AND CONDUCTORS BACK TO SOURCE.

SHEET KEYNOTES

- 1 EXISTING WALL MOUNTED CABINET TO BE RELOCATED SEE SHEET EP101 FOR LOCATION.



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-675-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107


NJRA Project # 24002.00
Construction Documents June 28, 2024

LEVEL 6
ELECTRICAL
DEMOLITION
PLAN

EDP101

C:\Users\baa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanArla.rvt

6/28/2024 10:30:15 AM



1 LEVEL 6 CEILING DEMOLITION PLAN
SCALE: 1/4" = 1'-0"


GENERAL SHEET NOTES

- UNLESS NOTED OTHERWISE REMOVE ALL LIGHTING FIXTURES DEVICES AND EQUIPMENT SHOWN DASHED. REMOVE CONDUIT AND WIRING BACK TO PANELBOARD OF ORIGIN OR TO FIRST ACTIVE DEVICE THAT REMAINS.
- SALVAGE ALL LIGHT FIXTURES, TWIST-LOCK RECEPTACLES AND WALLPLATES, CEILING SPEAKERS AND SECURITY AND FIRE ALARM DEVICES TO OWNER. PROTECT SALVAGED EQUIPMENT FROM DAMAGE.
- PRIOR TO SUBMITTING BID, VISIT THE SITE AND FIELD VERIFY THE EXTENT OF ELECTRICAL DEMOLITION WORK TO MEET THE INTENT OF THE BID DOCUMENTS AND INCLUDE ALL COSTS IN BID.
- PRIOR TO REMOVAL OF ANY ELECTRICAL EQUIPMENT OR WIRING, FIELD VERIFY THAT THE EQUIPMENT OR WIRING IS INACTIVE OR NO LONGER IN USE.
- REMOVE ALL DEVICES, RACEWAYS AND WIRING FROM WALLS TO BE REMOVED. WHERE ACTIVE RACEWAYS OCCUR IN WALLS TO BE REMOVED, RE-ROUTE THE RACEWAY WITH ASSOCIATED WIRING TO KEEP THE CIRCUIT OPERATIONAL.
- REMOVE ALL FIRE ALARM DEVICES WHERE EXISTING WALLS AND CEILINGS ARE BEING REMOVED WITH ASSOCIATED CONDUIT AND WIRING. EXISTING FIRE ALARM DEVICES AND SYSTEM NOT INDICATED FOR REMOVAL SHALL REMAIN ACTIVE THROUGHOUT DEMOLITION AND CONSTRUCTION UNTIL THE NEW SYSTEM IS TESTED AND OPERATIONAL. MAINTAIN ALL CLASS A FIRE ALARM INITIATING AND INDICATING LOOPS WHERE EXISTING DEVICES ARE REMOVED.
- REMOVE ALL ABANDONED RACEWAY, CONDUIT, WIRING AND CABLING WHETHER ABANDONED PREVIOUS TO THIS PROJECT OR AS A RESULT OF THIS PROJECT. NOT ALL ABANDONED ITEMS ARE SHOWN ON THESE PLANS AND FIELD VERIFICATION OF DEMOLITION SCOPE EXTENT IS REQUIRED.
- DEVICES MARKED "RR" ARE TO BE REMOVED AND RELOCATED PER NEW PLANS. EXTEND CIRCUITING AS REQUIRED FOR RELOCATION.
- REFER TO ARCHITECTURAL DRAWINGS FOR REMOVAL OF MOTORS, CONDUIT, CONDUCTOR AND CONTROL WIRING ASSOCIATED WITH EXISTING MOTORIZED DOORS, PARTITIONS AND LIGHTING.
- DEMOLISH ALL DATA AND WI-FI ACCESS POINTS WHETHER SHOWN ON DRAWINGS OR NOT WITHIN SCOPE OF WORK AREA.
- REMOVE FEEDERS FOR ALL DEMOLISHED PANELS, DISCONNECTS, ETC. BACK TO SOURCE
- ALL ITEMS INDICATED TO REMAIN SHALL BE PROTECTED DURING ALL PHASES OF CONSTRUCTION.
- CONTRACTOR TO TRACE AND LABEL ALL EXISTING LOADS TO REMAIN, THAT ARE CURRENTLY FED FROM PANELS THAT ARE BEING DEMOLISHED IN THIS PHASE. THESE LOADS TO BE RE-FED FROM NEW PANELS IN NEXT PHASE.
- ALL HVAC UNITS TO BE REMOVED BY MECHANICAL CONTRACTOR UNLESS NOTED OTHERWISE. REMOVE ALL ASSOCIATED RACEWAYS AND CONDUCTORS BACK TO SOURCE.

SHEET KEYNOTES



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-675-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6
5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 28, 2024

**LEVEL 6
LIGHTING
DEMOLITION
PLAN**
EDL101



GENERAL SHEET NOTES

- 1 PROVIDE DEDICATED NEUTRALS FOR ALL BRANCH CIRCUITS.
- 2 ALL RECEPTACLES WITHIN 6' OF THE EDGE OF A SINK SHALL BE GFCI PROTECTED.
- 3 ALL WIRING IN PATIENT CARE AREAS SHALL MEET THE REQUIREMENTS OF NEC 517.13.

SHEET KEYNOTES

- 1 CONTRACTOR TO RELOCATE EXISTING WALL MOUNTED CABINET. PRESERVE AND PROTECT ALL EXISTING TERMINATIONS. RE-TEST AND CERTIFY EXISTING TERMINATIONS AFTER CABINET HAS BEEN MOVED.
- 2 CONTRACTOR TO PROVIDE (2) NEW 4" CONDUIT SLEEVES THROUGH CEILING FOR CABLE PATHWAY INTO WALL MOUNTED CABINET.
- 3 CIRCUIT TO THE EXISTING 120V CIRCUIT FEEDING THIS SPACE.
- 4 PROVIDE (3) 40A/2P BREAKERS IN EXISTING SQUARE D PANEL 6LC.
- 5 PROVIDE (1) 40A/2P BREAKER AND (1) 60A/2P BREAKER IN EXISTING EATON PANEL 6LC.

NJRA ARCHITECTS

NJRA Architects, Inc.
 5223 S. Ascension Way, Suite 350
 Murray, Utah 84123
 801.364.9259
 www.njraarchitects.com

SPECTRUM ENGINEERS

324 S. State St., Suite 400
 Salt Lake City, UT 84111
 801-475-7077
 801-328-5151
 fax: 801-328-5155
 www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
 Murray, Utah 84107

NJRA Project # 2402.00
 Construction Documents June 28, 2024

**LEVEL 6
 POWER PLAN**

EP101

C:\Users\baan\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanA110.rvt

6/28/2024 10:30:38 AM

1 LEVEL 6 POWER PLAN
 SCALE: 1/4" = 1'-0"

C:\Users\baaa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central-BrendanAria.rvt


6/28/2024 10:30:40 AM

SHEET KEYNOTES


1 CONTRACTOR TO RELOCATE EXISTING WALL MOUNTED CABINET, PRESERVE AND PROTECT ALL EXISTING TERMINATIONS, RE-TEST AND CERTIFY EXISTING TERMINATIONS AFTER CABINET HAS BEEN MOVED.



NJRA Architects, Inc.
 5223 S. Ascension Way, Suite 350
 Murray, Utah 84123
 801.364.9259
 www.njraarchitects.com



SPECTRUM ENGINEERS
 324 S. State St., Suite 400
 Salt Lake City, UT 84111
 800-675-7077
 801-328-5151
 fax: 801-328-5155
 www.spectrum-engineers.com



ENLARGED TELECOM EQUIPMENT RACK PLAN
 SCALE: 1/4" = 1'-0"


Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6

5171 Cottonwood Street #650
 Murray, Utah 84107

NJRA Project # 24002.00
 Construction Documents June 28, 2024


ENLARGED TELECOM PLANS

EP451




C:\Users\baaa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanArlita.rvt

6/28/2024 10:30:46 AM




5 TYPICAL VOICE/DATA OUTLET PINNING DETAIL
SCALE: NTS




4 TYPICAL CABLE ID EXAMPLE DETAIL
SCALE: NTS


DATA DEVICE DROP SCHEDULE - EXISTING WALL MOUNT CABINET				
DATA DEVICE TYPE	DETAIL LOCATION	COMM ROOM LOCATION	TOTAL BY FLOOR	NUM. OF DROPS
LEVEL 6				
CEILING WIRELESS ACCESS POINT (2-DROP)		EXISTING WALL MOUNTED CABINET	3	6
WALL DATA (2-DROP)		EXISTING WALL MOUNTED CABINET	7	14
WALL DATA - ABOVE COUNTER (2-DROP)		EXISTING WALL MOUNTED CABINET	1	2
Grand total			11	22




3 TYPICAL 2-PORT WIRELESS ACCESS POINT
SCALE: NTS



1 TELECOM EQUIPMENT RACK ELEVATION
SCALE: NTS



2 TYPICAL 2-PORT WALL DATA OUTLET
SCALE: NTS



6 STATION PATCH PANEL, SPP1, SIEMON, ANGLED
SCALE: NTS

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

C:\Users\baa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanArlita.rvt


6/28/2024 10:30:48 AM

GENERAL SHEET NOTES


- 1 GROUNDING DETAIL SHOWN IS FOR DIAGRAMMATIC PURPOSES ONLY. ALL WIRE SIZES SHOWN IN COMMUNICATIONS ROOMS ARE TO BE USED. ANY WIRE SIZING TO GROUNDING BUS BAR AND BUILDING GROUND ARE SHOWN IN THE DIV. 26 SPECIFICATIONS.
- 2 ALL LOW VOLTAGE COMMUNICATIONS CONDUIT IN COMMUNICATIONS ROOM SHALL BE GROUNDED TO TELECOMMUNICATIONS GROUNDING BUS BAR.
- 3 "TMGB" SHOULD BE 1/4"x4"x24".
- 4 "TGB" SHOULD BE 1/4"x2"x24".
- 5 EMT CONDUIT GROUNDING CLAMP SHOULD BE ELECTROLYTIC CAST BRONZE (PANDUIT PART NUMBER GPL-XX-XX, OR EQUAL).
- 6 RIGID CONDUIT GROUND CLAMP SHOULD BE PART NUMBER O-2/GEDNEY BLG-XXXX, OR HBLG-XXXX, OR EQUAL.
- 7 GROUNDING LUGS SHOULD BE TWO-HOLE LONG BARREL LUGS (PANDUIT PART NUMBER LCC6, OR EQUAL).



NJRA Architects, Inc.
 5223 S. Ascension Way, Suite 350
 Murray, Utah 84123
 801.364.9259
 www.njraarchitects.com



SPECTRUM ENGINEERS
 324 S. State St., Suite 400
 Salt Lake City, UT 84111
 800-678-7077
 801-328-5151
 fax: 801-328-5155
 www.spectrum-engineers.com



1 TYPICAL TELECOM EQUIPMENT RACK GROUNDING DETAIL
 SCALE: NTS

Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6

5171 Cottonwood Street #650
 Murray, Utah 84107


NJRA Project # 240202.00
 Construction Documents June 28, 2024

TELECOM
 EQUIPMENT
 RACK
 GROUNDING
 DETAIL
EP552

EQUIPMENT SCHEDULE																																						
MARK	ITEM DESCRIPTION	LOAD DATA						WIRE AND CONDUIT SIZE	COND. AND CONDUIT SCHED.	OVERCURRENT PROTECTION			DISCONNECT			STARTER DATA										NOTES	MARK											
		HP	KW	MCA	FLA	VOLT	PH			Hz	FURN BY	DEVICE	LOCATION	FURN BY	DEVICE	LOCATION	FURN BY	DEVICE	LOCATION	SIZE	SPEED	CTRL VOLT	SELECTOR SWITCH	PUSH BUTTON	PILOT LAMP			NORMALLY OPEN CONTACTS	NORMALLY CLOSED CONTACTS	PHASE FAILURE RELAY	SCHEMATIC REFERENCE	REMOTE CTRL	EMG PWR					
EWH-1	WATER HEATER			33		208	1	60	3 #8, #10 GR 1" CND	8	E	40A/2P CB	PANEL	E	60A/2P FRN-40	ADJ TO EQUIP	E																					EWH-1
EWH-2	WATER HEATER			54		208	1	60	3 #4, #8 GR 1.25" CND	14	E	60A/2P CB	PANEL	E	60A/2P FRN-60	ADJ TO EQUIP	E																				EWH-2	



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com




SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-675-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

CONDUCTOR AND CONDUIT SCHEDULE									
SCHEDULE NUMBER (E.G.) 5 IG									
SUBSCRIPT (NOTE 5)									
SYM	AMP	CONDUIT SIZE	CONDUCTOR(QTY)	CONDUCTOR(SIZE)	NOTE 1	IG	SE	NOTES	
1	20	.75	2	12	12	12	8	2	
2	20	.75	3	12	12	12	8	2,3	
3	20	.75	4	12	12	12	8	2,3	
4	30	.75	2	10	10	10	8	2	
5	30	.75	3	10	10	10	8	2	
6	30	.75	4	10	10	10	8	2	
7	40	1	2	8	10	8	6	2	
8	40	1	3	8	10	8	6	2	
9	40	1	4	8	10	8	6	2	
10	55	1	2	6	10	8	4	2	
11	55	1	3	6	10	8	4	2	
12	55	1.25	4	6	10	8	4	2	
13	70	1	2	4	8	4	2	2	
14	70	1.25	3	4	8	4	2	2	
15	70	1.25	4	4	8	4	2	2	
16	85	1.25	2	3	8	3	2	2	
17	85	1.25	3	3	8	3	2	2	
18	85	1.25	4	3	8	3	2	2	
19	95	1.25	3	2	8	2	2	2	
20	95	1.50	4	2	8	2	2	2	
21	130	1.50	3	1	6	2	2	2	
22	130	1.50	4	1	6	2	2	2	
23	150	2	3	1/0	6	2	1/0	2	
24	150	2	4	1/0	6	2	1/0	2	
25	175	2	3	2/0	6	2	2/0	2	
26	175	2	4	2/0	6	2	2/0	2	
27	200	2	3	3/0	6	2	2/0	2	
28	200	2.50	4	3/0	6	2	2/0	2	
29	230	2.50	3	4/0	4	2	2/0	2	
30	230	2.50	4	4/0	4	2	2/0	2	
31	255	2.50	3	250	4	1	2/0	2	
32	255	2.50	4	250	4	1	2/0	2	
33	310	3	3	350	3	1/0	3/0	2	
34	310	3	4	350	3	1/0	3/0	2	
35	380	3.50	3	500	3	3/0	3/0	2	
36	380	4	4	500	3	3/0	3/0	2	
37	400	2 EA 2	3	3/0	3	3/0	3/0	2	
38	400	2 EA 2.50	4	3/0	3	3/0	3/0	2	
39	510	2 EA 2.50	3	250	1	4/0	3/0	2	
40	510	2 EA 3	4	250	1	4/0	3/0	2	
41	620	2 EA 3	3	350	1/0	4/0	3/0	2,4	
42	620	2 EA 3	4	350	1/0	4/0	3/0	2,4	
43	760	2 EA 3.50	3	500	1/0	4/0	3/0	2,4	
44	760	2 EA 4	4	500	1/0	4/0	3/0	2,4	
45	855	3 EA 3	3	300	2/0	4/0	3/0	2,4	
46	855	3 EA 3	4	300	2/0	4/0	3/0	2,4	
47	1000	3 EA 3.50	3	400	2/0	4/0	3/0	4	
48	1000	3 EA 3.50	4	400	2/0	4/0	3/0	4	
49	1140	3 EA 4	3	500	3/0	4/0	3/0	4	
50	1140	3 EA 4	4	500	3/0	4/0	3/0	4	
51	1240	4 EA 3	3	350	3/0	4/0	3/0	4	
52	1240	4 EA 3	4	350	3/0	4/0	3/0	4	
53	1675	5 EA 3.50	4	400	4/0	4/0	4/0	4	
54	2010	6 EA 3.50	4	400	250	250	250	4	
55	2660	7 EA 4	4	500	350	350	350	4	
56	3040	8 EA 4	4	500	500	500	500	4	
57	4180	11 EA 4	4	500	500	500	500	4	
58		3 EA 4						6	
59		6						6	
60		8 EA 4						6	

- CONDUCTOR AND CONDUIT SCHEDULE NOTES
- CONDUCTORS SHOWN ARE SHOWN FOR EACH CONDUIT WITH MODIFICATIONS AS NOTED IN NOTE 5. ALL CONDUCTORS SHOWN ARE THWN UNLESS OTHERWISE NOTED.
 - PROVIDE EQUIPMENT GROUND CONDUCTORS PER TABLE 250-122 WHEN CIRCUIT BREAKERS ARE SIZED GREATER THAN AMPERE RATING SHOWN IN TABLE.
 - PROVIDE #10 NEUTRALS FOR MULTIWIRE BRANCH CIRCUITS SERVING COMPUTERS.
 - GROUND (G) CONDUCTOR MAY BE DELETED ON SERVICE ENTRANCE CONDUCTORS.
 - WHEN SYMBOL SUBSCRIPT INDICATES "IG" INCLUDE "IG" OR INSULATED GROUND CONDUCTOR SCHEDULED ALONG WITH GROUND OR EQUIPMENT GROUND CONDUCTOR. WHEN SYMBOL SUBSCRIPT INDICATES "SE" SUBSTITUTE "SE" CONDUCTOR FOR "G" CONDUCTOR SHOWN WHICH IS SIZED FOR THE GROUNDING OF THE SECONDARY OF THE SEPARATELY DERIVED SYSTEMS.
 - RACEWAY ONLY. CONDUCTORS PROVIDED BY UTILITY.

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 2402.00
Construction Documents June 28, 2024

EQUIPMENT
SCHEDULE

EP601

SHEET KEYNOTES	
1	CONTRACTOR TO PROVIDE SLEEVES THROUGH ALL WALLS FOR CABLE PATHWAYS. ALL FIRE-RATED WALLS REQUIRE A FIRE-RATED SLEEVE. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION. ALL SMOKE/NON-RATED WALLS REQUIRE A CONDUIT SLEEVE WITH BUSHINGS AND ARE REQUIRED TO BE SEALED WITH FIRE-RATED CAULK AND PUTTY. CONTRACTOR TO DETERMINE FINAL NUMBER OF SLEEVES FOR PENETRATIONS THROUGH WALLS.


NJRA ARCHITECTS

NJRA Architects, Inc.
 5223 S. Ascension Way, Suite 350
 Murray, Utah 84123
 801.364.9259
 www.njraarchitects.com




SPECTRUM ENGINEERS

324 S. State St., Suite 400
 Salt Lake City, UT 84111
 800-678-7077
 801-328-5151
 fax: 801-328-5155
 www.spectrum-engineers.com



2 TELECOM CABLE RISER DIAGRAM
 SCALE: NTS



1 TELECOM CONDUIT RISER DIAGRAM
 SCALE: NTS

Canyon Surgical Associates
Clinic Remodel
 South Office Tower - Level 6

5171 Cottonwood Street #650
 Murray, Utah 84107


NJRA Project # 24002.00
 Construction Documents June 28, 2024

TELECOM
 RISER
 DIAGRAMS

EP651

C:\Users\baa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanA110.rvt

6/28/2024 10:30:33 AM



1 LEVEL 6 LIGHTING PLAN
SCALE: 1/4" = 1'-0"

GENERAL SHEET NOTES

SHEET KEYNOTES

- CONNECT TO THE EXISTING LIGHTING CIRCUIT THAT PREVIOUSLY FED THIS SPACE.
- CONNECT TO THE EXISTING LIGHTING CIRCUIT AND CONTROLS FEEDING THIS SPACE.

NJRA ARCHITECTS

NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com

SPECTRUM ENGINEERS

324 S. State St., Suite 400
Salt Lake City, UT 84111
801-478-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com


Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 28, 2024

LEVEL 1
LIGHTING
PLAN

EL101



LIGHTING/SPACE CONTROL TYPE SCHEDULE

WIRING LEGEND		APPROVED MANUFACTURERS	LIGHTING CONTROL ID	GENERAL NOTES															
—	LINE VOLTAGE WIRING	1. WATTSTOPPER (BASIS OF DESIGN)	1. # = NUMBER OF ZONES	1. COORDINATE INITIAL PROGRAMMING WITH OWNER AND MODIFY CONTROL TIMES AND OPERATION AS REQUESTED BY OWNER.															
- - -	0-10V WIRING	2. NLIGHT	2. D = DIMMING, S = SWITCHING	2. PROVIDE FINE TUNING PROGRAMMING AND ADJUSTMENTS UPON REQUEST BY OWNER WITHIN FIRST 6 MONTHS AFTER SUBSTANTIAL COMPLETION.															
- · - · -	CATSE CABLING	3. HUBBELL BUILDING AUTOMATION	3. P = DAYLIGHT PHOTOCELL	3. PROVIDE CUSTOMIZED ENGRAVED PERMANENT BUTTON LABELS ON EACH SWITCH, LABEL TO MATCH BUTTON LABEL ID OR AS DIRECTED BY OWNER.															
—	WIRING BY OTHERS	4. GREENGATE	4. L = PLUG LOAD CONTROLLER	4. PART NUMBERS SHOWN ARE BASED ON WATTSTOPPER AS THE BASIS OF DESIGN. ALL APPROVED MANUFACTURERS ARE SUBJECT TO MEETING ALL FUNCTIONS AND CAPABILITIES OF THE BASIS OF DESIGN SYSTEM AND PRODUCTS. FAILURE TO MEET THESE SHALL REQUIRE THE CONTRACTOR TO PROVIDE A SYSTEM THAT DOES AT NOT ADDITIONAL COST.															
○—○	TWP SEGMENT NETWORK CABLING		5. # = INSTANCE	5. REFER TO PLANS FOR LOCATIONS AND QUANTITIES OF DEVICES.															
				6. INSTALL ONE OF EACH CONTROL TYPE WITH PROGRAMMING, ADJUST, AND OBTAIN OWNERS APPROVAL PRIOR TO PROGRAMMING THE REMAINING CONTROLS.															
				7. WIRING MAY VARY BETWEEN MANUFACTURERS. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THE REQUIRED WIRING THAT WILL BOTH MEET THE MANUFACTURERS REQUIREMENTS AND MATCH WITH THE SHOWN SYSTEM.															
				8. PROVIDE COMPLETE SHOP DRAWING SUBMITTALS INCLUDING OCCUPANCY SENSOR LAYOUT AND COVERAGE PATTERNS. PROVIDE ADDITIONAL SENSORS AS REQUIRED FOR 100% COVERAGE OF SPACES WITH OCCUPANCY SENSOR CONTROL.															
ID	DETAIL	LIGHTS ON CONTROL	LIGHTS OFF CONTROL	LIGHTING CONTROL TYPE	DAYLIGHT SENSOR SETTING (FC)	TIME DELAY TO OFF (MIN)	BAS AUX RELAY SIGNAL	PLUG LOAD CONTROLLER	NETWORKED CONTROLS	BUTTON_1	BUTTON_2	BUTTON_3	BUTTON_4	BUTTON_5	BUTTON_6	BUTTON_7	BUTTON_8	BUTTON_9	NOTES
ID1		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	DIMMING 0-10V	-	15	RELAY CLOSED ON OCCUPANCY	-	-	FUNCTION: PRESS TOP-ON, HOLD TOP-RAISE LABEL ID: TOP. "ON/RAISE" BOTTOM "OFF/LOWER"	-	-	-	-	-	-	-	-	
IS3		MANUAL & OCCUPANCY	MANUAL OR OCCUPANCY	ON/OFF	-	15	RELAY CLOSED ON OCCUPANCY	-	-	FUNCTION: PRESS-ON LABEL ID: "ON"	FUNCTION: PRESS-OFF LABEL ID: "OFF"	-	-	-	-	-	-	-	

INTERIOR LIGHTING FIXTURE SCHEDULE

GENERAL NOTES											
1. SUBSTITUTIONS AND/OR EQUAL FIXTURES MUST RECEIVE APPROVAL PRIOR TO BIDDING. THEY MUST BE SUBMITTED TO THE ENGINEER NO LESS THAN 2 WEEKS PRIOR TO BID OPENING. 2. SAMPLES MUST BE PROVIDED FOR ANY AND ALL FIXTURES UPON A/E REQUEST PRIOR TO RELEASING FIXTURES. 3. ALL FIXTURES SHALL BE LISTED AND APPROVED FOR THEIR INTENDED USE AND LOCATION. 4. VERIFY THE PROPER MOUNTING KITS OR ACCESSORIES TO FACILITATE INSTALLATION AS SHOWN AT EACH LOCATION ON THE DRAWINGS. 5. COMPLY WITH THE "INTERIOR LIGHTING" SECTION OF THE SPECIFICATIONS. 6. ALL LIGHT FIXTURES TO BE EITHER "DL" OR "LIGHTING FACTS" LISTED OR TO BE APPROVED BY ARCHITECT/ENGINEER AND OWNER. 7. CONTRACTOR ALLOWANCE PRICES ARE ACCURATE WHEN THIS JOB WAS SPECIFIED. CONTRACTOR AND ELECTRICAL DISTRIBUTOR SHALL VERIFY THIS ALLOWANCE AND REPORT ANY PROBLEMS TO THE ENGINEER BEFORE THE BID. ALLOWANCE PRICE MAY OR MAY NOT INCLUDE LAMP(S) OR FREIGHT AS NOTED, AND DO NOT INCLUDE ANY TAXES.											
ID	DESCRIPTION	SIZE (NOMINAL)	DELIVERED DIRECT LUMENS	DELIVERED INDIRECT LUMENS	COLOR TEMP	CRI	TYPE	VOLTAGE	WATTS	MANUFACTURER (CATALOG SERIES)	
(D6)	DESCRIPTION: 6" ROUND, RECESSED LED DOWNLIGHT, SEMI-SPECULAR REFLECTOR MOUNTING, CEILING, RECESSED FINISH: WHITE TRIM FINISH OPTICS: - EM: -	LENGTH: - WIDTH: - DEPTH: 6" - 6"	1,500		3500K		0-10V DIMMING (1%)	120/277	19	GOTHAM (EVO 35/15 AR LSS MWD MVOLT G21 TRN) HALO (HC815D010HM612835 61MDHW) LIGHTOLIER (GRNP6RDL1583CCZ10U)	
(E1)	DESCRIPTION: EXIT SIGN, EDGE LIT LED ACRYLIC, SINGLE FACE, GREEN LETTERING MOUNTING: UNIVERSAL MOUNTING FINISH: BRUSHED ALUMINUM FINISH OPTICS: - BATTERY PACK EM: -	LENGTH: - WIDTH: - DEPTH: -			GREEN		NO DIMMING	120/277	3	DUAL-LITE (LECDGVA) EVEN-LITE (TEX-AC-G-2M) EMERGENSEE (SEEXLRN)	
(ETG22)	DESCRIPTION: 2' X 2' LED TROFFER, EDGE LIT PANELS, GRID LAY-IN MOUNTING: CEILING, RECESSED FINISH: SCBA OPTICS: - BATTERY PACK EM: -	LENGTH: 2' - 0" WIDTH: 2' - 0" DEPTH: -	3,400		4000K		0-10V DIMMING (1%)	120/277	40	METALUX (22EN-LD2-25-UNV-L835-CD1-U) HE WILLIAMS (AP-22-L34835-DIM1-UMV) LITHONIA (ENVX 2X2 HRCG 4000LM 80 DRI 35K MINH1 ZT MVOLT)	
(TG22)	DESCRIPTION: 2' X 2' LED TROFFER, EDGE LIT PANELS, GRID LAY-IN MOUNTING: CEILING, RECESSED FINISH: SCBA OPTICS: - EM: -	LENGTH: 2' - 0" WIDTH: 2' - 0" DEPTH: -	3,400		4000K		0-10V DIMMING (1%)	120/277	40	METALUX (22EN-LD2-25-UNV-L835-CD1-U) HE WILLIAMS (AP-22-L34835-DIM1-UMV) LITHONIA (ENVX 2X2 HRCG 4000LM 80 DRI 35K MINH1 ZT MVOLT)	
(TG24M)	DESCRIPTION: 2' X 4' LED TROFFER, EDGE LIT PANELS, GRID LAY-IN MOUNTING: CEILING, RECESSED FINISH: SCBA OPTICS: - EM: -	LENGTH: 4' - 0" WIDTH: 2' - 0" DEPTH: -	4,300		4000K		0-10V DIMMING (1%)	120/277	50	METALUX (24EN-LD2-45-UNV-L835-CD1-U) HE WILLIAMS (AP-22-L43835-DIM1-UMV) LITHONIA (ENVX)	

Canyon Surgical Associates
 Clinic Remodel
 South Office Tower - Level 6


5171 Cottonwood Street #650
 Murray, Utah 84107

C:\Users\baaa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central-BrandonA\lta.rvt

6/28/2024 10:30:35 AM

C:\Users\baaa\OneDrive - SPECTRUM ENGINEERS\Documents\240149-Elec-Central_BrendanArla.rvt

6/28/2024 10:30:54 AM




1 LEVEL 6 AUXILIARY PLAN
SCALE: 1/4" = 1'-0"

GENERAL SHEET NOTES

○ SHEET KEYNOTES



NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



SPECTRUM ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Canyon Surgical Associates
Clinic Remodel
South Office Tower - Level 6

5171 Cottonwood Street #650
Murray, Utah 84107

NJRA Project # 24002.00
Construction Documents June 28, 2024

LEVEL 1
AUXILIARY
PLAN

EY101