

Intermountain Health Intermountain Life Flight Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

Construction Documents

IH PROJECT #: 10017913

DESIGN TEAM

ARCHITECT

NJRA Architects, Inc.

5223 South Ascension Way, Suite 350
Murray, Utah 84123
Phone: 801.364.9259

Contacts:

Project Manager: Robert Howell
Email: robhow@njraarchitects.com

MECHANICAL ENGINEER

Resolut Group

181 E 5600 S Suite 200
Murray UT 84124

Phone: 801.530.3148

Contacts:

Project Manager: Jed Lyman
Email: jlyman@resolutgroup.com

ELECTRICAL ENGINEER

Spectrum Engineers

324 South State Street, Suite 400
Salt Lake City, Utah 84111

Phone: 801.328.5151

Contacts:

Project Manager: Jason Worthen
Email: Jason.Worthen@speceng.com

STRUCTURAL ENGINEER


Reaveley Engineers

675 East 500 South, Suite 400
Salt Lake City, Utah 84102

Phone: 801.505.4015

Contacts:

Project Manager: Dorian Adams
Email: dadams@reaveley.com



Intermountain Life Flight Life Flight Simulator

NJRA Project # 25252.00
Construction Documents Dec. 11. 2025


NOTES ON VENDOR SUPPLIED EQUIPMENT INSTALLATION

EQUIPMENT DOCUMENTATION AND LITERATURE FOR THE VARIOUS SIMULATOR EQUIPMENT (MOOG MOTION BASE, LEONARDO FLIGHT SIMULATOR, AND MARSHALL INTEGRATION) HAVE BEEN INCLUDED FOR COORDINATION PURPOSES. INTERMOUNTAIN HEALTH SHALL PAY MOOG, LEONARDO AND MARSHALL FOR THEIR CONSTRUCTION WORK. THE GENERAL CONTRACTOR AND THEIR SUBCONTRACTORS SHALL COORDINATE WITH THE SITE PREPARATION SPECIFICATIONS **INCLUDED IN THE PROJECT MANUAL** AND PROVIDE REQUIRED WORK SCHEDULING AND COORDINATION WITH VENDORS DURING CONSTRUCTION. ANY ITEMS MENTIONED AS, "PROVIDED OTHERS" (OR WHERE A PROVISION IS TO BE SUPPLIED BY THE VENDOR IS NOT EXPLICITLY INDICATED) IN THE VENDORS' LITERATURE SHALL BE PROVIDED BY THE GENERAL CONTRACTOR AND THEIR SUBCONTRACTORS. IF THERE IS ANY CLARIFICATION REQUIRED, CONTRACTORS SHALL CHECK WITH THE A/E DESIGN TEAM DURING THE BIDDING PHASE. ANY WORK REQUIRED BY EQUIPMENT VENDORS, AND LISTED IN VENDORS' DRAWINGS AS "BY OTHERS" THAT IS OMITTED BY THE GENERAL CONTRACTOR AND THEIR SUBCONTRACTORS IN THEIR ORIGINAL BIDS MUST BE PROVIDED AT NO COST TO THE OWNER.

CONTRACTOR SHALL BE RESPONSIBLE FOR DISPOSING OF ANY WASTE OR PACKAGING, IN ACCORDANCE WITH THE SPECIFICATIONS, GENERATED BY THE OWNER'S EQUIPMENT VENDORS AS IT RELATES TO EQUIPMENT PACKAGING AND INSTALLATION UNLESS NOTED OTHERWISE IN THE INDIVIDUAL VENDORS' DRAWINGS. COORDINATE WITH EACH VENDOR FOR PACKAGING TO BE DISPOSED.

Cover Sheet

G001


INTERIM LIFE SAFETY MEASURES

IMPLEMENTATION OF INTERIM LIFE SAFETY MEASURES (ILSM) IS REQUIRED IN OR ADJACENT TO ALL CONSTRUCTION AREAS AND THROUGHOUT BUILDINGS WITH EXISTING LSC DEFICIENCIES. ILSM APPLY TO ALL PERSONNEL, INCLUDING CONSTRUCTION WORKERS, MUST BE IMPLEMENTED UPON PROJECT DEVELOPMENT, AND CONTINUOUSLY ENFORCED THROUGH PROJECT COMPLETION. ILSM ARE CONSTRUCTED WITHIN A SINGLE ENVELOPE IN THE EXISTING HANGAR ENVELOPE, INTEGRATING POWER, COMMUNICATIONS, AND SAFETY SYSTEMS WHILE MAINTAINING EXISTING MEANS OF EGRESS. EXISTING MEANS OF EGRESS AND OCCUPANT LOADS REMAIN UNCHANGED. HEAT PUMPS WILL BE MOUNTED ON THE ROOF OF THE EXISTING HANGAR BUT THE EXTERIOR ENVELOPE OF THE EXISTING HANGAR IS OTHERWISE NOT MODIFIED.

1. ENSURING EXITS PROVIDE FREE AND UNOBSTRUCTED EGRESS. PERSONNEL SHALL RECEIVE TRAINING IF ALTERNATIVE EXITS MUST BE DESIGNATED. BUILDINGS OR AREAS UNDER CONSTRUCTION MUST MAINTAIN ESCAPE FACILITIES FOR CONSTRUCTION WORKERS AT ALL TIMES. MEANS OF EGRESS IN CONSTRUCTION AREAS MUST BE INSPECTED.

2. ENSURING FREE AND UNOBSTRUCTED ACCESS TO EMERGENCY DEPARTMENTS/ SERVICES AND FOR EMERGENCY FORCES.

3. ENSURE FIRE ALARM, DETECTION, AND SUPPRESSION SYSTEMS ARE NOT IMPAIRED. A TEMPORARY, BUT EQUIVALENT, SYSTEM SHALL BE PROVIDED WHEN ANY FIRE SYSTEM IS IMPAIRED. TEMPORARY SYSTEM MUST BE INSPECTED AND TESTED MONTHLY.

4. ENSURING TEMPORARY CONSTRUCTION PARTITIONS ARE SMOKE TIGHT AND BUILT OF NONCOM OR LIMITED COMBUSTIBLE MATERIALS THAT WILL NOT CONTRIBUTE TO THE DEVELOPMENT OR SPREAD OF FIRE.

5. PROVIDING ADDITIONAL FIRE-FIGHTING EQUIPMENT AND USE TRAINING OF PERSONNEL.

6. PROHIBITING SMOKING IN ACCORDANCE WITH MA.1.3.15 AND IN OR ADJACENT TO ALL CONSTRUCTION AREAS.

7. DEVELOPING AND ENFORCING STORAGE, HOUSEKEEPING, AND DEBRIS REMOVAL PRACTICES THAT REDUCE THE FLAMMABLE AND COMBUSTIBLE FIRE LOAD OF THE BUILDING TO THE LOWEST LEVEL NECESSARY FOR DAILY OPERATIONS.

8. CONDUCTING A MINIMUM OF TWO FIRE DRILLS PER SHIFT PER QUARTER.

9. INCREASING HAZARD SURVEILLANCE OF BUILDINGS, GROUNDS, AND EQUIPMENT WITH SPECIAL ATTENTION TO EXCAVATIONS, CONSTRUCTION AREAS CONSTRUCTION STORAGE, AND FIELD OFFICES.

10. TRAINING PERSONNEL WHEN STRUCTURAL OR COMPARTMENT FEATURES OF FIRE SAFETY ARE COMPROMISED.

11. CONDUCTING ORGANIZATION WIDE SAFETY EDUCATION PROGRAMS TO ENSURE AWARENESS OF ANY LSC DEFICIENCIES, CONSTRUCTION HAZARDS, AND THESE ILSM.

PROJECT DESCRIPTION

PROJECT DESCRIPTION: THE PROJECT INVOLVES THE CONSTRUCTION OF A LIFE FLIGHT SIMULATION SPACE FOR INTERMOUNTAIN LIFE FLIGHT LOCATED INSIDE AN EXISTING SECURE AIRCRAFT HANGAR. THE SCOPE INCLUDES TWO SEPARATE SIMULATION ROOMS FOR MEDICAL AIRCRAFT SIMULATION AND A FLIGHT SIMULATOR. BOTH SIMULATION MODULES ARE CONSTRUCTED WITHIN A SINGLE ENVELOPE IN THE EXISTING HANGAR ENVELOPE, INTEGRATING POWER, COMMUNICATIONS, AND SAFETY SYSTEMS WHILE MAINTAINING EXISTING MEANS OF EGRESS. EXISTING MEANS OF EGRESS AND OCCUPANT LOADS REMAIN UNCHANGED. HEAT PUMPS WILL BE MOUNTED ON THE ROOF OF THE EXISTING HANGAR BUT THE EXTERIOR ENVELOPE OF THE EXISTING HANGAR IS OTHERWISE NOT MODIFIED.

VICINITY MAP

DRAWING INDEX
GENERAL

G001 Cover Sheet
G002 General Information
G003 General Information
G004 American National Standard Institute Requirements
G005 General Legend & Notes
G111 Code Compliance Plan Level 1 - Overall

STRUCTURAL

SE001 General Structural Notes
SE002 Legends & Abbreviations
SF101 Floor and Roof Framing Plans
SF102 Structural Framing Elevations
SW501 Typical Cold-Formed Steel Stud Details
SW502 Steel Stud Details
SW503 Steel Stud Roof Details
SW601 Steel Stud Wall and Wood Schedules and Details

ARCHITECTURAL

A113 Floor Plan Level 1 - Overall
A120 Floor Plan Level 2 - Overall
A202 Exterior Elevations - Overall
A351 Wall Sections
A401 Enlarged Views
A402 Enlarged Views
A501A Wall Types
A502A Wall Details
A503A Ceiling Details
A505A Cabinet Legend & Details
A505B Cabinet Details
A505C Cabinet Details
A506A Details
A601A Door Schedule
A603A Finish Schedule & Details

MECHANICAL

M001 HVAC Title Sheet
M113 Mechanical Plan Level 1 - Overall
M401 Enlarged Mechanical Plan
M501 Mechanical Details
M601 Mechanical Schedules

PLUMBING

P001 Plumbing Title Sheet
P113 Plumbing Plan Level 1 - Overall
P401 Enlarged Plumbing Plan

ELECTRICAL

EE001 Electrical Cover Sheet
EE002 Symbols Legend
EE501 Electrical Details
EE701 Typical Mounting Details
EE702 Typical Labeling Details
EP100 Level 1 Overall Power Plan
EP101 Level 1 Power Plan
EP102 Level 2 Power Plan
EP103 Telecom Equipment Rack Elevations
EP104 Telecom Details
EP401 One-Line Diagrams
EP402 Electrical Equipment and Floorbox Schedules
EP450 Telecom Riser Diagrams
EL101 Level 1 Lighting Plan
EY101 Level 1 Auxiliary Plan

APPROVALS

Approvers Name, Title Date

Approvers Name, Title Date

Approvers Name, Title Date

Approvers Name, Title Date

ABBREVIATIONS

&	AND	DWL.	DOWEL	INT.	INTERIOR	P.S.F.	POUNDS PER SQUARE FOOT	V.C.P.	VITREOUS CLAY PIPE
@	AT	DN.	DOWN	INV.	INVERT	R	RADIUS	W	WATER CLOSET
Ø	DIAMETER	D.S.	DOWN SPOUT	J	JANITOR	REC.	RECOMMENDATION	W.C.	WATER CLOSET
(E), EXIST.	EXISTING	D.W.V.	DRAINAGE WASTE VENT	JAN.	JANITOR	REC'D	RECD	W.C.	WATER CLOSET
(N)	NEW	DWG.	DRAWING	JT.	JOINT	REG.	REGISTER	W.R.	WATER RESISTANT
d	PENNY			JST.	JOIST	REG'D	REQUIRED	W.P.	WATERPROOF
#	POUND OR NUMBER	EA.	EACH			P.A.	RETURN AIR	W.H.F.	WELDED WIRE FABRIC
A		E.W.C.	ELEC. WATER COOLER	L	LAMINATED	REV.	REVISION	W.F.	WIDE FLANGE
AC.	ACOUSTIC	EL/ELEC.	ELECTRIC	LAM.	LAMINATED	R.D.	ROOF DRAIN	WD.	WINDOW
ADD.	ADDENDUM	ELEV.	ELEVATION	LDG.	LANDING	RFG.	ROOFING	W/O	WITHOUT
A/C	AIR CONDITIONING	EQ.	EQUAL	LAV.	LAVATORY	RM.	ROOM	WD.	WOOD
ALT.	ALTERNATE	EQUIP.	EQUIPMENT	LT.	LIGHT	RGH.	ROUGH		
AL.	ALUMINUM	EXH.	EXHAUST	L.W.C.	LIGHT WEIGHT CONCRETE	RND.	ROUND		
A.B.	ANCHOR BOLT	EXIST.	EXISTING	LVR.	LOUVER				
ARCH.	ARCHITECT(URAL)	EXJ.	EXPANSION JOINT	M	MACHINE BOLT	SCR.	SCREW		
ASP.	ASPHALT	EXT.	EXTERIOR	M.B.	MACHINE BOLT	SECT.	SECTION		
B		F.	FEET	M.F.R.	MACHINE MANUFACTURER	SEL.	SELECT		
B.SMT.	BASEMENT	F.F.V.	FIELD VERIFY	MATL.	MATERIAL	SHT.	SHEET		
B.M.	BENCHMARK	FIN.	FINISHED(ED)	MAX.	MAXIMUM	SIM.	SIMILAR		
BLKG.	BLOCKING	F.E.	FIRE EXTINGUISHER	MECH.	MECHANICAL	SLDG.	SLIDING		
BD.	BOARD	F.E.C.	FIRE EXTINGUISHER CABINET	MTL.	METAL	SM.	SMOOTH		
B.O.	BOTTOM OF	FIXT.	FIXTURE	MIN.	MINIMUM	SPEC.	SPECIFICATION		
BLDG.	BUILDING	FL.	FLASHING	MLDG.	MOLDING	SPL.	SPLASH		
C		G.	GALVANIZED	MULL.	MULLION	SQ.	SQUARE		
CABT.	CABINET	GALV.	GALVANIZED	N.	NATURAL GRADE	STD.	STANDARD		
C.I.P.	CAST IN PLACE	GA.	GAUGE	N.G.	NATURAL GRADE	STRUCT.	STRUCTURE		
C.B.	CATCH BASIN	G.C.	GENERAL CONTRACTOR	NOM.	NOMINAL	S.A.	SUPPLY AIR		
CLG.	CEILING	G.S.N.	GENERAL STRUCTURAL NOTES	N/A	NOT APPLICABLE	SUSP.	SUSPENDED		
CL.	CENTER LINE	GL.	GLASS	N.I.C.	NOT IN CONTRACT	SW.BD.	SWITCHBOARD		
C.T.	CERAMIC TILE	GD.	GRADE	N.T.S.	NOT TO SCALE	T	TELEPHONE COMPANY		
CH.	CHANNEL	GRL.	GRILLE	O.C.	ON CENTER	T.G.	TEMPERED GLASS		
C.O.	CLEAN OUT	GRD.	GROUND	O.D.	OUTSIDE DIAMETER	T&G.	TEMPERED GLASS		
CLR.	CLEAR	GYP.	GYPSUM	O.R.D.	OVERFLOW DRAIN	T&B	TOP & BOTTOM		
CL.	CLOSET			O.F.S.	OVERFLOW SCUPPER	T.C.	TOP OF CURB		
COL.	COLUMN	HDW.	HARDWARE	O.F.C.I.	OWNER FURNISHED, CONTRACTOR INSTALLED	T.O.D.	TOP OF DECK		
CONC.	CONCRETE	HDWD.	HARDWOOD	O.F.O.I.	OWNER FURNISHED, OWNER INSTALLED	T.O.P.	TOP OF PARAPET		
COND.	CONDITION	HT.	HEIGHT	PT.	PAINT	U.N.O.	UNLESS NOTED OTHERWISE		
CONN.	CONNECTION	H.P.	HIGH POINT	PR.	PAINTED	V	VENT		
CONST.	CONSTRUCTION	H.R.	HORIZONTAL	PNL.	PANEL	V.C.	VENT THROUGH ROOF		
CONT.	CONTINUOUS	H.B.	HOSE BIB	d	PENNY	V.G.	VERTICAL		
CJ	CONTROL JOINT	H.W.	HOT WATER	P.I.	PLASTIC LAMINATE	V.G.	VERTICAL GRAIN		
D.P.	DAMP PROOFING	HR.	HOUR	PL.	PLATE	V.E.	VESTIBULE		
D.B.	DECK BEARING			PLBG.	PLUMBING	V.E.T.	VINYL COMPOSITION TILE		
DIAG.	DIAGONAL	IN.	INCH	P.S.I.	POUND PER SQUARE INCH	V.C.T.	VINYL COMPOSITION TILE		
DIA.	DIAMETER	I.D.	INSIDE DIAMETER						
DIM.	DIMENSION	INSUL.	INSULATION						

DEFERRED SUBMITTALS

THE CONTRACTOR SHALL SUBMIT THE FOLLOWING TO THE BUILDING OFFICIAL FOR REVIEW WITH AN ACCOMPANYING LETTER FROM THE ARCHITECT STATING THAT THE CONTENTS OF THE SUBMITTAL ARE IN CONFORMANCE WITH THE DESIGN WORK RELATED TO THE DEFERRED SUBMITTAL IS NOT TO COMMENCE UNTIL THE BUILDING OFFICIAL HAS APPROVED THE SUBMITTAL.

1. DETAILS AND ENGINEERING CALCULATIONS FOR ALL NONSTRUCTURAL COMPONENTS THAT ARE PERMANENTLY ATTACHED TO STRUCTURES AND THEIR SUPPORTS AND ATTACHMENTS. THESE SHALL BE DESIGNED AND CONSTRUCTED TO RESIST THE EFFECTS OF EARTHQUAKE MOTION IN ACCORDANCE WITH ASCE 7-05, REFERENCE IBC SECTION 1613.1. THIS INCLUDES:
- ELECTRICAL
- MECHANICAL SYSTEMS
- PLUMBING SYSTEMS
- DECORATIVE ARCHITECTURAL COMPONENTS.


2. DETAILS AND ENGINEERING CALCULATIONS FOR THE FIRE SPRINKLER AND FIRE DETECTION SYSTEMS, WHICH ARE TO BE DESIGN-BUILD BY THE CONTRACTOR TO COMPLY WITH NFPA 13 AND SHALL INCLUDE:
- AUTOMATIC FIRE SPRINKLER PLANS
- HOOD FIRE SUPPRESSION
- CLASS K FIRE EXTINGUISHER LOCATION(S)

3. STRUCTURAL TRUSS AND JOIST DESIGNS (AS LISTED IN THE STRUCTURAL DRAWINGS).

SPECIAL INSPECTIONS

DEFINITIONS


- GENERAL: BASIC CONTRACT DEFINITIONS ARE INCLUDED IN THE CONDITIONS OF THE CONTRACT.
- "APPROVED": WHEN USED TO CONVEY ARCHITECT'S ACTION ON CONTRACTOR'S SUBMITTALS, APPLICATIONS AND REQUESTS, "APPROVED" IS LIMITED TO ARCHITECT'S DUTIES AND RESPONSIBILITIES AS STATED IN THE CONDITIONS OF THE CONTRACT.
- "DIRECTED": A COMMAND OR INSTRUCTION BY ARCHITECT. OTHER TERMS INCLUDING "REQUESTED," "AUTHORIZED," "SELECTED," "REQUIRED" AND "PERMITTED" HAVE THE SAME MEANING AS "DIRECTED."
- "INDICATED": REQUIREMENTS EXPRESSED BY GRAPHIC REPRESENTATIONS OR IN WRITTEN FORM ON DRAWINGS, IN SPECIFICATIONS, AND IN OTHER CONTRACT DOCUMENTS. OTHER TERMS INCLUDING "SHOWN," "NOTED," "SCHEDULED," AND "SPECIFIED" HAVE THE SAME MEANING AS "INDICATED."
- "REGULATIONS": LAWS, ORDINANCES, STATUTES, AND LAWFUL ORDERS ISSUED BY AUTHORITIES OF THE STATE, COUNTY, AND MUNICIPAL GOVERNMENTS AND AGREEMENTS WITHIN THE CONSTRUCTION INDUSTRY THAT CONTROL PERFORMANCE OF THE WORK.
- "FURNISH": SUPPLY AND DELIVER TO PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS.
- "INSTALL": UNLOAD, TEMPORARILY STORE, UNPACK, ASSEMBLE, ERECT, PLACE, ANCHOR, APPLY, WIRE TO DIMENSIONS, FINISH, CURE, PROTECT, CLEAN, AND SIMILAR OPERATIONS AT THE PROJECT SITE.
- "PROTECT": DRESS, DRESS AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE.
- "PROJECT SITE": SPACE AVAILABLE FOR PERFORMING CONSTRUCTION ACTIVITIES. THE EXTENT OF PROJECT SITE IS SHOWN ON DRAWINGS AND MAY OR MAY NOT BE IDENTICAL WITH THE DESCRIPTION OF THE LAND ON WHICH PROJECT IS TO BE BUILT.




1 Typical Mounting Heights


SCALE: 3/8" = 1'-0"

LEGEND - MATERIALS




GENERAL INFORMATION SYMBOLS & TAGS





DOORS AND DOORWAYS



MANEUVERING CLEARANCE AT SWINGING DOORS




FIG. 404.2.4.1




FIG. 404.2.4.1




FIG. 404.2.4.1

FIG. 404.2.4

TWO DOORS IN A SERIES




FIG. 404.2.4

MANEUVERING CLEARANCE AT SLIDING AND FOLDING DOORS




FIG. 404.2.4



FIG. 404.2.4



FIG. 404.2.4

CLEAR FLOOR SPACE




FIG. 304.3

SIZE OF WHEELCHAIR TURNING SPACE




FIG. 405.5

POSITION OF CLEAR FLOOR OR GROUND SPACE




FIG. 305.7

MANEUVERING CLEARANCE IN AN ALCOVE




FIG. 306.3

KNEE CLEARANCE

FIG. 306.2

TOE CLEARANCE

FIG. 307.4

REDUCED VERTICAL CLEARANCE

GENERAL SITE AND BUILDING ELEMENTS




FIG. 503.3

PASSENGER LOADING ZONE ACCESS AISLE




FIG. 502.2/502.3

VEHICLE PARKING SPACE/PARKING SPACE ACCESS AISLE




FIG. 504.5

STAIR NOSINGS




FIG. 505.4

HANDRAIL HEIGHT



FIG. 505.5

HANDRAIL CLEARANCE




FIG. 505.10.1

TOP AND BOTTOM HANDRAIL EXTENSIONS AT RAMPS




FIG. 505.10.2

BOTTOM HANDRAIL EXTENSIONS AT STAIRS




FIG. 505.10.2

TOP HANDRAIL EXTENSIONS AT STAIRS



FIG. 504.2

TREADS AND RISERS FOR ACCESSIBLE STAIRWAYS

COMMUNICATION ELEMENTS AND FEATURES




FIG. 702.3.5.1

APPLIANCE SPACING IN CORRIDORS




FIG. 702.3.3.1

LOCATION OF WALL-MOUNTED APPLIANCES




FIG. 702.3.3.2

LOCATION OF CEILING-MOUNTED APPLIANCES




FIG. 702.3.6.2

APPLIANCE LOCATION IN SLEEPING ROOMS




FIG. 702.3.8

MOUNTING LOCATION AT DOORS

BUILDING BLOCKS




FIG. 303.2

VERTICAL CHANGES IN LEVEL

FIG. 303.3

LIMITS OF PROTRUDING OBJECTS




FIG. 307.3

POST-MOUNTED PROTRUDING OBJECTS

PLUMBING ELEMENTS AND FACILITIES




FIG. 402.5

DRINKING FOUNTAIN SPUT LOCATION




FIG. 404.2/404.3.1

WATER CLOSET LOCATION/SIZE CLEARANCE




FIG. 604.2/604.5.1

HEIGHT OF WATER CLOSET/SIDE WALL GRAB BAR FOR WATER CLOSET




FIG. 604.5.2

REAR WALL GRAB BAR FOR WATER CLOSET




FIG. 604.7

DISPENSER LOCATION




FIG. 604.8.1.1

WHEELCHAIR ACCESSIBLE TOILET COMPARTMENTS




FIG. 604.8.3




FIG. 608.3.2




FIG. 606.3

HEIGHT OF LAVATORIES AND SINKS

ACCESSIBLE ROUTES




FIG. 403.5

CLEAR WIDTH OF AN ACCESSIBLE ROUTE




FIG. 403.5.1

CLEAR WIDTH OF DOORWAYS




FIG. 404.2.3

RAMP LANDINGS




FIG. 405.7

RAMP EDGE PROTECTION




FIG. 406.3

COUNTER SLOPE OF SURFACES ADJACENT TO CURB RAMPS




FIG. 406.12

ISLANDS




FIG. 406.4

SIDES OF CURB RAMPS





FIG. 406.11

DIAGONAL CURB RAMPS




FIG. 407.2.3.2.1


HEIGHT OF ELEVATOR VISIBLE SIGNALS




LEGEND - DEMOLITION FLOOR PLAN




LEGEND - FLOOR & DIMENSION PLANS



LEGEND - REFLECTED CEILING PLAN



LEGEND - ROOF PLAN



GENERAL NOTES

- A. STRUCTURAL, MECHANICAL, AND ELECTRICAL DRAWINGS (IF PRESENT) ARE SUPPLEMENTAL TO THE ARCHITECTURAL DRAWINGS. THE CONTRACTOR IS RESPONSIBLE FOR THE GENERAL CONSTRUCTION TO COMPLY WITH THE ARCHITECTURAL DRAWINGS BEFORE THE INSTALLATION OF MECHANICAL OR ELECTRICAL CONSTRUCTION. ANY DISCREPANCIES BETWEEN THE ARCHITECTURAL AND CONSULTING ENGINEERS DRAWINGS SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION FOR CLARIFICATION. ANY CONSTRUCTION INSTALLED IN CONFLICT WITH THE ARCHITECTURAL DRAWINGS SHALL BE REMOVED BY THE CONTRACTOR AT HIS/HER OWN EXPENSE AND AT NO EXPENSE TO THE OWNER OR ARCHITECT.
- B. ALL WORK SHALL COMPLY WITH THE CURRENT ADA ACCESSIBILITY GUIDELINES (AMERICANS WITH DISABILITIES ACT).
- C. REFER TO THE CODE COMPLIANCE PLAN FOR APPLICABLE CODE GOVERNING THIS WORK. CODE REQUIREMENTS AND REGULATIONS SHALL BE CONSIDERED AS MINIMUM REQUIREMENTS. DOCUMENTS GOVERNING THE (IF APPLICABLE) CODE AND REGULATION REQUIREMENTS CONTRACT DOCUMENTS SHALL TAKE PRECEDENCE. IF CONFLICT EXIST, THE MORE STRINGENT SHALL APPLY. COMPLY WITH REQUIREMENTS OF THE ADOPTED EDITIONS OF THE INTERNATIONAL CODE COUNCIL CODES, THE CODES AND STANDARDS REFERENCED WITHIN THE ICC CODES AND THE AMERICAN NATIONAL STANDARDS (ANSI).
- D. THE CONTRACTOR SHALL PROVIDE ADEQUATE BARRICADES AND PROTECTIVE DEVICES SEPARATING CONSTRUCTION AREAS. TEMPORARY PASSAGES SHALL BE PROVIDED AS REQUIRED, PRIOR TO DELIVERY OF MATERIALS TO CONSTRUCTION ZONE AND REMOVAL OF WASTE FROM SITE. THE CONTRACTOR SHALL CHECK WITH THE OWNER FOR APPROVAL.
- E. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROPER LOCATION AND SIZE OF OPENINGS FOR ALL TRADES AND SHALL COORDINATE ALL CONSTRUCTION AS INDICATED BY THE CONTRACT DOCUMENTS, INCLUDING SHOP DRAWINGS REVIEWED BY THE ARCHITECT.
- F. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO COMMENCEMENT OF WORK.
- G. FOR ALL TRADES WORK AS OCCURS, CONTRACTOR SHALL COORDINATE WITH THE OWNER AND MANUFACTURERS TO ACCOMPLISH THE WORK IN THE MINIMUM OF INTERRUPTION TO NORMAL BUILDING PROCEDURES. SYSTEM SHUTDOWNS OF HVAC, PLUMBING, ELECTRICAL, AND NOISY CONSTRUCTION INCLUDING ROTO HAMMER, SAW CUTTING, CONCRETE ANCHORS, ETC. SHALL BE COORDINATED WITH THE OWNER AT LEAST 72 HOURS PRIOR TO COMMENCEMENT.
- H. THE CONTRACTOR SHALL NOT REMOVE THE EXISTING PLASTER BOARD OF NEW CONSTRUCTION OR STRUCTURAL WALL UNLESS NOTED OTHERWISE.
- I. ALL DRAWINGS, THOUGH NOTED TO SCALE ARE FOR ILLUSTRATION ONLY. THE CONTRACTOR SHALL NOT SCALE DRAWINGS.
- J. WHEN A DETAIL IS IDENTIFIED AS TYPICAL, THE CONTRACTOR IS TO APPLY THIS DETAIL IN ESTIMATING AND CONSTRUCTION TO EVERY LIKE CONDITION WHETHER OR NOT THE REQUIREMENT IS NOTED.
- K. DRAWINGS HAVE BEEN DETAILED IN COMPLIANCE WITH ILL LISTING REQUIREMENTS AND IBC REPORTS FOR THE MATERIALS SPECIFIED. IF AN ALTERNATE OR SUBSTITUTED MATERIAL IS ACCEPTED AS AN EQUAL BY THE GENERAL CONTRACTOR, HE/SHE WILL ASSUME THE RESPONSIBILITY FOR WHATEVER CONSTRUCTION MODIFICATION AND/OR ADDITIONAL COSTS ARE REQUIRED.
- L. ALL EXISTING FIRE PROOFING MATERIALS MAY NOT BE STORED IN THE CORRIDORS AT ANY TIME. BLOCKAGE OF ANY REQUIRED EXIT IS PROHIBITED.
- M. ALL PENETRATIONS INTO SOUND OR FIRE RATED PARTITIONS, FLOOR OR CEILING ASSEMBLIES SHALL BE SEALED WITH APPROVED PERMANENT RESILIENT SEALANT. REFER TO IBC CURRENT VERSION FOR REQUIREMENTS FOR OPENINGS IN FIRE RATED WALLS. FOR OPENINGS LESS THAN 12" SQUARE INCORPORATE SPAN BEVELS BETWEEN THE WALL AND ALLOW PENETRATION TO MOVE FREELY TO PREVENT THAWING OUT. NOT FLAME OR GASES, ELECTRICAL DEVICES, RECESSED CABINETS, ETC. SHALL BE SEALED, LINER, INSULATED OR OTHERWISE TREATED TO MAINTAIN THE INTEGRITY OF THE ASSEMBLY. SEE PENETRATION DETAILS.
- N. ABBREVIATIONS THROUGHOUT THE PLAN ARE THOSE IN COMMON USE. THE ARCHITECT IS NOT RESPONSIBLE FOR THE MEANING OF THESE ABBREVIATIONS.
- O. THE CONTRACTOR SHALL VERIFY SIZES AND LOCATIONS OF WATER AND DRAIN INSTALLATIONS AND OTHER REQUIRED SERVICES WITH EQUIPMENT MANUFACTURERS.
- P. MAINTAIN ALL EXISTING SPRAY-APPLIED FIRE PROOFING ON STEEL STRUCTURAL MEMBERS. WHERE EXISTING FIRE PROOFING IS REMOVED FOR INSTALLATION OF NEW BEAMS, UNITS, ETC. THE CONTRACTOR SHALL PATCH AGAIN WITH EQUIVALENT FIRE PROOFING MATERIAL TO MATCH ADJACENT EXISTING MATERIAL.
- Q. ALL WOOD CANTS, NAILERS, CURBS, ETC. THROUGHOUT JOB SHALL BE FIRE RETARDANT PRESSURE-TREATED, AS PER I.B.C. CURRENT VERSION. SEE RELEVANT DETAILS.
- R. CONTRACTOR SHALL REFER TO THE PROJECT MANUAL FOR A COMPLETE LIST OF GENERAL CONDITIONS, SPECIAL CONDITIONS AND OTHER NOTES.

GENERAL NOTES - DOOR SCHEDULE

- A. SEE PROJECT MANUAL FOR DOOR SCHEDULE.
- B. SUB-CONTRACTOR UNDER SECTION ALUMINUM ENTRANCES AND STOREFRONT SHALL PROVIDE ALL THE DOOR HARDWARE FOR ALL ALUMINUM DOORS. SEE DOOR SCHEDULE FOR ALUMINUM DOORS AND THE REQUIRED HARDWARE.
- C. SUB-CONTRACTOR UNDER SECTION DOOR HARDWARE, SHALL PROVIDE ALL THE DOOR HARDWARE FOR ALL THE WOOD AND HOLLOW METAL DOORS. SEE DOOR SCHEDULE FOR WOOD AND HOLLOW METAL DOORS AND THE REQUIRED HARDWARE.
- D. ALL EXTERIOR DOORS SHALL BE INSULATED.
- E. FIELD VERIFY WINDOW AND DOOR FRAME OPENING SIZES BEFORE FRAME INSTALLATION. OVERALL DIMENSIONS INDICATED FOR EACH FRAME TYPE ARE ROUGH OPENING SIZES IN WALLS. CONTRACTOR SHALL ADJUST INNER DIMENSIONS AS REQUIRED TO MAKE DOORS AND WINDOWS WORK.
- F. ELECTRICAL DRAWDOWNS AS WELL AS CARD READERS AND ALARM SYSTEMS AS PART OF THE DOOR ACTUATION ARE INCLUDED AS PART OF THE ELECTRICAL PLANS AND THE HARDWARE GROUPS. GENERAL CONTRACTOR IS RESPONSIBLE TO COORDINATE LOCATIONS OF CARD READERS ETC. SHOWN ON ARCHITECTURAL AND ELECTRICAL DRAWINGS WITH ALL TRADES INVOLVED.
- G. COORDINATE DOORS & GATES OUTSIDE BUILDING WITH SITE PLAN.

GENERAL NOTES - EXTERIOR ELEVATIONS

- A. SEE WINDOW SCHEDULE FOR WINDOW OPENINGS AND SILL HEIGHT. SEE DOOR SCHEDULE FOR DOOR OPENING SIZE. SEE LEGEND FOR BRICK VENEER TYPE.
- B. NOT ALL MECHANICAL GRILLES ARE SHOWN ON THESE ELEVATIONS. COORDINATE ALL GRILLE LOCATIONS WITH MECHANICAL DRAWINGS.
- C. ALL EXTERIOR WALL FINISHES ARE TO BE 6" ABOVE FINISH GRADE TYPICAL. SEE WALL SECTIONS.
- D. ALL FINISHES TO BE INSTALLED PER MANUFACTURER RECOMMENDATIONS AND PER SPECIFICATION SECTION IN THE PROJECT MANUAL.

GENERAL NOTES - BUILDING SECTIONS

- A. BUILDING SECTIONS INDICATE THE RELATIONSHIP BETWEEN THE DIFFERENT ROOMS AND THE EXTERIOR. THE INTENT IS TO ILLUSTRATE THE CONCRETE FLOOR SLAB ON GRADE, THE FLOOR TO FLOOR HEIGHTS, SLOPES, EXTENT OF REQUIRED REINFORCEMENT, UNDERWALL FOOTINGS, CONCRETE SLAB ON GRADE, ETC. REFER TO RELEVANT WALL SECTIONS FOR DETAILED DESCRIPTION OF WALL AND ROOF CONSTRUCTION.
- B. SEE CIVIL DRAWINGS FOR BUILDING FINISHED FLOOR ELEVATION AND HOW REFERENCE ELEVATION OF 100'-0" RELATED TO THE EXISTING CONTOUR LINES AND SPOT ELEVATIONS. SOIL CUT AND FILL REQUIREMENTS SHALL BE DETERMINED BASED ON THE SITE EXISTING CONTOUR LINES AND PROPOSED NEW CONTOUR LINES. SEE GEOTECHNICAL STUDY FOR SOIL COMPACTION AND EXTENT OF STRUCTURAL FIL REQUIREMENTS.

GENERAL NOTES - FLOOR & DIM. PLANS

- A. REFER TO THE CODE COMPLIANCE PLANS FOR INDICATION OF FIRE RATED WALLS.
- B. AT LOCATIONS WITHOUT CEILINGS (ROOM IS OPEN TO STRUCTURE ABOVE), EXTEND ALL CEILINGS, SOFFITS, AND HEADERS (INCLUDING ALL STUD FRAMING, GYPSUM BOARD INSULATION & CMU, WHERE APPLICABLE) TO THE METAL ROOF DECK ABOVE.
- C. WHEN FLOOR HEIGHT VARIES IN A ROOM, THE CEILING HEIGHT SHOWN IS THE HEIGHT ABOVE THE FLOOR AT THE ENTRY. UNO.
- D. SEE INTERIOR ELEVATIONS FOR TOILET AND BATHROOM ACCESSORIES (GRAB BARS, DRAINS, ETC).
- E. AT ALL VERTICAL EDGES OF INTERIOR CMU WALLS THAT ARE VISIBLE, USE BULLNOSE CMU BLOCKS FROM FINISHED FLOOR ELEVATION TO A HEIGHT OF 7'-4".
- F. FOR CLARITY SAME DIMENSIONS ARE NOT SHOWN AT THE FOLLOWING LOCATIONS:
 - a. WHERE THE FACE OF WALL COINCIDES WITH THE MAIN GRID LINE OR 4'-0" X 4'-0" SUBGRID.
 - b. WHERE THE CENTER OF WALL COINCIDES WITH THE MAIN GRID LINE OR 4'-0" X 4'-0" SUBGRID.
- G. VERIFY WITH ARCHITECT FOR DIMENSIONS NOT SHOWN.
- H. SEE STRUCTURAL DRAWINGS FOR CMU WALLS, MASONRY COLUMNS, AND MASONRY BEAMS. SEE BUILDING EXTERIOR ELEVATIONS FOR VENEER TYPES. SEE FINISH SCHEDULE FOR CMU THAT IS HONED, SCORED, SEALED, PAINTED, ETC.
- I. SEE CIV. FOOD SERVICE, PLUMBING, AND MECHANICAL DRAWINGS FOR FLOOR SINK, PLUG GRILLS, AND OPENINGS IN FLOOR SLABS AND ROOFS FOR DUCTWORK, ETC.
- J. SEE DOOR AND WINDOW SCHEDULE FOR THE REQUIRED DOOR AND WINDOW OPENING SIZES.
- K. SEE FINISH SCHEDULE AND STRUCTURAL DRAWINGS AND PROVIDE RECESS IN CONCRETE FLOOR SLAB AS REQUIRED TO ACCOMMODATE FLOOR FINISHES.
- L. SEE CIV. CONCRETE DRAWINGS FOR CONCRETE FLOOR SLAB FINISHES. FOR A THICK SET MORTAR FOR CERAMIC TILE FINISH, SLOPE SHALL BE AT 1/8" PER FOOT TOWARDS THE FLOOR DRAIN. CONCRETE FLOOR SLAB, THAT IS NOT ON GRADE, NEED NOT BE RECESSED. IN SUCH LOCATION, USE THIN SET MORTAR FOR CERAMIC TILE FINISH WITH A 1/8" SLOPE TOWARDS DRAINS.
- M. ALL FLOOR PLATES, PIPES, ETC. SHALL PASS THROUGH FIRE RATED BARRIER WALLS. SHALL BE SEALED COMPLETELY WITH FIRE RATED SEALANTS, FILL GAP BETWEEN FLUTES OF THE METAL DECK AND METAL TRACK TOP RUNNER WITH FIRE RATED SEALANTS. SEAL TIGHTLY AROUND PIPES, CONDUITS, DUCTS, ETC. THAT PENETRATES THE FIRE BARRIER WALL WITH FIRE RATED SEALANTS. APPLY SEALANT AS PER MANUFACTURER'S RECOMMENDATIONS. PROVIDE RECESS IN CONCRETE FLOOR SLAB AS REQUIRED INSTALLED AROUND PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE FIRE WALL. SEE MECHANICAL DRAWINGS FOR FIRE AND SMOKE DAMPERS.
- N. WALL CABINETS HAVE A DEPTH OF 1'-3" UNLESS NOTED OTHERWISE.
- O. ALL MASONRY MORTAR JOINTS LOCATED INSIDE THE BUILDING SHALL BE TOOLED JOINTS. UNLESS NOTED OTHERWISE. MASONRY JOINTS ON THE BUILDING EXTERIOR SIDE SHALL BE RAKE JOINTS. APPLY SEALANT AS INDICATED IN EXTERIOR ELEVATIONS.
- P. SEE CIV. FLOOR PLAN SHEET FOR ANGLES, PIVOT POINT AND DIMENSIONS BETWEEN GRID LINES.
- Q. SEE CODE COMPLIANCE FLOOR PLANS FOR LOCATION OF FIRE BARRIER, NON FLAMMABLE, ETC.
- R. SEE ENLARGED FLOOR PLANS FOR ADDITIONAL DIMENSIONS.

GENERAL NOTES - ROOF PLAN

- A. BUILDING COMPONENTS (ROOF DRAINS, HATCH, ETC.) ARE DRAWN AT 1/4" = 1'-0" SCALE. COMPONENTS SHALL APPEAR HALF THE SIZE (SMALLER) ON PLANS DRAWN AT 1/8" = 1'-0" SCALE.

GENERAL NOTES - ROOF PLAN





- A. PROVIDE CRICKETS ON THE HIGH SIDE OF ROOF AT ALL CURB LOCATIONS FOR MECHANICAL EQUIPMENT, SKYLIGHT, ROOF HATCH, ETC. WHETHER INDICATED ON THE ROOF PLAN OR NOT.
- B. PROVIDE WEATHERHEAD (GOOSENECK 2" CONDUIT) WHERE CONDUCTORS PENETRATE ROOF FOR DISCONNECT SWITCHES, POWER OUTLETS, ETC. SECURE GOOSENECK TO STRUCTURE BELOW.
- C. PROVIDE ROOF ACCESS POINTS FOR MOUNTING MECHANICAL EQUIPMENT TO AND FROM ROOF HATCHES AND OTHER ROOF ACCESS POINTS, AND AROUND MECHANICAL EQUIPMENT REQUIRING PERIODIC MAINTENANCE.

GENERAL NOTES - WALL SECTIONS

- A. ALL EXTERIOR WALL FINISHES ARE TO BE 6" ABOVE FINISH GRADE, TYPICAL.
- B. SEE WINDOW SCHEDULE FOR WINDOW OPENINGS AND SILL HEIGHT (UNLESS NOTED ON THE EXTERIOR ELEVATIONS). SEE DOOR SCHEDULE FOR DOOR OPENING SIZES.
- C. ALL FINISHES TO BE INSTALLED PER MANUFACTURER RECOMMENDATIONS AND PER SPECIFICATION SECTION IN THE PROJECT MANUAL.
- D. SEE FINISH FLOOR PLANS FOR AREAS WHERE HONED CMU BLOCKS ARE INDICATED. AT THESE AREAS, THE CONTRACTOR HAS THE OPTION OF USING A REGULAR BLOCK IN CONCEALED AREAS AND CEILING SPACES THAT ARE NOT VISIBLE.
- E. SPACING BETWEEN STRUCTURAL MEMBERS SHALL FOLLOW INDICATIONS GIVEN ON STRUCTURAL PLANS (TYPICAL).
- F. FIRE PROTECTION SYSTEM ASSEMBLIES, ELEMENTS, AND MEMBERS SHALL COMPLY WITH ALL THE CODE REQUIREMENTS, TYPICAL. REFER TO CODE COMPLIANCE PLANS.
- G. WOOD MATERIAL UNDER TYPE IIB CONSTRUCTION SHALL BE FIRE-RETARDANT, PRESSURE-TREATED, TYPICAL, UNG.
- H. ALL INTERIOR WALLS SHALL BE BUILT FOLLOWING WALL TYPE DETAILS, TYPICAL.
- I. IN ROOMS/AREAS WHERE HONED, SCORED OR COLORED CMU, BLOCKS ARE INDICATED FOR WALLS IN THE FINISH SCHEDULE, CONTRACTOR HAS THE OPTION OF USING REGULAR BLOCKS EXCEPT WHERE HONED CMU BLOCKS ARE REQUIRED. IN THESE AREAS, THE CONTRACTOR HAS THE OPTION OF USING A REGULAR BLOCK IN CONCEALED AREAS AND CEILING SPACES THAT ARE NOT VISIBLE. THIS DOES NOT APPLY TO AREAS THAT CAN CHANGE OVER THE LIFE OF THE BUILDING SUCH AS WALL LOCATED BEHIND CABINETS, ARTWORK, WHITE BOARD, TACK BOARD, ETC. WHEN OTHER BLOCKS ARE USED, THE STRUCTURAL INTEGRITY OF THE BLOCK SHALL REMAIN THE SAME AS BLOCK INDICATED IN STRUCTURAL DRAWINGS AND SPECIFICATION SECTION IN THE PROJECT MANUAL.
- J. AT INTERIOR MASONRY WALL OUTSIDE CORNERS, PROVIDE BULL NOSE BLOCK.
- K. CORE DRILLING WALLS AND SLABS: CONTRACTOR SHALL USE GROUND PENETRATING RADAR OR OTHER APPROVED METHOD TO SCAN CONCRETE OVER METAL DECK, CONCRETE SUSPENDED SLABS, MASONRY WALLS, AND CONCRETE WALLS TO LOCATE REINFORCING BARS AND CONDUITS. HOLLOW CORE WALLS ARE NOT REINFORCED. ALL OPENINGS AND GROUPS OF OPENINGS SHALL BE REINFORCED AS SHOWN ON THE STRUCTURAL DRAWINGS. OPENINGS NOT SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER PRIOR TO DRILLING.
- L. FOR ALL CABINETS PROVIDE BACKING IN WALL AS PER DETAIL A.4.505B.

GENERAL NOTES - INTERIOR ELEVATIONS

- A. PROVIDE LOCKS FOR CABINETS AS INDICATED ON THE CABINET LEGEND ON SHEET A.505A AND IF INDICATED ON INTERIOR ELEVATIONS.
- B. IN ROOMS WHERE CABINETS ARE REQUIRED TO BE LOCKED, PROVIDE LOCKS OPERATED WITH KEYS.
- C. FOR TYPICAL MOUNTING HEIGHTS, SEE SHEET G.003. FOLLOW THE HEIGHT UNLESS NOTED OTHERWISE. IN INTERIOR ELEVATIONS, VERIFY WITH ARCHITECT FOR ITEMS NOT INDICATED.
- D. CONTRACTOR SHALL VERIFY WITH OWNER FOR OWNERSHIP OF CONTRACTOR INSTALLED ITEMS AND PROVIDE BACKING IN WALL AS REQUIRED. INSTALLATION OF INTERIOR DOORS, DOOR SWINGS, DOOR SWINGS AND DOOR SWINGS AND DOOR SWINGS AS SHOWN ON THE INTERIOR ELEVATIONS OF EACH ROOM, WHERE MULTIPLE FINISHES ARE REQUIRED FOR CABINETS, WALLS, ETC. IN THE ROOM, EACH FINISH IS INDICATED SEPARATELY. CONTACT ARCHITECT FOR REQUIRED CLARIFICATIONS.
- E. CONTRACTOR SHALL PROVIDE FILLER PANELS (PLASTIC LAMINATE HAPPED OVER 5/8" PARTICLE BOARD) WHEREVER GAP OCCURS BETWEEN CABINETS AND WALL. G. SEE FINISH FLOOR PLANS AND FINISH SCHEDULE A.603A FOR WALL, CABINET AND COUNTERTOP FINISHES.
- H. SEE SHEET A.605A FOR CABINET LEGEND. TYPE B1, W, T, ETC. UNLESS NOTED OTHERWISE, ALL CABINETS ARE TO BE COUNTERTOP MOUNTED. COUNTERTOP MOUNTED CABINETS ARE NOT SHOWN ON THE INTERIOR ELEVATIONS OF THE SAME PLANS (PL.2, PL.3, ETC.) AS INDICATED ON THE INTERIOR ELEVATION OF EACH ROOM, WHERE MULTIPLE FINISHES ARE REQUIRED FOR CABINETS, WALLS, ETC. IN THE ROOM, EACH FINISH IS INDICATED SEPARATELY. CONTACT ARCHITECT FOR REQUIRED CLARIFICATIONS.
- I. COUNTERTOPS ARE TO BE CALLED SUPPORTED BY WALLS AND BASE CABINETS. IN PLACES WHERE COUNTERTOP SPANS EXCEEDS 4', OTHER SUPPORTS SHALL BE PROVIDED AS INDICATED IN DETAILS A.4.505B, AND A.5.4.505B.
- J. AS INDICATED ON INTERIOR ELEVATIONS, WALL CABINETS AT CERTAIN LOCATIONS MAY REQUIRE A VERTICAL OR A SLOPED FASCIA PANEL.
- K. AN ENLARGED FLOOR PLAN HAS BEEN INCLUDED ALONG WITH INTERIOR ELEVATIONS FOR ROOMS THAT ARE COMPLEX IN DESIGN, SUCH AS BATHS AND KITCHENS. AREAS THAT ARE COMPLEX IN DESIGN, SUCH AS BATHS AND KITCHENS, ARE NOT SHOWN ON THE FLOOR PLANS. STARTING WITH SHEET A.251, ENLARGED FLOOR PLANS ARE NOT SHOWN FOR ROOMS THAT ARE SIMPLE IN DESIGN. INTERIOR ELEVATIONS OF SUCH SIMPLE ROOMS ARE INDICATED ON THE A.250 SERIES SHEETS (STARTING WITH SHEET A.251).


CODE REVIEW

International Building Code (IBC)	2021
International Existing Building Code (IEBC)	2021
International Fire Code	2021
International Plumbing Code (IPC)	2021
National Electric Code (NEC)	2020
NFPA 101 Life Safety Code	2018
ANSI ICC.A11.1	2017
ADA Standard for Accessible Design	2010
Guidelines for Design & Construction of Hospital and Healthcare Facilities	2010

Existing Hangar

Actual Stories: 1 (Hangar)
 Occupancy: S-1
 Construction Type: Non Combustible
 Fireproofing: Yes
 Automatically Sprinkled: Yes

Allowable Area
 For S-1 Occupancy & Type V-B Const.: 9000 sq. ft. (Table 506.2)
 Area increase due to frontage: N/A
 Total allowable area per floor: 9000 sq. ft. (Table 506.2)
 Project Remodel Area: 1,780 sq. ft.

Allowable Stories
 For S-1 Occupancy & Type V-B Const.: 1 story (Table 504.3)
 Actual Stories: 1 above grade

Common path of egress travel in exit access areas
 For S-1 Occupancy: 75 feet (1006.3.4[2])

Exit access travel distance
 For S-1 Occupancy: 230 feet (with sprinkler system) (Table 1017.2)

Corridor Width
 For S-1 Occupancy: 44 inches (1020.3)

Construction Type: Type V-B

Fire resistance rating requirements for building elements (Table 601)
 Structural frame - N/A
 Exterior Bearing walls - N/A
 Interior Non-Bearing walls - N/A
 Floor Construction - N/A
 Roof Construction - N/A

Sprinkler System
 Entire Building is fully equipped with automatic sprinkler system.


Occupant Load (Table 1004.1.1)
 Business- 150 sq.ft. per person
 Total Occupant Load = 12 occupants

Egress width calculation:

KEYED NOTE

SYMBOL	DESCRIPTION	FIRE RESISTANCE RATING	DOOR FIRE RATING	WINDOW FIRE RATING
● - - - - - >	COMMON PATH OF TRAVEL	N/A	N/A	N/A
● - - - - - >	TRAVEL DISTANCE	N/A	N/A	N/A
ROOM NAME SF. ROOM # O.L. #	OCCUPANT LOAD	N/A	N/A	N/A
--- SP ---	SMOKE PARTITION WALL	0 HOUR	SMOKE	SMOKE
--- SB ---	SMOKE BARRIER WALL	1 HOUR	1/3 HOUR	1/3 HOUR
◆ ◆ ◆ ◆ ◆ ◆ ◆	1 HOUR FIRE RATED WALL	1 HOUR	3/4 HOUR	3/4 HOUR
◆ ◆ ◆ ◆ ◆ ◆ ◆	2 HOUR FIRE RATED WALL	2 HOUR	1-1/2 HOUR	1-1/2 HOUR

VIEW & PRINT THIS SHEET IN COLOR FOR CLARITY

**1. Design Criteria**

1.1. Governing Building Code	A. Risk Category	2021 International Building Code (IBC)
1.2. Floor Live Loading	A. Floor Live Load	100 psf
1.3. Roof Loading	A. Roof Live Load	40 psf
1.4. Earthquake	A. Seismic Design Category	D
	B. Spectral Response Accelerations:	
	$S_1 = 1.541 \text{ g}$	$S_{60} = 1.233 \text{ g}$
	$S_1 = 0.549 \text{ g}$	$S_{60} = 0.641 \text{ g}$
C. Site Class	D. Basic Seismic-Force-Resisting System	
E. Importance Factor, I_s	F. Redundancy Factor, P	$I_s = 3.00$
G. Analysis Period	H. Equivalent Lateral Force (Static)	1.0
I. Design Base Shear		9 kips

2. Concrete

2.1. Materials shall comply with the Standards specified in American Concrete Institute (ACI) 318-19, "Building Code Requirements for Structural Concrete".												
A. Concrete mix design requirements shall be as follows:												
<table border="1"> <tr> <td>Location</td> <td>Fat at 28 days (psi)</td> <td>Max W/C Ratio</td> <td>Air Content (%)</td> <td>Max Aggregate Size</td> <td>Exposure Classes*</td> </tr> <tr> <td>Footings</td> <td>3000</td> <td>0.50</td> <td>1%</td> <td>1"</td> <td>F O S C W</td> </tr> </table>	Location	Fat at 28 days (psi)	Max W/C Ratio	Air Content (%)	Max Aggregate Size	Exposure Classes*	Footings	3000	0.50	1%	1"	F O S C W
Location	Fat at 28 days (psi)	Max W/C Ratio	Air Content (%)	Max Aggregate Size	Exposure Classes*							
Footings	3000	0.50	1%	1"	F O S C W							
Exposure Classes are per ACI 318, Section 19.3.1.1, where F, S, C and W are exposure categories for freezing and thawing, sulfate, and corrosion protection of reinforcement, and contact with water, respectively.												
B. Cementitious Materials:												
1. Portland Cement (ASTM C150)	a. Type I or Type II cement S0											
2. Fly Ash (ASTM C618, Class C, F, or N) maximum fly ash content as a percentage of total weight of cementitious materials shall be 25 percent.												
C. Aggregates:	1. For concrete with exposure class W1, evidence shall be submitted that aggregates comply with the following:											
	a. Aggregates are not alkali-silica reactive or measures to mitigate alkali-silica reactivity have been established.											
	b. Aggregates are not alkali-carbonate reactive.											
D. Concrete Density (Maximum Air-Dry Weight):	1. Normal weight concrete shall be approximately 145 to 155 pounds per cubic foot. Aggregate shall be ASTM C33.											
E. Steel Reinforcement:	1. ASTM A615 Grade 60, fy = 60,000 psi min. unless noted otherwise.											
F. Admixtures:	1. Air-entraining admixtures, comply with ASTM C 230 (when used).											
	a. Tolerance on air content as delivered shall be +/- 1.5%.											
	b. When air content of a truss finished floor slab exceeds 3%, there is an increased risk for delaminations and blistering to occur. When this situation is present, the Contractor shall pay special attention to the finishing procedures to help minimize such risks. Refer to ACI 302.1R-15 "Guide for Concrete Floor and Slab Construction" for further information.											
	2. The use of super plasticizers and water reducers is allowed, but not required.											
	3. Calcium chloride or admixtures containing calcium chloride shall not be added to the concrete mix.											
G. Chloride Ion Maximum water-soluble chloride in hardened concrete is a range between 28 and 42 days concrete for maximum exposure, including w/c aggregates, concrete admixtures, and admixtures shall not exceed a maximum, by weight of cementitious materials, of 1.00% for concrete with exposure class C0.												
H. Shrinkage Limit: Interior slabs on grade shall have a drying shrinkage limit of 0.04% tested in accordance with ASTM C157. Drying shrinkage test results shall be submitted with my designs.												
I. Only one grade or type of concrete shall be poured on the site at any given time.												
2. Formwork shall comply with ACI Standards Publication 347 and the project specifications. The Contractor shall be responsible for the design, detailing, care, placement and removal of the formwork and shores.												
A. Pre-camber forms and screeds with a camber of 1/8 inch per every 10 feet of span to compensate for dead load deflection, unless noted otherwise.												
3. Concrete cover requirements for deformed bar reinforcing steel shall comply with ACI 318, "Building Code Requirements for Structural Concrete".												
A. Casting Concrete: Specified Cover	1. concrete not exposed to weather or in contact with ground											
	Slabs, Walls, Joists; #11 bars and smaller 3/4"											
2. Minimum Spacing of Reinforcement	A. For parallel reinforcing bars in a horizontal layer, clear spacing between bars shall be at least the greatest of 1 inch, nominal diameter of the bars considered, and 1/4 times the nominal maximum size of coarse aggregate in the concrete.											
B. If scheduling reinforcing cannot meet these provisions, note the Engineer of Record.												
4. Construction Joints and Control Joints	A. All horizontal and vertical construction joints shall have a surface intentionally roughened to 1/4 inch amplitude. A continuous 2x2" grid may be used on elements other than shear walls.											
B. Provide reinforcement dowels to match the member reinforcement across the joint, unless noted otherwise. For dowels across construction joints and wall to footing connections of concrete shear walls, refer to specific project plans, schedules, and details.												
C. Slab on grade shall have construction or control joints spaced not to exceed 30 times the slab thickness in any direction.												
D. Control joints shall be installed in slabs on grade so the length to width ratio of the slab is no less than 12.5:1. See typical details for joint configuration.												
E. All sawcut control joints shall be completed within 12 hours of concrete placement.												
5. Debonding: All debonding shall be detailed, bolted & supported to comply with ACI 315, "Details and Detailing of Concrete Reinforcement and the Reinforcing Steel Institute (RSI) recommendations. Reinforcing bars shall not be welded unless specifically shown on drawings.												
A. All reinforcing shall be developed in compliance with the CONCRETE REINFORCING BAR DEVELOPMENT AND LAP SCHEDULE. As indicated in the drawings or upon approval of the Engineer of Record, standard tension hooks or embedded bars described by the TENSION SCHEDULE.												
B. All embedded elements and dowels shall be securely tied to formwork or to adjacent reinforcing prior to the placement of concrete.												
C. Use chairs or other support devices recommended by RSI and tie reinforcement bars prior to placing concrete.												
D. Where required, reinforcement is to be terminated in a standard hook or headed bar anchor. Refer to the TENSION HOOK DEVELOPMENT SCHEDULE and the REINFORCEMENT END HOOK SUPPORT SCHEDULE as appropriate.												
E. Contractor shall coordinate placement of all openings, curbs, dowels, sleeves, conduits, bolts, inserts and other embedded items in concrete placement details.												
F. All reinforcement shall be bent cold and shall be bent only once at the same location. All reinforcement shall be shop bent, unless otherwise permitted by the Engineer of Record.												
6. No aluminum conduit or product containing aluminum or any other material injurious to concrete shall be embedded in concrete.												
7. Unless otherwise noted, all slabs on grade shall be 4 inches thick.												

3. Cold-Formed Steel

3.1. General Conditions
A. The architect and steel framing drawings and details provide the general design intent and do not cover all conditions. The Contractor shall provide cold-formed framing as required to complete the wall section geometry as shown in the architectural drawings, including additional studs and connections as required to provide a complete installation. The Contractor shall provide engineering for conditions not specifically detailed in the construction drawings.
3.2. Material
A. Studs:
1. Base metal thickness of less than 16 mils: ASTM A1003 or A653, Fy = 33 ksi.
2. Base metal thickness of 16 mil or greater: ASTM A1003 or A653, Fy = 50 ksi.
B. Track Connection Clips, and Miscellaneous Shapes:
1. Base metal thickness of less than 54 mil: A1003 or A653, Fy = 33 ksi.
2. Base metal thickness of 54 mil or greater: A1003 or A653, Fy = 50 ksi
C. Design, fabrication and construction shall comply with the following Codes and Standards from the American Iron and Steel Institute (AISI):
A. AISI S100-16(2020) w/S2-20, "North American Specification for the Design of Cold-Formed Steel Structural Members" 2016 Edition (Revised 2020), 2020 Edition.
B. AISI S220-20, "Code of Practice for Cold-Formed Steel Framing," 2020
C. AISI S220-20, "North American Standard for Cold-Formed Steel Nonstructural Framing," 2020
D. AISI S240-20, "North American Standard for Design of Cold-Formed Steel Structural Framing," 2020
E. AISI S400-20, "North American Standard for Seismic Design of Cold-formed Steel Structural Systems," 2020
3.4. Cold-Formed Steel Framing
A. All cold-formed steel (and/or) joist framing members along with all runner, bridging, and end track shall be of the designation shown on the plans, schedules, and details. The framing member designators used in the plans, schedules, and details allow the convention established by the Steel Stud Manufacturers' Association (SSMA) and the North American Steel Stud and joist Association (NASSFA). Framing members provided shall comply with the conventions according to this convention. See Steel Stud Manufacturers' Association- Nomenclature for an explanation of the stud or track designations.
B. All components shall be galvanized.
C. When noted in the drawings, all framing members shall have a base metal thickness of 33 mil or greater.
D. All jamb, header, and sill components shall be continuous without splices unless noted otherwise. Jams shall extend continuous from floor to roof, or wing gir.
E. Web plates for header stud or joist framing shall not be located within 12 inches of the support.
F. Fasteners for steel track components shall be self-drilling and self-tapping meeting ASTM C153. Screw-type fasteners shall penetrate the pinned materials with a minimum of three threads exposed. Furnish, install, and tighten screws per the manufacturer's recommendations and per the sizes indicated in the details. The minimum screw-type fastener size shall be #10 for any connection, unless noted otherwise, or the manufacturers' minimum recommended size for framing clips and joists. Spans shall be the center-to-center spacing of at least 3 times the nominal diameter of the screw unless noted otherwise. Screws shall have center-to-screw to edge-of-steel dimensions of at least 1.5 times the nominal diameter of the screw unless noted otherwise.

5. Miscellaneous

5.1. Post-Installed Anchors in Concrete
A. Anchorage to hardened concrete shall include all mechanical and adhesive anchors and epoxy doweled reinforcing bars as size, quantity, spacing, and embedment as shown on the drawings. Additional anchors shall not be used without approval from the Engineer of Record prior to installation.
B. Connection clips as specified in the schedules and details use The Steel Network (TSN) products as the basis of design. Other manufacturer's connection clips must be submitted for review and approved by the Architect/Engineer prior to use and shall be used in accordance with the manufacturer's instructions and applicable code evaluation reports and the Quality Assurance and Statement of Special Inspections sections of the General Structural Notes.
C. Anchorage to Concrete:
1. All post-installed anchors into hardened concrete shall be selected from the following pre-approved products, unless noted otherwise:

Steel Screw Anchor	Evaluation Report
Hilti Kwik HUS-EZ	ICC ESR-3027
DeWalt Screw-Bolt*	ICC ESR-3889
Simpson Titen HD	ICC ESR-2713


Steel Expansion/Wedge Anchor	Evaluation Report
Hilti Kwik Bolt T2	ICC ESR-4266
DeWalt Power-Stud® SD2	ICC ESR-2502
Simpson Strong-Bolt 2	ICC ESR-3037

Adhesive Anchor System	Evaluation Report
Hilti HIT-HY 200	ICC ESR-4686
Hilti HIT-HY 400	ICC ESR-4685
Hilti HIT-RE 500 V3	ICC ESR-3814
DeWall AC200+	ICC ESR-4027
DeWall Pure 110+	ICC ESR-3298
Simpson SET-1G	ICC ESR-4057


3.5. Welding:
A. The steel contractor shall contact the Quality Assurance Agency prior to beginning any welds. A program of joint preparation and welding processes shall be worked out between the two parties before that welding is started so that controls will be in place from the beginning.
B. Certification of Welders: All shop and field welding shall be executed by AWS certified welders who have been specifically certified for the process of welding being performed. The welder's certification will be considered as being current unless the welder is not engaged in the process of welding for a period exceeding six months or that is required by the certification to be renewed by the Certification and registration agency in compliance with AWS Standards. Certification and appropriate records must be provided to the Architect prior to beginning work.
C. Welds noted otherwise, all welded connections shall be done using 1/8 inch AWS type 6013 or 7014 rod with a welding heat of 60-110 amperes depending on the gauge of material and the fit of parts. Wire tying of framing components shall not be permitted. Welds and damaged coatings on studs shall be repaired with zinc galvanizing repair parts.

4. Wood

4.1. Fabrication and construction shall comply with the following Codes and Standards:
A. American Wood Council National Design Specification for Wood Construction 2018 Edition and Supplement (NDS and NDS Supplement)
B. Florida Building Code Wood and Seismic 2021 Edition (SDPWS)
C. Aggregates:
1. For concrete with exposure class W1, evidence shall be submitted that aggregates comply with the following:
a. Aggregates are not alkali-silica reactive or measures to mitigate alkali-silica reactivity have been established.
b. Aggregates are not alkali-carbonate reactive.
D. Concrete Density (Maximum Air-Dry Weight):
1. Normal weight concrete shall be approximately 145 to 155 pounds per cubic foot. Aggregate shall be ASTM C33.
E. Steel Reinforcement:
1. ASTM A615 Grade 60, fy = 60,000 psi min. unless noted otherwise.
F. Admixtures:
1. Air-entraining admixtures, comply with ASTM C 230 (when used).
a. Tolerance on air content as delivered shall be +/- 1.5%.
b. When air content of a truss finished floor slab exceeds 3%, there is an increased risk for delaminations and blistering to occur. When this situation is present, the Contractor shall pay special attention to the finishing procedures to help minimize such risks. Refer to ACI 302.1R-15 "Guide for Concrete Floor and Slab Construction" for further information.
2. The use of super plasticizers and water reducers is allowed, but not required.
3. Calcium chloride or admixtures containing calcium chloride shall not be added to the concrete mix.
G. Chloride Ion Maximum water-soluble chloride in hardened concrete is a range between 28 and 42 days concrete for maximum exposure, including w/c aggregates, concrete admixtures, and admixtures shall not exceed a maximum, by weight of cementitious materials, of 1.00% for concrete with exposure class C0.
H. Shrinkage Limit: Interior slabs on grade shall have a drying shrinkage limit of 0.04% tested in accordance with ASTM C157. Drying shrinkage test results shall be submitted with my designs.
I. Only one



12/11/2025



CONCRETE REINFORCING BAR DEVELOPMENT AND LAP SPLICE LENGTH SCHEDULE																						
BAR SIZE	fc = 3000 PSI			fc = 4000 PSI			fc = 4500 PSI			fc = 5000 PSI			fc = 6000 PSI			fc = ALL						
	Ld	Lt	Lsb	Lstb	Ld	Lt	Lsb	Lstb	Ld	Lt	Lsb	Lstb	Ld	Lt	Lsb	Lstb	Ldc	Lsc				
#3	17"	22"	22"	28"	15"	19"	19"	25"	14"	18"	18"	23"	13"	17"	17"	22"	12"	16"	20"	8"	12"	
#4	22"	29"	29"	38"	19"	25"	25"	33"	18"	24"	24"	31"	17"	23"	23"	29"	16"	21"	27"	10"	15"	
#5	28"	36"	36"	47"	24"	31"	31"	41"	23"	30"	30"	38"	22"	28"	28"	36"	20"	26"	26"	33"	12"	19"
#6	33"	43"	43"	56"	29"	37"	37"	49"	27"	35"	35"	46"	26"	34"	34"	44"	24"	31"	31"	40"	15"	23"
#7	48"	63"	63"	81"	42"	54"	54"	71"	40"	51"	51"	67"	38"	49"	49"	63"	34"	45"	45"	58"	17"	27"
#8	55"	72"	72"	93"	48"	62"	62"	81"	45"	59"	59"	76"	43"	56"	56"	72"	39"	51"	51"	66"	19"	30"
#9	62"	81"	81"	105"	54"	70"	70"	91"	51"	66"	66"	86"	48"	63"	63"	81"	44"	57"	57"	74"	22"	34"
#10	70"	91"	91"	118"	61"	79"	79"	102"	57"	74"	74"	96"	54"	71"	71"	92"	50"	64"	64"	84"	24"	39"
#11	78"	101"	101"	131"	67"	87"	87"	114"	64"	82"	82"	107"	60"	78"	78"	102"	55"	71"	71"	93"	27"	43"
#14	93"	121"	NA	NA	81"	105"	NA	NA	76"	99"	NA	NA	72"	94"	NA	NA	66"	86"	NA	NA	33"	NA
#18	124"	161"	NA	NA	108"	140"	NA	NA	101"	132"	NA	NA	96"	125"	NA	NA	88"	114"	NA	NA	43"	NA


NOTES:
1. DEFINITIONS:
Ld: TENSION DEVELOPMENT LENGTH FOR REINFORCEMENT SATISFYING THE FOLLOWING CONDITIONS:
SLABS AND WALLS: CLEAR SPACING > 2db AND CONCRETE CLEAR COVER > db
BEAMS AND COLUMNS: CLEAR COVER SPACING > db AND CONCRETE CLEAR COVER > db
Lt: DEVELOPMENT LENGTH FOR TOP BARS IN TENSION
Lsb: TENSION LAP SPLICE LENGTH FOR OTHER THAN TOP BARS (CLASS B)
Lstb: TENSION LAP SPLICE LENGTH OF TOP BARS.
Ldc: DEVELOPMENT LENGTH FOR BARS IN COMPRESSION. TO BE USED ONLY WHEN SPECIFIED IN DETAILS.
Lsc: TIED COLUMN LAP SPLICE IN COMPRESSION. TO BE USED ONLY WHEN SPECIFIED IN DETAILS.
db: NOMINAL BAR DIAMETER (INCHES)
TOP BARS: HORIZONTAL BEAM REINFORCEMENT WITH MORE THAN 12 INCHES OF CONCRETE CAST BELOW
2. MULTIPLY VALUES IN SCHEDULE BY 1.5 IF CLEAR SPACING OR CONCRETE COVER DO NOT MEET REQUIREMENTS FOR Ld IN NOTE 1.
3. MULTIPLY VALUES IN SCHEDULE BY 1.3 FOR USE IN LIGHTWEIGHT AGGREGATE CONCRETE.
4. FOR EPOXY COATED BAR: MULTIPLY VALUES IN SCHEDULE BY 1.5 FOR BARS WITH CLEAR COVER < 3db OR CLEAR SPACING < 6db. OTHERWISE MULTIPLY VALUES BY 1.2.
5. a. FOR BUNDLED BARS OF THREE OR LESS MULTIPLY LENGTHS BY 1.2.
b. FOR BUNDLED BARS OF FOUR OR MORE MULTIPLY LENGTHS BY 1.33.
c. INDIVIDUAL BAR SPLICES WITHIN A BUNDLE SHALL NOT OVERLAP. ENTIRE BUNDLES SHALL NOT BE LAP SPLICED.
6. SCHEDULE LENGTHS ARE FOR fy=60ksi REINFORCING, MULTIPLY LENGTHS BY 1.53 FOR fy=80ksi, 2.17 FOR fy=100ksi REINFORCING.
7. LAP SPLICES ARE NOT PERMITTED FOR #14 & #18 BARS. USE BAR COUPLERS PER G.S.N.
8. MINIMUM CLEAR SPACING BETWEEN THE CONTACT LAP SPLICES SHOWN IN THIS SCHEDULE AND ADJACENT SPLICES OR BARS SHALL BE IN ACCORDANCE WITH THE DETAILING PROVISIONS OF GENERAL STRUCTURAL NOTES.

SCREW ANCHORS IN CONCRETE SCHEDULE				
ANCHOR SIZE	MINIMUM EDGE DISTANCE (Cac)	EMBEDMENT LENGTH (H nom)	MINIMUM CONCRETE THICKNESS (H min)	MINIMUM ANCHOR SPACING (S min)
3/8"Ø	6 1/2"	2 7/8"	4 1/2"	3 3/4"
1/2"Ø	10"	3 7/8"	6"	5"
5/8"Ø	10"	5 1/8"	8"	6"
3/4"Ø	16"	5 3/4"	10"	7"

NOTES:
1. THIS SCHEDULE SHALL BE USED ONLY WHERE SPECIFICALLY REFERENCED ON THE DRAWINGS.
ANCHORS AT OTHER LOCATIONS MUST BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
2. EDGE DISTANCE, Cac, AND EMBEDMENT LENGTHS, H nom, AND ANCHOR SPACING SPECIFIED ON PLANS OR DETAILS TAKE PRECEDENCE OVER VALUES IN THIS SCHEDULE.
3. ANCHORS LOCATED WHERE THE THICKNESS OF THE EXISTING CONCRETE MEMBER DOES NOT MEET THE REQUIRED MINIMUM CONCRETE THICKNESS MUST BE APPROVED BY THE STRUCTURAL ENGINEER PRIOR TO INSTALLATION.
4. SEE GENERAL STRUCTURAL NOTES FOR LIST OF APPROVED ANCHORS AND OTHER REQUIREMENTS FOR USING EXPANSION ANCHORS.

4. THIS SCHEDULE SHALL BE USED ONLY WHERE SPECIFICALLY REFERENCED ON THE DRAWINGS AND AT OTHER LOCATIONS WITH APPROVAL OF THE STRUCTURAL ENGINEER.
5. EDGE DISTANCE, Cac, AND EMBEDMENT LENGTHS, H nom, AND ANCHOR SPACING SPECIFIED ON PLANS OR DETAILS TAKE PRECEDENCE OVER VALUES IN THIS SCHEDULE.
6. ANCHORS LOCATED WHERE THE THICKNESS OF THE EXISTING CONCRETE MEMBER DOES NOT MEET THE REQUIRED MINIMUM CONCRETE THICKNESS MUST BE APPROVED BY THE STRUCTURAL ENGINEER PRIOR TO INSTALLATION..
7. SPECIAL INSPECTION IS REQUIRED DURING INSTALLATION OF ALL SCREW ANCHORS PER THE CODE EVALUATION REPORT FOR THE ANCHOR AND THE QUALITY ASSURANCE SECTION OF THE GENERAL STRUCTURAL NOTES.
8. SEE GENERAL STRUCTURAL NOTES FOR LIST OF APPROVED ANCHORS AND OTHER REQUIREMENTS FOR USING SCREW ANCHORS.


6. SCREW ANCHORS SHALL ONLY BE USED IN INTERIOR DRY LOCATIONS



A3 SCREW ANCHORS IN CONCRETE SCHEDULE
SE002 NO SCALE


ABBREVIATIONS	
@	AT
AB	ANCHOR BOLT (S)
ABV	ABOVE
ALT	ALTERNATE
APPRO	APPROXIMATE
ARCH	ARCHITECT(URAL)
BLDG	BUILDING
BLW	BELLOW
BM	BEAM
BOT	BOTTOM
BRB	BUCKLING-RESTRAINED BRACE
BRG	BEARING
BTWN	BETWEEN
CJ	CONSTRUCTION JOINT OR CONTROL JOINT
CJP	COMPLETE JOINT PENETRATION
CMU	CONCRETE MASONRY UNIT
COL	COLUMN
CONC	CONCRETE
CONST	CONSTRUCTION
CONT	CONTINUOUS
CONTR	CONTRACTOR
CTR	CENTER
D.B.	DECK BEARING
db	DIAMETER OF REINFORCING BAR
DBA	DEFORMED BAR ANCHORS
DBL	DOUBLE
DET	DETAIL
DIA (OR Ø)	DIAMETER
DIAG	DIAGONAL
DIM	DIMENSION
DK	DECK
DN	DOWN
DWG	DRAWING
DWL	DOWEL
E.F.	EACH FACE
E.J.	EXPANSION JOINT (SEISMIC SEPARATION JOINT)
E.W.	EACH WAY
EA	EACH
EL	ELEVATION
ELEC	ELECTRICAL
ELEV	ELEVATOR
ENG	ENGINEER
EQ	EQUAL
EQUIP	EQUIPMENT
EXIST (E)	EXISTING
EXP	EXPANSION / EXPOSED
EXT	EXTERIOR
F.D.	FLOOR DRAIN
F.F.	FINISH FLOOR
F.V.	FIELD VERIFY
FDTN	FOUNDATION
FIN	FINISH
FL	FLOOR
FT	FOOT
FTG	FOOTING
GA	GAUGE
GALV	GALVANIZED
GLB	GLU-LAMINATED BEAM
GR	GRADE
GSN	GENERAL STRUCTURAL NOTES
HB	HORIZONTAL BRIDGING
HORIZ	HORIZONTAL
HSA	HEADED STUD ANCHORS
HSS	HOLLOW STRUCTURAL STEEL
HT	HEIGHT
I.F.	INSIDE FACE
IBC	INTERNATIONAL BUILDING CODE
ICC	INTERNATIONAL CODE COUNCIL
IN	INCH
INSUL	INSULATION
INT	INTERIOR
JST	JOIST
JT	JOINT
K	KIPS - 1,000 POUNDS
KLF	KIPS PER LINEAL FOOT
KSF	KIPS PER SQUARE FOOT
KSI	KIPS PER SQUARE INCH
LBS	POUNDS
Ld, Lt, Lsb, Lstb, Ldc, Lsc	SEE CONCRETE REINFORCING BAR DEVELOPMENT AND LAP LENGTH SCHEDULE
LF	LINEAL FOOT
LFRS	LATERAL FORCE RESISTING SYSTEM (SFRS & WFRS)
LLH	LONG LEG HORIZONTAL
LLV	LONG LEG VERTICAL
LSH	LONG SIDE HORIZONTAL
LSV	LONG SIDE VERTICAL
MAS	MASONRY
MAX	MAXIMUM
MCJ	MASONRY CONTROL JOINT
MECH	MECHANICAL
MFGR	MANUFACTURER
MIN	MINIMUM

ABBREVIATIONS	
MISC	MISCELLANEOUS
NIC	NOT IN CONTRACT
NORM	NORMAL
NTS	NOT TO SCALE
O.C.	ON CENTER
O.F.	OUTSIDE FACE
OPNG	OPENING
OPP	OPPOSITE
OWSJ	OPEN WEB STEEL JOIST
P.T.	POST-TENSIONED
PAF	POWER ACTUATED FASTENER
PCF	POUNDS/CUBIC FOOT
PJP	PARTIAL JOINT PENETRATION
PL	PLATE
PLF	POUNDS/LINEAL FOOT
PNL	POLYMER
PSF	POUNDS/SQ FOOT
PSI	POUNDS/SQ INCH
R.D.	ROOF DRAIN
REINF	REINFORCING
REQD	REQUIRED
SDS	SELF-DRILLING SCREW
SFRS	SEISMIC FORCE RESISTING SYSTEM
SHT	SHEET
SI	SPECIAL INSPECTION (SP. INSP.)
SIM	SIMILAR
SOG	SLAB ON GRADE
SQ	SQUARE
STAG	STAGGERED
STD	STANDARD
STIFF	STIFFENER
STL	STEEL
STRUCT	




NOTE:
PROTECT EXISTING SLAB ON GRADE. DO NOT ANCHOR ANYTHING INTO THE EXISTING SLAB ON GRADE.

NOTES:
1 ALIGN WALL STUDS WITH ROOF JOISTS PER DETAIL D1/SW601.
2 PROVIDE AN ADDITIONAL WALL STUD, BACK TO BACK, UNDER THE BEARING POINTS OF BACK TO BACK ROOF JOISTS.
3 SEE SHEET SW601 FOR DIAPHRAGM SCHEDULE AND DETAIL.
4 SEE SHEET SW601 FOR STEEL STUD WALL SCHEDULE.
5 USE 8-3/4"Φ HILTI HY 200 V3 + HIT-Z WITH 4" EMBEDMENT FOR CONNECTION OF SCISSORLIFT TO CONCRETE.



A1
LEVEL 1 FRAMING PLAN
SF101
SCALE: 1/4" = 1'-0"

12/15/2025 11:03:39 AM



A4
ROOF FRAMING PLAN
SF101
SCALE: 1/4" = 1'-0"


Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project #
Construction Documents
Dec 11, 2025


FLOOR AND
ROOF
FRAMING
PLANS

SF101




12/11/2025

WALL FRAMING PLAN NOTES	
1. VERIFY WALL OPENING WITH ARCHITECTURAL AND MEP.	
2. PROVIDE DRIFT/DEFLECTION CONNECTIONS AT NON-LOAD BEARING PARTITION WALLS. SEE ARCH FOR LOCATIONS.	
3. INSTALL WALL STUDS IN-LINE WITH JOISTS, AT DOUBLE JOISTS, PROVIDE BACK TO BACK STUD IN WALL. FASTEN WEBS TOGETHER W/ #10 @ 12" O.C.	
4. SEE TYPICAL LOAD-BEARING STEEL STUD WALL SCHEDULE ON SW601.	
5. PROVIDE BRIDGING @ 4'-0" O.C. ON WALL UNO. PER DETAIL A2/SW501.	



C1 West Elevation
SF102 SCALE: 1/4" = 1'-0"



C4 North Elevation
SF102 SCALE: 1/4" = 1'-0"



Intermountain Health
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project #
Construction Documents
Dec 11, 2025


STRUCTURAL
FRAMING
ELEVATIONS

SF102




Detail Name
D4 JOIST BLOCK AND STRAP BRIDGING
SW501 NO SCALE


NOTE:
PROTECT EXISTING SLAB ON GRADE. DO NOT ANCHOR ANYTHING INTO THE EXISTING SLAB ON GRADE.




C1 TYPICAL BOTTOM TRACK ANCHORAGE DETAILS
SW501 NO SCALE




SW502-01




JAMB STUD BASE AT CONT BOTTOM TRACK




C4 TYPICAL HEADER CONNECTION DETAILS
SW501 NO SCALE




C5 TYPICAL SILL CONNECTION DETAILS
SW501 NO SCALE





OPTION #1
A2 TYPICAL STEEL STUD WALL BRIDGING DETAIL
SW501 NO SCALE




OPTION #2




A5 TYPICAL HEADER CONNECTION DETAILS
SW501 NO SCALE



D3 BLOCKING AND JOISTS AT STEEL STUD WALL
SW503 NO SCALE



D4 STEEL STUD JOIST BEARING AT STEEL STUD WALL
SW503 NO SCALE



D5 STEEL STUD JOIST BEARING AT STEEL STUD WALL
SW503 NO SCALE



Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116


NJRA Project #
Construction Documents
Dec 11, 2025

STEEL STUD
ROOF DETAILS

SW503




BEARING STIFFENER ON INSIDE WEB
OF HORIZONTAL FRAMING MEMBER



BEARING STIFFENER ON OUTSIDE WEB
OF HORIZONTAL FRAMING MEMBER

NOTE: PROVIDE 600T125-54 x 12" LONG BEARING STIFFENER AT BACK-TO-BACK JOIST CONDITIONS

D1 TYPICAL IN LINE FRAMING DETAIL
SW601 NO SCALE




B1 WOOD DIAPHRAGM ISOMETRIC DETAIL
SW601 NO SCALE

WOOD DIAPHRAGM SCHEDULE						
MARK	MINIMUM WOOD SHEATHING THICKNESS	WOOD SHEATHING EDGES	SCREW SPACING			MINIMUM SCREW SIZE
			A	B	C	
WD-1	1-1/8" T&G	BLOCKED	6"	6"	12"	#8
WD-2	15/32" STRUCT-1	NO BLOCKING REQ'D	6"	6"	12"	#8

NOTES:
1. SEE DETAIL B1/SW601 FOR TYPICAL LAYOUT OF STRUCTURAL PANEL DIAPHRAGMS.
2. WHERE PANEL EDGE BLOCKING NOT REQUIRED, FASTEN TO JOIST BLOCKING.
3. COMMON FASTENER SPACING CRITERIA:
A. CONTINUOUS WOOD SHEATHING PANEL EDGES AND DIAPHRAGM BOUNDARY EDGES.
DIAPHRAGM BOUNDARIES INCLUDE SHEAR WALLS, PERIMETER TRACKS, BEAMS, TOP PLATES, AND RIM BOARDS IN LINE WITH SHEAR WALLS.
B. ALL OTHER PANEL EDGES.
C. INTERMEDIATE PANEL SUPPORTS (IN FIELD FASTENING).
4. ALL WOOD STRUCTURAL PANELS SHALL BE A.P.A. RATED EXPOSURE 1.
5. USE SIMPSON PHDC11516B OR ENGINEER APPROVED EQUIVALENT FOR FIRE RETARDANT TREATED SHEATHING IF REQUIRED.

C1 WOOD DIAPHRAGM SCHEDULE
SW601 NO SCALE




B3 TYPICAL EDGE BLOCKING DETAIL
SW601 NO SCALE

MEMBER DEPTH:
(EXAMPLE: 6" = 600 x 1/100 INCHES)
ALL MEMBER DEPTHS ARE TAKEN IN 1/100 INCHES.
FOR ALL "T" SECTIONS, MEMBER DEPTH IS INSIDE TO INSIDE

MATERIAL THICKNESS:
(EXAMPLE: 0.054 IN = 54 MILS; 1 MIL = 1/1000 IN.)

STYLE:
(EXAMPLE: STUD OR JOIST SECTION = S)
S = STUD OR JOIST
T = TRACK
U = CHANNEL SECTIONS
F = FURRING CHANNEL SECTIONS




A2 STEEL STUD MANUFACTURERS ASSOCIATION - NOMENCLATURE
SW601 NO SCALE

STEEL STUD WALL SCHEDULE														
MARK	WALL FRAMING						WALL ANCHORAGE			WALL SHEATHING	EDGE FASTENERS	FIELD FASTENERS	STUD BRACING REQUIRED	REMARKS
	STUDS	SPACING	BOTTOM TRACK	TOP TRACK	END STUDS	BOTTOM TRACK ANCHORAGE	END STUDS OR POST ANCHORAGE	SIZE	SPACING	SIZE	SPACING	SIZE	SPACING	
SSW-1	600S162-54	24"	600T125-54	600T125-54	600S162-54	TO CONCRETE FOOTING ONLY, DO NOT FASTEN TO EXIST SLAB ON GRADE 1/2" DIA Kwik-Bolt SCREW ANCHOR W/4.25" NOMINAL EMBEDMENT @ 12" O.C.	DO NOT ANCHOR TO EXIST CONCRETE SLAB	15/32 STRUCT-1 SHEATHING	#10	12" O.C.	#10	12" O.C.	HORIZONTAL BRIDGING @ 48" O.C. SEE A2/SW501	

NOTES:

1. ALL STUDS AND TRACK SHALL BE OF ASTM A1003 STRUCTURAL GRADE 50 TYPE H STEEL.
2. WHERE STUD MUST BE CUT DUE TO THE PLACEMENT OF ANCHOR BOLTS OR OTHER PRODUCTS, AN ADDITIONAL STUD SHALL BE INSERTED ALONG SIDE.
3. ALL PANEL EDGES SHALL BE SOLID BLOCKED PER DETAIL B1/SW601.
4. DISTANCE FROM PANEL EDGE TO SCREW SHALL BE NOT LESS THAN 3/8".
5. SHEATHING SHALL BE APPLIED WITH EDGES 1/8" APART AT SIDE JOINTS AND 1/16" APART AT END JOINTS.
6. ALL SCREWS SHALL BE #10 SELF TAPPING SCREWS W/FLAT HEAD AND A MINIMUM DIAMETER OF 0.3 INCHES.
7. AT VERTICAL OFFSETS IN EXTERIOR STUD WALL, PROVIDE ADDITIONAL STAGGERED 600S162-54 STUD.
8. PROVIDE BRIDGING @ 4'-0" O.C. TYPICAL U.N.O. BRIDGING SHALL BE CAPABLE OF RESISTING A MOMENT OF 0.42k-in. SUBMIT BRIDGING SYSTEM FOR REVIEW.




STEEL STUD WALL OPENING SCHEDULE

NO. OF TRIM STUDS (T)	WIDTH OF OPENING	JAMB		HEADER	
		SIZE	TYPE	NO. OF KING STUDS	SIZE
0	UP TO 3'-6"	600S162-54	J1	1+T	600T162-54
		600T162-54			600T162-54
1	UP TO 6'-0"	600S162-54	J1	1+T	2-800S162-54
		600T162-54			600T162-54
1	UP TO 10'-0"	(2) 600S162-54	J2	1+T	2-1400S162-68
		600T162-54			600T162-54

NOTES:

1. SEE ARCHITECTURAL DRAWINGS FOR LOCATIONS OF ALL OPENINGS IN STUD WALLS.
2. ALL STUD SIZE DESIGNATIONS ARE PER THE STANDARD ESTABLISHED BY THE STEEL STUD MANUFACTURER'S ASSOCIATION (SSMA) AND THE NORTH AMERICAN STEEL FRAMING ALLIANCE (NASFA).
3. AT CONTRACTOR'S OPTION, USE #12 SCREWS @ 12" O.C. TO ATTACH TRACK/OTHER STUDS TO JAMB/HEADER STUDS TYPICAL IN LIEU OF WELDING.
4. OTHER PROPRIETARY STUD FRAMING SYSTEMS MAY BE USED WITH WRITTEN APPROVAL BY THE STRUCTURAL ENGINEER.
5. SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
6. PROVIDE BEARING STIFFENER FOR HEADER TYPE H1 PER DETAIL D1/SW601.




HEADER TYPE H1

HEADER TYPE H2

JAMB TYPE J1

JAMB TYPE J2



A3 TYPICAL STUD WALL FRAMING SCHEDULE WITH FRAMED OPENING DETAIL
SW601 NO SCALE

MEMBER DEPTH:
(EXAMPLE: 6" = 600 x 1/100 INCHES)
ALL MEMBER DEPTHS ARE TAKEN IN 1/100 INCHES.
FOR ALL "T" SECTIONS, MEMBER DEPTH IS INSIDE TO INSIDE

FLANGE WIDTH:
(EXAMPLE: 1.5/8" = 1.625" = 162 x 1/100 INCHES)

MEMBER DEPTH


FLANGE WIDTH

FLANGE THICKNESS:
(EXAMPLE: 0.054 IN = 54 MILS; 1 MIL = 1/1000 IN.)

MEMBER DEPTH

FLANGE THICKNESS

MEMBER DEPTH



Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025


Floor Plan
Level 1 -
Overall

A113


KEYED NOTES

GENERAL NOTES

- A. SEE SHEET G003 AND GO01 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.



1 Floor Plan Level 1
SCALE: 1" = 10'-0"



Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025


Floor Plan
Level 2 -
Overall


A120

KEYED NOTES


GENERAL NOTES

- A. SEE SHEET G003 AND GO01R SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.






KEYED NOTES



1 North Elevation



2 West Elevation

GENERAL NOTES

- A. SEE SHEET G003 AND GO01R SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.

Intermountain Health
Intermountain Life Flight
Life Flight Simulator



2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025

Exterior
Elevations -
Overall

A202

VIEW & PRINT THIS SHEET IN COLOR FOR CLARITY



1 Life Flight Simulator
SCALE: 1/4" = 1'-0"

KEYED NOTES

GENERAL NOTES

- A. SEE SHEET G003 AND GO003 SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.


Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025


Wall Sections

A351



KEYED NOTES

03.01 CONCRETE BASE. SEE STRUCTURAL DRAWINGS.
 05.01 SAFETY GATE OR CHAIN, IN COLOR, WITH WARNING SIGNAGE.
 05.02 PROVIDE SECURE LATCHING TO HANDRAIL.
 05.32 GUARDRAIL OR HANDRAIL, RAIL SHALE BE CONSTRUCTED WITH STEEL COMPONENTS PAINTED SAFETY YELLOW. ATTACH HANDRAIL TO WALL OR GUARDRAIL WHEREVER POSSIBLE EVERY 16'. OTHERWISE, ANCHOR GUARDRAIL AND HANDRAIL TO FLOOR DIAGONALLY AS REQUIRED AND PROVIDE STANDBY GUARDRAIL AT FLOOR.
 06.03 TEMPORARY RAMPS.
 09.01 STAIR AND PLATFORM, FRAME STAIR USING LIGHT GAUGE STEEL FRAMING, PLYWOOD SHEATHING, DECKING AND STAIR TREADS, FINISH EXTERIOR WITH DRYWALL AND PAINT, ADD NON-SLIP RUBBER STAIR TREADS TO STAIRS AND RISERS, ADD FLOORING TO PLATFORM TO MATCH FLOORING THROUGHOUT.
 09.02 FRAMED FLOOR.
 09.03 WALL BASE. STUD FRAMED WALL WITH EXTERIOR SHEATHING, FINISH WITH EXTERIOR AND INTERIOR DRYWALL AND PAINT, PROVIDE ACOUSTICAL BATT WITHIN CAVITY OF WALL. SEE STRUCTURAL DRAWINGS.
 09.05 RAISED DISC RUBBER FLOORING TILES, MANUFACTURER SHALL BE JOHNSONITE ROUNDEL RAISED ROUND RUBBER FLOORING, COLOR SHALL BE SELECTED BY OWNER/ARCHITECT.
 09.08 WALL BASE. SEE FINISH FLOOR PLANS FOR WALL BASE TYPE INDICATED WITH A WALL BASE TAG (AS B1, B2, B3, ETC.). SEE FINISH SCHEDULE ON SHEET A603A FOR MATERIAL, SIZE, COLOR, ETC. FOR EACH WALL BASE TAG.
 09.13 ACOUSTICAL CEILING TILE AND GRID, MANUFACTURER SHALL BE USG, RADAR 22111, WHITE.
 09.26 LVT FLOOR COVERING, MANUFACTURER SHALL BE MANNINGTON COMMERCE, COLOR TERRACOTTA, COLOR SHALL BE SELECTED BY OWNER/ARCHITECT.
 11.01 MOVEABLE GANGWAY, WITH RAILING, ON LOCKING CASTERS.
 11.02 DOCK LIFT, 6'X8' VESTIL MANUFACTURING MODEL "WL-100-5-48" AND ASSOCIATED CONTROL CABINET AND HYDRAULIC PUMP, CONTRACTOR FURNISHED CONTRACTOR INSTALLED.
 11.03 MOOG MOTION BASE, MODEL MB-EP-D-0074/2000G, OWNER FURNISHED CONTRACTOR SHALL FURNISH MOTION BASE AS REQUIRED, CONTRACTOR SHALL PROVIDE ELECTRICAL DISCONNECT (LOCATED ELSEWHERE) AND CONDUCTORS WITHIN CONDUIT AS REQUIRED, SEE VENDOR DOCUMENTATION IN PROJECT MANUAL FOR SPECIFIC REQUIREMENTS FOR INSTALLATION.
 11.04 SINGLE CONTROL DESKTOP SWITCH W/ LIGHT W/ BUTTON BY VENDOR CONTRACTOR, SEE VENDOR (MOOG) DOCUMENTATION, SEE MECHANICAL DRAWINGS.
 11.05 INTEGRATION RACK, VENDOR FURNISHED CONTRACTOR INSTALLED.
 11.07 COMPUTER, WALL MOUNTED, CONTRACTOR SHALL FURNISH AND INSTALL WALL MOUNT FOR VENDOR SUPPLIED COMPUTER.
 11.08 WORKSTATION, VENDOR SUPPLIED WORKSTATION.
 11.09 COMPUTER, NOT IN CONTRACT, OWNER FURNISHED OWNER INSTALLED, PROVIDE GROMMET COUNTERTOP WHERE COMPUTER OCCURS ON COUNTERTOP, KNEE SPACES AS REQUIRED.
 11.10 FLIGHT SIMULATOR BY LEONARDO, SEE VENDOR DOCUMENTATION IN PROJECT MANUAL FOR SITE PREPARATION REQUIREMENTS.
 11.11 TV, MOUNTED ON ARTICULATING ARM MOUNT, TO DISPLAY RECORDINGS, ELECTRICAL BACK BOX AND CONDUIT CONNECTION TO RACK SUPPLIED AND INSTALLED BY CONTRACTOR, TV SHALL BE VENDOR FURNISHED, CONTRACTOR INSTALLED, SEE ELECTRICAL DRAWINGS.
 11.13 FLIGHT SIMULATOR CONSOLE, VENDOR FURNISHED OWNER INSTALLED, PROVIDE WALL MOUNTED METAL BRACKET TO SUPPORT THE TV, BRACKET SIZE AND MODEL SHALL BE BASED ON THE TV SIZE, PROVIDE PLYWOOD BACKING IN WALL AS REQUIRED TO SUPPORT THE TV BRACKET, PROVIDE POWER, DATA AND HDMI PORT, SEE ELECTRICAL DRAWINGS.
 12.09 FUSELAGE, FUSELAGE CONDUIT, VENDOR FURNISHED OWNER INSTALLED, MECHANICAL CONDUIT AS SET, SEE MECHANICAL DRAWINGS.
 22.05 PLUG STRIP FOR CHARGING, SEE ELECTRICAL DRAWINGS.
 26.02 PROVIDE POWER AND DATA (INTRANET AND CONNECT TO IH NETWORK)
 26.03 UMBILICAL CONDUIT UNDER FLOOR
 26.04 2 REGULAR POWER OUTLETS, NETWORK OUTLETS IN FUSELAGE FOR PATIENT MONITOR & MANNEQUIN
 26.05 CONDUIT FROM RACK TO FUSELAGE
 26.06 CONDUIT FROM RACK TO TV
 26.07 CONDUIT FROM RACK TO CONSOLE
 26.08 FLOOR BOX, PROVIDE POWER, DATA AT FLOOR BOX, SEE ELECTRICAL DRAWINGS.
 26.09 LIGHTS AND DIMMER TYPICAL
 26.11 MOTION BASE ELECTRICAL DISCONNECT, CONTRACTOR FURNISHED, CONTRACTOR INSTALLED.



1 Floor Plan Level 1
SCALE: 1/4" = 1'-0"

1/8/2026 9:51:47 AM

2 Reflected Ceiling Plan Level 1
SCALE: 1/4" = 1'-0"

2



Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116


GENERAL NOTES

A. SEE SHEET G003 AND GO01 FOR SYMBOLS, GENERAL NOTES AND LEGEND.
 B. SEE SHEET A505A FOR CABINET LEGEND.
 C. SEE SHEET A601A FOR DOOR SCHEDULE.
 D. SEE SHEET A602A FOR WINDOW SCHEDULE.
 E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.

Enlarged
Views

A401

25252.00
Construction Documents
Dec. 11, 2025




Enlarged
Views

A402

KEYED NOTES


- 01.01 STEEL COLUMN EXISTING
- 07.01 ROOFING EXISTING, PATCH AS REQUIRED. CONSULT WITH OWNER FOR ROOFING WARRANTY INFORMATION
- 22.04 MECHANICAL HVAC LINE TO MECHANICAL CONDENSER UNIT MOUNTED ON ROOF. SEE MECHANICAL DRAWINGS
- 23.01 ROOFTOP UNIT ON MIRO STAND. SEE MECHANICAL DRAWINGS
- 23.02 HEAT PUMP CONDENSOR UNIT ON MIRO STAND. SEE MECHANICAL DRAWINGS



3 Mechanical Detail
SCALE: 3' = 1'-0"

GENERAL NOTES


- A. SEE SHEET G003 AND GO003 SYMBOLS, GENERAL NOTES AND LEGEND.
- B. SEE SHEET A505A FOR CABINET LEGEND.
- C. SEE SHEET A601A FOR DOOR SCHEDULE.
- D. SEE SHEET A602A FOR WINDOW SCHEDULE.
- E. SEE SHEET A603A FOR FINISH SCHEDULE AND GENERAL NOTES.




1 Simulation Roof Plan
SCALE: 1/4" = 1'-0"

2 Roof Plan
SCALE: 1/4" = 1'-0"



NORTH















07.01
23.01
07.01
23.02





KEYED NOTE

- LINE OF FLOOR OR ROOF DECK AS OCCURS.
- TO ACCOMMODATE FOR STRUCTURE DEFLECTION, PROVIDE SLIP CONNECTION BETWEEN TOP RUNNER TRACK AND METAL STUD FRAMING. SEE DETAIL 1401.
- STUD FRAMING AROUND DUCT OPENINGS. SEE DETAIL 1401.
- METAL STUDS, 20 GA STRUCTURAL (33 MILS) AT 16" O.C. U.N.O. BASED ON WALL TYPES INDICATED IN FLOOR PLAN. PROVIDE STUD SIZE AS INDICATED IN WALL TYPES WITH TRACK RUNNERS AT TOP AND BOTTOM. FOR STUD FRAMING AROUND DUCT OPENINGS, USE 20 GA STUDS, 33 MILS, AT 16" O.C.
- LINE OF CEILING AS OCCURS, SEE REFLECTED CEILING PLAN.
- STEEL STUDS, "C-H" SHAPED, 20 GA STRUCTURAL AT 24" O.C.
- PROVIDE ACOUSTIC INSULATION BLANKET FOR FULL DEPTH OF THE STUD CAVITY THROUGHOUT UNO. FOR 4" & 3 5/8" STUDS PROVIDE R-13 UNFACED BATT INSULATION AND FOR 6" STUDS PROVIDE R-19 UNFACED BATT INSULATION. PROVIDE KRAFT FACED INSULATION FOR ALL APPLICATIONS AT EXTERIOR WALLS.
- GYPSUM BOARD 1/2" THICK, TYPE-X, U.N.O. ATTACHED TO METAL STUD FRAMING. SEE GENERAL NOTES B BELOW.
- ANCHOR BASED TRACK TO CONCRETE FLOOR BELOW. SEE DETAIL 8/A502A.
- FILL GAP BETWEEN DECK AND METAL TRACK TOP RUNNER WITH FIRESTOP SEALANT. SEAL TIGHTLY AROUND ALL PIPES, CONDUITS, DUCTS, ETC. ON EACH SIDE OF THE FIRE BARRIER WALL (CONTINUOUS) WITH APPROVED FIRESTOP SEALANT INSTALLED AROUND ALL PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE FIRE BARRIER.
- FILL GAP BETWEEN DECK AND METAL TRACK TOP RUNNER WITH ACOUSTIC SEALANT. SEAL TIGHTLY AROUND ALL PIPES, CONDUITS, DUCTS, ETC. ON EACH SIDE OF THE FIRE BARRIER WALL (CONTINUOUS) AND AROUND ALL PENETRATIONS TO MAINTAIN THE INTEGRITY OF THE WALL (CONTINUOUS).
- STOP GYPSUM BOARD 1/4" ABOVE FLOOR DECK. ON EACH SIDE OF WALL, PROVIDED ACOUSTIC SEALANT AROUND ALL PIPES, CONDUITS, DUCTS, ETC. ON EACH SIDE OF THE FIRE BARRIER WALL (CONTINUOUS).
- OUTLET BOX AS OCCURS. PROVIDE FIRE BARRIER MOLDABLE PUTTY PADS AND FIRESTOP SEALANT AROUND ELECTRICAL BOXES AT ALL RATED WALLS AND SOUND PARTITION WALLS. TYPE-X.
- PROVIDE STUDS, SPACERS AND BLOCKING AT FURRING WALL. SEE DETAIL 12/A502A.
- LINE INDICATES EXISTING WALL OR STRUCTURE. PROVIDE 1/4" AIR GAP. GYPSUM BOARD SHAFTE LINEAR PANEL, 1/16" THICK, TYPE-X, ATTACHED TO "C-H" STUDS.
- STUD RUNNER, "J" SHAPED WITH UNEQUAL LEGS OF 1" AND 2", 20 GA, ATTACHED TO FLOOR AND STRUCTURE ABOVE WITH FASTENERS LOCATED NO GREATER THAN 2' FROM ENDS AND NO MORE THAN 24" O.C. RUNNERS SHOULD BE POSITIONED WITH SHORT LEG TO FINISHED SIDE OF WALL.
- STOP STUD RUNNER AT BASE OF STAIR.
- STOP PLATE, 3/4" X 3/4" X 1/4" DIA. MULTI-HY200 EPOXY ANCHORS WITH 1/8" DIA. HOLE, 2-ANCHORS AT 6" O.C.
- TUBE STEEL, 3" X 3/16" AT 6" O.C.
- WALL CAP, SOLID SURFACE MATERIAL ATTACHED TO WALL BELOW.
- PLYWOOD, 3/4" THICK, CONTINUOUS FIRE TREATED, ATTACH PLYWOOD TO VERTICAL STEEL POST WITH L-SHAPED METAL CLIPS AND FASTENERS.
- PROVIDE 1/4" RADIUS ROUNDED EDGE, CONTINUOUS.
- METAL STUDS 16 GA STRUCTURAL (33 MILS) AT 16" O.C. PROVIDE RUNNERS AT TOP AND BOTTOM. ATTACH TOP RUNNER TO PLYWOOD AND VERTICAL STEEL POST.
- LINE OF FLOOR.
- REINFORCED CHANNEL, 2" X 1/2", INSTALLED HORIZONTALLY AND SPACED AT 24" O.C.
- WHERE CONDITIONS PROHIBIT EXTENDING STUDS TO DECK, PROVIDED CROSS BRACING FROM TOP RUNNER OF WALL TO STRUCTURE ABOVE WITH 3-5/8" 20 GA STUDS AT 4'-0" O.C. ALTERNATE DIRECTION OF BRACING TO STRUCTURE EVERY 48" AS CONDITIONS ALLOW.
- TOP TRACK, 18 GA, REQUIRED AT CROSS-BRACED WALLS.




1 Wall Types (Note: See dimension floor plans for locations of wall types used in this project. Some wall types shown above may not be used in this project.)






1 Cabinet Legend
Note: See Interior Elevations (S.I.E.) for occurrence of cabinet types used in this project. Some cabinet type shown above may not be used in this project.

SCALE: 3/8" = 1'-0"




2 Wall Cabinet with Door

SCALE: 1" = 1'-0"




3 Wall Cabinet without Door

SCALE: 1" = 1'-0"




4 Wall Cabinet Door & Shelf

SCALE: 1" = 1'-0"




5 Base Cabinet with Door

SCALE: 1" = 1'-0"




6 Base Cabinet with Drawer and Door

SCALE: 1" = 1'-0"




7 Base Cabinet with Drawers

SCALE: 1" = 1'-0"




8 Base Cabinet with Drawers

SCALE: 1" = 1'-0"



9 Base Cabinet with Two File Drawers

SCALE: 1" = 1'-0"




10 Base Cabinet without Door

SCALE: 1" = 1'-0"

KEYED NOTES

- FILE DRAWER, MINIMUM WIDTH SHALL BE 1'-4" TO HANG FOLDERS (FOR 8-1/2" x 11" SIZE PAPER).
- DETAIL FOR STEEL SUPPORTS FOR COUNTERTOP AT STUD WALLS.
- DETAIL FOR STEEL SUPPORTS FOR COUNTERTOP AT MASONRY AND CONCRETE WALLS.
- STEEL SUPPORT FOR COUNTERTOP. SEE RELEVANT DETAIL FOR STUD WALL, CMU, AND CONCRETE WALL. SUPPORT IS NOT REQUIRED IF THERE IS AN ADJACENT BASE CABINET.
- FILED PANEL FOR EXTENDED WALL CABINET, TYPICALLY LOCATED AT ROOM CORNER.
- SINK. SEE ARCHITECTURAL AND PLUMBING DRAWINGS FOR SINK TYPE.
- PROVIDE END PANEL MATCHING THE FRONT SKIRT PANEL, IF THERE IS A ADJACENT BASE CABINET, END PANEL IS NOT REQUIRED.



KEYED NOTES 

1. END PANEL AT BOTH ENDS TO BE CONTINUOUS WITHOUT BREAK/REVEAL BETWEEN SLANTED FASCIA (DUST TOP) AND WALL OR FULL HEIGHT CABINET.
2. SLANTED FASCIA (DUST TOP), TYPICAL MITERED AT CORNER.

1 Slanted Fascia (Dust Top) Miter Detail at Corner Cabinets

SCALE: 3/4" = 1'-0"

2

Wall Cabinet Fascia

SCALE: 1 1/2" = 1'-0"

KEYED NOTES 

1. LINE OF WALL
2. LINE OF CEILING. SEE REFLECTED CEILING PLAN.
3. BRACE PANEL. PROVIDE BRACE AS REQUIRED TO SUPPORT THE VERTICAL FASCIA PANEL. LOCATE BRACE AT 3'-0" O.C.
4. SLANTED FASCIA PANEL. PLASTIC LAMINATE WRAPPED OVER PLYWOOD.
5. WALL CABINET AS OCCURS.
6. VERTICAL FASCIA, PLASTIC LAMINATE WRAPPED OVER PLYWOOD.

NOTE: FOR SLANTED FASCIA CORNER CONDITION, SEE DETAIL **1/A505B**. SEE INTERIOR ELEVATIONS FOR VERTICAL AND SLANTED FASCIA LOCATIONS.

KEYED NOTES 

1. LINE OF FLOOR.
2. WALL BASE. SEE FINISH SCHEDULE.
3. LINE OF MASONRY OR CONCRETE WALL AS OCCURS.
4. COUNTERTOP SUPPORT, PAINTED. SUPPORT SHALL BE STEEL ANGLE, 2"X2"X1/4", PIECES MITERED AND WELDED @ 90° ANGLE AS INDICATED CHAMFER EXPOSED EDGE (BELOW COUNTERTOP EDGE) AND GRIND ALL EXPOSED EDGES SMOOTH. ATTACH SUPPORT TO MASONRY OR CONCRETE WALL WITH 3/8" EPOXY BOLTS, AS SHOWN. SUPPORTS SHALL BE LOCATED VERTICALLY ON WALL AT 4'-0" O.C. MAXIMUM.
5. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL [6 / A505B](#)
6. PROVIDE GROMMETS AT COMPUTER MONITOR LOCATIONS, KNEE SPACES, COUNTERTOP EQUIPMENT, ETC.
7. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL [6 / A505B](#)

Steel Support For Countertop at Masonry & Concrete Walls

4

SCALE: 1" = 1'-0"

7 Sink with Base Cabinet

SCALE: 1" = 1'-0"

KEYED NOTES 

1. LINE OF WALL, AS OCCURS. IF CABINET IS LOCATED AT AN ISLAND, PROVIDE PLASTIC LAMINATE COVERED BACK PANEL, WHERE EXPOSED. NO BACKSPLASH IS NECESSARY.
2. DOOR PULL. SEE SPECIFICATIONS IN PROJECT MANUAL.
3. PLASTIC LAMINATE CABINET DOOR.
4. WALL BASE. SEE FINISH SCHEDULE.
5. CABINET BASE. COORDINATE WITH ELECTRICAL DRAWINGS FOR POWER, DATA OUTLETS THAT ARE LOCATED HERE.
6. LINE OF FLOOR.
7. SEAL TIGHTLY AROUND PIPE PENETRATIONS WITH CAULKING. PROVIDE STAINLESS STEEL ESCUTCHEON PLATE AROUND DRAIN AND WATER LINES.
8. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL [9 / A505B](#)
9. SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION. SEE DETAIL [6 / A505B](#)
10. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL [6 / A505B](#)
11. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL [3 / A505B](#)

KEYED NOTES

1. LINE OF WALL.
2. KNEE AND TOE CLEARANCE REQUIRED FOR ADA.
3. SKIRT PANEL, PLASTIC LAMINATE REMOVABLE ACCESS PANEL WITH 2" ALUMINUM Z-CLIPS MOUNTED ON BACK SIDE OF PANEL (TOTAL 4 CLIPS - TWO ON EACH SIDE OF PANEL)
4. PLASTIC LAMINATE SUPPORT PANEL, 2" X 2" X 1" THICK X CONT., ANCHORED TO CABINET. THIS PANEL TO BE ON EACH END OF CABINET TO SUPPORT ACCESS PANEL. INSTALL TWO ALUMINUM Z-CLIPS ON EACH SIDE OF CABINET TO SUPPORT ACCESS PANEL. OPENING ABOVE PANEL TO BE KEPT AT MINIMUM JUST ENOUGH TO REMOVE ACCESS PANEL.
5. WALL BASE. SEE FINISH SCHEDULE.
6. LINE OF FLOOR.
7. SEAL TIGHTLY AROUND PIPE PENETRATIONS WITH CAULKING. PROVIDE STAINLESS STEEL ESCUTCHEON AROUND DRAIN AND WATER LINES.
8. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL **6/A505B**
9. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL **6/A505B**
10. SINK. SEE PLUMBING DRAWINGS. SINK SHALL PROVIDE ADA COMPLIANT BOWL DEPTH. SEE DETAIL **9/A505B**
11. PLASTIC LAMINATE FASCIA PANEL.
12. CABINET BODY. ATTACH TO WALL PER TYPICAL DETAIL **3/A505B**

NOTE: PROVIDE STEEL SUPPORT WITHIN ASSEMBLY WHERE COUNTER IS UNSUPPORTED, TYP.

KEYED NOTES 

1. LINE OF WALL.
2. FASTENERS AS REQUIRED. ALIGN WITH STUDS WHERE POSSIBLE.
3. STEEL BACKING PLATE. PLATE SHALL BE 15 GAUGE, 6" WIDE WITH REQUIRED LENGTH TO COVER CABINETS.
4. SOLID WOOD BLOCKING, TYPICALLY ATTACHED TO CABINET BODY.
5. COUNTERTOP AND BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL **6/A505B**
6. CABINET BASE BOX. BOX SHALL BE BUILT WITH PLYWOOD, 3/4" THICK, PRESSURE TREATED. BASE BOX SHALL BE ANCHORED TO FLOOR WITH STEEL "L" CLIPS AND FASTENERS AS REQUIRED. BASE CABINET SHALL BE ATTACHED TO THE BASE BOX.
7. LINE OF FLOOR.
8. NEW WALL (OR EXISTING WALL WHERE OCCURS). SEE WALL TYPE FOR WALL CONSTRUCTION.

NOTE: WHEN CABINETS ARE MOUNTED TO CONCRETE WALL OR MASONRY (CMU BLOCKS) WALL, BACKING PLATES ARE NOT REQUIRED. PROVIDE COMPATIBLE MASONRY WALL ANCHORS AND FASTENERS TO ATTACH THE CABINETS.

The diagram illustrates a cabinet body being attached to a wall. The cabinet is shown in an elevation view, with its front panel and side panels. The attachment points are labeled with hexagonal callouts: 2, 3, 4, 5, 6, and 7. Callout 2 is at the top left, 3 is at the top right, 4 is on the side panel, 5 is at the top center, 6 is at the bottom center, and 7 is at the bottom right. Two vertical dashed lines represent the wall, and a horizontal dashed line represents the floor. A vertical dimension line indicates a height of 6" from the floor to the top of the cabinet. A horizontal dimension line indicates a distance of 4" from the left wall to the center of the cabinet. A vertical dimension line also indicates a height of 6" from the floor to the top of the cabinet. A vertical line on the right is labeled 'SEE INTERIOR ELEVATION' and 'E' at the top. A scale bar at the bottom left indicates a scale of 1" = 1'-0".

KEYED NOTES 


1. LINE OF FLOOR.
2. WALL BASE. SEE FINISH SCHEDULE.
3. WALL. SEE FLOOR PLAN & WALL TYPES.
4. COUNTERTOP SUPPORT, PAINTED. SUPPORT SHALL BE STEEL ANGLE, 2"X2"X1/4", PIECES MITERED AND WELDED @ 90° ANGLE AS INDICATED. CHAMFER EXPOSED EDGES SMOOTH. ATTACH SUPPORT TO METAL STUDS INSIDE WALL WITH 1/4" BOLTS, AS SHOWN. AT FLOOR, PROVIDE 3" WIDE X 6" LONG X 1/4" THICK, BASE STEEL PLATE WELDED TO VERTICAL STEEL ANGLE. ATTACH BASE PLATE TO FLOOR WITH TWO 1/2" DIAMETER ANCHOR BOLTS (ON EITHER SIDE OF THE VERTICAL ANGLE) WITH 3" MINIMUM EMBED IN CONCRETE FLOOR. CONTRACTOR SHALL REVIEW INTERIOR ELEVATIONS AND LOCATE SUPPORTS DURING WALL CONSTRUCTION. SUPPORT SPACING SHALL NOT EXCEED 4'-0" O.C. MAXIMUM.
5. BACKSPLASH. SEE TYPICAL COUNTERTOP DETAIL [6/A505B](#)
6. PROVIDE GROMMETS AT COMPUTER MONITOR LOCATIONS, KNEE SPACES, COUNTERTOP EQUIPMENT, ETC.
7. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL [6/A505B](#)

Steel Support for Countertop at Stud Wall

SCALE: 1" = 1'-0"

KEYED NOTES 

1. STAINLESS STEEL SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION.
2. INTEGRAL MONOLITHIC MATERIAL SINK. SEE PLUMBING DRAWINGS AND ARCHITECTURAL DRAWINGS FOR INTERIOR DIMENSIONS AND LOCATION.
3. COUNTERTOP. SEE FINISH FLOOR PLAN AND INTERIOR ELEVATIONS FOR REQUIRED MATERIAL AT DIFFERENT LOCATIONS. SEE TYPICAL COUNTERTOP DETAIL [6/A5](#).
4. BASE CABINET OR FASCIA PANEL AS OCCURS, SEE INTERIOR ELEVATIONS.
5. LINE OF WALL.
6. SEAL EXPOSED CUT EDGE OF COUNTERTOP WITH SEALER TO PREVENT WATER DAMAGE.
7. PROVIDE SMOOTH AND SEAMLESS TRANSITION WHERE SINK IS ATTACHED TO COUNTERTOP. UNLESS NOTED OTHERWISE, SINK COLOR SHALL MATCH COUNTERTOP COLOR. VERIFY WITH ARCHITECT FOR SINK COLOR IF A MATCH PREFORMED SINK IS NOT AVAILABLE.



A Stainless Steel Sink - Section View

B Integral Monolithic Material Sink - Section View

Stainless Steel Sink - Plan View


Integral Monolithic Material Sink - Plan View

Typical Sink Detail

KEYED NOTES 

1. COUNTERTOP. PLASTIC LAMINATE WRAPPED OVER WOOD SUBSTRATE, 3/4" THICK. SUBSTRATE SHALL BE AS PER ARCHITECTURAL WOODWORK INSTITUTE (AWI) STANDARDS FOR "PREMIUM" GRADE. PROVIDE FULL ROUND EDGE AS INDICATED. WHERE PLASTIC LAMINATE COUNTERTOP IS CALLED OUT AT SINK LOCATIONS, USE EXTERIOR GRADE MARINE PLYWOOD WITH AN IMPERVIOUS SEAL. SEE DETAIL **9/A505B**
2. BACKSPLASH, INTEGRAL. PLASTIC LAMINATE SHALL RUN CONTINUOUSLY FROM COUNTERTOP TO BACKSPLASH. BACKSPLASH SHALL HAVE A 3/4" RADIUS EDGE AT TOP AS INDICATED.
3. PROVIDE FULL ROUND (BULL NOSE) EDGE AT ALL PLASTIC LAMINATE COUNTERTOPS, TYPICAL.
4. BASE CABINET DOOR AS OCCURS.
5. EXPOSED END OF THE COUNTERTOP SHALL BE WRAPPED WITH PLASTIC LAMINATE, UNLESS NOTED OTHERWISE. WHERE INDICATED IN FINISH FLOOR PLANS AND/OR INTERIOR ELEVATIONS, PROVIDE SOLID SURFACE END CAP AS PER DETAIL "E".
6. SIDESPASH. PLASTIC LAMINATE OVER WOOD SUBSTRATE, 3/4" THICK. SUBSTRATE SHALL BE AS PER ARCHITECTURAL WOODWORK INSTITUTE (AWI) STANDARDS FOR "PREMIUM" GRADE. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPASH ABUTS WALL AND COUNTERTOP. UNLESS NOTED OTHERWISE, SIDESPASH IS REQUIRED AT ALL LOCATIONS WHERE COUNTERTOP ABUTS VERTICAL SURFACES SUCH AS WALLS, BUILDING COLUMNS, TALL CABINETS, ETC.
7. COUNTERTOP, MONOLITHIC MATERIAL. ATTACH COUNTERTOP TO BASE CABINET AND/OR STEEL SUPPORTS WHERE OCCURS.
8. PROVIDE 1/8" RADIUS AT ALL EXPOSED EDGE MATERIAL

9. BACKSPLASH, MONOLITHIC MATERIAL. ATTACH BACKSPLASH TO COUNTERTOP TO PERFORM AS INTEGRAL BACKSPLASH. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPASH ABUTS WALL.
10. SIDESPASH, MONOLITHIC MATERIAL. ATTACH SIDESPASH TO WALL. PROVIDE CONTINUOUS CLEAR SEALANT WHERE SIDESPASH ABUTS WALL AND COUNTERTOP. UNLESS NOTED OTHERWISE, SIDESPASH IS REQUIRED AT ALL LOCATIONS WHERE COUNTERTOP ABUTS VERTICAL SURFACES SUCH AS WALLS, BUILDING COLUMNS, TALL CABINETS, ETC.
11. BASE CABINET AS OCCURS. SEE INTERIOR ELEVATIONS. AT KNEE SPACE LOCATIONS AND WHERE THERE ARE NO BASE CABINETS TO SUPPORT THE COUNTERTOP, PROVIDE STEEL SUPPORTS PER DETAILS **4 / A505B** AND **5 / A505B**
12. END CAP. SOLID SURFACE MATERIAL ATTACHED TO COUNTERTOP. PROVIDE MATCHING BULL NOSE EDGE AT FRONT AND 1/8" RADIUS EDGE AS INDICATED.
13. LINE OF WALL.



6 Typical Countertop Detail

SCALE: 1" = 1'-0"

NOTE: SEE INTERIOR ELEVATIONS AND FINISH FLOOR PLANS FOR LOCATIONS OF DIFFERENT COUNTERTOPS ("PL" AND/OR "MM") REQUIRED IN THIS PROJECT.
SEE FINISH SCHEDULE, SHEET A603A, FOR COLOR, STYLE, ETC. FOR VARIOUS COUNTERTOP MATERIALS ("PL" DENOTES PLASTIC LAMINATE AND "MM" DENOTES MONOLITHIC MATERIAL).

KEYED NOTES

1. DRAWER BOTTOM PANEL. SEE SPECIFICATIONS IN PROJECT MANUAL FOR TYPICAL DRAWER CONSTRUCTION.
2. FILE DRAWER BODY.
3. ALUMINUM STRAP (2" WIDE X 1/8" THICK) ATTACHED TO DRAWER BODY WITH FASTENERS AT 6" O.C. SHIM AS REQUIRED.
4. FILE FOLDER, OWNER FURNISHED OWNER INSTALLED ITEM.

5. DRAWER SLIDE.

File Drawer Edge

SCALE: 6" = 1'-0"

1' - 4" 1' - 0" CLEAR

1 1/2" 1 1/2" 1 1/2"

8 1/2" 1' - 0"

1 1/2"


10

File Drawer Section


Detailed description: The image contains two technical drawings of a file drawer. The top drawing is a cross-sectional view of a slide assembly. It shows a grey slide (2) with a metal track (3) attached to its top edge. A small gap of 3/4" is indicated between the slide and the adjacent wall. A lock mechanism (4) is shown at the top right. The bottom drawing is a longitudinal section of the drawer. It shows the slide assembly within a frame. The total width is 1' - 4", and the clear width is 1' - 0". The height of the drawer is 8 1/2", and the handle is located 1 1/2" from the bottom. The slide assembly is 1 1/2" wide. Callouts labeled A point to the top edge of the slide assembly in both drawings.

EYED NOTES 

LINE OF WALL.
EXTEND THIS WALL CABINET TO WALL AS INDICATED.
FIXED SHELF.
OUTLINE OF CABINET THAT OCCURS ON SIDE WALL.
OUTLINE OF CABINET THAT OCCURS ON FRONT WALL.
FILLER PANEL, PLASTIC LAMINATE OVER 3/4" PARTICLE BOARD, AS REQUIRED.



Front Elevation



CABINET SECTION

FRONT WALL

1' - 3" U.N.O. 1"

SEE INTERIOR ELEVATIONS

SEE INTERIOR ELEVATIONS

1

5

5

5

2

5

5

6

4





4


3

A

A


Wall Cabinet - Extended at Corners





KEYED NOTES

1. GYPSUM BOARD, 5/8" THICK, TYPE X; ATTACHED TO PLYWOOD.
2. 7/16" FRIW PLYWOOD SHEATHING.
3. LIGHT GAUGE STUD FRAMING, 16-GAUGE AS REQUIRED.
4. ONE PIECE RUBBER NOSING/TREAD/RISER WITH RAISED DISC PATTERN.
5. STEEL STUD TRACK, 16-GAUGE AS REQUIRED.
6. LINE OF FLOOR.
7. BRACING AS REQUIRED.
8. 1" OSB STAIR TREAD.
9. 5/8" FRIW PLYWOOD DECKING.
10. PREFABRICATED SELF-CLOSING SAFETY GATE, PAINTED "SAFETY YELLOW".
11. SAFETY RAILING AND HANDRAIL, STEEL, PAINTED "SAFETY YELLOW"; PROVIDE MOUNTING PLATE WITH 4 SCREWS PER PLATE ANCHORED ATOP RUBBER TREAD, THROUGH OSB STAIR TREAD AND INTO METAL BACKING.
12. NOT USED.




1 Stair Detail

SCALE: 1" = 1'-0"

KEYED NOTES

1. GYPSUM BOARD, 5/8" THICK, TYPE X; ATTACHED TO PLYWOOD.
2. 7/16" FRIW PLYWOOD SHEATHING.
3. LIGHT GAUGE STUD FRAMING, 16-GAUGE AS REQUIRED.
4. ONE PIECE RUBBER NOSING/TREAD/RISER WITH RAISED DISC PATTERN.
5. STEEL STUD TRACK, 16-GAUGE AS REQUIRED.
6. LINE OF FLOOR.
7. BRACING AS REQUIRED.
8. 1" OSB STAIR TREAD.
9. 5/8" FRIW PLYWOOD DECKING.
10. PREFABRICATED SELF-CLOSING SAFETY GATE, PAINTED "SAFETY YELLOW".
11. SAFETY RAILING AND HANDRAIL, STEEL, PAINTED "SAFETY YELLOW"; PROVIDE MOUNTING PLATE WITH 4 SCREWS PER PLATE ANCHORED ATOP RUBBER TREAD, THROUGH OSB STAIR TREAD AND INTO METAL BACKING.
12. LINE OF WALL.




2 Stair Detail

SCALE: 1" = 1'-0"



KEYED NOTES

1. CONCRETE BASE, SEE STRUCTURAL DRAWINGS.
2. PLYWOOD DECKING, SEE STRUCTURAL DRAWINGS.
3. FLOOR JOIST, SEE STRUCTURAL DRAWINGS.
4. TRUCK SCISSOR DOCK LIFT.



3 Floor Section - Dock Lift

SCALE: 1" = 1'-0"




DOOR SCHEDULE

DOOR #	# OF PANELS	DOOR			FRAME			DETAILS			DOOR #	FIRE RATING (MINUTES)	HARDWARE GROUP	COMMENTS
		W1	W2	HEIGHT	THICKNESS	MATERIAL	TYPE (2/A601A)	DEPTH	MATERIAL	JAMB	HEAD			
A100	2	3'-0"		7'-0"	1 3/4"	WD	A	1	8 1/4"	HM		A100		
A101A	1	3'-0"		7'-0"	1 3/4"	WD	A	1	8 1/4"	HM		A101A	1	
A101B		10'-0"		12'-0"								A101B		
A102A	2	3'-0"		7'-0"	1 3/4"	WD	A	1	8 1/4"	HM		A102A	1	
A102B	1	3'-0"		7'-0"	1 3/4"	WD	A	1	8 1/4"	HM		A102B	1	
A102C	1	4'-0"		7'-0"	1 3/4"	WD	A	1	8 5/8"	HM		A102C	1	

1 Door Types

NOTE: REFER TO 'DOOR SCHEDULE' TABLE FOR DOOR TYPES REQUIRED FOR THIS PROJECT. SOME DOOR TYPE ELEVATIONS INDICATED ABOVE, MAY NOT BE APPLICABLE TO THIS PROJECT.

SCALE: 1/4" = 1'-0"




2 Frame Types

NOTE: REFER TO 'DOOR SCHEDULE' FOR FRAME TYPES REQUIRED FOR THIS PROJECT. SOME FRAME TYPE ELEVATIONS INDICATED ABOVE MAY NOT BE APPLICABLE TO THIS PROJECT.

SCALE: 1/4" = 1'-0"


COMMENTS

1. PROVIDE LOCKING HARDWARE










3 Door Frame in Stud Wall

SCALE: 3" = 1'-0"




FINISH SCHEDULE						GENERAL NOTES			
TAG	FINISH TYPE	SIZE	MATERIAL DESCRIPTION	MANUFACTURER	STYLE	MODEL #	COLOR	COMMENTS	
1. FINISH SCHEDULE									
A. BASIS-OF-DESIGN FOR FINISHES: FINISHES INDICATED ON THE FINISH SCHEDULE ARE BASED ON THE NAMED MANUFACTURER AND THEIR PRODUCTS. SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE THE NAMED PRODUCT OR A COMPARABLE PRODUCT BY ONE OF THE APPROVED MANUFACTURERS LISTED IN THE PROJECT MANUAL. SEE RELEVANT SPECIFICATION SECTION.									
B. SEE 'SAMPLE LAYOUT' INDICATED ON THE FINISH SCHEDULE PLANS FOR CLARIFICATION ON HOW TO LAY OUT FINISHES. FINISHES ARE IDENTIFIED WITH FINISH TAGS FOR FLOORS, WALLS, MISCELLANEOUS SURFACE, ETC. SEE FINISH FLOOR PLANS FOR REQUIRED FINISHES (INDICATED WITH FINISH TAGS SUCH AS F1, B1, W1, ETC.).									
C. LINE OF TRANSITION BETWEEN DIFFERENT TYPES OF FLOOR COVERINGS IS INDICATED ON THE FINISH FLOOR PLANS. IN PLACES WHERE TWO DIFFERENT FLOOR COVERINGS ARE ADJACENT, PROVIDE METAL TRANSITION STRIPS AS THE RELEVANT FLOOR COVERING TRANSITION DETAILS' INDICATED IN THE CONSTRUCTION DOCUMENTS. WHERE TWO ROOMS ARE REQUIRED TO HAVE DIFFERENT FLOOR COVERINGS, LINE OF TRANSITION SHALL TYPICALLY OCCUR BELOW THE CENTERLINE OF THE DOOR LOCATED BETWEEN THE TWO ROOMS, AS THESE ARE THE LINES NOT INDICATED BELOW THE DOOR IN THE FINISH FLOOR PLANS. CONTRACTOR SHALL PROVIDE METAL TRANSITION STRIPS (MANUFACTURED BY SCHLUTER OR EQUIVALENT) AS REQUIRED. AT EXTERIOR DOORS, PROVIDE ALUMINUM THRESHOLD MATCHING THE DOORWAY, FOR REVEAL FINISHES. COORDINATE WITH DEMOLITION FLOOR PLAN AND NEW FLOOR PLAN TO DETERMINE WHERE NEW ABUTS EXISTING FLOOR COVERING THAT IS SCHEDULED TO REMAIN.									
D. LINE OF TRANSITION BETWEEN DIFFERENT TYPES OF WALL FINISH IS INDICATED ON THE INTERIOR ELEVATIONS AND FINISH FLOOR PLANS. FOR REQUIRED WALL PROTECTION TYPE (INDICATED WITH TAG WP1, WP2, ETC.), ON WALLS, COORDINATE WITH FINISH FLOOR PLANS AND INTERIOR ELEVATIONS.									
E. THERE ARE AREAS WHERE SURFACES THAT ARE EXPOSED AND WILL REQUIRE A FINISH. SUCH MISCELLANEOUS SURFACES ARE INDICATED IN THE DRAWINGS WITH FINISH TAGS SUCH AS MS1, MS2, ETC.									
F. PAINT ALL EXPOSED VISIBLE ITEMS SUCH AS METAL DECK, STEEL ANGLES, STEEL BEAMS, STEEL TRUSSES, MISC. STEEL ITEMS, PIPES, CONDUITS, ETC. UNLESS SPECIFIED AS 'NOT TO BE PAINTED'. PAINT COLOR IS DETERMINED BY THE GENERAL FINISH IS REQUIRED. PAINT SURFACES USE FIELD COLORS AND ACCENT COLORS SPECIFIED BY THE ARCHITECT. DO NOT PAINT CONCEALED SURFACES, FINISHED METAL SURFACES, OPERATING PARTS, AND PRE-FINISHED ITEMS. VERIFY PAINTING SURFACE (SUCH AS STEEL, CONCRETE, MASONRY, GYPSUM BOARD, WOOD, ETC.) AND PAINT COLOR (SUCH AS WHITE, BLACK, ETC.) IN THE INTERIOR ELEVATIONS PROJECT MANUAL UNDER RELEVANT SPECIFICATION SECTION. ALL HOLLOW METAL DOOR AND WINDOW FRAMES SHALL BE PAINTED. USE SEMI-GLOSS FINISH ON DOOR FRAMES.									
G. IN ROOMS AND AREAS WHERE GYPSUM BOARD CEILING IS INDICATED, PAINT CEILING WITH THE SAME COLOR PAINT AS ADJACENT WALLS. IN WET ROOMS LIKE SHOWER, BATH, ETC. WHERE EPOXY IS INDICATED AS A REQUIREMENT ON WALLS, PAINT CEILINGS AND SOFFITS WITH EPOXY BASE PAINT. ALL GYPSUM BOARD SOFFITS SHALL BE PAINTED. COORDINATE ACCENT COLOR LOCATIONS WITH ARCHITECT WHEREVER INDICATED.									
H. SEE INTERIOR ELEVATIONS FOR PLASTIC LAMINATE FINISHES OVER CABINETS, COUNTERTOPS, WALLS, ETC. PLASTIC LAMINATE FINISHES ARE INDICATED AS PL1, PL2, ETC. COUNTERTOPS THAT ARE MONOLITHIC MATERIAL (SUCH AS SOLID SURFACE, QUARTZ, ETC. AND NOT PLASTIC LAMINATE WRAPPED) ARE INDICATED AS MM1, MM2, ETC.									
I. WHERE PORCELAIN AND/OR CERAMIC TILE FINISHES ARE INDICATED, PROVIDE METAL EDGE STRIPS (MANUFACTURED BY SCHLUTER OR EQUIVALENT) AT ALL DOORS AND COUNTERTOPS TO COORDINATE WITH FINISH.									
J. IN ROOMS AND AREAS (SUCH AS TOILET ROOMS, SHOWERS, ETC.) WHERE CERAMIC OR PORCELAIN TILES ARE INDICATED FOR WALL AND FLOOR FINISH, INSTALL BOTTOM ROW OF WALL TILE FIRST PER DETAIL 1/A603B. PROVIDE QUARTZ THRESHOLD AT DOORS TO TOILET ROOMS THAT ARE USED BY MULTIPLE USERS. SEE DETAILS 3 & 4 SHEET A603B.									
K. WHERE GYPSUM BOARD WALL ABUTS MASONRY WALL, PROVIDE REVEAL AS PER DETAIL 2/A603B.									
2. COMMENTS									
1. INFORMATION FOR THE FIRST COMMENT									
2. INFORMATION FOR THE SECOND COMMENT									
3. INFORMATION FOR THE THIRD COMMENT									
4. INFORMATION FOR THE FORTH COMMENT									





KEYNOTES



1 MECHANICAL PLAN LEVEL 1 - OVERALL
1' = 10'-0"

12/11/2025 9:52:34 AM



181 E 5000 S, Murray, UT 84107 | 801.330.3148
info@resolutgroup.com | resolutgroup.com


Project #: 250881

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116


MECHANICAL
PLAN LEVEL 1
- OVERALL

M113



KEYNOTES

- CONNECT REFRIGERANT PIPING TO EACH INDIVIDUAL AC UNIT. ALL PIPING SHALL BE INSULATED AND SHALL EXIT THE NEW EXTERIOR WALL AT A SINGLE LOCATION SO THAT ALL PIPING CAN BE ROUTED OVERHEAD TO RISE UP THE EXISTING COLUMN OF THE HANGAR. INSTALL PIPING ON A HORIZONTAL LADDER SUPPORT. USE STRUT CONNECTORS TO ATTACH PIPING TO LADDER SUPPORT. USE A BRIDGE CAP BETWEEN NEW SIMULATOR BUILDING AND EXISTING COLUMN. USE STRUT PIPE CLAMPS TO ATTACH EACH PIPE TO EACH RUNG. ATTACH LADDER TO SIMULATOR BUILDING WITH 3/4" DIA. X 1/2" LONG CONE NUTS AND OTHER COMPATIBLE STRUT CONNECTORS TO BUILD LADDER SUPPORT PIPING EVERY 4 FT VERTICALLY AND HORIZONTALLY BELOW ROOF STRUCTURE.
- ROUTING OF REFRIGERANT PIPING TO PENETRATE ROOF IN THIS LOCATION AND CONNECT TO OUTDOOR UNIT MOUNTED ON ROOF. SEE ARCHITECTURAL FOR FLASHING AND PATCH AND REPAIR DETAILS.
- MOUNT OUTDOOR HEAT PUMP ON MRO INDUSTRIES PLATFORM OR EQUIVALENT AND WIDEN THE STANCHION SUPPORTS TO 10" IN DIAMETER. MOUNT OUTDOOR HEAT PUMP DIRECTLY ABOVE THE EXISTING TRUSS AND THE OTHER TWO LEGS ARE DIRECTLY ABOVE A PURFLIN.
- MOUNT LOUVER 18' 0" ABOVE FINISHED FLOOR.
- PROVIDE A DEDICATED DUCT TO CHARGE TO PREVENT DEBRIS FROM FALLING INTO UNIT. DISCHARGE RETURN AIR INTO HANGAR.
- MOUNT OUTDOOR HEAT PUMP ON MRO INDUSTRIES PLATFORM OR EQUIVALENT.
- MRO INDUSTRIES SHALL PROVIDE SEISMIC AND WIND CALCULATIONS USING A LICENSED ENGINEER. MRO INDUSTRIES SHALL PROVIDE SEISMIC AND WIND CALCULATIONS FOR THE PLATEFORM TO ROOF DECK. PLATEFORM SHALL SIT ON ROOF USING NO PENETRATING BASES. SEISMIC AND WIND RESTRAINT SHALL BE PROVIDED BY THE PLATEFORM TO FASTENERS THROUGH THE ROOF DECK WITH A TIGHT SEAL USING ANCHOR BOLTS AND SEALANT. SEE SEISMIC DESIGN DRAWINGS FOR SEISMIC DESIGN CATEGORY.
- LICENSED ENGINEER SHALL PROVIDE SEISMIC RESTRAINT DESIGN FOR PLATEFORM. SEE STRUCTURAL DRAWINGS FOR SEISMIC DESIGN CATEGORY.



1 ENLARGED MECHANICAL PLAN
1/4" = 1'-0"



181 E 5000 S, Murray, UT 84107 | 801.530.3148
info.resolutgroup.com | resolutgroup.com

Project #: 25081
100% CDS



Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116


12/11/2025 9:52:35 AM

ENLARGED
MECHANICAL
PLAN


M401




4 ROUND DUCT ELBOWS DETAIL
12" = 1'-0"



1 DUCT WITH HIGH EFFICIENCY FITTING DETAIL
12" = 1'-0"



2 RECTANGULAR DUCT LINER DETAIL
12" = 1'-0"




NOTE
USE SPECIFIED SPACING AND NOT LESS THAN ONE
SUPPORT PER BRANCH.
3 ROUND DUCT SUPPORT DETAIL
12" = 1'-0"



181 E 5000 S, Murray, UT 84107 | 801.330.3148
info@resolutgroup.com | resolutgroup.com

Project #: 250881



ID	MANUFACTURER AND MODEL NUMBER	LOCATION	TYPE	AIR			VRF	ELECTRICAL	PHYSICAL			NOTES	
				USAGE	AIRFLOW RATE (CFM)	TOTAL LOAD (BTU/H)			ENTERING TEMP (DBWB)	REFRIGERANT	MOP	MCA	
IDU-1	MITSUBISHI PUHY-P168YNU-A	AVIATION SIMULATION A119	CEILING CASSETTE	HEATING 1236	54000	70/-	R454B	15	1.24	208/160	33/33/12	66	1
IDU-2	MITSUBISHI PUZ-AK48NL	CLINIC AIRCRAFT SIMULATION A118	CEILING CASSETTE	HEATING 1200	60000	70/-	R454B	--	2	208/160	33/33/12	57	1.2

1. PROVIDE ACCESSORY CONDENSATE PUMP. CONDENSATE PUMP IS POWERED BY THE OUTDOOR UNIT.

2. INDOOR UNIT IS POWERED BY OUTDOOR UNIT.

ID	MANUFACTURER AND MODEL NUMBER	DESCRIPTION	AIR			VRF	ELECTRICAL	PHYSICAL			NOTES	
			NOMINAL TONNAGE	USAGE	AMBIENT DESIGN (°F)			LOAD (BTU/H)	REFRIGERANT	MOP	MCA	
ODU-1	MITSUBISHI PUHY-P168YNU-A	AIR COOLED HEAT PUMP	14	HEATING 36	180000	R454B	50	30	460/3/60	69/30/72	759	
ODU-2	MITSUBISHI PUZ-AK48NL	AIR COOLED HEAT PUMP	4	COOLING 100	160000	R454B	67	38	460/3/60	42/14/59	265	

ID	MANUFACTURER AND MODEL NUMBER	LOCATION	USAGE	OUTSIDE/SUPPLY			RETURN/EXHAUST			EFFECTIVE			ELECTRICAL			PHYSICAL			NOTES
				TOTAL/SENSIBLE LOAD (BTU/H)	AIRFLOW RATE (CFM)	ENTERING TEMP DBWB (°F)	LEAVING TEMP DBWB (°F)	STATIC PRESSURE (IN. WATER)	AIRFLOW RATE (CFM)	ENTERING TEMP DBWB (°F)	STATIC PRESSURE (IN. WATER)	SENSIBLE/LATENT (%)	MCA (A)	MOP (A)	MOTOR (HP)	VOLT/PH/Hz	LENGTH/ WIDTH/ HEIGHT (IN)	26 / 23 / 13	
ERV-1	RENEWERA EV PREMIUM M	HANGAR	HEAT 15979/12960 COOL 7707/3283	160	-5/-	45.6/34.6	1	160	75/-	1	160	--	15	15	120/160	26 / 23 / 13	1		

ID	MANUFACTURER AND MODEL NUMBER	LOCATION	TYPE	RECEIVER			ELECTRICAL	PHYSICAL			NOTES	
				MAX FLOW EA PUMP (ACFM)	MAXIMUM PUMP PRESS (PSIG)	RECEIVER SIZE (GAL)		MOTOR QUAN. (HP)	MOTOR SPEED (RPM)	AMPS	VOLT/PH	
AC-1	INGERSOLL RAND P1.5U-A9	HANGAR	RECIPROCATING TWO STAGE	4.6	135	20	HORIZONTAL	1	2	1775	15	120/60

GRILLES, REGISTERS AND DIFFUSERS												
ID	MANUFACTURER	MODEL	MAX NC	DESCRIPTION								
CD-1	TITUS	OMNI	30	SQUARE PLAQUE FACE CEILING DIFFUSERS. REMOVABLE FACE & CORE. C.W./O.B.D. FRAME SHALL BE FOR SURFACE OR LAY-IN MOUNTING AS REQUIRED BY CEILING TYPE. LAY-IN FRAMES HOLE BE 24" x 24", 36" x 12" OR 24" x 24" OR 12" x 12" AS REQUIRED TO FIT CEILING TILE SPACE AVAILABLE.								
RG-1	TITUS	PAR	30	PERFORATED FACE RETURN AIR UNIT. REMOVABLE FACE & CORE. FRAME SHALL BE FOR SURFACE OR LAY-IN MOUNTING AS REQUIRED BY CEILING TYPE. LAY-IN FRAMES HOLE BE 24" x 24", 36" x 12" OR 12" x 12" AS REQUIRED TO FIT CEILING TILE SPACE AVAILABLE. AIR QUANTITY SHALL MATCH ROOM SUPPLY OR EXHAUST AIR QUANTITY.								
SWS-1	TITUS	300	30	DOUBLE DEFLECTION HIGH SIDEWALL SUPPLY REGISTER. VERTICAL FRONT WITH HORIZONTAL REAR DEFLECTION ADJUSTABLE VANES SPACED AT 3/4 INCH O.C. COMPLETE WITH OBD AND REMOVABLE CORE.								
SWR-1	TITUS	355	30	SIDEWALL RETURN AIR GRILLE. HORIZONTAL STATIONARY 35" DEFLECTION VANES SET ON 1/2 INCH CENTER. COMPLETE WITH OBD ADJUSTABLE THROUGH FACE.								



181 E 5000 S, Murray, UT 84107 | 801/530-3148
info@resolutgroup.com | resolutgroup.com

Project #: 25081

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116


2500081
Dec 11, 2025

MECHANICAL
SCHEDULES

M601


GENERAL PLAN SYMBOLS		PLUMBING SYMBOLS		PLUMBING SYMBOLS		PROJECT REQUIREMENTS	
	PLAN REVISION NUMBER		2" NOMINAL PIPE SIZE		PIPE ACCESSORY NOTES	1 THE PROJECT GENERAL NOTES APPLY TO ALL DISCIPLINES.	
	DETAIL NUMBER ON SHEET		ABOVE GROUND PIPING		FCO CLEANOUT	2 REMOVE ALL UNUSED PIPING, DUCTWORK, EQUIPMENT, AND ACCESSORIES.	
	SCHEMATIC NUMBER WHERE DETAIL IS PLACED		BELOW GROUND PIPING		WCO LINE CLEANOUT	3 THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING ALL EXISTING CONDITIONS FOR PLUMBING AND MECHANICAL SYSTEMS WITHIN THE SCOPE OF WORK SPACE AND WITHIN CLOSE PROXIMITY TO THE SCOPE OF WORK SPACE. THE CONTRACTOR WILL FIELD VERIFY AS MUCH AS IS REASONABLE BEFORE THE FINAL BID. AFTER THE FINAL BID THE CONTRACTOR WILL NOTIFY THE OWNER, ARCHITECT, AND MECHANICAL DESIGN ENGINEER IMMEDIATELY UPON DISCOVERY OF EXISTING CONDITIONS THAT MAY AFFECT THE DESIGN.	
	KEYNOTE SYMBOL		(E) EXISTING PIPE TO REMAIN		BACKWATER SWING CHECK	4 WHERE FLOOR DRAINS OCCUR WITH THE LIMITS OF CONSTRUCTION, PREVENT CONSTRUCTION DEBRIS FROM ENTERING DRAIN BODY BY SEALING DRAIN OPENING PRIOR TO START OF WORK. UNSEAL DRAINS AT COMPLETION OF CONSTRUCTION.	
	CONTINUATION SYMBOL		PIPE TO BE DEMOLISHED		CHECK CHECK VALVE	5 COORDINATE INSTALLATION OF PIPING, DUCTWORK, CONDUIT, LIGHTS, CABLE TRAY, STRUCTURE, EQUIPMENT, CEILINGS, ARCHITECTURAL COMPONENTS, AND ANYTHING ELSE PERTAINING TO THE PROJECT TO PREVENT CONFLICTS.	
	POINT WHERE NEW CONNECTS TO EXISTING		DCW DOMESTIC COLD-WATER		BALANCE BALANCING VALVE	6 THE CONTRACTOR SHALL BE FAMILIAR WITH ALL THE CONDITIONS BOTH EXISTING AND THOSE ILLUSTRATED BY THESE DOCUMENTS AND THOSE OF OTHER DISCIPLINES, INCLUDING, BUT NOT LIMITED TO ARCHITECTURAL, CIVIL, ELECTRICAL, VENTILATION, PLUMBING, AND OTHER SYSTEMS INVOLVED ON THIS PROJECT.	
	POINT WHERE EXISTING IS TO BE DEMOLISHED		NPW NON-POTABLE WATER		CIRC CIRCUIT SETTER	7 FINAL PRODUCT SHALL BE A COMPLETE AND FUNCTIONING SYSTEM, AND SHALL CONFORM TO ALL REQUIREMENTS OF APPLICABLE FEDERAL, STATE, AND LOCAL CODES, INCLUDING BUT NOT LIMITED TO THE INTERNATIONAL BUILDING CODE, INTERNATIONAL MECHANICAL CODE, AND INTERNATIONAL PLUMBING CODE.	
	Room 1 ROOM NAME / NUMBER		SCW SOFT COLD - WATER		GATE GATE VALVE	8 LOCATE EQUIPMENT REQUIRING ACCESS 2'-0" MAXIMUM ABOVE CEILING.	
	AREA BEING DEMOLISHED		FCW FILTERED COLD - WATER		QUICK QUICK OPENING VALVE	9 ALL ROOF MOUNTED EQUIPMENT SHALL BE A MINIMUM 10'-0" FROM EDGE OF ROOF.	
	AREA NOT IN CONTRACT		ROS REVERSE OSMOSIS WATER		S/O BALL VALVE	10 COORDINATE INSTALLATION OF DUCTWORK, PIPING AND MECHANICAL EQUIPMENT WITH NEC CLEARANCES INCLUDING THE SPACE ABOVE ELECTRICAL PANELS, TRANSFORMERS AND OTHER ELECTRICAL EQUIPMENT. NO PIPING OR DUCTWORK TO RUN OVER ELECTRICAL PANELS, VFD'S OR MCC'S. PROTECT EQUIPMENT WITH A 42" DEEP ZONE IN FRONT OF PANELS, VFD'S AND MCC'S. PROVIDE PANS IF REQUIRED UNDER PIPING.	
ABBREVIATIONS			ROR REVERSE OSMOSIS WATER		STRAIN FLUID STRAINER	11 FIRE SEAL AROUND DUCT AND PIPING PENETRATIONS OF FIRE RATED WALLS. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR CAULKING AND SEALING ALL PENETRATIONS IN FIRE AND SMOKE RATED PARTITIONS TO MAINTAIN RATINGS. REFER TO SPECIFICATION.	
	DI DEIONIZED WATER		DIR RECIRCULATION		GAS-CNTRL EMERGENCY GAS SHUTOFF	12 PROVIDE SLEEVES AND/OR OPENINGS TO RUN PIPES AND DUCTS THROUGH FOUNDATIONS, FLOORS, WALLS, AND ROOF.	
	DHW DOMESTIC HOT - WATER		DHW140 DOMESTIC HOT - WATER 140		PLUG PLUG VALVE	13 TRANSITION PIPING AND DUCTWORK SIZES TO MATCH THE SIZE OF EQUIPMENT CONNECTION.	
	DHWR DOMESTIC HOT - WATER RECIRCULATION		DHWR140 DOMESTIC HOT-WATER RECIRCULATION 140		GAS COCK GAS SHUTOFF COCK	14 ALL PIPE AND DUCT SIZES SHOWN SHALL BE CONTINUED IN THWTE DIRECTION OF FLOW UNTIL ANOTHER SIZE IS SHOWN.	
	NPHW NON-POTABLE HOT WATER		SS SANITARY DRAIN		REG GAS REGULATOR	15 FOR DETAILS, EQUIPMENT CONNECTIONS, AND PIPE SIZES NOT SHOWN ON THE SEGMENTS, REFER TO DETAILS, SCHEDULES, AND SPECIFICATIONS.	
	V SANITARY VENT		WV SANITARY WET VENT		T/VT/P THERMOSTATIC VALVE	16 INSTALL ALL EQUIPMENT IN ACCORDANCE WITH THE RESPECTIVE MANUFACTURER'S WRITTEN INSTALLATION INSTRUCTIONS, AT A LEVEL OF WORKMANSHIP CONSISTENT WITH THE SPECIFICATIONS.	
	CWV COMBINATION DWV		CD CONDENSATE DRAIN		PRIMER TRAP PRIMER	17 MECHANICAL CONTRACTOR SHALL ENSURE THAT ALL EQUIPMENT IS PROVIDED AND INSTALLED WITH CLEARANCES PER MANUFACTURERS' RECOMMENDATIONS. THE CONTRACTOR SHALL MAINTAIN PROPER SERVICE SPACE FOR COIL PULLS, BAS DEVICES, MAINTENANCE ACCESS, ETC.	
	ID INDIRECT DRAIN		GW GREASE WASTE		M-CNTRL ELEC. CONTROL VALVE	18 INSTALL EXPOSED PIPING AND DUCTWORK AS HIGH AS PRACTICAL IN ROOMS WITHOUT CEILINGS.	
	GV GREASE VENT		OW OIL WASTE		TMV-XT/P MIXING VALVE	19 LOCATIONS OF PIPING, DUCTWORK AND EQUIPMENT, AS INDICATED ON THE DRAWING, ARE APPROXIMATE AND SUBJECT TO MINOR ADJUSTMENTS IN THE FIELD, INCLUDING, BUT NOT LIMITED TO, OFFSETS AND TRANSITIONS. NEW DUCTWORK, PIPING AND EQUIPMENT SHALL BE COORDINATED WITH STRUCTURE, LIGHTS, REFLECTED CEILING PLANS, CABLE TRAY, ELECTRICAL CONDUIT, PLUMBING, MECHANICAL AND FIRE PROTECTION PIPING. ALL OTHER TRADES AND ALL OTHER EXISTING CONDITIONS TO AVOID INTERFERENCE IN THE FIELD.	
	OW OIL VENT		FOR FUEL OIL RETURN		TMVEM EMERGENCY MIXER	20 THE CONTRACTOR SHALL INFORM THE DESIGNER OF ANY PROPOSED DEVIATIONS FROM THE CONTRACT DOCUMENTS.	
	FOS FUEL OIL SUPPLY		FOS FUEL OIL SUPPLY		PRV PRESSURE REDUCING VALVE	21 IF CONTRACTOR ENCOUNTERS MATERIAL WHICH MAY CONTAIN ASBESTOS, IMMEDIATELY STOP WORK IN THIS AREA AND NOTIFY THE OWNER.	
	PD PUMP DISCHARGE		PD PUMP DISCHARGE		METER WATER METER	22 DETAILS REFERENCE ALL SHEETS.	
	SHWR SOLAR WATER RETURN		SHWS SOLAR WATER SUPPLY		METER IRRIGATION METER	23 INSTALL ALL PIPING AND DUCTWORK WITHOUT FORCING OR SPRINGING.	
	RD ROOF DRAIN		RDO ROOF DRAIN OVERFLOW		DOUBLE CHECK VALVE	24 LOCATE VALVING, ACCESSORIES, AND EQUIPMENT IN ACCESSIBLE LOCATIONS. WHERE LOCATED ABOVE HARD CEILING PROVIDE AN ACCESS DOOR IN CEILING. MINIMUM ACCESS DOOR SIZE OF 24" X 24". COORDINATE EXACT LOCATION AND STYLE WITH ARCHITECT. EQUIPMENT SHALL BE LOCATED IN THE CEILING CAVITY SO IT CAN BE SAFELY SERVICED FROM SOMEONE STANDING ON A LADDER PLACED BELOW THE CEILING ACCESS.	
	RDO ROOF DRAIN OVERFLOW		CO2 CARBON DIOXIDE GAS		FLOOR DRAIN DESIGN SIZE	25 WHERE VALVING, ACCESSORIES, OR EQUIPMENT IS LOCATED IN A WALL, PROVIDE AN APPROPRIATELY SIZED ACCESS DOOR. COORDINATE ACCESS DOOR SIZE, LOCATION, AND STYLE WITH ARCHITECT.	
	CO2 CARBON DIOXIDE GAS		HE HELIUM GAS		2 FD-1 IDENTITY TYPE	26 CONTRACTOR TO PROVIDE VALVE IDENTIFICATION AND LOCATION ON ALL CEILING TILES WHERE VALVES ARE LOCATED.	
	IA INSTRUMENT AIR		N2 NITROGEN GAS		2 DFU DRAINAGE FIXTURE UNITS	27 CONTRACTOR TO PROVIDE DELEGATED DESIGN OF SEISMIC BRACING AS A DEFERRED SUBMITTAL. SEE SPECIFICATION 23 0548 - VIBRATION AND SEISMIC CONTROLS FOR HVAC.	
	MA MEDICAL AIR		N20 NITROUS OXIDE GAS		2 FD-3 FLOOR DRAIN W/ DEEP SEAL TRAP		
	MV MEDICAL VACUUM		O2 OXYGEN GAS		2 FD-3P FLOOR DRAIN W/ TRAP PRIMER "P" INDICATES PRIMER CONNECTION		
	N20 NITROUS OXIDE GAS		WAGD WASTE ANESTHESIA GAS DISPOSAL		3 FD-1 FLOOR DRAIN W/ INTEGRAL CLEANOUT		
	O2 OXYGEN GAS		CA COMPRESSED AIR		3 AD-1 AREA DRAIN (NO TRAP)		
	WAGD WASTE ANESTHESIA GAS DISPOSAL		G NATURAL GAS		6 DD-1 DECK DRAIN		
	CA COMPRESSED AIR		LP LIQUID PROPANE		3 HD-1 HUB DRAIN (FUNNEL TYPE)		
	G NATURAL GAS		6 SD-1 COMBINATION DRAIN		3 FS-4 FLOOR SINK		
	LP LIQUID PROPANE		8 SD-12 ROOF DRAIN		6 SD-1 2000 SF RAINFALL SURFACE AREA		
	PIPE RISE / DROP						
EQUIPMENT ABBREVIATIONS						PLUMBING GENERAL NOTES	
AC	AIR CONDITIONING UNIT	ET	EXPANSION TANK			1 ALL WORK DONE SHALL BE PERFORMED WITH WATER CONTROL IN MIND. CONTAINMENT OF WATER IS NECESSARY TO PREVENT WATER FROM DAMAGING AREAS ON FLOORS BELOW.	
ACCU	AIR COOLING CONDENSING UNIT	EW	ELECTRIC WATER HEATER			2 PLUMBING DRAWINGS ARE SCHEMATIC IN NATURE. FIELD VERIFY EXACT PIPE ROUTING AND COORDINATE WITH ALL OTHER TRADES.	
AHU	AIR HANDLING UNIT	FCU	FAN COIL UNIT			3 ALL PIPING IN PLUMBING SHALL BE ARRANGED TO ALLOW MAINTENANCE ACCESS.	
AS	AIR SEPARATOR	FP	FIRE PUMP			4 NO PIPING TO RUN OVER ELECTRICAL PANELS, VFD'S OR MCC'S. PROTECT EQUIPMENT WITH A DEEP ZONE IN FRONT OF PANELS, VFD'S, AND MCC'S.	
B	BOILER	GI	GREASE INTERCEPTOR			5 CONTRACTOR TO PROVIDE VALVE IDENTIFICATION AND LOCATION ON ALL CEILING TILES WHERE VALVES ARE LOCATED.	
CH	CHILLER	GRV	GRAVITY ROOF VENTILATOR			6 PIPING AND ROUTING SHOWN, INCLUDING ALL BELOW FLOOR DECK PIPING IS APPROXIMATE. IT IS UP TO THE CONTRACTOR TO FIELD VERIFY THE EXACT LOCATION AND SIZE OF ALL PIPING.	
CT	COOLING TOWER	HWP	HEATING WATER PUMP			7 INSTALL ALL EQUIPMENT WITH SUFFICIENT CLEARANCE FOR MAINTENANCE PER MANUFACTURERS' RECOMMENDATION.	
CUH	CABINET UNIT HEATER	HRU	HEAT RECOVERY UNIT			8 DRAIN PANS SHALL BE INSTALLED UNDER ANY PIPING THAT MAY CONTAIN WATER INSTALLED IN AN ELECTRICAL, DATA, IT, OR OTHER ROOM WITH SENSITIVE ELECTRICAL EQUIPMENT. THIS INCLUDES, BUT IS NOT LIMITED TO HYDRONIC, WASTE, DOMESTIC, ROOF DRAIN, ETC.	
CHWP	CHILLED WATER PUMP	PRV	POWER ROOF VENTILATOR			9 ALL PIPING UTILIZED IN CONDITIONED AIR STREAMS, CONDITIONED SPACES, OR RETURN AIR PLENUMS SHALL COMPLY WITH NFPA 90A FLAME SPREAD, SMOKE DEVELOPMENT, AND FUEL CONTRIBUTION OF 25/50, RESPECTIVELY, AS WELL AS ALL APPLICABLE BUILDING CODES AND PROJECT SPECIFICATIONS.	
DBP	DOMESTIC WATER BOOSTER PUMP	RE	RETURN/EXHAUST FAN			10 WHERE NON-PLENUM-RATED PIPING IS PERMITTED OR REQUIRED WITHIN CONDITIONED AIR STREAMS, CONDITIONED SPACES, OR RETURN AIR PLENUMS, IT SHALL BE INSULATED TO ACHIEVE NFPA 90A FLAME SPREAD, SMOKE DEVELOPMENT, AND FUEL CONTRIBUTION RATINGS OF 25/50, RESPECTIVELY, AND SHALL COMPLY WITH ALL APPLICABLE BUILDING CODES AND PROJECT SPECIFICATIONS.	
DC	DUCT MOUNTED COIL	RTU	ROOFTOP UNIT				
DCP	DOMESTIC WATER CIRCULATING PUMP	SP	SUMP PUMP				
EF	EXHAUST FAN	UH	UNIT HEATER				
EDC	ELECTRIC DUCT COIL	WH	WATER HEATER				





KEYNOTES

1 TERMINATE CONDENSATE PIPING AT EXISTING FLOOR DRAIN IN THIS APPROXIMATE LOCATION
WITH FIXED AIR GAP.



181 E 5000 S, Murray, UT 84107 | 801.330.3148
info@resolutgroup.com | resolutgroup.com

Project #: 250881

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

12/11/2025 9:52:37 AM



PLUMBING
PLAN LEVEL 1
- OVERALL

P113

1 PLUMBING PLAN LEVEL 1 - OVERALL
1" = 10'-0"

12/11/2025 9:52:37 AM

KEYNOTES
1 EXTEND 1/2" COMPRESSED AIR PIPING FROM AIR COMPRESSOR TO MOTION BASE. FINAL
REGULATORS AND CONNECTION REQUIREMENTS BY OTHERS.



1 ENLARGED PLUMBING PLAN
1/4" = 1'-0"



181 E 5000 S, Murray, UT 84107 | 801.530.3148
info@resolutgroup.com | resolutgroup.com
Project #: 25081
100% CDS
Dec 11, 2025

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

ENLARGED
PLUMBING
PLAN

P401



SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
REFERENCE AND LINE SYMBOLS	
	DETAIL INDICATOR: A5 INDICATES DETAIL NUMBER, E-501 INDICATES DRAWING SHEET WHERE DETAIL IS SHOWN.
	ELEVATION OR SECTION INDICATOR, EXTERIOR: A5 INDICATES ELEVATION OR SECTION NUMBER, E-201 INDICATES DRAWING SHEET WHERE ELEVATION OR SECTION IS SHOWN.
	ELEVATION OR SECTION INDICATOR, INTERIOR: A5 INDICATES ELEVATION OR SECTION NUMBER, E-201 INDICATES DRAWING SHEET WHERE ELEVATION OR SECTION IS SHOWN.
ROOM NAME	ROOM IDENTIFIER WITH ROOM NAME AND NUMBER.
	KEYNOTE INDICATOR.
	REVISION INDICATOR.
	EQUIPMENT INDICATOR.
	MECHANICAL EQUIPMENT INDICATOR: "XX" INDICATES EQUIPMENT TYPE, "MDP" IDENTIFIES EQUIPMENT PANEL IS CIRCUITED TO. REFER TO EQUIPMENT SCHEDULE FOR ADDITIONAL INFORMATION.
	BREAK, STRAIGHT: TO BREAK PARTS OF DRAWING
	BREAK, ROUND
MATCH LINE SEE XX(XXX)	MATCH LINE INDICATOR: CENTER, EXTRA WIDE LINE.
	NEW LINE: MEDIUM LINE.
	HIDDEN FEATURES LINE: HIDDEN, THIN LINE
	EXISTING TO REMAIN LINE: THIN LINE
	DEMOLITION LINE: DASHED, MEDIUM LINE
	PROPERTY LINE: DASHED, WIDE LINE.
	CONTRACT LIMIT LINE: DASHDOT, WIDE LINE.
XXX EF-X	ELECTRICAL EQUIPMENT INDICATOR: "XXX" INDICATES TYPE OF EQUIPMENT OR EQUIPMENT ID, "EF-X" IDENTIFIES MECHANICAL EQUIPMENT BEING SERVED. REFER TO EQUIPMENT SCHEDULE FOR ADDITIONAL INFORMATION.
XX 1LA-3	EQUIPMENT INDICATOR: "XX" INDICATES EQUIPMENT MARK SHOWN ON EQUIPMENT SCHEDULE. "1LA-3" IDENTIFIES PANEL EQUIPMENT IS CIRCUITED TO, REFER TO EQUIPMENT SCHEDULE FOR ADDITIONAL INFORMATION.
	IN-GRADE PULLBOX INDICATOR: "XXXT" INDICATES LABEL SHOWN ON SCHEDULE. "#" IDENTIFIES SEQUENCE NUMBER SHOWN ON SITE AND NUMBER DIAGRAM. REFER TO PLANS AND EXTERIOR PULLBOX SCHEDULE FOR ADDITIONAL INFORMATION.
WIRING METHODS	
	WIRING.
	WIRING TURNED UP OR TOWARDS OBSERVER.
	WIRING TURNED DOWN OR AWAY FROM OBSERVER.
	SINGLE BRANCH CIRCUIT HOME RUN TO PANELBOARD WITH DEDICATED NEUTRAL CONDUCTOR: LETTER AND NUMBER NOTATION IDENTIFY PANEL AND CIRCUIT NUMBER.
	BRANCH CIRCUIT HOME RUN TO PANELBOARD: NUMBER OF ARROWS INDICATES NUMBER OF CIRCUITS. LETTER AND NUMBER NOTATIONS IDENTIFY PANEL AND CIRCUIT NUMBERS. NUMBER IN BOX REFERS TO THE CONDUCTOR AND CONDUIT SCHEDULE.
	LOW VOLTAGE WIRING: DIVIDE, MEDIUM LINE.
	CONDUIT STUB DIMENSION RECORD DRAWINGS AND MARK.
	CONDUCTOR & CONDUIT ("CC") SCHEDULE INDICATOR: "X" INDICATES CONDUCTOR MATERIAL. REFER TO ONE-LINE DIAGRAM.
	ADA ACCESS PUSH PLATE
	JUNCTION BOX.
	JUNCTION BOX, CEILING.
	JUNCTION BOX, SYSTEMS FURNITURE CONNECTION.
	JUNCTION BOX, SYSTEMS FURNITURE POWER CONNECTION.
	PULL BOX.
	CABLE TRAY ABOVE ACCESSIBLE CEILING. "A" DENOTES CABLE TRAY WIDTH, "B" DENOTES CABLETRAY DEPTH, "C" DENOTES CABLE TRAY ELEVATION ABOVE OR BELOW FINISHED SURFACE.
	LADDER RACK
	CABLE J-HOOKS ABOVE ACCESSIBLE CEILING.
	MECHANICAL EQUIPMENT CONNECTION. REFER TO EQUIPMENT SCHEDULE FOR REQUIREMENTS.
	ELECTRIC VEHICLE CHARGING STATION.
	GROUND BUSBAR: REFER TO GROUNDING RISER DIAGRAM FOR ADDITIONAL INFORMATION.
CONDUIT TYPES	
	RIGID NONMETALLIC CONDUIT, POWER 208V
	RIGID NONMETALLIC CONDUIT, POWER 480V
	RIGID NONMETALLIC CONDUIT, POWER 600V
	RIGID NONMETALLIC CONDUIT, COMMUNICATIONS
	RIGID METALLIC CONDUIT, POWER 208V
	RIGID METALLIC CONDUIT, POWER 480V
	RIGID METALLIC CONDUIT, POWER 600V
	RIGID METALLIC CONDUIT, COMMUNICATIONS

SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
WIRING DEVICES	
	RECEPTACLE, SINGLE: NEMA 5-20R.
	RECEPTACLE, DUPLEX: NEMA 5-20R.
	RECEPTACLE, DUPLEX, ABOVE COUNTER: NEMA 5-20R.
	RECEPTACLE, DUPLEX, CEILING: NEMA 5-20R.
	RECEPTACLE, DUPLEX, DEDICATED CIRCUIT: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, DRINKING FOUNTAIN: CONCEAL WATER COOLER RECEPTACLE BEHIND WATER COOLER. SEE MECHANICAL/PLUMBING SHOP DRAWINGS FOR INSTALLATION
	RECEPTACLE, DUPLEX, ISOLATED GROUND: NEMA 5-20R.
	RECEPTACLE, DUPLEX, SWITCHED: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, WET LABEL: "WEATHERPROOF IN USE": NEMA 5-20R.
	RECEPTACLE, DUPLEX, HOSPITAL GRADE: NEMA 5-20R.
	RECEPTACLE, DUPLEX, ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, DUPLEX, HOSPITAL GRADE ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, HOSPITAL GRADE: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, CENTER, EXTRA WIDE LINE: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, HOSPITAL GRADE ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, DUPLEX, RECESSED: NEMA 5-20R.
	RECEPTACLE, DUPLEX, SWITCHED, RECESSED: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, HOSPITAL GRADE: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, HOSPITAL GRADE ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, CONNECTED TO UPS: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, WITH GROUND FAULT CIRCUIT INTERRUPTER, HOSPITAL GRADE: NEMA 5-20R.
	RECEPTACLE, SPECIAL PURPOSE: PROVIDE RECEPTACLE TO MATCH EQUIPMENT PLUG: NEMA 5-20R.
	RECEPTACLE, DRYER: NEMA 14-30R.
	RECEPTACLE, RANGE: NEMA 14-50R.
	MULTI-OUTLET ASSEMBLY: NEMA 5-20R.
	DROP CORD: SEE DETAIL.
	THERMOSTAT.
	FLUSH FLOOR BOX: "#" SHOWN ON DRAWINGS. REFER TO WIRING DEVICE SCHEDULE IN THE ELECTRICAL SPECIFICATIONS FOR CONFIGURATION AND DEVICES.
	FB# = FLOOR NUMBER, D# = DEPTH, A# = AV GANGS
	POWER POLE: "#" SHOWN ON DRAWINGS. REFER TO WIRING DEVICE SCHEDULE IN THE ELECTRICAL SPECIFICATIONS FOR CONFIGURATION AND DEVICES.
	PT# = POLE, THRU GANGS D# = DATA CABLES A# = AV GANGS
	FLUSH FIRE RATED POKE THRU: "#" SHOWN ON DRAWINGS. REFER TO WIRING DEVICE SCHEDULE IN THE ELECTRICAL SPECIFICATIONS FOR CONFIGURATION AND DEVICES.
	CIRCUIT BREAKER, ADJUSTABLE TRIP CURVE: "L"=LONG TIME CURVE ADJUSTMENT, "S"=SHORT TIME CURVE ADJUSTMENT, "I"=INSTANTANEOUS CURVE ADJUSTMENT, "G"=GROUND FAULT ADJUSTMENT. FULLY COMPLIANT WITH NEC 210.13, 215.10 AND 230.95. (ONE-LINE DIAGRAM)
	SWITCH, SINGLE POLE ("X" INDICATES FIXTURES CONTROLLED).
	SWITCH, DOUBLE POLE ("X" INDICATES FIXTURES CONTROLLED).
	SWITCH, THREE-WAY ("X" INDICATES FIXTURES CONTROLLED).
	SWITCH, FOUR-WAY ("X" INDICATES FIXTURES CONTROLLED).
	SWITCH, DOOR.
	SWITCH, KEY OPERATED.
	SWITCH, PILOT LIGHT.
	SWITCH, TIMER OPERATED.
	SWITCH, WEATHERPROOF.
	RECEPTACLE, DUPLEX, TAMPER RESISTANT: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, WITH GROUND FAULT CIRCUIT INTERRUPTER, HOSPITAL GRADE: NEMA 5-20R.
	RECEPTACLE, QUADRUPLE, WITH GROUND FAULT CIRCUIT INTERRUPTER, HOSPITAL GRADE ON EMERGENCY POWER: NEMA 5-20R.
	RECEPTACLE, DUPLEX, WITH GROUND FAULT CIRCUIT INTERRUPTER, CONNECTED TO UPS: NEMA 5-20R.
	WYE CONNECTION (ONE-LINE DIAGRAM).
	DISTRIBUTION PANELBOARD, MOTOR CONTROL CENTER, PLUG-IN BUSWAY, MEDIUM VOLTAGE SWITCHBOARD (ONE-LINE DIAGRAM).
	PANELBOARD (ONE-LINE DIAGRAM).
	PANELBOARD WITH MAIN LUGS ONLY: BUS SIZE AND PHASE AS SHOWN (ONE-LINE DIAGRAM).
	PANELBOARD WITH MAIN CIRCUIT BREAKER: SIZE AND PHASE AS SHOWN (ONE-LINE DIAGRAM).




SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
SITE ELECTRICAL AND COMMUNICATIONS UTILITIES	
	ELECTRIC LINE: THIN LINE: 10 = SINGLE PHASE, 20 = 3-PHASE, 30 = 3-PHASE, O = OVERHEAD, U = UNDERGROUND, P = PRIMARY, S = SECONDARY
	LIGHTNING ARRESTOR.
	UTILITY POLE.
	UTILITY, DISTRIBUTION SWITCH OR SWITCHING STATION.
	UTILITY, PRIMARY ELECTRICAL HAND HOLE.
	UTILITY SERVICES, MANHOLE.
	UTILITY, COMMUNICATIONS MANHOLE.
	UTILITY, ELECTRICAL MANHOLE.
	UTILITY, TELEPHONE MANHOLE.
	PRECAST CONCRETE, COMMUNICATION VAULT.
	PRECAST CONCRETE, ELECTRICAL VAULT.
	PRECAST CONCRETE, TELEPHONE VAULT.
	PRECAST CONCRETE, MANHOLE, TRANSFORMER VAULT.
	PRECAST CONCRETE, PULLBOX.
	IN-GRADE PULLBOX, HAND HOLE, OPTIONS WITH SQUARE OR ROUND CORNERS: REFER TO PLANS AND EXTERIOR PULLBOX SCHEDULE FOR ADDITIONAL INFORMATION.
	SUBSTATION.
	TRANSFORMER.
	DISCONNECT WITH FUSE AND MOTOR STARTER COMBINATION (ONE-LINE DIAGRAM).
	OVERLOAD RELAY (ONE-LINE DIAGRAM).
	STARTER (ONE-LINE DIAGRAM).
	CIRCUIT BREAKER (ONE-LINE DIAGRAM).
	CIRCUIT BREAKER WITH SHUNT TRIP (ONE-LINE DIAGRAM).
	CIRCUIT BREAKER, MOTOR CIRCUIT PROTECTION (ONE-LINE DIAGRAM).
	POWER POLE: "#" SH




SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
LIGHTING	
(W-3)	Fixture identification: (W-3) indicates fixture type as scheduled.
(W-3E)	Fixture identification: Emergency lighting fixture with battery pack and/or generator and/or centralized inverter and/or centralized UPS connection as indicated in plans. (W-3E) indicates fixture type as scheduled.
EM	EMERGENCY.
NL	NIGHT LIGHT: DO NOT SWITCH.
↑	EGRESS DIRECTION ARROW (EXIT SIGNS).
⊗	EXIT SIGN: SINGLE FACE; CEILING MOUNTED
⊗⊗	EXIT SIGN: SINGLE FACE; WALL MOUNTED
⊗⊗	EXIT SIGN: DOUBLE FACE; CEILING MOUNTED
⊗⊗	EXIT SIGN: DOUBLE FACE; WALL MOUNTED
LIGHTING CONTROL	
✳	OCCUPANCY SENSOR, DUAL TECHNOLOGY, OMNI-DIRECTIONAL, CEILING.
✳	OCCUPANCY SENSOR, DUAL TECHNOLOGY, WALL.
✳	OCCUPANCY SENSOR, DUAL TECHNOLOGY, DIRECTIONAL.
(P)	PHOTOCELL.
(P)	PHOTOCELL, WALL MOUNTED.
✳	VACANCY SENSOR, DUAL TECHNOLOGY, OMNI-DIRECTIONAL, CEILING.
✳	VACANCY SENSOR, DUAL TECHNOLOGY, WALL.
✳	CEILING FAN.
✳	SWITCH/OCCUPANCY SENSOR COMBO, DUAL TECHNOLOGY, WALL.
✳	SWITCH/VACANCY SENSOR COMBO, DUAL TECHNOLOGY, WALL.
✳	DIMMER SWITCH/OCCUPANCY SENSOR COMBO, DUAL TECHNOLOGY, WALL.
✳	DIMMER SWITCH/VACANCY SENSOR COMBO, DUAL TECHNOLOGY, WALL.
✳ _{a,b}	LOW VOLTAGE DIGITAL LIGHTING CONTROL SWITCH: LETTER "a,b" INDICATES ZONING WHERE SHOWN (REFER TO PLANS, SCHEDULES, AND DETAILS FOR EXACT BUTTON CONFIGURATION AND PROGRAMMING REQUIREMENTS)
RC	DIGITAL LIGHTING ROOM CONTROLLER
DC	DIGITAL LIGHTING DIMMING CONTROLLER
LC	DIGITAL PLUG LOAD CONTROLLER
LS	LIGHTING NETWORK SWITCH.
NR	LIGHTING NETWORK ROUTER.
SM	LIGHTING NETWORK SEGMENT MANAGER
NB	LIGHTING NETWORK BRIDGE
ET	LIGHTING EMERGENCY TRANSFER DEVICE
CL X	LIGHTING SPACE CONTROL TYPE. X INDICATES TYPE. SEE SCHEDULE / DIAGRAM.
TWO-WAY COMMUNICATIONS	
2WA	TWO-WAY COMMUNICATIONS MAIN CONTROL STATION (ANNUNCIATOR)
RC5	TWO-WAY COMMUNICATIONS REMOTE CALL STATION
▼	DATA CONNECTION: TWO-WAY EMERGENCY COMMUNICATION SYSTEM

SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
FIRE ALARM	
FAA	FIRE ALARM ANNUNCIATOR PANEL.
FACP	FIRE ALARM CONTROL PANEL, SEMI-RECESSED.
FATC	FIRE ALARM TERMINAL CABINET: NAC, SLC, SPEAKER CIRCUITS; AMPLIFIERS, BATTERIES
HVAC	CONTROL PANEL FOR HVAC: SMOKE CONTROL, STAIR PRESSURIZATION.
EVAC	VOICE EVACUATION PANEL.
PRE	PRE-ACTION CONTROL PANEL.
MIC	REMOTE VOICE EVACUATION MICROPHONE.
FPC	FIRE PUMP CONTROLLER.
JPC	JOCKEY PUMP CONTROLLER.
C	AUTOMATIC DOOR CLOSERS: DOOR CLOSERS SHALL BE FURNISHED WITH DOOR HARDWARE AND CONNECTED BY FIRE ALARM INSTALLER.
CM	CONTROL MODULE.
MM	MONITOR MODULE.
F	FIRE ALARM MANUAL PULL STATION.
R	SHUT DOWN RELAY: INSTALL RELAY IN CONTROL CIRCUIT OF EQUIPMENT TO BE CONTROLLED IN THE EVENT OF A FIRE.
FS	WATER FLOW SWITCH: FLOW SWITCHES SHALL BE PROVIDED AND INSTALLED BY FIRE SPRINKLER CONTRACTOR AND SHALL BE CONNECTED TO LOCATIONS SHOWN ON THE FIRE SPRINKLER SHOP DRAWINGS.
VS	VALVE SUPERVISORY SWITCH, TAMPER SWITCH: TAMPER SWITCHES SHALL BE PROVIDED AND INSTALLED BY FIRE SPRINKLER CONTRACTOR AND SHALL BE CONNECTED TO LOCATIONS SHOWN ON THE FIRE SPRINKLER SHOP DRAWINGS.
PS	PRESSURE SUPERVISORY SWITCH: PRESSURE SWITCHES SHALL BE PROVIDED AND INSTALLED BY FIRE SPRINKLER CONTRACTOR AND SHALL BE CONNECTED TO LOCATIONS SHOWN ON THE FIRE SPRINKLER SHOP DRAWINGS.
○	MAGNETIC DOOR HOLDER.
○	DETECTOR, SMOKE.
○	DETECTOR, SMOKE, WALL MOUNTED.
○ _A	DETECTOR, SMOKE WITH AUXILIARY CONTACT.
○ _{BR}	DETECTOR, SMOKE, BEAM RECEIVER.
○ _{BT}	DETECTOR, SMOKE, BEAM TRANSMITTER.
○ _E	DETECTOR, SMOKE, ELEVATOR RECALL DESIGNATION.
○ _G	DETECTOR, SMOKE WITH GUARD.
○ _R	DETECTOR, SMOKE, RESIDENTIAL.
○ _S	DETECTOR, SMOKE WITH STROBE.
○ _{RS}	DETECTOR, SMOKE, RESIDENTIAL WITH SOUNDER BASE.
○ _{AS}	DETECTOR, SMOKE, AIR SAMPLING SYSTEM PORT LOCATION.
○	DETECTOR, SMOKE, DUCT WITH HOUSING AND SAMPLING TUBE.
SD	SMOKE DAMPER: 120V POWER FROM ELECTRICAL SYSTEM.
○ _{FSD}	COMBINATION FIRE/SMOKE DAMPER: 120V POWER FROM ELECTRICAL SYSTEM.
RTS	REMOTE ALARM INDICATING AND TEST SWITCH.
○	DETECTOR, HEAT.
○	DETECTOR, CARBON MONOXIDE.
○	STROBE, WALL MOUNTED.
○ ₇₅	STROBE, WALL MOUNTED. SUBSCRIPT INDICATES CANDELA RATING.
○ _{WP}	ALARM, HORN/SPEAKER, WALL MOUNTED, WEATHERPROOF.
○ ₁	ALARM, HORN/STROBE, WALL MOUNTED, ONE ASSEMBLY.
○ ₇₅	ALARM, HORN/STROBE, WALL MOUNTED, ONE ASSEMBLY. SUBSCRIPT INDICATES CANDELA RATING.
○ _C	ALARM, CHIME/STROBE, WALL MOUNTED, ONE ASSEMBLY.
○ _G	ALARM, HORN/STROBE WITH GUARD, WALL MOUNTED, ONE ASSEMBLY.
○ _M	ALARM, MINI HORN/STROBE, WALL MOUNTED, ONE ASSEMBLY.
○	SPEAKER, WALL MOUNTED, EVACUATION.
○	SPEAKER, WALL MOUNTED, EVACUATION, COMBINATION STROBE.
○ ₇₅	SPEAKER, WALL MOUNTED, EVACUATION, COMBINATION STROBE. SUBSCRIPT INDICATES CANDELA RATING.
○ ₇₅	ALARM, HORN/STROBE, ONE ASSEMBLY, CEILING MOUNTED. SUBSCRIPT INDICATES CANDELA RATING.
○ ₇₅	ALARM, HORN, CEILING MOUNTED. SUBSCRIPT INDICATES CANDELA RATING.
○ ₇₅	SPEAKER/STROBE, CEILING MOUNTED. SUBSCRIPT INDICATES CANDELA RATING.
○	SPEAKER, CEILING MOUNTED.
○ ₇₅	ALARM, STROBE, CEILING MOUNTED. SUBSCRIPT INDICATES CANDELA RATING.
○	BELL, ELECTRIC, 120V FROM ELECTRICAL SYSTEM OR 24V FROM FIRE ALARM SYSTEM


SYMBOLS LEGEND	
SYMBOL	DESCRIPTION
CLOCK	
○○	CLOCK.
○○ _G	CLOCK, SURFACE WITH WIRE GUARD.
NURSE CALL	
○	JUNCTION BOX.
○	CORRIDOR LIGHT.
○	BATHROOM PULL CORD STATION.
○	DUTY STATION.
○	EMERGENCY ASSISTANCE CALL STATION.
○ _{CB}	EMERGENCY ASSISTANCE CODE BLUE CALL STATION.
○	PATIENT STATION.
○	STAFF STATION.
○	TOUCH SCREEN NURSE CALL MASTER STATION.
○	ZONE LIGHT CONTROLLER.
○	NURSE CALL AREA CONTROL UNIT & POWER SUPPLIES.
TV DISTRIBUTION	
—T—	TV DISTRIBUTION CABLE, INDIVIDUAL DROPS.
—TR—	TV DISTRIBUTION CABLE, TRUNK.
○	COMBINER.
○	DIRECTIONAL COUPLER.
○	DISTRIBUTION AMPLIFIER (ONE-LINE DIAGRAM).
○	SPLITTER (ONE-LINE DIAGRAM).
○	TV OUTLET.
○	SATELLITE ANTENNA.
○	TV ANTENNA (ONE-LINE DIAGRAM).
—WW—	TERMINATOR, 75 OHM (TV DISTRIBUTION).
○ _X	CONDUIT STUBBED TO ACCESSIBLE CEILING PROVIDED BY HDMI CABLE BETWEEN HDMI RECEPTACLES. "X" INDICATES QUANTITY OF HDMI PORTS WHEN GREATER THAN 1.



3 TYPICAL CONDUIT RACK DETAIL
SCALE: NTS



2 RECESSED FIXTURE MOUNTING DETAIL
SCALE: NTS




NOTES:
1. TYPICAL FOR WOOD AND METAL STUD ROUGH-IN.
2. PLASTER RINGS NOT SHOWN.
3. LOCATE ALL OUTLET BOXES IN ACCORDANCE WITH ARCHITECTURAL AND MECHANICAL DRAWINGS AND WITH ALL APPLICABLE SHOP DRAWINGS.
4. IN ACCORDANCE WITH IBC 714.3.2 EXCEPTION 1, OUTLETS ON OPPOSITE SIDES OF WALLS OR PARTITIONS IN THE SAME STUD SPACE IN A RATED FIRE SEPARATION WALL MUST BE SEPARATED BY A MINIMUM OF 24" HORIZONTAL DISTANCE OR LISTED, SOUND AND FIRE RATED PUTTY PADS SHALL BE USED ON THE OUTLET BOXES.
5. IN NON-RATED WALLS, OUTLETS ON OPPOSITE SIDES OF WALLS OR PARTITIONS MUST BE SEPARATED BY 16" FOR SOUND ATTENUATION.


1 TYPICAL ROUGH-IN REQUIREMENTS DETAIL
SCALE: NTS




7 FIRE STOP FOR METAL
CONDUIT THROUGH
GYPSUM WALL BOARD
SCALE: NTS



5 TYPICAL FIRE STOP FOR
CABLES/CONDUIT THROUGH
CONCRETE WALLS
SCALE: NTS



4 TYPICAL RACEWAY SUPPORT METHODS DETAIL
SCALE: NTS







6 TYPICAL FIRE STOP FOR
CABLES/CONDUIT THROUGH
CONCRETE FLOORING
SCALE: NTS





GENERAL SHEET NOTES

- 1 MOUNTING HEIGHTS OF ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE FOLLOWING ORDER OF PRIORITY:
A - ELEVATIONS (ARCHITECTURAL, ELECTRICAL, MECHANICAL, ETC).
B - EQUIPMENT SHOP DRAWINGS.
C - FIELD INSTRUCTIONS.
- 2 LOCATE RECEPTACLES SERVING THE SAME TYPE OF USE AT A UNIFORM HEIGHT UNLESS DIRECTED OTHERWISE.
- 3 MECHANICAL, ELECTRICAL, AND COMMUNICATION ROOMS: COORDINATE LOCATION OF LIGHTING AND POWER RECEPTACLES WITH EQUIPMENT, PIPING, AND DUCTWORK. DO NOT INSTALL RECEPTACLES BEHIND EQUIPMENT OR WHERE OTHERWISE INACCESSIBLE. POSITION LIGHTING REGARDLESS OF WHERE SHOWN ON DRAWING TO PROVIDE PROPER ILLUMINATION.
- 4 MOUNT RECEPTACLE BOXES FOR SWITCHES AND RECEPTACLES WITH LONG AXIS OF THE DEVICE VERTICAL UNLESS OTHERWISE INDICATED.
- 5 SET BOXES WITH PLASTER RINGS FLUSH WITH FINISHED SURFACE.
- 6 LOCATE BOX COVERS OR DEVICE PLATES SO THEY WILL NOT SPAN DIFFERENT TYPES OF BUILDING FINISHES EITHER VERTICALLY OR HORIZONTALLY.
- 7 VERIFY ALL DOOR CONDITIONS ON ARCHITECTURAL DRAWINGS PRIOR TO INSTALLING SWITCHES.
- 8 LOCATE WIRING DEVICES WHICH ARE ADJACENT AND ARE COMPATIBLE VOLTAGES IN ONE PLATE.
- 9 WHERE DEVICES ARE LOCATED IN CLOSE PROXIMITY OF THE SAME VERTICAL PLANE, ALIGN DEVICES VERTICALLY PER THE TYPICAL WALL MOUNTED DEVICES ALIGNMENT DETAIL, UNLESS OTHERWISE INDICATED.




C4 COMMUNICATIONS MOUNTING DETAILS






TYPICAL LABELING FOR PANELBOARDS
IN NON-PUBLIC LOCATIONS




TYPICAL LABELING FOR SWITCHBOARDS



TYPICAL LABELING FOR DISCONNECTS

1 LEVEL 1 OVERALL POWER PLAN

SCALE: 1/8" = 1'-0"



GENERAL SHEET NOTES

- 1 PROVIDE DEDICATED NEUTRALS FOR ALL BRANCH CIRCUITS.
- 2 PROVIDE NEW TYPED PANEL SCHEDULES FOR ALL PANELS AFFECTED BY THE PROJECT.
- 3 UNLESS OTHERWISE NOTED, CONTRACTOR SHALL PROVIDE ALL DISCONNECTS AND MAKE FINAL EQUIPMENT CONNECTIONS. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT VENDORS AND ALL EQUIPMENT INSTALLATION REQUIREMENTS.

NJRA
ARCHITECTS

NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



SHEET KEYNOTES

- 1 PROVIDE NEW 20A/2P CIRCUIT BREAKER IN EXISTING SIEMENS PANEL.

SPECTRUM
ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
801-328-5177
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Intermountain Health
Intermountain Life Flight
Life Flight Simulator


2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025

LEVEL 1
OVERALL
POWER PLAN

EP100

1 LEVEL 1 POWER PLAN
SCALE: 1/4" = 1'-0"



GENERAL SHEET NOTES

- 1 PROVIDE DEDICATED NEUTRALS FOR ALL BRANCH CIRCUITS.
- 2 PROVIDE NEW TYPED PANEL SCHEDULES FOR ALL PANELS AFFECTED BY THE PROJECT.
- 3 UNLESS OTHERWISE NOTED, CONTRACTOR SHALL PROVIDE ALL DISCONNECTS AND MAKE FINAL EQUIPMENT CONNECTIONS. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT VENDORS AND ALL EQUIPMENT INSTALLATION REQUIREMENTS.

NJRA
ARCHITECTS

NJRA Architects, Inc.
5223 S. Ascension Way, Suite 350
Murray, Utah 84123
801.364.9259
www.njraarchitects.com



SHEET KEYNOTES

- 1 PROVIDE RECEPTACLES AND DATA NEAR BASE OF FUSELAGE. RUNNING POWER/DATA INTO THE FUSELAGE WILL NEED TO BE COORDINATED WITH OWNER.
- 2 PROVIDE FSR PWB-100 RECESSED TV BACKBOX FOR POWER/DATA RECEPTACLES BEHIND TV.
- 3 PANEL MP WILL BE FURNISHED BY EQUIPMENT VENDOR. CONTRACTOR TO CONNECT POWER TO PANEL. LOAD SIDE CONNECTIONS TO THE SIMULATION EQUIPMENT WILL BE INSTALLED BY THE VENDOR.

SPECTRUM
ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025

LEVEL 1
POWER PLAN


EP101




GENERAL SHEET NOTES


- 1 PROVIDE DEDICATED NEUTRALS FOR ALL BRANCH CIRCUITS.
- 2 PROVIDE NEW TYPED PANEL SCHEDULES FOR ALL PANELS AFFECTED BY THE PROJECT.
- 3 UNLESS OTHERWISE NOTED, CONTRACTOR SHALL PROVIDE ALL DISCONNECTS AND MAKE FINAL EQUIPMENT CONNECTIONS. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT VENDORS AND ALL EQUIPMENT INSTALLATION REQUIREMENTS.

SHEET KEYNOTES





DATA DEVICE DROP SCHEDULE - LEVEL 2 TDR				
DATA DEVICE TYPE	DETAIL LOCATION	COMM ROOM LOCATION	TOTAL BY FLOOR	NUM. OF DROPS
Level 1				
CEILING DATA (2-DROP)	EXISTING TDR		2	4
CEILING WIRELESS ACCESS POINT (2-DROP)	EXISTING TDR		4	8
FLOOR DATA (4-DROP)	EXISTING TDR		3	12
WALL DATA (2-DROP)	EXISTING TDR		4	8
WALL DATA (4-DROP)	EXISTING TDR		2	8
Grand total			15	40



TYPICAL EQUIPMENT RACK
ELEVATION DETAIL, EXISTING TDR
1 SCALE: NTS




PINNING (T568B)


<u>PIN #</u>	<u>RP-COLOR</u>
#5	T1-W/BL
#4	R1-BL/W
#1	T2-W/O
#2	R2-O/W
#3	T3-W/GR
#6	R3-GR/W
#7	T4-W/BR
#8	R4-BR/W

The logo for Spectrum Engineers. It features a circular graphic on the left composed of overlapping colored bands in blue, green, yellow, and red. To the right of the graphic, the word "SPECTRUM" is written in a large, bold, blue sans-serif font. Below "SPECTRUM", the word "ENGINEERS" is written in a smaller, blue sans-serif font.

TYPICAL VOICE/DATA OUTLET PINNING DETAIL



TYPICAL 2-PORT WIRELESS ACCESS POINT



TYPICAL 4-PORT WALL DATA OUTLET




Diagram illustrating a 48-port patch panel with numbered ports and a panel-mounted equipment rack.

Annotations:


- NUMBERED PORT LABELS, BY INSTALLER (TYP)
- CAT 6A, RJ-45 INSERT, DATA/ WIRELESS (TYP)
- PATCH PANEL LABEL (EXAMPLE ONLY)
- 1RU ANGLED PA
PANEL MOUNTED
EQUIPMENT RAC

The patch panel features 48 numbered ports (1 through 48) with corresponding labels on the front panel. The panel is labeled "SIEMON". The panel is mounted in a "1RU ANGLED PA" (Panel Mounted Equipment Rack) unit.

6 STATION PATCH PANEL DETAIL (SPP1)

SCALE: NTS

5 TYPICAL CABLE IDENTIFICATION WRAP AROUND DETAIL



TYPICAL 2-PORT WALL DATA OUTLET


GENERAL SHEET NOTES

1. PROVIDE NEMA 3R ENCLOSURES FOR EQUIPMENT LOCATED OUTDOORS. REFER TO PLANS FOR EQUIPMENT LOCATIONS.
2. REFER TO PLANS FOR CONSTRAINTS ON PHYSICAL DIMENSIONS AND CLEARANCE REQUIREMENTS OF EQUIPMENT. PROVIDE EQUIPMENT DIMENSIONS THAT FALL WITHIN THE CONSTRAINTS OF EACH SPECIFIC LOCATION.
3. ALL EQUIPMENT SHALL BE CONSTRUCTED AND BRACED FOR THE SEISMIC CONDITIONS OF THE PROJECT. REFER TO ELECTRICAL SPECIFICATIONS FOR REQUIREMENTS.
4. PROVIDE PERFORMANCE TESTING FOR GROUND-FAULT PROTECTION SYSTEMS ON SITE WITH A WRITTEN RECORD OF THIS TEST SUBMITTED TO THE AUTHORITY HAVING JURISDICTION PER NEC 230.95(C).

SHEET KEYNOTES

1. PROVIDE NEW BREAKER IN EXISTING SIEMENS PANEL.

BRANCH CIRCUIT CONDUCTOR AND CONDUIT SIZING TABLE

CIRCUIT AMPACITY/VOLTAGE	CIRCUIT LENGTH	CONDUCTOR SIZE (PHASE, NEUTRAL AND GR)	CONDUIT SIZE
20A/120V	0' - 60'	#12 AWG	0.75" Ø
20A/120V	60' - 95'	#10 AWG	0.75" Ø
20A/120V	95' - 150'	#8 AWG	1" Ø
20A/120V	150' - 240'	#6 AWG	1.25" Ø
20A/277V	0' - 140'	#12 AWG	0.75" Ø
20A/277V	140' - 220'	#10 AWG	0.75" Ø
20A/277V	220' - 350'	#8 AWG	1" Ø
20A/277V	350' - 550'	#6 AWG	1.25" Ø

NOTES:

1. WIRE SIZING IS BASED ON COPPER CONDUCTORS SUPPLYING A 20A, 120V CIRCUIT AT THE INDICATED VOLTAGE, ASSUMED TO BE 80% LOADED (16A), WITH MAXIMUM VOLTAGE DROP OF 3% AT THE LOAD.
2. DOWN-SIZED WIRE AT DEVICE/LOAD AS REQUIRED AND TERMINATE CONDUCTORS IN A SAFE AND CODE COMPLIANT MANNER.
3. CONDUIT SIZE IS BASED ON A MAXIMUM OF 3 CIRCUITS PER CONDUIT, EACH WITH A SEPARATE NEUTRAL CONDUCTOR.

EQUIPMENT NAMEPLATE SCHEDULE

EQUIPMENT ID SCHEME	FIRST DIGIT - BUILDING LEVEL (0, 1, 2, ETC) SECOND DIGIT - PANEL TYPE M - MECHANICAL H - (277480) L - LIGHTING E - EMERGENCY S - STANDBY O - EQUIPMENT U - UPS K - KITCHEN (120/208) THIRD DIGIT - BUILDING AREA (A, B, C, ETC) FOURTH DIGIT - SEQUENCE # (1,2,3,...)
---------------------	--

LABEL FORMAT	[NAME] [SYSTEM] [VOLTAGE] [FED FROM] [SOURCE(S)]
--------------	--

LABEL EXAMPLE	PANEL 100-A ¹ STANDBY POWER 120/208V FED FROM BUS-A / XFMR 4TA
---------------	---

BUSWAY	LABEL BUSWAY EVERY 6' WHERE EXPOSED TO VIEW AND EVERY 15' WHERE NOT EXPOSED TO VIEW
--------	--

OTHER	
-------	--

COLOR SCHEME

SYSTEM	EQUIPMENT	NAMEPLATE COLOR	
		TEXT	BACKGROUND
NORMAL POWER	ALL GEAR NOT INCLUDED BELOW	WHITE	BLACK
STANDBY POWER	MDPS1 AND ALL DOWNSTREAM GEAR, WHITE EXCEPT UPS GEAR AS NOTED	WHITE	ORANGE
EMERGENCY POWER	GDP1, GDP2, ATS-E AND ALL DOWNSTREAM GEAR	WHITE	RED
LEGALLY-REQUIRED STANDBY POWER	ATS-S AND ALL DOWNSTREAM GEAR	RED	WHITE
UPS "A" POWER	UPSA AND ALL DOWNSTREAM GEAR	WHITE	BLUE
UPS "B" POWER	UPSb AND ALL DOWNSTREAM GEAR	BLACK	YELLOW


COPPER CONDUCTOR AND CONDUIT SCHEDULE

SCHEDULE NUMBER	(E.G. 1G)
SUBSCRIPT (NOTE 5)	(E.G. 1G)

CONDUCTOR AND CONDUIT SCHEDULE NOTES

1. CONDUCTORS SHOWN ARE SHOWN FOR EACH CONDUIT WITH MODIFICATIONS AS NOTED IN NOTE 5. ALL CONDUCTORS SHOWN ARE THIN UNLESS OTHERWISE NOTED.
2. PROVIDE EQUIPMENT GROUND CONDUCTORS PER TABLE 250-122 WHEN CIRCUIT BREAKERS ARE SIZED GREATER THAN AMPERE RATING SHOWN IN TABLE.
3. PROVIDE #10 NEUTRALS FOR MULTIWIRE BRANCH CIRCUITS SERVING COMBINED LOADS.
4. GROUND (G) CONDUCTOR MAY BE DELETED ON SERVICE ENTRANCE CONDUCTORS.
5. SYMBOL SUBSCRIPTS:
"2N": INCLUDE TWO NEUTRAL CONDUCTORS AS SCHEDULED FOR PHASE AND NEUTRAL CONDUCTORS WHERE THE CONDUCTOR IS #10 OR LARGER. INCLUDE A SINGLE 200% RATED CONDUCTOR THAT IS TWICE THE IMPACT OF THE SCHEDULED PHASE AND NEUTRAL CONDUCTOR WHERE THE CONDUCTOR IS BELOW #10 IN SIZE.
"CI": PROVIDE CIRCUIT INTEGRITY CABLE: TYPE TWO-HOUR FIRE RESISTIVE CABLES IN CONDUIT OR PROVIDE FEEDER ENCASED IN CONCRETE.
"FG": FULL SIZE GROUND, SIZE EQUIPMENT GROUND CONDUCTOR TO BE SAME SIZE AS THE PHASE CONDUCTORS.
"HH": NEUTRAL CURRENTS EXIST DUE TO HIGH HARMONIC "NONLINEAR" LOADS. CURRENT CARRYING CONDUCTORS DERATED ACCORDINGLY. PROVIDE THE IGHH SIZE FOR THE EQUIPMENT GROUNDING CONDUCTOR.
"IG": INCLUDE IG INSULATED/ISOLATED GROUND CONDUCTOR SCHEDULED ALONG WITH THE GROUND OF EQUIPMENT GROUND CONDUCTOR.
"MC": PROVIDE FEEDER IN METAL-CLAD CABLE: TYPE MC IN PLACE OF SINGLE CONDUCTORS IN CONDUIT.
"SE": SUBSTITUTE "SE" CONDUCTOR FOR "G" CONDUCTOR SHOWN, WHICH IS SIZED FOR THE GROUNDING OF THE SECONDARY OF THE SEPARATELY DERIVED SYSTEM.
"SER": PROVIDE SERVICE-ENTRANCE CABLE: TYPE SE OR SER IN PLACE OF SINGLE CONDUCTORS IN CONDUIT.
6. CONDUCTOR AND CONDUIT SCHEDULE NOTES

SYM	AMP	AMPS	HH	CONDUT	CONDUT (NOTE 1)		
					QTY	SIZE	G
1	20	-	0.75	2	12	12	8
2C	20	-	0.75	3	12	12	8
3C	20	-	0.75	4	12	12	8
4C	30	-	0.75	2	10	10	8
5C	30	-	0.75	3	10	10	8
6C	30	-	0.75	4	10	10	8
7C	40	-	1	8	10	8	6
8C	40	-	1	3	8	10	6
9C	40	-	1	4	8	10	6
10C	55	-	1	2	6	10	8
11C	55	-	1	3	6	10	8
12C	60	-	1.25	4	6	10	8
13C	70	-	1	2	4	8	2
14C	70	-	1.25	3	4	8	2
15C	70	-	1.25	4	4	8	2
16C	85	-	1.25	2	8	3	2
17C	85	-	1.25	3	8	3	2
18C	85	-	1.25	4	3	8	3
19C	95	-	1.25	3	2	8	2
20C	95	-	1.25	4	2	8	2
21C	130	-	1.5	3	1	2	2
22C	130	-	1.5	4	1	6	2
23C	150	-	2	3	1/0	6	2
24C	150	-	2	4	1/0	6	2
28C	200	-	180	2.5	4	3/0	2
29C	230	-	2.5	3	4/0	4	2
30C	230	-	208	2.5	4	4/0	4
34C	310	-	280	3	4	350	3
35C	380	-	3	3	500	3	3/0
37C	400	-	2.5	3	3	3/0	2
38C	400	-	280	2.5	4	3/0	3
42C	620	-	560	2.5	4	350	1/0
52C	1240	-	1120	4	4	350	3/0
53C	1675	-	1520	5	4	400	4/0



FLOORBOX SCHEDULE

FLOORBOX SCHEDULE

USE

CFG CONCRETE FLOOR, ON GRADE

CONNECTIONS

C1 RECESSED CABLE CONNECTIONS BELOW FLOOR WITH HINGED LID FOR ACCESS THAT CAN BE CLOSED WHILE IN USE.

COVER

CV1 FLANGED WITH CARPET INSERT FOR CARPET AREAS, FLANGELESS FLUSH GRAY BRUSHED ALUMINUM LID

FINISH

AL ALUMINUM

FLOORBOX COVER SHAPE

FLOORBOX GANGS

DATA CABLES

A/V GANGS

FB#.D#.A#

NO...

1

2

ID	DESCRIPTION	SIZE (NOMINAL)	DEVICE / GANGS						USE	CONNECTION	COVER	FINISH	MANUFACTURER (CATALOG SERIES)	NOTES
			DUPLEX	FURNITURE	DATA CABLES	DATA GANGS	AV GANGS	SPARE						
FB6.D4.A1	6 GANG POWER/DATA & A/V FLOORBOX	LENGTH:12" WIDTH: 10" DEPTH: 6"	4	4	1	1	0	0	CFG	C1	CV1	AL	WIREMOLD (RFBA6R300G) HUBBELL (CFB45G55CRE) FSR (FL-500)	
FB10.D4.A4	10 GANG POWER/DATA FLOORBOX	LENGTH:12" WIDTH: 10" DEPTH: 6"	4	4	1	4	1	1	CFG	C1	CV1	AL	WIREMOLD (RFBA10R550G) HUBBELL (CFB10G55CRE) FSR (FL-600)	

EQUIPMENT SCHEDULE

EQUIPMENT SCHEDULE KEY			NOTES:							GENERAL NOTES:									
E - DIVISION 26			1. PROVIDE MANUAL STARTER WITH THERMAL OVERLOAD AND RELAY FOR ATC/BAS CONTROL.								1. LOCATE ELECTRICAL EQUIPMENT IN ACCESSIBLE LOCATION, SUCH THAT IT IS WITHIN SIGHT OF THE EQUIPMENT IT IS SERVING, AND COMPLIES WITH N.E.C. REQUIRED CLEARANCES.								
Q - FURNISHED WITH EQUIPMENT, INSTALLED BY DIV.26			2. PROVIDE FUSED DISCONNECT ELEVATOR POWER MODULE WITH SHUNT TRIP.								2. CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE AND SIZE FEEDER, STARTER, DISCONNECT AND OVERCURRENT PROTECTION IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS OF ACTUAL EQUIPMENT SUPPLIED.								
LABEL			LOAD DATA							WIRE AND CONDUIT SIZE		OCPD		DISCONNECT		MOTOR CONTROLLER		NEMA ENCLOSURE RATING	
QTY	DESCRIPTION	HP	kW	MCA	FLA	V	PH	DEVICE	FED FROM	PROVIDED BY	DEVICE	PROVIDED BY	DEVICE	SIZES	NOTES				
AC-1	AIR COMPRESSOR	2	-	-	15	120	1	2 #12, #12 GR 0.75" CND	20/1 CB	E	30A/1P FRS-20	E	-	-	-				
ERV-1	ENERGY RECOVERY VENTILATOR	-	-	15	12	120	1	2 #12, #12 GR 0.75" CND	20/1 CB	E	30A/1P FRS-15	E	-	-	-				
IDU-1	INDOOR UNIT	-	-	-	2	208	1	2 #12, #12 GR 0.75" CND	20/2 CB	E	30A/2P FRS-10	E	-	-	-				
IDU-2	INDOOR UNIT	-	-	-	2	208	1	2 #12, #12 GR 0.75" CND	20/2 CB	E	30A/2P FRS-10	E	-	-	-				
ODU-1	OUTDOOR UNIT	-	-	30	24	480	3	3 #6, #10 GR 1" CND	50/3 CB	E	60A/3P FRS-50	Q	-	-	-				
ODU-2	OUTDOOR UNIT	-	-	38	31	480	3	3 #4, #8 GR 1.25" CND	70/3 CB	E	100A/3P FRS-60	Q	-	-	-				



 **SPECTRUM**
ENGINEERS

 **E N G I N E E R S**
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

Intermountain Life Flight Life Flight Simulator

JRA Project # 25252.0
Construction Documents Dec. 11, 2013


ELECTRICAL EQUIPMENT AND FLOORBOX SCHEDULES EP602




SHEET KEYNOTES

- CONTRACTOR TO PROVIDE SLEEVES THROUGH ALL WALLS FOR CABLE PATHWAYS. ALL FIRE-RATED WALLS REQUIRE A FIRE-RATED SLEEVE. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION. ALL SMOKE/NON-RATED WALLS REQUIRE A CONDUIT SLEEVE WITH BUSHINGS AND ARE REQUIRED TO BE SEALED WITH FIRE-RATED CAULK AND PUTTY. CONTRACTOR TO DETERMINE FINAL NUMBER OF SLEEVES FOR PENETRATIONS THROUGH WALLS.
- CONTRACTOR TO STUB CONDUIT TO NEAREST ACCESSIBLE J-HOOK PATHWAY. MAXIMUM SPACING OF J-HOOKS TO BE 48" ON-CENTER.
- A SINGLE BEND CANNOT BE GREATER THAN 90 DEGREES.
- NO MORE THAN 180 DEGREE IN BENDS IS ALLOWED WITH PROVIDING AN ACCESSIBLE PULL BOX. PULL BOX MUST BE IN AN ACCESSIBLE CEILING SPACE FOR ONGOING SUPPORT AND MAINTENANCE.
- A SINGLE CONDUIT FOR HORIZONTAL CABLE CANNOT RUN MORE THAN 100' CONTINUOUSLY WITHOUT A PULL BOX OR AN ACCESSIBLE PULL POINT.
- TELECOMMUNICATIONS CONDUIT SHOULD NOT RUN OVER OR ADJACENT TO BOILERS, INCINERATORS, HOT WATER LINES, OR STEAM LINES.
- ALL CONDUIT MUST BE SEALED PROPERLY AFTER CABLE INSTALLATION TO ENSURE ANY RATED WALL ASSEMBLIES ARE RETURNED TO THE ORIGINAL WALL RATING.
- TELECOMMUNICATIONS WORK AREA OUTLET SHOULD BE LOCATED WITHIN 3' OF THE CEILING OUTLET AND INSTALLED AT THE SAME ELEVATION.
- THE DAISY CHAINING OF TELECOMMUNICATIONS BOXES IS NOT ALLOWED. ALL CONDUIT RUNS MUST BE DEDICATED TO ONE OUTLET LOCATION.
- ALL CONDUITS INSTALLED FOR THE USE OF BACKBONE CABLE MUST USE LONG SWEEPS.
- VERTICAL SLEEVES MUST EXTEND A MINIMUM OF 3' ABOVE THE FINISHED FLOOR BUT NO MORE THAN 8' ABOVE THE FINISHED FLOOR.
- VERTICAL SLEEVES MUST BE COORDINATED WITH THE ENLARGE TELECOM VIEWS TO ENSURE PROPER CIRCULATION SPACE IS GIVEN.
- VERTICAL SLEEVES SHOULD BE ADJACENT TO THE WALL AND IN A CORNER WHERE AT ALL POSSIBLE TO ALLOW FOR PROPER CABLE RACKING. NO MORE THAN TWO ROWS OF SLEEVES ARE ALLOWED.
- VERTICALLY MOUNTED LADDER RACK IS REQUIRED TO SUPPORT CABLE. CABLE SHOULD BE SUPPORTED IN A VERTICAL POSITION TO ENSURE CABLE DOES NOT SLIP.
- ALL VERTICAL SLEEVES MUST BE PROPERLY SEALED AFTER USE.
- ALL CONDUIT SHOULD HAVE A PULL CORD INSTALLED WITH A MINIMUM TEST RATING OF 200 LBS.
- AFTER CONDUIT INSTALLATION CONDUITS SHOULD BE LEFT CLEAN, DRY, AND UNOBSTRUCTED. REAMED AND FITTED WITH BUSHINGS, CAPPED FOR PROTECTION, AND LABELED FOR IDENTIFICATION.
- ALL CABLE TRAY INSTALLATION MUST UTILIZE TRAPEZE MOUNTING. NO CENTER HANG SUPPORTS ARE ALLOWED. NO WALL MOUNTS WILL BE ALLOWED. IF TRAPEZE SUPPORTS CANNOT BE USED, A REQUEST MUST BE SUBMITTED TO ALLOW ALTERNATE MOUNTING METHODS.
- ALL CABLE TRAY MUST BE SEISMICALLY BRACED.
- ALL CABLE TRAY THAT PENETRATES A RATED WALL ASSEMBLY MUST BE SEALED TO RETURN THE WALL TO ITS ORIGINAL RATING.

GENERAL SHEET NOTES



1 TELECOM CONDUIT RISER DIAGRAM
SCALE: NTS




2 TELECOM CABLE RISER DIAGRAM
SCALE: NTS



GENERAL SHEET NOTES


INTERIOR LIGHTING FIXTURE SCHEDULE

GENERAL NOTES

	<ol style="list-style-type: none"> 1. SUBSTITUTIONS AND/OR EQUAL FIXTURES MUST RECEIVE APPROVAL PRIOR TO BIDDING, THEY MUST BE SUBMITTED TO THE ENGINEER NO LESS THAN 2 WEEKS PRIOR TO BID OPENING. 2. SAMPLES MUST BE PROVIDED FOR ANY AND ALL FIXTURES UPON A/E REQUEST PRIOR TO RELEASING FIXTURES. 3. ALL FIXTURES SHALL BE LISTED AND APPROVED FOR THEIR INTENDED USE AND LOCATION. 4. VERIFY THE PROPER MOUNTING KITS OR ACCESSORIES TO FACILITATE INSTALLATION AS SHOWN AT EACH LOCATION ON THE DRAWINGS. 5. COMPLY WITH THE "INTERIOR LIGHTING" SECTION OF THE SPECIFICATIONS. 6. ALL LIGHT FIXTURES TO BE EITHER "DLC" OR "LIGHTING FACTS" LISTED OR TO BE APPROVED BY ARCHITECT/ENGINEER AND OWNER. 7. CONTRACTOR ALLOWANCE PRICES ARE ACCURATE WHEN THIS JOB WAS SPECIFIED, CONTRACTOR AND ELECTRICAL DISTRIBUTOR SHALL VERIFY THIS ALLOWANCE AND REPORT ANY PROBLEMS TO THE ENGINEER BEFORE THE BID. ALLOWANCE PRICE MAY OR MAY NOT INCLUDE LAMP(S) OR FREIGHT AS NOTED, AND DO NOT INCLUDE ANY TAXES.
--	---

ID	DESCRIPTION	SIZE (NOMINAL)	LUMINAIRE				DRIVER			MANUFACTURER (CATALOG SERIES)
			DELIVERED DIRECT LUMENS	DELIVERED INDIRECT LUMENS	COLOR TEMP	CRI	TYPE	VOLTAGE	WATTS	
(EFG24)	DESCRIPTION: 2' X 4' LED FLAT PANEL, GRID LAY-IN MOUNTING: CEILING, RECESSED FINISH: SCBA OPTICS: - OPTIONS: - EM: GENERATOR TRANSFER DEVICE	LENGTH: 4' - 0" WIDTH: 2' - 0" DEPTH: -	4,300		4000K	80	0-10V DIMMING (1%)	120/277	50	DAYBRITE (2FPZ43L8354DSUNV DIM/BODINE GTD10DIM) LITHONIA (CPANL/IOTA ETS-DR) METALUX (24CGTX 45 GTRD L835)
(FG24)	DESCRIPTION: 2' X 4' LED FLAT PANEL, GRID LAY-IN MOUNTING: CEILING, RECESSED FINISH: SCBA OPTICS: - OPTIONS: - EM: -	LENGTH: 4' - 0" WIDTH: 2' - 0" DEPTH: -	4,300		4000K	80	0-10V DIMMING (1%)	120/277	50	DAYBRITE (2FPZ43L8354DSUNV DIM) LITHONIA (EPANL) METALUX (24CGTX 45 L835)
E3-1	DESCRIPTION: IN-USE LIGHT MOUNTING: UNIVERSAL FINISH: SCBA OPTICS: - OPTIONS: - EM: AC ONLY	LENGTH: WIDTH: DEPTH: DIAMETER:		RED	NO DIMMING		120/277	3	KENALL (METMSU MW R IN USE DT) LITHONIA (LQM P W 1 R 120-277 IN USE) CHLORIDE (AMS GW IN USE RFR) EMERGENSEE (SEEXEL-1-G-C-A-CUST OM-IN USE)	

HEX SHEET KEYNOTES



1 LEVEL 1 LIGHTING PLAN

SCALE: 1/4" = 1'-0"

Intermountain Life Flight Life Flight Simulator

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025

LEVEL 1 LIGHTING PLAN


EL101



GENERAL SHEET NOTES

□ SHEET KEYNOTES

1 PROVIDE MONITOR MODULE FOR SIMULATION EQUIPMENT TO TRANSMIT FIRE WARNING SIGNALS TO THE BUILDING FIRE ALARM SYSTEM.



1 LEVEL 1 AUXILIARY PLAN
SCALE: 1/4" = 1'-0"

Intermountain Health
Intermountain Life Flight
Life Flight Simulator

2284 160 N
Salt Lake City, UT 84116

NJRA Project # 25252.00
Construction Documents Dec. 11, 2025

LEVEL 1
AUXILIARY
PLAN

EY101