# INTERIOR LIGHTING FIXTURE SCHEDULE

## ABBREVIATIONS

**MOUNTING**

- B - BASE
- C - CEILING
- F - FLANGE
- G - GRID
- P - PENDANT
- PL - POLE
- R - RECESSED
- S - SURFACE
- W - WALL

**LUMINAIRE OPTIONS**

- ARHR - AIR RETURN AND HEAT REJECTION
- DL - DAMP LOCATION
- EQC - EARTHQUAKE CLIPS
- F - FUSING
- HLD - HINGED AND LATCHED DOOR
- HS - HOUSE SIDE SHIELD
- PS - PHOTOCELL SWITCH
- QRS - QUARTZ RESTRIKE
- ST - STATIC
- WG - WIRE GUARD
- WL - WET LOCATION




**FINISH**

- MW - MATTE WHITE
- BL - BLACK
- SL - SILVER
- GL - GOLD
- CL - CLEAR
- PW - PAINTED WHITE
- EA - EXTRUDED ALUMINUM
- S - STEEL
- GS - GALVANIZED STEEL
- C - CAST
- CBA - COLOR BY ARCHITECT
- SCBA - STANDARD COLOR BY ARCHITECT
- CCA - CUSTOM COLOR BY ARCHITECT
- FS 209D - MEETS FEDERAL STANDARD 209D
- TP - THERMALLY PROTECTED
- FL - FLUSH
- R - REGRESS
- M - MITERED

**DIFFUSER/LENS**

- #A - ACRYLIC #THICK
- #OA - ACRYLIC #THICK (OPAL)
- GC - GLASS (CLEAR)
- GO - GLASS (OPAL)
- GF - GLASS (FROSTED)
- SGL - SOFT GLOW LENS
- HPL - HIGH PERFORMANCE LENS
- DO - DROP OPAL
- CGL - CONVEX GLASS LENS
- S - SATIN LENS

**REFLECTOR**

- OP - NONE/OPEN
- SP - SPECULAR
- SS - SEMI-SPECULAR
- D - DIFFUSE (WHITE ENAMEL)
- SC - SPECULAR (COLORED)
- PR - PRISMATIC
- FDR - FULL DEPTH REFLECTOR
- DS - DIFFUSE (SEMI SPECULAR) SILVER
- LI - LOW IRIDESCENT
- IR - IRIDESCENT
- SL - SILVER
- GL - GOLD
- CA - CLEAR ALZAK

**NOTES**

## GENERAL NOTES

1. PROVIDE UNIT PRICES AND FIXTURE BRAND SELECTED FOR ADD/DELETE CHANGES FOR EACH FIXTURE TYPES SHOWN WITHIN 48 BUSINESS HOURS OF THE BID DATE. FAILURE TO COMPLY WITH THIS REQUIREMENT MAY DISQUALIFY THE PRODUCTS AND EMPOWER THE ENGINEER TO DETERMINE FAIR VALUE FOR FIXTURE AND INSTALLATION CHANGES, WITHOUT FURTHER INPUT FROM THE CONTRACTOR OR INSTALLER.
2. CONTRACTOR ALLOWANCE PRICES ARE ACCURATE WHEN THIS JOB WAS SPECIFIED, CONTRACTOR AND ELECTRICAL DISTRIBUTOR SHALL VERIFY THIS ALLOWANCE AND REPORT ANY PROBLEMS TO THE ENGINEER BEFORE THE BID. ALLOWANCE PRICE MAY OR MAY NOT INCLUDE LAMP(S) OR FREIGHT AS NOTED, AND DO NOT INCLUDE ANY TAXES.
3. SUBSTITUTIONS AND/OR EQUAL FIXTURES MUST RECEIVE APPROVAL PRIOR TO BIDDING, THEY MUST BE SUBMITTED TO THE ENGINEER NO LESS THAN 2 WEEKS PRIOR TO BID OPENING.
4. SAMPLES MUST BE PROVIDED FOR ANY AND ALL FIXTURES UPON A/E REQUEST PRIOR TO RELEASING FIXTURES.
5. ALL FIXTURES SHALL BE LISTED AND APPROVED FOR THEIR INTENDED USE AND LOCATION.
6. VERIFY THE PROPER MOUNTING KITS OR ACCESSORIES TO FACILITATE INSTALLATION AS SHOWN AT EACH LOCATION ON THE DRAWINGS.
7. COMPLY WITH THE "INTERIOR LIGHTING" SECTION OF THE SPECIFICATIONS.
8. REFER TO SPECIFICATIONS FOR IMPORTANT TECHNICAL REQUIREMENTS FOR LIGHTING FIXTURES, DRIVERS, AND LAMPS.
9. ALL LIGHT FIXTURES TO BE EITHER "DLC" OR "LIGHTING FACTS" LISTED OR TO BE APPROVED BY ARCHITECT/ENGINEER AND OWNER.

| ID | DESCRIPTION | NOMINAL SIZE | | | | MOUNTING | TYPE | COLOR TEMP | CRI | DRIVER CONFIGURATION | VOLTAGE | WATTS | FINISH | FIXTURE LUMENS | DIFFUSER/LENS | REFLECTOR | OPTIONS | NOTES | MANUFACTURER (CATALOG SERIES) | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | LENGTH | DEPTH | HEIGHT | DIAMETER/ APERTURE | | | | | | | | | | | | | | OPTION 1 | OPTION 2 | OPTION 3 |
| (DX-1) | 6" ROUND, RECESSED LED DOWNLIGHT, SEMI-SPECULAR REFLECTOR, WHITE TRIM FINISH | - | - | - | 0' - 6" | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 19 | - | 1500 | | | - | | GOTHAM (EVO-35/15-6AR-WD-LSS-MVOLT-EZ10-TRW) | LITON (LHALD612C034UE-D10/LRALD6SWF160-B60-T35) | PORTFOLIO (LD6B15D010/EU6B10208035/6LBW2H HB26) |
| (DX-1B) | 6" ROUND, RECESSED LED DOWNLIGHT, SEMI-SPECULAR REFLECTOR, BLACK TRIM FINISH | - | - | - | 0' - 6" | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 19 | - | 1500 | | | - | | GOTHAM (EVO-35/15-BR-WD-LSS-MVOLT-EZ10-TRBL) | LITON (LHALD612C034UE-D10/LRALD6-BLACK FLANGE-160-B60-T35) | PORTFOLIO (LD6B15D010/EU6B10208035/6LBW-BLACK PAINTED-MB HB26) |
| (DX-2) | 6" ROUND, RECESSED LED DOWNLIGHT, SEMI-SPECULAR REFLECTOR, WHITE TRIM FINISH | - | - | - | 0' - 6" | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 23 | - | 2000 | | | - | | GOTHAM (EVO-35/20-6AR-WD-LSS-MVOLT-EZ10-TWR) | LITON (LHALD625CO71-D10/LRALD6SWF151-B60-T35) | PORTFOLIO (LD6B20D010/EU6B10208035/6LBW2H HB26) |
| (DX-4) | 6" ROUND, RECESSED LED SHOWER DOWNLIGHT, LENSED, WHITE TRIM FINISH | - | - | - | 0' - 6" | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 19 | - | 1500 | | | - | | GOTHAM (EVO-35/15-6DFR-MVOLT-EZ10-TWR) | HALO (PD615D010B/PDM6B835/64VDFWC) | INTENSE (SS6G3DR-L4-358-IC632-C-SF-CR) |
| (DX-23) | 4" ROUND, RECESSED LED WALL WASH, SEMI-SPECULAR REFLECTOR, WHITE TRIM FINISH | - | - | - | 0' - 4" | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 19 | - | 1000 | | | - | | GOTHAM (EVO-WW-35/10-4AR-LSS-MVOLT-GZ10-TRW)) | LITON (LHALD412C35UE-D10 LRALD471SWF 062 T35) | PORTFOLIO (LD4B10D010/EU4B10208035/4LWW2H HB26) |
| (E10-1) | EXIT SIGN, EDGE LIT LED ACRYLIC, SINGLE FACE, GREEN LETTERING, BRUSHED ALUMINUM FINISH, UNIVERSAL MOUNTING | - | - | - | - | UNV | LED | GREEN | | NO DIMMING | 120/277 | 3 | | 0 | | | AC ONLY | | DUAL-LITE (LECSGWA) | EVENLITE (TEX-AC-G-1C) | CHLORIDE (44RLU-1-G) |
| (E10-2) | EXIT SIGN, EDGE LIT LED ACRYLIC, DUAL FACE, GREEN LETTERING, BRUSHED ALUMINUM FINISH, UNIVERSAL MOUNTING | - | - | - | - | UNV | LED | GREEN | | NO DIMMING | 120/277 | 3 | - | 0 | | | AC ONLY | | DUAL-LITE (LECDGWA) | EVENLITE (TEX-AC-G-2M) | CHLORIDE (44RLU-2-G) |
| (GS-2) | 2' X 4' LED TROFFER, EDGE LIT PANELS, GRID LAY-IN | 4' - 0" | 2' - 0" | - | - | CR | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 38 | - | 4300 | | | - | | METALUX (24EN-LD2-45-UNV-L835-CD1-U) | PINNNACLE (LU24 A B35CL4300 GX U OL1 1 0 W) | FOCAL PONT(FEQ2 24 AC 4500L 35K 1C UNV LD1 G WH) |
| (TX-1) | PENDANT | - | - | - | 0' - 6" | CP | LED | 3500K | | 0-10V DIMMING (10%) | 120/277 | 7 | | 400 | | | - | | OXYGEN (37-653-35124) | | |
| (UC-5) | 28" LED UNDERCABINET LIGHT | 2' - 4" | - | - | - | S | LED | 3500K | | NO DIMMING | 120/277 | 8 | - | 600 | | | - | | DAY-BRITE (LINCS100E-L28-935-UNV-WHG-DIM) | KENALL (AUCLED-1-MW-11L35K-2-A-2-7) | AIREY-THOMPSON (13HC-N-35K-24-2-3-D11) |
| (WS-2) | 2' LED VANITY LIGHT, SATIN CHROME FINISH, 2.25" WIDE | 2' - 0" | 0' - 2.25" | - | - | WS | LED | 3500K | | NO DIMMING | 120/277 | 19 | - | 2000 | | | - | | EDGE LIGHT (TW12-S11-1RE-24*-35K-CH) | EUREKA (3541-23-LED-17.40-120/277-SC-WH) | LBL (LW496-OP-XX-LED-277) |

2 2


NJRA ARCHITECTS

NJRA Architects, Inc.
5272 S. College Drive, Suite104
Murray, Utah 84123
801.364.9259
www.njraarchitects.com


LICENSED PROFESSIONAL ENGINEER
No. 185978
PETER E. JOHANSEN
04/22/19

Intermountain Healthcare
IMC Kidney Services Remodel

5121 Cottonwood Street
Murray, UT 84107

NJRA Project # 19206.00
Construction Documents Apr 24, 2019
2 Addenda Date 2

INTERIOR LIGHTING FIXTURE SCHEDULE

EL601

5/8/2019 2:45:55 PM