

R 14

high speed feeder

R-14 HIGH SPEED CONTINUOUS FEEDER

From Straight Shooter, the company that brought real innovation to friction feeding comes the all new R-14 high speed friction feeder! The versatile R-14 comes with all the features our feeders are known for, including:

- BUCKLE SEPARATION
- REPOSITIONABLE FEED BELTS
- STRAIGHT FEEDING AND
- 5 MINUTE BELT CHANGES

Now you get even more with the R-14! More belts, more separators, 14" wide capacity, and our exclusive rear belt guide positioners. All of this comes in a clean, easy to use package at an unbeatable price!

Great for feeding a wide variety of media into:

- INKJET MACHINES
- TABBING EQUIPMENT
- FOLDERS
- LAMINATORS
- LABELING EQUIPMENT



GET THE MOST OUT OF YOUR PRODUCTION EQUIPMENT!

Straight Shooter feeders are designed to take the hassle out of feeding. In today's competitive marketplace, you need a feeder that you can count on to run whatever comes your way. **The R-14 delivers!**

Based on our popular SS12 and C-12 models the R-14 offers simple setup, versatility, and reliability in a wider format. The R-14 easily handles up to 14" wide stock at speeds up to 40,000 pieces per hour!



Our exclusive new rear belt guides make repositioning the feed belts easier than ever! Even adjust them while running your job!



Buckle Separation™, another Straight Shooter innovation, easily separates documents without the jams common with traditional feeders. The R-14 comes with **three** independently adjustable separators... **Versatility!**

SPECIFICATIONS

Media Handling:

Width: 3" minimum up to 14" maximum
Length: 2" minimum up to 17" maximum
Thickness: Single sheet up to 3/8" thick
Speeds: Up to 40,000 postcards per hour

Power:

120 vac, 5 amp standard, (240 optional)
Available interlocks: Dry contact, 12 vdc,
24 vdc, 24 vac. Others upon request.
Dimensions: 17" wide x 17" long
Weight: 40 lbs



AUTOMATED EQUIPMENT SERVICE, INC.

MAIL PROCESSING SYSTEMS

(845) 452-2100 (518) 459-4545
(914) 478-2100 (607) 733-2108

info@AESMailPro.com