



# RESTAURANT EQUIPMENT HAWAII



## CABINET CONSTRUCTION

STURDY AND CORROSION-RESISTANT DESIGN FEATURES BOTH A 430 TYPE STAINLESS STEEL EXTERIOR AND INTERIOR. FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSULATION ENHANCES THE STRUCTURAL INTEGRITY OF THE CABINET AND PROMOTES ENERGY EFFICIENCY.

13/4" THICK STAINLESS STEEL TOP SURFACE FEATURES RAISED MARINE EDGES TO HELP CONTAIN SPILLS AND LEAKS. ACCOMMODATES UP TO 730 LB. OF WEIGHT.

## REFRIGERATION SYSTEM

ENVIRONMENTALLY SAFE R290 REFRIGERANT. REAR-MOUNTED CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

## DRAWERS

2 REFRIGERATED DRAWERS CAN EACH ACCOMMODATE 1 FULL SIZE, 4" DEEP AND (3) 1/6 SIZE, 4" DEEP FOOD PANS.

## MODEL FEATURES

DIGITAL TEMPERATURE CONTROLLER MAKES OPERATION SIMPLE. AUTO DEFROST FEATURE FOR INTUITIVE CLEANING AND MAINTENANCE.

OUTFITTED WITH (4) 4" CASTERS FOR MOBILITY PRIOR TO CLEANING AND SERVICING TASKS.

## - CHEF BASE

A PRACTICAL STORAGE AND PRODUCTIVITY SOLUTION FOR BUSY KITCHENS.

## SPECIAL FEATURES

- 13/4" THICK STAINLESS STEEL TOP WITH MARINE EDGES TO CONTAIN SPILLS
- TOP ACCOMMODATES UP TO 730 LB. OF WEIGHT
- 2 REFRIGERATED DRAWERS FOR FOOD STORAGE
- DIGITAL TEMPERATURE CONTROLS HOLD AT 33-40°F
- TEMPERATURE DISPLAY FOR EASY MONITORING
- FOAMED-IN-PLACE POLYURETHANE INSULATION
- ENVIRONMENTALLY-FRIENDLY R290 REFRIGERANT
- 430 TYPE STAINLESS STEEL INTERIOR AND EXTERIOR
- AUTO DEFROST FEATURE
- 1/6 HP COMPRESSOR



PARTS & LABOR



COMPRESSOR

WARRANTY  
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS.



# RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR  
RESTAURANTS & BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON  
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

## TECHNICAL DATA

### DIMENSIONS

EXTERIOR DIMENSIONS	36 <sup>3</sup> / <sub>8</sub> "W X 32 <sup>1</sup> / <sub>8</sub> "D X 25 <sup>7</sup> / <sub>8</sub> "H
INTERIOR DIMENSIONS	24 <sup>5</sup> / <sub>8</sub> "W X 27 <sup>1</sup> / <sub>2</sub> "D X 16 <sup>1</sup> / <sub>2</sub> "H
NUMBER OF DRAWERS	2
4" DEEP PAN CAPACITY	(1) FULL + (3) 1/6
NET VOLUME	6.5 CU. FT.
PACKAGING DIMENSIONS	39"W X 35"D X 28 <sup>1</sup> / <sub>2</sub> "H

### COOLING

TEMPERATURE RANGE	33°F-40°F
REFRIGERANT	R290
MAX. AMBIENT TEMPERATURE	100°F
DEFROSTING	AUTOMATIC
TEMPERATURE CONTROLLER	DIGITAL
HORSEPOWER	1/6

### CONSTRUCTION

EXTERIOR MATERIAL	430 STAINLESS STEEL
TOP MATERIAL	430 STAINLESS STEEL
INSULATION MATERIAL	FOAMED-IN-PLACE POLYURETHANE
TOP EDGE	MARINE
WEIGHT CAPACITY	730 LB.
TOP THICKNESS	1 <sup>3</sup> / <sub>4</sub> "

### ELECTRICAL

VOLTAGE	115
AMPS	2.5
HZ	60
PHASE	1
PLUG TYPE	NEMA 5-15P
ELECTRICAL CORD LENGTH	84"

## PLAN VIEW

