



RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES WHITE-COATED ALUMINUM INTERIOR WALLS AND STAINLESS STEEL FLOOR. EXTERIOR FEATURES PEEL AND CHIP-RESISTANT, POWDER-COATED COLD ROLLED STEEL THAT IS DURABLE AND PERMANENT.

FOAMED-IN-PLACE POLYURETHANE INSULATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY.

ONE-PIECE GRILL IS EASILY REMOVED FOR CLEANING AND SERVICING. 2 DUAL-PANE TEMPERED GLASS DOORS SELF-CLOSES TO SAVE ENERGY.

REFRIGERATION SYSTEM

ENVIRONMENTALLY-SAFE R290 REFRIGERANT. BOTTOM-MOUNTED CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

“NO STOOP” LOWER SHELF MAXIMIZES VISIBILITY BY RAISING MERCHANDISED PRODUCT TO A HIGHER LEVEL.

SHELVING

8 PLASTIC COATED STEEL SHELVES INCLUDED. EACH ARE ADJUSTABLE AND ACCOMMODATE UP TO 90 LB.

MODEL FEATURES

COPPER EVAPORATOR COIL ELIMINATES THE POTENTIAL OF CORROSION. CONVENIENT CLEAN-OUT DRAIN BUILT INTO CABINET FLOOR. FEATURES BUILT-IN AUTOMATIC DEFROST. DIGITAL CONTROLLER FEATURES AUTO- DEFROST FUNCTION. LED LIGHTED INTERIOR SAVES ENERGY BY PRODUCING LESS HEAT AND MAXIMIZES PRODUCT VISIBILITY IN DISPLAY AREA.

SPECIAL FEATURES

- ECO-FRIENDLY R290 HYDROCARBON REFRIGERANT
- 2 SELF-CLOSING, GLASS SWING DOORS
- 8 EPOXY-COATED STEEL SHELVES EACH HOLDS UP TO 90 LB. OF WEIGHT
- BRIGHT, LED LIGHTING
- MAINTAINS TEMPERATURES BETWEEN (-8)°F AND (-1)°F
- EASY-TO-USE, DIGITAL TEMPERATURE CONTROLS
- FOAMED-IN-PLACE POLYURETHANE INSULATION
- WHITECOATED STEEL EXTERIOR AND PAINTED ALUMINUM INTERIOR
- STAINLESS STEEL FLOOR
- AUTO DEFROST FOR EASY MAINTENANCE
- 115V, 1/4 HP



PARTS & LABOR



COMPRESSOR

WARRANTY
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS.



RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR
RESTAURANTS & BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

TECHNICAL DATA

DIMENSIONS

EXTERIOR DIMENSIONS	53 1/8"W x 31 7/8"D x 84 3/8"H
INTERIOR DIMENSIONS	50"W x 28 3/8"D x 61 7/8"H
NET VOLUME	42.5 CU. FT.
NET WEIGHT	437 LBS.
GROSS WEIGHT	480 LBS.
PACKAGING DIMENSIONS	54 1/4"W x 33"D x 84 1/2"H

COOLING

TEMPERATURE RANGE	(-8)°F - (-1)°F
REFRIGERANT	R290
MAX. AMBIENT TEMPERATURE	90°F
DEFROSTING	AUTOMATIC
TEMPERATURE CONTROLLER	DIGITAL
HORSEPOWER	1/4

CONSTRUCTION

EXTERIOR MATERIAL	COATED STEEL
INTERIOR MATERIAL	PAINTED ALUMINUM
INSULATION MATERIAL	FOAMED-IN-PLACE POLYURETHANE
SHELF SIZE	(8) 24 3/8" x 23 5/8"
SHELF MATERIAL	EPOXY-COATED STEEL
SHELF LOAD CAPACITY	90 LB.

ELECTRICAL

VOLTAGE	115
AMPS	10.5
HZ	60
PHASE	1
PLUG TYPE	NEMA 5-20P
ELECTRICAL CORD LENGTH	96"

PLAN VIEW

