

RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

Heavy duty construction includes a white steel interior and a type 430 stainless steel exterior, resulting in strength, durability, and an attractive appearance. Stainless steel top adds counter space to merchandise cones and toppings.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSU-LATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY.

FRONT AND REAR GRILLS ARE EASILY REMOVED FOR CLEANING AND SERVICING. SINGLE LID DESIGN ALLOWS FOR EASY ACCESS.

REFRIGERATION SYSTEM

Environmentally-friendly R290 refrigerant. Front- and rear- breathing design allows for installation adjacent to other equipment or cabinetry. Cold wall design prevents cold air from escaping.

SHELVING

(6) EPOXY-COATED SHELVES INCLUDED. EACH HOLDS (2) 3-GALLON ICE CREAM TUBS AT THE PERFECT HEIGHT FOR SERVICE. ADDITIONAL STORAGE FOR (8) 3-GALLON TUBS UNDERNEATH.

MODEL FEATURES

Bright LED lighting enhances product visibility. Included tub covers create a clean appearance.

Pre-drilled holes for dipper well installation on either the left or right side of the cabinet.

INCLUDED NIGHT COVERS PROTECT PRODUCT DURING OFF HOURS.

PREPROGRAMMED DIGITAL CONTROLS.

SPECIAL FEATURES

- $\bullet \ Eco\mbox{-}Friendly R290 \mbox{hydrocarbonrefriger-} \\ Ant$
- Durableandattractivetype430stainlesssteel

EXTERIOR

• Maintainstemperaturefrom(-15)to(-8) Fforice

CREAM STORAGE AND SERVICE

• Sixepoxy-coatedsteelshelveshold(2)3-gallon

Tubs each for a total of 12 tubs, with storage for

- (8) 3-GALLON TUBS UNDERNEATH
- FOAMED-IN-PLACEPOLYURETHANEINSULATION
- Easy-to-readpreprogrammeddigitaltemperature

CONTROLLER

• 115V;1/2HP



WARRANTY
RESIDENTIAL: REH ASSUMES NO
LIABILITY FOR PARTS OR LABOR COVERAGE
FOR COMPONENT FAILURE, FACTORY DEFECT
OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE
OR RESIDENTIAL APPLICATIONS







RESTAURANT EQUIPMENT HAWAII

Quality Commercial Equipment For Restaurants & Bars Visit Our Online Store For Pricing & Information on Equipment, Food Trucks & OurCommisary Kitchen 808-845-5052

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	673/4"W x 28"D x 511/4"H
Interior Dimensions	617/8"W x 22"D x 281/4"H
NET VOLUME	19.9 cu. ft.
NET WEIGHT	310 гв.
Gross Weight	432 гв.
Packaging Dimensions	72"W x 321/4"D x 58"H

COOLING

Temperature Range	(-15) to (-8)°F
Refrigerant	R290
Max. Ambient Temperature	90°F
Defrosting	Automatic
Temperature Controller	Digital
HorsePower	1/2

Construction

Exterior Material	White-Coated Steel
Interior Material	White-Coated Steel
Insulation Material	FOAMED-IN-PLACE POLYURETHANE
TUB HOLDER CAPACITY (3 GALLON TUBS)	12
Storage Capacity (3 Gallon Tubs)	8
BTU (BTU/HR)	1794

ELECTRICAL

Voltage	115
Amps	5.64
Hz	60
Phase	1
Plug Type	NEMA 5-15P
ELECTRICAL CORD LENGTH	84"

PLAN VIEW

