

Restaurant Equipment Hawaii



CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES WHITE-COATED ALUMINUM INTERIOR WALLS AND STAINLESS STEEL FLOOR. EXTERIOR FEA-TURES PEEL AND CHIP-RESISTANT, POWDER-COATED COLD ROLLED STEEL THAT IS DURABLE AND PERMANENT.

LED LIGHTED INTERIOR SAVES ENERGY BY PRODUCING LESS HEAT AND MAXIMIZES PRODUCT VISIBILITY IN DISPLAY AREA.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSU-LATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY.

ONE-PIECE GRILL IS EASILY REMOVED FOR CLEANING AND SERVIC-ING. DUAL-PANE TEMPERED GLASS DOOR SELF-CLOSES TO SAVE ENERGY.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Bottom mount CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE. "NO STOOP" LOWER SHELF MAXIMIZES VISIBILITY BY RAISING MERCHAN-DISED PRODUCT TO A HIGHER LEVEL.

SHELVING

FOUR WHITE EPOXY-COATED STEEL SHELVES INCLUDED. MODEL FEATURES

COPPER EVAPORATOR COIL ELIMINATES THE POTENTIAL OF CORRO-SION. CONVENIENT CLEAN-OUT DRAIN BUILT INTO CABINET FLOOR. EASY TO READ DIGITAL CONTROLS.

SPECIAL FEATURES

- SINGLE SELF-CLOSING, ANTI-FOG GLASS DOOR
- INTERIOR LED LIGHTING
- (4) Epoxy-coated steel shelves included
- FOAMED-IN-PLACE POLYURETHANE INSULATION
- BOTTOM MOUNT CONDENSING UNIT
- Removable door gasket for easy cleaning
- Automatic defrosting
- STAINLESS STEEL FLOOR
- COPPER EVAPORATOR
- AVAILABLE IN BLACK



WARRANTY RESIDENTIAL: REH ASSUMES NO

LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS IN-STALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS



©Restaurant Equipment Hawaii

WWW.RESTAURANTEQUIPMENTHAWAII.COM



Restaurant Equipment Hawaii

Quality Commercial Equipment For Restaurants & Bars Visit Our Online Store For Pricing & Information on Equipment, Food Trucks & OurCommisary Kitchen 808-845-5052

TECHNICAL DATA

DIMENSIONS	
Exterior Dimensions	215/8"W x 215/8"D x 63"H
INTERIOR DIMENSIONS	187/8"W x 181/4"D x 46"H
NET VOLUME	8.6 cu. ft.
NET WEIGHT	190 lbs.
GROSS WEIGHT	224 lbs.
PACKAGING DIMENSIONS	233/4"W x 243/4"D x 69"H

CONSTRUCTION

Exterior Material	COATED STEEL
INTERIOR MATERIAL	PAINTED ALUMINUM
Insulation Material	Foamed-In-Place Polyurethane
SHELF SIZE	(4) 14" x 18"
SHELF MATERIAL	EPOXY-COATED STEEL
Shelf Load Capacity	90 lb.

Cooling	
TEMPERATURE RANGE	33°F - 40°F
Refrigerant	R290
Max. Ambient Temperature	90°F
DEFROSTING	AUTOMATIC
Temperature Controller	DIGITAL
HorsePower	1/5
HORSELOWER	1,0

Electrical

Voltage	115
Amps	2.88
Hz	60
PHASE	1
Plug Type	NEMA 5-15P
Electrical Cord Length	84"

PLAN VIEW

