



RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES WHITE-COATED ALUMINUM INTERIOR WALLS AND STAINLESS STEEL FLOOR. EXTERIOR FEATURES PEEL AND CHIP-RESISTANT, POWDER-COATED COLD ROLLED STEEL THAT IS DURABLE AND PERMANENT.

LED LIGHTED INTERIOR SAVES ENERGY BY PRODUCING LESS HEAT AND MAXIMIZES PRODUCT VISIBILITY IN DISPLAY AREA.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSULATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY.

ONE-PIECE GRILL IS EASILY REMOVED FOR CLEANING AND SERVICING. DUAL-PANE TEMPERED GLASS DOOR SELF-CLOSES TO SAVE ENERGY.

REFRIGERATION SYSTEM

ENVIRONMENTALLY-SAFE R290 REFRIGERANT. BOTTOM-MOUNTED CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

“NO STOOP” LOWER SHELF MAXIMIZES VISIBILITY BY RAISING MERCHANDISED PRODUCT TO A HIGHER LEVEL.

SHELVING

FOUR WHITE EPOXY-COATED STEEL SHELVES INCLUDED. EACH ACCOMMODATE UP TO 90 LB.

MODEL FEATURES

COPPER EVAPORATOR COIL ELIMINATES THE POTENTIAL OF CORROSION. CONVENIENT CLEAN-OUT DRAIN BUILT INTO CABINET FLOOR.

EASY TO READ DIGITAL CONTROLS.

- SINGLE SELF-CLOSING, ANTI-FOG GLASS DOOR
- INTERIOR LED LIGHTING
- (4) EPOXY-COATED STEEL SHELVES INCLUDED
- FOAMED-IN-PLACE POLYURETHANE INSULATION
- BOTTOM MOUNT CONDENSING UNIT
- REMOVABLE DOOR GASKET FOR EASY CLEANING
- AUTOMATIC DEFROSTING
- STAINLESS STEEL FLOOR
- COPPER EVAPORATOR
- AVAILABLE IN BLACK
- ECO-FRIENDLY R290 HYDROCARBON REFRIGERANT



PARTS & LABOR



COMPRESSOR

WARRANTY
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS.



RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR
RESTAURANTS & BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

TECHNICAL DATA

DIMENSIONS

EXTERIOR DIMENSIONS	28 ³ / ₈ "W x 31 ⁷ / ₈ "D x 84 ³ / ₈ "H
INTERIOR DIMENSIONS	25 ¹ / ₄ "W x 28 ³ / ₈ "D x 62 ¹ / ₂ "H
NET VOLUME	23 CU. FT.
NET WEIGHT	320 LBS.
GROSS WEIGHT	352 LBS.
PACKAGING DIMENSIONS	30"W x 65 ¹ / ₂ "D x 85 ¹ / ₂ "H

COOLING

TEMPERATURE RANGE	33°F - 40°F
REFRIGERANT	R290
MAX. AMBIENT TEMPERATURE	90°F
DEFROSTING	AUTOMATIC
TEMPERATURE CONTROLLER	DIGITAL
HORSEPOWER	1/5

CONSTRUCTION

EXTERIOR MATERIAL	COATED STEEL
INTERIOR MATERIAL	PAINTED ALUMINUM
INSULATION MATERIAL	FOAMED-IN-PLACE POLYURETHANE
SHELF SIZE	(4) 24 ¹ / ₄ " x 23 ¹ / ₄ "
SHELF MATERIAL	EPOXY-COATED STEEL
SHELF LOAD CAPACITY	90 LB.

ELECTRICAL

VOLTAGE	115
AMPS	3
HZ	60
PHASE	1
PLUG TYPE	NEMA 5-15P
ELECTRICAL CORD LENGTH	96"

PLAN VIEW

