



RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

DURABLE TYPE 201 STAINLESS STEEL CONSTRUCTION WITH HINGED LID(S). OPTIONAL GLASS SNEEZE GUARD AVAILABLE. COMPACT, COUNTERTOP DESIGN WITH SHALLOW DEPTH REQUIRES MINIMAL SPACE AND LEAVES COUNTER ROOM AT THE FRONT OF THE UNIT.

REFRIGERATION SYSTEM

1/6 HP COMPRESSOR USES R600A REFRIGERANT. OPERATION REQUIRES AN 115V ELECTRICAL CONNECTION. COLD WALL DESIGN KEEPS FOOD COLD EVEN WITH REPEATED LID OPENING.

STORAGE

INCLUDES PAN SUPPORT BARS TO HOLD FOOD PANS (SOLD SEPARATELY).

MODEL FEATURES

INTUITIVE, EASY TO READ ELECTRONIC CONTROLS. OPERATES IN AN AMBIENT TEMPERATURE UP TO 90°. FOAMED-IN-PLACE POLYURETHANE INSULATION. AUTOMATIC DEFROST SYSTEM.

SPECIAL FEATURES

- HOLDS UP TO (6) 1/3 SIZE OR (12) 1/6 SIZE (SOLD SEPARATELY)
- COMPACT, COUNTERTOP DESIGN GIVES CUSTOMERS EASY ACCESS TO CONDIMENTS
- ECO-FRIENDLY R600A HYDROCARBON REFRIGERANT
- HINGED LID CLOSES OFF FOOD PANS FOR SAFETY FROM CONTAMINANTS WITHOUT NEEDING INDIVIDUAL LIDS
- OPTIONAL GLASS SNEEZE GUARD SHOWCASES CONDIMENTS WHILE PREVENTING CONTAMINATION
- INTUITIVE DIGITAL TEMPERATURE CONTROLS WITH BACK-LIT LIGHT SWITCH
- MAINTAINS A TEMPERATURE RANGE FROM 33-41° FAHRENHEIT
- DURABLE TYPE 201 STAINLESS STEEL HOLDS UP TO WEAR-AND-TEAR
- NON-SCRATCH PLASTIC FEET WILL NOT LEAVE MARKS ON YOUR COUNTERTOP
- 115V, 1/6 HP



WARRANTY
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS.



PARTS & LABOR



COMPRESSOR



RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR
RESTAURANTS & BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

TECHNICAL DATA

DIMENSIONS

EXTERIOR DIMENSIONS	59 1/16"W x 15 9/16"D x 11 1/2"H
INTERIOR DIMENSIONS	45 1/4"W x 12 1/4"D x 6 1/2"H
HEIGHT WITH LID OPEN	23 1/4"
NET WEIGHT	56 LB.
GROSS WEIGHT	112 LB.
PACKAGING DIMENSIONS	62 5/8"W x 18 1/4"D x 18 1/8"H

COOLING

TEMPERATURE RANGE	33°-40°F
REFRIGERANT	R600A
MAX. AMBIENT TEMPERATURE	90°F
DEFROSTING	AUTOMATIC
TEMPERATURE CONTROLLER	DIGITAL
HORSEPOWER	1/6

CONSTRUCTION

CAPACITY	(6) 1/3 OR (12) 1/6 SIZE PANS
EXTERIOR MATERIAL	SS201
INTERIOR MATERIAL	SS201
DOOR TYPE	METAL LID
INSULATION	FOAM-ED-IN-PLACE POLYURETHANE
BTU	402

ELECTRICAL

VOLTAGE	115
AMPS	1.6
Hz	60
PHASE	1
PLUG TYPE	NEMA 5-15P
ELECTRICAL CORD LENGTH	60"

PLAN VIEW

