

Restaurant Equipment Hawaii



CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES BLACK PLASTIC COATED STEEL EXTERIOR WITH PAINTED ALUMINUM INTERIOR. STAINLESS STEEL LOCKING LIDS AND COUNTERTOP SURFACE.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSU-LATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY. INSULATED LOCKING LID HELPS MAINTAIN SAFE PRODUCT TEMPERATURES.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Bottom-mounted CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

SHELVING

3 EPOXY-COATED STEEL DIVIDERS INCLUDED.

MODEL FEATURES

PREPROGRAMMED DIGITAL CONTROLLER FEATURES AUTO-DEFROST FUNCTION. INCLUDED BOTTLE OPENER WITH REMOVABLE CAP CATCHER MAKES SERVICE CONVENIENT, LOCKING STAINLESS STEEL LIDS PROTECTS CONTENTS DURING OFF HOURS.

SPECIAL FEATURES

• Eco-friendly R290 hydrocarbon REFRIGERANT

• DURABLE BLACK COATED STEEL EXTERIOR; PAINTED ALUMINUM INTERIOR • MAINTAINS TEMPERATURES FROM 33 TO 40°F

• Spacious 12.7 cu. ft. interior features 3 EPOXY-COATED DIVIDERS • INCLUDES 2 LOCKING LIDS AND COMES WITH 1 REMOVABLE BOTTLE OPENER/CAP CATCHER

- FOAMED-IN-PLACE POLYURETHANE INSULATION
- Easy-to-read digital temperature CONTROLLER AND AUTO-DEFROST FUNCTION AND AUTO-DEFROST FUNCTION • 115V. 1/6 нр



WARRANTY RESIDENTIAL: REH assumes no LABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS IN-STALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS



PARTS & LABOR

©Restaurant Equipment Hawaii

WWW.RESTAURANTEQUIPMENTHAWAII.COM



Restaurant Equipment Hawaii

QUALITY COMMERCIAL EQUIPMENT FOR RESTAURANTS & BARS VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON EQUIPMENT, FOOD TRUCKS & OURCOMMISARY KITCHEN 808-845-5052

TECHNICAL DATA

DIMENSIONS	
Exterior Dimensions	491/2"W x 28"D x 341/4"H
INTERIOR DIMENSIONS	453/8"W x 23"D x 26"H
NET VOLUME	12.7 cu. ft.
NET WEIGHT	181 lb.
GROSS WEIGHT	224 lb.
PACKAGING DIMENSIONS	56"W x 323/4"D x 413/4"H

CONSTRUCTION

Exterior Material	Black Coated Steel
INTERIOR MATERIAL	PAINTED ALUMINUM
Insulation Material	FOAMED-IN-PLACE POLYURETHANE
SHELF SIZE	(3) 23" x 26"
Shelf Material	EPOXY COATED STEEL

Cooling	
TEMPERATURE RANGE	33°F-40°F
Refrigerant	R290
Max. Ambient Temperature	90° F
Defrosting	AUTOMATIC
Temperature Controller	DIGITAL
HorsePower	1/6

Electrical

Voltage	115
Amps	2.28
Hz	60
PHASE	1
Plug Type	NEMA 5-15P
Electrical Cord Length	90"

PLAN VIEW

