



# RESTAURANT EQUIPMENT HAWAII



## CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES 430 TYPE STAINLESS STEEL EXTERIOR WITH A 304 TYPE STAINLESS STEEL INTERIOR AND AN OVERALL 35 1/4" WORKING HEIGHT.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSULATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY. INSULATED LID HELPS MAINTAIN SAFE PRODUCT TEMPERATURES.

FULL LENGTH, 111 1/2" DEEP CUTTING BOARD FOR EASY PREP WORK.

EASY-TO-USE RECESSED FULL-LENGTH STAINLESS STEEL HANDLES. DOOR STAYS OPEN PAST 90° FOR EASY LOADING, BUT WILL SELF-CLOSE UNDER 90° TO SAVE ENERGY.

## REFRIGERATION SYSTEM

ENVIRONMENTALLY SAFE R290 REFRIGERANT. REAR-MOUNTED CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

## SHELVING

2 EPOXY-COATED WIRE SHELVES ACCOMMODATE UP TO 90 LB. EACH.

## MODEL FEATURES

PREPROGRAMMED DIGITAL CONTROLLER FEATURES AUTO-DEFROST FUNCTION.

TOP PAN RAIL HOLDS UP TO (16) 1/6 SIZE, 6" DEEP FOOD PANS.

PAN RAIL IS AIR COOLED FROM THE BOTTOM.

## SPECIAL FEATURES

- ECO-FRIENDLY R290 HYDROCARBON REFRIGERANT
- TOP HOLDS UP TO (16) 1/6 SIZE, 6" DEEP FOOD PANS
- FULL LENGTH, 3/4" THICK, 11 1/2" DEEP CUTTING BOARD FOR EASY PREP WORK
- INSULATED LID HELPS MAINTAIN SAFE PRODUCT TEMPERATURES
- DOUBLE SELF-CLOSING SWING DOORS WITH RECESSED FULL-LENGTH STAINLESS STEEL HANDLES
- 2 EPOXY COATED WIRE SHELVES
- 430 TYPE STAINLESS STEEL EXTERIOR AND 304 TYPE STAINLESS STEEL INTERIOR
- DIGITAL TEMPERATURE CONTROLS HOLD AT 33-40°F
- 115V, 1/4 HP
- PAN RAIL IS AIR COOLED FROM THE BOTTOM



PARTS & LABOR



COMPRESSOR

WARRANTY  
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS.



# RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR  
RESTAURANTS & BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON  
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

## TECHNICAL DATA

### DIMENSIONS

EXTERIOR DIMENSIONS	60 1/4" W x 31" D x 42 3/8" H
INTERIOR DIMENSIONS	56 1/4" W x 23 3/4" D x 23 1/2" H
NET VOLUME	15 CU. FT.
NET WEIGHT	352 LB.
GROSS WEIGHT	418 LB.
PACKAGING DIMENSIONS	64 1/2" W x 33 3/4" D x 45 1/2" H

### COOLING

TEMPERATURE RANGE	33°F-40°F
REFRIGERANT	R290
MAX. AMBIENT TEMPERATURE	90°F
DEFROSTING	AUTOMATIC
TEMPERATURE CONTROLLER	DIGITAL
HORSEPOWER	1/4

### CONSTRUCTION

EXTERIOR DIMENSIONS	TYPE 430 STAINLESS STEEL
INTERIOR MATERIAL	TYPE 304 STAINLESS STEEL
INSULATION MATERIAL	FOAMED-IN-PLACE POLYURETHANE
SHELF SIZE	(2) 27 9/16" x 17 1/16"
SHELF MATERIAL	EPOXY-COATED STEEL
SHELF LOAD CAPACITY	90 LB.

### ELECTRICAL

VOLTAGE	115
AMPS	7.8
Hz	60
PHASE	1
PLUG TYPE	NEMA 5-15P
ELECTRICAL CORD LENGTH	84"

## PLAN VIEW

