



RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

HEAVY DUTY CONSTRUCTION INCLUDES 430 TYPE STAINLESS STEEL EXTERIOR WITH A 304 TYPE STAINLESS STEEL INTERIOR AND AN OVERALL 35 1/4" WORKING HEIGHT.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSULATION ENHANCES THE STRUCTURAL STRENGTH OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY. INSULATED LID HELPS MAINTAIN SAFE PRODUCT TEMPERATURES.

FULL LENGTH, 11 1/2" DEEP CUTTING BOARD FOR EASY PREP WORK.

EASY-TO-USE RECESSED FULL-LENGTH STAINLESS STEEL HANDLES. DOOR STAYS OPEN PAST 90° FOR EASY LOADING, BUT WILL SELF-CLOSE UNDER 90° TO SAVE ENERGY.

REFRIGERATION SYSTEM

ENVIRONMENTALLY SAFE R290 REFRIGERANT. REAR-MOUNTED CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

SHELVING

3 EPOXY-COATED WIRE SHELVES ACCOMMODATE UP TO 90 LB. EACH.

MODEL FEATURES

PREPROGRAMMED DIGITAL CONTROLLER FEATURES AUTO-DEFROST FUNCTION.

TOP PAN RAIL HOLDS UP TO (18) 1/6 SIZE, 6" DEEP FOOD PANS. PAN RAIL IS AIR COOLED FROM THE BOTTOM.

SPECIAL FEATURES

- ECO-FRIENDLY R290 HYDROCARBON REFRIGERANT
- TOP HOLDS UP TO (18) 1/6 SIZE, 6" DEEP FOOD PANS
- FULL LENGTH, 3/4" THICK, 11 1/2" DEEP CUTTING BOARD FOR EASY PREP WORK
- INSULATED LID HELPS MAINTAIN SAFE PRODUCT TEMPERATURES
- THREE SELF-CLOSING SWING DOORS WITH RECESSED FULL-LENGTH STAINLESS STEEL HANDLES
- 3 EPOXY COATED WIRE SHELVES
- 430 TYPE STAINLESS STEEL EXTERIOR AND 304 TYPE STAINLESS STEEL INTERIOR
- DIGITAL TEMPERATURE CONTROLS HOLD AT 33-40°F
- 115V, 3/4 HP
- PAN RAIL IS AIR COOLED FROM THE BOTTOM



PARTS & LABOR



COMPRESSOR

WARRANTY
RESIDENTIAL: REH ASSUMES NO LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL, FOODSERVICE OR RESIDENTIAL APPLICATIONS.



RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR RESTAURANTS &
BARS

VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN

808-845-5052

TECHNICAL DATA

Dimensions

| | |
|---------------------------|---|
| Exterior Dimensions | 70 ³ / ₈ "W x 31"D x 42 ³ / ₈ "H |
| Interior Dimensions | 66 ¹ / ₂ "W x 23 ³ / ₄ "D x 23 ¹ / ₂ "H |
| Working Height | 35 ¹ / ₄ " |
| Overall Height (Lid Open) | 47 ¹ / ₄ " |
| Net Volume | 18 cu. ft. |
| Net Weight | 506 lb. |
| Gross Weight | 583 lb. |
| Packaging Dimensions | 74 ³ / ₄ "W x 33 ³ / ₄ "D x 45 ¹ / ₂ "H |

Construction

| | |
|---------------------|--|
| Exterior Material | Type 430 Stainless Steel |
| Interior Material | Type 304 Stainless Steel |
| Insulation Material | Foamed-in -place polyurethane |
| Shelf Size | (3) 21 ⁵ / ₈ " x 17 ¹ / ₁₆ " |
| Shelf Material | Epoxy-coated steel |
| Shelf Load Capacity | 90 lb. |

Cooling

| | |
|--------------------------|-------------|
| Temperature Range | 33°F - 40°F |
| Refrigerant | R290 |
| Max. Ambient Temperature | 90°F |
| Defrosting | Automatic |
| Temperature Controller | Digital |
| Horsepower | 3/4 |

Electrical

| | |
|------------------------|------------|
| Voltage | 115 |
| Amps | 8.8 |
| Hz | 60 |
| Phase | 1 |
| Plug Type | NEMA 5-15P |
| Electrical Cord Length | 84" |

PLAN VIEW

