

RESTAURANT EQUIPMENT HAWAII



CABINET CONSTRUCTION

Heavy duty construction includes 430 type stainless steel EXTERIOR WITH A 304 TYPE STAINLESS STEEL INTERIOR AND AN OVERALL 351/4" WORKING HEIGHT.

Full length, 8" deep cutting board for easy prep work.

FOAMED-IN-PLACE CFC- AND HCFC-FREE POLYURETHANE INSU-LATION ENHANCES THE STRUCTURAL INTEGRITY OF THE CABINET AND HELPS INCREASE ENERGY EFFICIENCY.

2 doors feature easy-to-use recessed handles for quick in-TERIOR ACCESS. DOOR STAYS OPEN PAST 90 FOR EASY LOADING, BUT WILL SELF-CLOSE UNDER 90 TO SAVE ENERGY.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Rear-mounted CONDENSING UNIT POSITIONED FOR EASY MAINTENANCE.

SHELVING

2 EPOXY-COATED STEEL SHELVES INCLUDED. EACH ACCOMMO-DATES UP TO 90 LB.

MODEL FEATURES

Preprogramed digital controls, Auto- defrost function SIMPLIFIES MAINTENANCE AND SERVICE.

Top pan rail holds up to (24) 1/6 size, 6" deep food pans. PAN RAIL IS AIR COOLED FROM THE BOTTOM.

STAINLESS STEEL SANDWICH PREP TABLE

KEEP INGREDIENTS WITHIN A SAFE TEMPERATURE RANGE IN A SLEEK, DURABLE, AND EASY-TO-CLEAN ENVIRONMENT

SPECIAL FEATURES

- Eco-friendly R290 hydrocarbon refrigerant
- Top holds up to (24) 1/6 size, 6" deep food pans
- Full length, 3/4" thick, 8" deep cutting board for easy prep WORK
- Insulated Lid Helps maintain safe product temperatures
- Double self-closing swing doors with recessed handles
- 2 EPOXY COATED WIRE SHELVES
- 430 Type stainless steel exterior and 304 type stainless steel INTERIOR
- Digital temperature controls hold at 33-40° F
- 115V, 1/4 HP
- PAN RAIL IS AIR COOLED FROM THE BOTTOM



WARRANTY RESIDENTIAL: REH ASSUMES NO

LIABILITY FOR PARTS OR LABOR COVERAGE FOR COMPONENT FAILURE, FACTORY DEFECT OR ANY OTHER DAMAGES FOR UNITS IN-STALLED IN NON-COMMERCIAL FOODSERVICE OR RESIDENTIAL APPLICATIONS







RESTAURANT EQUIPMENT HAWAII

Quality Commercial Equipment For Restaurants & Bars Visit Our Online Store For Pricing & Information on Equipment, Food Trucks & OurCommisary Kitchen 808-845-5052

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	601/4"W x 35"D x 457/8"H
Interior Dimensions	561/4"W x 233/4"D x 231/2"H
Net Volume	15 cu. ft.
Net Weight	385 гв.
Gross Weight	451 гв.
PACKAGING DIMENSIONS	641/2"W x 391/4"D x 49"H

Cooling

Temperature Range	33°F-40°F
Refrigerant	R290
Max. Ambient Temperature	90°F
Defrosting	Automatic
Temperature Controller	Digital
HorsePower	1/4

CONSTRUCTION

Exterior Dimensions	430 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	FOAMED-IN-PLACE POLYURETHANE
SHELF SIZE	(2) 279/16" x 171/16"
SHELF MATERIAL	EPOXY-COATED STEEL
SHELF LOAD CAPACITY	90 lb.

ELECTRICAL

Voltage	115
Amps	7.8
Hz	60
Phase	1
Plug Type	NEMA 5-15P
Electrical Cord Length	84"

PLAN VIEW

