



# RESTAURANT EQUIPMENT HAWAII



- RUGGED STAINLESS STEEL FRONT AND ALUMINUM SIDES
- 6" ADJUSTABLE STAINLESS STEEL LEGS
- 30,000 BTU OPEN TOP BURNERS WITH STANDING PILOT IGNITION
- 12" x 12" HEAVY-DUTY LIFT-OFF CAST IRON GRATES
- PULL-OUT CRUMB TRAY WITH WELDED CORNERS
- DURABLE METAL CONTROL KNOBS
- 250-550°F OVEN TEMPERATURE RANGE
- 2 CHROME PLATED OVEN RACKS WITH 4 RACK POSITIONS
- PORCELAINIZED OVEN BOTTOM FOR EASY CLEANING
- 4 3/4" DEEP BACK SHELF AND 2" FRONT LEDGE FOR ADDED STORAGE AND SAFETY
- KICK PLATE PROTECTS INTERNAL COMPONENTS AND PROVIDES EASY ACCESS FOR SERVICING
- 3/4" REAR GAS CONNECTION

THIS COMMERCIAL RANGE IS EQUIPPED WITH 4 BURNERS AND A SPACIOUS OVEN, MAKING IT THE MOST VERSATILE PIECE OF EQUIPMENT IN YOUR KITCHEN. EFFORTLESSLY BOIL, SAUTÉ, SIMMER, AND PERFORM A VARIETY OF OTHER COOKING TASKS ATOP THE HEAVY-DUTY CAST IRON GRATES. THE GENERAL-PURPOSE OVEN PROVIDES A CONVENIENT WAY TO WARM OR BAKE FOODS.



WARRANTY  
RESIDENTIAL: REH  
ASSUMES NO LIABILITY FOR PARTS  
OR LABOR COVERAGE FOR  
COMPONENT FAILURE, FACTORY  
DEFECT OR ANY OTHER DAMAGES  
FOR UNITS INSTALLED IN  
NON-COMMERCIAL FOODSERVICE OR  
RESIDENTIAL APPLICATIONS.



PARTS & LABOR



# RESTAURANT EQUIPMENT HAWAII

QUALITY COMMERCIAL EQUIPMENT FOR RESTAURANTS & BARS  
 VISIT OUR ONLINE STORE FOR PRICING & INFORMATION ON  
EQUIPMENT, FOOD TRUCKS & OUR COMMISARY KITCHEN  
 808-845-5052

## TECHNICAL DATA

OVERALL SIZE	24"Wx32 <sup>5/8</sup> " Dx60"H
OVEN INTERIOR SIZE	20 <sup>5/8</sup> "Wx25 <sup>7/8</sup> "Dx13"H
BURNER BTU	30,000
OVEN BTU	30,000
TOTAL RANGE BTU	150,000
KNOB STYLE	METAL

CONTROL TYPE	MANUAL
GAS INLET SIZE	3/4"
SHIPPING CARTON SIZE	29"Wx40 <sup>1/2</sup> "Dx35"H
WEIGHT	366LBS
FREIGHT CLASS	110

COOKING SURFACE	12"x12" CAST IRON GRATES
POWER	NATURAL GAS OR LIQUID PROPANE
BURNER STYLE	OPEN TOP
TOTAL BURNERS	4
TOTAL OVENS	1
MAXIMUM OVEN TEMP	550°F

## INSTALLATION

INSTALL THE COMMERCIAL RANGE ON AND AROUND NON-COMBUSTIBLE SURFACES, ALLOWING 6" OF CLEARANCE ON THE SIDES OF THE RANGE AND 6" OF CLEARANCE FROM THE BACK OF THE RANGE. INSTALL UNDERNEATH A VENTILATION HOOD THAT CORRESPONDS WITH LOCAL AND NATIONAL CODES.

- 3/4" REAR GAS CONNECTION CONFIGURED FOR AREAS AT AN ALTITUDE LESS THAN 2,000 FT
- MANUAL GAS SHUT-OFF VALVE AND GAS PRESSURE REGULATOR MUST BE INSTALLED FOR SAFETY AND EASE OF SERVICING

## PLAN VIEW

