

RESTAURANT EQUIPMENT HAWAII



HIGHLIGHTS

THE 500 LB. MODULAR ICEMAKER IN STAINLESS STEEL FROM REH IS A VERY RELIABLE AND VERSATILE ICE MAKER THAT PRODUCES UP TO 500 LBS. OF ICE PER DAY, WITH AN 350 LB. CAPACITY STORAGE BIN WITH DOOR ACTIVATED LIGHT.

This #304 Stainless steel construction provides durability to a unit that is low-maintenance and easy to clean with a self-clean system.

THE UNIT PRODUCES CRYSTAL CLEAR ICE CUBES THAT WORK GREAT FOR APPLICATIONS IN RESTAURANTS, BARS, HOTELS, GROCERY STORES AND MORE.

This unit runs on a standard household electrical current and is ETL approved for commercial use, pairing high output and capacity with easy to use control panel, compact design.

- \bullet Up to 500 lbs. Of daily ice production to provide a steady supply
- ${ullet}$ 350 LB. STORAGE BIN WITH AUTOMATIC SHUT-OFF WHEN BIN IS FULL
- •Produces high-quality, crystal clear ice cubes
- •ADJUSTABLE LEGS ALLOW YOU TO CONTROL THE HEIGHT AND ACCOMMODATE UNEVEN FLOORING
- •Easy self-clean system
- •FLEXIBLE HOSES FOR WATER CONNECTION AND DRAIN PIPE INCLUDED
- •Adjustible Ice thickness by the push of a button Water filter and ice scoop included



WARRANTY
RESIDENTIAL: REH ASSUMES NO
ILABILITY FOR PARTS OR LABOR COVERAGE
FOR COMPONENT FAILURE, FACTORY DEFECT
OR ANY OTHER DAMAGES FOR UNITS INSTALLED IN NON-COMMERCIAL FOODSERVICE
OR RESIDENTIAL APPLICATIONS.







RESTAURANT EQUIPMENT HAWAII

Quality Commercial Equipment For Restaurants & Bars Visit Our Online Store For Pricing & Information on Equipment, Food Trucks & OurCommisary Kitchen 808-845-5052

TECHNICAL DATA

WATER

A COLD WATER SUPPLY WITH WATER PRESSURE BETWEEN 0.13 MPA [19 PSI] AND 0.55 MPA [80 PSI] IS REQUIRED TO OPERATE ICE MAKER. IF YOU HAVE QUESTIONS ABOUT YOUR WATER PRESSURE, CALL A LICENSED, QUALIFIED PLUMBER.

LOCATION

To ensure proper ventilation for your ice maker, the front side must be completely unobstructed. The ice maker may be closed-in on the top and two sides, but the installation should allow the ice! To be pulled forward for servicing if necessary.

Installation of the ice maker requires a cold water supply inlet of 1/4" (6.35 mm) OD soft copper tubing with a shutoff valve or

Choose a well ventilated area with temperatures above 55°F (13°C) and below 110°F (43°C). Best results are obtained between 70°F and 90°F (21°C and 32°C).

IMPORTANT

A DRAIN PUMP IS NECESSARY WHEN A FLOOR DRAIN IS NOT AVAILABLE.

DRAIN PUMP, ONLY TO CARRY THE WATER TO AN EXISTING DRAIN.

NOTES

IF THE DRAIN HOSE BECOMES TWISTED AND WATER CANNOT DRAIN, YOUR ICE MAKER WILL NOT WORK. IT MAY BE DESIRABLE TO INSULATE THE DRAIN LINE THOROUGHLY UP TO THE DRAIN INLET.

PLAN VIEW

