

**MATERIAL SAFETY DATA SHEET (OSHA-20)
IN CASE OF LEAK, SPILL, FIRE, EXPOSURE,
OR ACCIDENT CALL CHEMTREC:
UNITED STATES: 1-800-424-9300
INTERNATIONAL: 202-483-7616 (collect)**

**Show Car Products LLC
53 Welcome Home Road
Grant, AL 35747
(256)-728-4925**

Section I Product Identification

E-210 "Lift-Out"

(Light Brown liquid with clean scent)

08/28/07

Section II Hazardous Ingredients

Chemical Name:	%	PEL/OSHA	TLV-ACGIH	CAS NUMBER
2-Butoxyethanol	3-7	50 ppm	25 ppm	111-76-2

Section III Physical Data

Boiling Point: >212 F	Specific Gravity: 1.07	Vapor Pressure: 20	Volatiles: 80%
Vapor Density: >1	Solubility: 100% in water	Evaporation Rate: <1	Apper & Odor: See Sec.I

Section IV Fire & Explosion Data

NFPA CODES: **Health:** 1 **Flammability:** 0 **Reactivity:** 0 **Flash Point:** None

Extinguishing Media: Not a fire hazard.

Hazardous Decomposition: None.

Special Fire Fighting Procedures: None

Unusual Fire & Explosion Hazards: None

Section V Health Hazard Data

Permissible Exposure Level: See Section II under PEL/OSHA

Effects of Overexposure: (Acute & Chronic)

Eyes: Can cause irritation.

Skin: Prolonged or repeated contact can cause moderate irritation, defatting & dermatitis.

Inhalation: Breathing of dust or mist can cause mild to severe irritation of nasal or respiratory passage.

Ingestion: Can cause gastro-intestinal irritation, nausea, vomiting, and diarrhea. Over exposure to glycol ethers has apparently been found to cause anemia, liver abnormalities, kidney damage, lung damage, and blood abnormalities in laboratory animals.

Carcinogenicity: **NTP:** No **IARC:** No **OSHA:** No

Signs and symptoms of exposure: See Health effects (Acute & Chronic): burning sensations in eyes and on skin areas contacted.

Medical Conditions Aggravated by Exposure: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to this product.

First Aid Procedures:

Eyes: Flush eyes for 30 minutes with cool water. Consult a physician.

Skin: Flush area exposed for 30 minutes with large amounts of running water. Remove contaminated clothing and shoes. Wash before reuse. Consult a physician immediately.

Inhalation: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Call physician immediately.

Primary routes of entry: Skin and inhalation.

Continued on Back

E-210 "Lift-Out"

Section VI Reactivity

Incompatibility: Avoid contact with acids and strong oxidizers such as chlorine, etc.

Hazardous Decomposition: See Section IV

Hazardous Polymerization: Will not Occur

Stability: Stable

Section VII Spill or Leak Procedures

Steps to be taken in case material is Released or Spilled: Absorb the large spill with plenty of absorbent material. Wash the residue down the drain or pit with plenty of water. Use plenty of water on a small spill. Please note that material is very very slippery when spilled, so use extreme caution when cleaning up spills.

Waste disposal method: Dispose of according to Local, State, and Federal regulations for biodegradable detergents.

Section VIII Protective Equipment to be Used

Respiratory Protection: An appropriate hydrocarbon canister or respirator for organic vapor should be worn if exposure will be prolonged.

Ventilation: N/E

Protective gloves: Wear-resistant gloves such as rubber, PVC

Eye Protection: Eye wash and quick drench facilities.

Other protective equipment: None known.

Section IX Special Precautions and Other Comments

Other Controls: N/L.

Work Practices: Eye wash and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

Hygienic Practices: Avoid contact with eyes, skin, and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothes promptly and wash thoroughly before reuse.

Precautions to be taken in Storing and Handling: Store between 40 and 120 degrees F. Protect from physical damage and keep tightly closed.

Disclaimer Of Liability

The information contained herein is based on data considered to be accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product.

End MSDS